

API planning

Endpoint routes and expected responses for the MinamiAI backend — authentication, conversations, messaging, and speech synthesis.

Main route

GET / → Landing page

- **OK** Shows the animated Minami scene as the entry point of the application, before any authentication has happened.
- **OK** The character is rendered and idle-animating immediately, whether or not a session exists.

Auth routes

POST /api/auth/register → Result

- **201** Success responds with a JWT, and the client transitions directly into the chat view.
- **400** Username taken or fails validation; shows registration errors inline.

POST /api/auth/login → Result

- **200** Success responds with a JWT.
- **401** Invalid credentials; shows login errors inline rather than redirecting.

Conversation routes

POST /api/chat/conversation → Result · requires JWT

- **201** Returns a new `conversation_id`, called once per session on load.
- **401** Not logged in.

GET /api/chat/conversations → Result · requires JWT

- **200** List of the user's past conversations (id, title, created_at), sorted most recent first, for the history sidebar.
- **200** Empty list for a new user.
- **401** Not logged in.

GET /api/chat/history/:conversation_id → Result · requires JWT

- **200** Full message list for that conversation, ordered oldest to newest.
- **403** Conversation does not belong to the requesting user.
- **404** Conversation does not exist.

Message routes

POST /api/chat/message → Result · requires JWT

Body: { `conversation_id`, `content` }

- **200** Minami's reply text. Memory extraction runs afterward in the background and does not block this response.

- **400** `content` is empty.
- **403** `conversation_id` does not belong to the requesting user.
- **502** Groq API call fails or times out.

POST `/api/chat/tts` → Result · requires JWT

Body: `{ text }`

- **200** Audio stream (`audio/wav` or `audio/mpeg`) synthesized from the given text.
- **400** `text` is empty or exceeds the length cap.
- **502** ElevenLabs call fails.

Memory routes (admin)

GET `/api/admin/memories` → Result · requires JWT, role = admin

- **200** List of memories, filterable by `<query>` params for `user_id` , `importance` , and expiry status.
- **200** Empty list if no memories match the filter.
- **403** Requesting user is not an admin.

PATCH `/api/admin/memories/:id` → Result · requires JWT, role = admin

Body may include `content` , `importance` , or `expires_at` .

- **200** Updated memory.
- **400** `importance` outside 1–5, or the importance/expiry pairing violates the tier-5-is-permanent rule.
- **404** Memory does not exist.

DELETE `/api/admin/memories/:id` → Result · requires JWT, role = admin

- **204** Deleted.
- **404** Memory does not exist.

POST `/api/admin/memories/bulk_delete` → Result · requires JWT, role = admin

Body: `{ ids: [...] }`

- **200** Count of memories deleted.
- **400** `ids` is empty or contains non-existent ids; the response lists which ids were skipped rather than failing the whole batch.

Notes on cross-cutting behavior

- Every route above except `/` , `/api/auth/register` , and `/api/auth/login` requires a JWT in the `Authorization` header. A missing or invalid token responds with 401 across the board rather than a route-specific message.
- Ownership checks (403) always run before existence checks (404) would otherwise leak information, so a user probing another user's resource ids sees a consistent 403 rather than learning whether the id exists.
- Unhandled server-side failures — a Groq timeout, a database connection drop, an ElevenLabs outage — fall through to a 500/502 response with a generic error body, and are what triggers the frontend's `triggerError()` path: a red-tinted bubble and a surprised expression, rather than a blank screen.