

Task 1

Amountti 1000 dan katta qatorlar saralanadi

Task 3

ALLEXCEPT(Sales, Sales[Region]) -bunda regionga nisbatan filter o'chirilmaydi

ALL(Sales)-bunda esa sales jadvaliga keladigan hamma filterlar qaytariladi

Task 5

ALLSELECTED funksiyasining maqsadi – foydalanuvchi tanlagan (selections) kontekstdagi barcha qiymatlarni qaytarish.

Task 9

ALLSELECTED ba'zan pivot jadvalda “kutilmagan” natija berishi mumkin, sababi:

1. **Foydalanuvchi tanlovi konteksti** (slicer, filter, row/column field) — pivot jadval o'zi ham kontekst yaratadi, shuning uchun ALLSELECTED qaysi kontekstni “saqlab qolish” kerakligini boshqa vizualdagidan boshqacha talqin qilishi mumkin.
2. **Row/Column field'lar** — pivotda bir nechta maydon ishlatilsa (Region, Category, va hokazo), ALLSELECTED ularning barchasini hisobga olib qoladi. Natija kutilgandan murakkabroq bo'lib chiqadi.
3. **Filter darajasi** — slicer'da tanlangan qiymatlar bilan pivotdagi grouping darajalari to'liq mos kelmasa, ALLSELECTED “kutilmagan” bo'luvchi (denominator) qaytarishi mumkin.

Task 11

High Sales = CALCULATE(SUM(Sales\[Amount]), FILTER(Sales, Sales\[Amount] > 1000))

High Sales= CALCULATE(SUM(Sales\[Amount]), Sales\[Amount] > 1000)

Task 12

Top 2 Products Sales =

```
CALCULATE (
    SUM ( Sales[Amount] ),
    FILTER (
        TOPN (
            2,
            SUMMARIZE (
                Sales,
                Sales[Product],
                "TotalSales", SUM ( Sales[Amount] )
            ),
            [TotalSales],
            DESC
        ),
        TRUE ()
    )
)
```

chiqaramiz

-- 1. Sotuv summasini hisoblaymiz
-- 2. FILTER orqali filterlash
-- 3. TOPN ichida eng yuqori N ta qator tanlanadi
-- faqat eng yuqori 2 ta product
-- 4. Har bir product bo'yicha jami sotuvni
-- Product darajasida guruhlash
-- 5. TotalSales bo'yicha saralash
-- eng kattasidan kichigiga
-- 6. FILTER sharti (har doim true, chunki TOPN natijasi o'zi filter)