Agentic AI for Vulnerability Confirmation and Patch Validation in Open-Source Software

SC4079

Dheeraj

College of Computing and Data Science
Nanyang Technological University

Supervisor: Assoc Prof. Chee Wei Tan

A Final Year Project Report
Academic Year 2026/2027

October 24, 2026

Abstract

An artificial intelligence system's ability to exploit software does not establish that it can reliably secure it. This project extended an existing exploit-confirmation prototype into a two-part, evidence-gated system for using large language models to secure open-source software: (1) dynamic confirmation and patch validation for already-published CVEs, and (2) reachability-filtered static analysis on real upstream free5GC source. Across five evolving pipeline rounds and a 36-run hosted-Claude comparison, dynamic exploit confirmation proved consistently achievable: all six catalogue classes were confirmed at least once, and every hosted model confirmed all six exploits. Patch validation proved substantially harder, and its own acceptance criterion needed correction twice. The original two-check criterion was found, by trace-level inspection, to accept a patch whose vulnerable route had merely crashed, indistinguishable to the check from a genuine fix; this was corrected into a four-outcome verdict. External review then found that corrected verdict itself still only checked for crash-absence on a benign request, not correct legitimate behaviour: a limitation this project reproduced and closed where possible.

Three independent real-upstream cases reached this project's strongest standards of evidence: a real, pinned-version PyPI package (`jaraco.context`, CVE-2026-23949); a real, disclosed, unauthenticated-disclosure advisory in OpenEMR (GHSA-q366-cv5v-83w8), confirmed by content-verified request/response evidence and extending this method to a second domain, healthcare; and all four manually selected handlers of a real, disclosed free5GC vulnerability pattern, disclosed as four separate CVEs sharing one root cause (CVE-2026-40245 through CVE-2026-40248): a harness running the real vulnerable and patched `free5gc/udr` binaries in a fuller deployment (real MongoDB, real free5GC NRF) confirmed by direct HTTP exchange that the vulnerable build permits an unauthorized read of one record or the entire subscription collection, an unauthorized write, and an unauthorized delete, all through the same one-line missing-`return` defect, and that the real fix commit closes all four while preserving legitimate behaviour for the specific operations tested (a content-verified legitimate read, seed writes, and a separately confirmed legitimate delete). This project's contribution is not a single confirmation or patch-acceptance rate, but an account of how far an evidence-gated workflow can progress toward reproducible evidence, and where its own validation judgments can fail: a limitation found, fixed, and narrowed under independent review.

Acknowledgements

I would like to thank my supervisor, Associate Professor Chee Wei Tan, for his guidance and feedback throughout this project. I also thank the Nanyang Technological University College of Computing and Data Science for the resources that supported this work, and the fellow student whose ProvTrail tool this project integrates with (Chapter 1) for that collaboration.

Contents

Abstract **i**

Acknowledgements **ii**

1 Introduction **1**

1.1 Background 1
1.2 Research Gap 2
1.3 Objectives 2
1.4 Scope 3
1.5 Project Phases and Scope Evolution 4
1.6 Ethics and Responsible Use 5

2 Literature Review **6**

2.1 Overview 6
2.2 Agentic AI for Automated Security Testing 6
2.3 Cyber Reasoning Systems and the AIxCC/OSS-CRS Ecosystem 7
2.4 Reachability-Filtered Vulnerability Triage 8
2.5 Research Gap 10

3 Methodology **12**

3.1 Project Context 12
3.2 Methodology Overview 12
3.3 Alternative Approach Considered 14
3.4 System Architecture 14
3.4.1 System Description 14
3.4.2 Major System Components 16
3.4.3 Architecture Diagram 16
3.5 Data Sources and Preprocessing 20
3.5.1 Advisory and Source Data 20
3.5.2 Preprocessing Steps 20
3.6 Algorithms and Models Used 21

3.6.1 Model and Algorithm Selection . . . 21
3.6.2 Key Parameters and Settings . . . 22
3.7 Implementation Details . . . 22
3.7.1 Programming Environment . . . 22
3.7.2 Implementation Procedure . . . 23
3.8 Testing and Validation . . . 24
3.8.1 Testing Strategy . . . 24
3.8.2 free5GC Runtime Validation Harness . . . 24
3.9 Evaluation Metrics . . . 26
3.10 Limitations and Assumptions (Method-Related) . . . 30

4 Results and Discussion **33**
4.1 Results . . . 33
4.1.1 Exploit Confirmation Across the CVE Catalogue . . . 38
4.1.2 Patch Generation and Validation . . . 39
4.1.3 Real-Upstream Validation: CVE-2026-23949 . . . 43
4.1.4 Real-Upstream Validation: OpenEMR (GHSA-q366-cv5v-83w8) . 45
4.1.5 Multi-Model Comparison . . . 47
4.1.6 Multi-Model Comparison: Hosted Claude Models . . . 47
4.1.7 Reachability Filtering on Real Upstream Source . . . 50
4.1.8 Classification Ablation . . . 53
4.1.9 Extended Model-Access Comparison: OpenAI API, Codex CLI, and AIxTech Gateway . . . 54
4.1.10 OAuth2-Enforced Follow-Up and Repeatability Check . . . 56
4.2 Discussion . . . 57
4.2.1 Interpreting the Confirmation-Rate Progression . . . 57
4.2.2 Why Patch Validation Lagged Confirmation . . . 57
4.2.3 Runtime and Model-Size Findings . . . 59
4.2.4 Classification Reliability and the Structured-Data Advantage . . . 59
4.2.5 Relationship to the AIxCC/OSS-CRS Benchmark Context . . . 59
4.2.6 Limitations, Trade-offs, and Sources of Uncertainty . . . 60
4.3 Summary and Implications . . . 61

5 Conclusion **62**
5.1 Summary of the Project . . . 62
5.2 Objective Closure . . . 62
5.3 Key Findings . . . 64
5.4 Contributions . . . 65
5.5 Limitations . . . 66

5.6 Future Work 67

A Reproducibility Details **72**

A.1 Full CVE Catalogue 72

A.2 free5GC Runtime Validation Evidence Bundle 74

A.3 Model and Sampling Configuration 77

A.4 Hosted Claude Comparison: Per-CVE Cost and Time 80

A.5 Validation Criteria (Quick Reference) 82

A.6 Relationship to AIxCC/OSS-CRS Vocabulary (Condensed) 82

B Selected Trace Excerpts **84**

B.1 The False-Acceptance Case: CVE-2026-78683, Round 4 vs. Round 5 . . . 84

B.2 The Markdown-Fence Crash (Round 3) 84

B.3 free5GC Upstream Compile Verification 85

B.4 free5GC LLM-Generated Patch: Multi-Model Comparison 85

B.5 free5GC Adversarial Bypass-Probe: Can a Model Find a Way Past the Real Fix? 88

B.6 Classification Ablation: NVD/GHSA Ground-Truth Cross-Check 91

C Verbatim Prompts (Representative Sample) **92**

D Repository and Artifact Access **94**

List of Figures

3.1 System architecture: advisory-driven exploit confirmation pipeline, from advisory intake through classification, dynamic execution, self-improvement, and patch generation/acceptance. 18
3.2 The Stage 3.6 interpreter branch: routes execution to `python` or `node` depending on target file extension. 19
3.3 The shared live-model backend used across Stages 3.5, 3.7, and 3.8, including the persisted-lesson store. 19

4.1 Dynamic confirmation rate across the five catalogue verification rounds (Table 4.2). The non-monotonic dip at Round 3 and the jump at Round 4 are discussed in Section 4.2.1. 39
4.2 Total CLI-reported cost estimate against `confirmed_fix` count for each of the 6 hosted Claude models (Table 4.7). Cost and screening-pass rate are visibly not monotonically related: Haiku 4.5, the cheapest model, ties the best rate. 49

List of Tables

1.1 Objective-to-evidence map: what question each part of the evaluation answers. . . . 3

3.1 Major system components and their functions. . . . 16
3.2 Advisory and source data used in evaluation. . . . 20
3.3 Representative models and algorithms invoked by the pipeline (not the full eight-model comparison, which is reported in full in Table 4.6). . . . 21
3.4 Key parameters and settings. . . . 22
3.5 Programming environment. . . . 23
3.6 free5GC handler-to-CVE mapping (one shared root cause, one shared fix commit, four separate CVE identifiers). . . . 25
3.7 Evaluation metrics and their justification. . . . 26

4.1 Consolidated overview of the major experiments reported in this chapter. 34
4.2 Dynamic confirmation rate by round. . . . 38
4.3 The six surviving patched artifacts under the stronger, content-verified reassessment: expected vs. actual response on both the malicious and legitimate request. . . . 42
4.4 Real-upstream four-way validation result: CVE-2026-23949 (`jaraco.context`). 44
4.5 Real-upstream validation result: GHSA-q366-cv5v-83w8 (OpenEMR `admin.php`). . . . 46
4.6 Confirmation rate by model (6 CVEs each). . . . 47
4.7 Confirmation and patch outcomes by hosted Claude model (6 CVEs each, 36 runs total). . . . 48
4.8 Stage 2 classification ablation (n=6). . . . 53
4.9 Prose-only condition: micro-averaged precision, recall, and F1. . . . 54
4.10 OpenAI API sweep: all 23 requested model identities, across four experiment families. . . . 55
4.11 Codex CLI sweep: all 18 requested model identities, free5GC target. . . . 55

5.1 Objective-by-objective closure. . . . 63

A.1 All eleven CVEs used across this project's evaluation: six in the main catalogue (Chapter 4), four in the free5GC work (Chapter 3, Table 3.6), and one in the ProvTrail integration (Chapter 3). A twelfth case, OpenEMR's GHSA-q366-cv5v-83w8 (Section 4.1.4), carries no CVE number and so is not listed below. 72
A.2 free5GC runtime validation evidence bundle (`free5gc_runtime_case/`). . . 75
A.3 Exact configuration values used across the live-LLM evaluation (Chapter 4), read directly from `cve_pipeline.py`. 77
A.4 Round-to-commit mapping for the live-LLM catalogue runs (Chapter 4). 79
A.5 Per-CVE cost (USD) and wall-clock time (s) for every model–CVE cell in the hosted Claude comparison (36 cells total). 80

B.1 free5GC LLM-generated patch: eight locally-hosted models (Section B.4). *Pass* = `confirmed_fix_all_four_handlers`; *Partial* = `partial_or_inconclusive`. 86
B.2 free5GC LLM-generated patch: eight hosted Claude models, CLI-reported cost estimate (Section B.4). *Pass* = `confirmed_fix_all_four_handlers`. . 87
B.3 free5GC bypass-probe: eight locally-hosted models against the real fix (Section B.5). 89
B.4 free5GC bypass-probe: eleven named hosted Claude models against the real fix, CLI-reported cost estimate (Section B.5). 90
B.5 Ground-truth CWE cross-check between NVD and GitHub Security Advisories (Section 4.1.8). 91

D.1 Where each result reported in this thesis lives in the repository. 95

Chapter 1

Introduction

1.1 Background

An artificial intelligence (AI) system's ability to exploit software does not establish that it can reliably secure it. Recently in July 2026, OpenAI models undergoing cybersecurity evaluation with reduced safeguards bypassed isolation controls and compromised parts of Hugging Face's infrastructure [1]. The incident reminded us why advances in automated exploitation must be followed up with careful evaluation of their defensive use.

Agentic AI offers one approach to automated security testing. An agent uses a Large Language Model (LLM), which processes text and code in order to select tools as well as revise its actions using feedback [2]. For example, it would generate a test for a suspected vulnerability, run it, and investigate an unsuccessful attempt. Weiss and Khayet developed a pipeline that generates exploits from published vulnerability information and checks them against both vulnerable and patched software versions [3]. Their method formed the basis of AI-exploit-CVE, a prototype developed and presented at DEFCON Singapore. Weiss and Khayet's account is a personal blog post used here as the origin of the idea being extended, not as evidence for any claim; the experimental records in this thesis were generated by this project; claims of dynamic confirmation are supported by the execution evidence described for each experiment. The system built in this project is an LLM-assisted workflow with code-defined stages and bounded feedback; autonomous tool selection is available on a separate optional path but is not the configuration evaluated in the model comparisons in Chapter 4.

Broader capabilities have emerged from the Defense Advanced Research Projects Agency's AI Cyber Challenge (AIxCC), which discovered 54 of 63 synthetic vulnerabilities and patched 43, approximately 86% and 68% of the total [4]. Its winning system, ATLANTIS, combines language models with program analysis to discover vulnerabilities and generate fixes [5]. The Open Source Cyber Reasoning System framework (OSS-CRS) provides a common interface for building and running automated vulnerability discovery

and fixing systems [6]. These developments provide a foundation for extending the prototype beyond individual, disclosed vulnerabilities.

1.2 Research Gap

However, applying these capabilities requires evidence that the tests represent the software being assessed. An exploit that succeeds against a simplified reproduction may not work against the real application. Likewise, a patch that compiles may leave the vulnerability unresolved or disrupt legitimate functions. The central question for this project is therefore: what executable evidence is sufficient to distinguish exploit confirmation, patch-screening success, and bounded functional preservation in an LLM-assisted known-CVE workflow, and where does each evidence tier fall short?

1.3 Objectives

This study aims to develop and evaluate an agentic workflow for confirming disclosed vulnerabilities and validating candidate patches with executable evidence, using the stage vocabulary and evidence-gating philosophy of ATLANTIS and OSS-CRS as a conceptual frame rather than integrating their implementations directly (Chapter 2 states precisely where this project's stages align with theirs and where they do not). The workflow is evaluated on two tracks: a catalogue of six disclosed CVEs reproduced as minimal local targets, and free5GC, an open-source implementation of a 5G wireless network core used for research and testing [7], where a shared missing-`return` defect across four selected handlers of one source file is analysed and patched against the real, cloned upstream source rather than a reproduction, and evaluated as a real upstream runtime case. This single root cause is disclosed as four separate CVEs (CVE-2026-40245 through CVE-2026-40248), one per handler, all closed by the same upstream fix commit; Section 3.8.2 states the exact handler-to-CVE mapping. Alongside compile-time verification of the broader four-handler patch set, the DELETE handler (CVE-2026-40246) was additionally run and exercised live, against a real local MongoDB instance, to confirm the exploit and the fix by direct HTTP exchange rather than by compilation alone. A further, narrower integration links the pipeline to ProvTrail, a companion student's tool for identifying JavaScript and TypeScript code resembling known vulnerable implementations; this integration is limited to SARIF-based ingestion plumbing and one hand-authored, dynamically confirmed demonstration case, not a systematic evaluation of ProvTrail's own flagged findings. SARIF, the Static Analysis Results Interchange Format [8], is the interchange format between ProvTrail's static findings and this project's dynamic-confirmation pipeline.

Table 1.1 states, for each central question investigated, the evidence available for it in this report, so a reader can locate the relevant result directly rather than reconstructing

the mapping from the narrative.

Table 1.1: Objective-to-evidence map: what question each part of the evaluation answers.

Question	**Evidence in this report**
What executable evidence supports exploit confirmation, and what signal errors were found?	A real subprocess exit code or HTTP exchange ("dynamically confirmed"), together with the documented trace-level investigations that found specific harness signal errors and the oracle limits that remain (Sections 4.2.1 and 4.2.2); selective inspection, not independent adjudication of every recorded success.
How strong are the patch-acceptance checks?	A historical liveness screen (raw `patch_validated`), a corrected heuristic screen (`patch_verdict`, intentionally weaker than a repair guarantee), and stronger bounded content checks on specified subsets: 6 recoverable synthetic artifacts and three real-upstream cases (Section 4.1.2).
Does reachability-filtered analysis of one file's call graph transfer to real evidence against the actual deployed service, not just a reduced function count?	The free5GC case study: compile-verified, then runtime-confirmed across all four of this project's manually selected handlers against a real, deployed stack (Section 3.8.2).

1.4 Scope

Evaluation covers the six-CVE reproduction catalogue described above, run across multiple verification rounds and across a comparison of eight locally hosted models plus a later 36-run comparison of six hosted Claude models, and the one free5GC case study, in controlled local environments; within that case study, all four analysed handlers (CVE-2026-40245 through CVE-2026-40248, Section 3.8.2) were additionally evaluated at runtime against a fuller deployment (a real, locally hosted MongoDB backend and a real free5GC NRF), rather than by compile-time verification alone, with OAuth2 enforcement explicitly disabled for these runtime checks (a later, separate follow-up, Section 4.1.10, extends a subset of them with OAuth2 enforcement turned on). This assesses whether suspected

vulnerabilities can be dynamically reproduced and whether a proposed patch causes the original exploit to fail under an automated criterion. Full functional preservation (whether a patch also preserves the affected route's behaviour for a legitimate, non-malicious request, rather than merely the absence of a crash) was not part of the original broad synthetic evaluation across the full catalogue and every model compared. It was added later, at different evidence strengths, not as a check performed uniformly across every result in this evaluation: the real-upstream cases (Sections 4.1.3, 4.1.4, and 3.8.2) use case-specific response-content or state checks against actual software, detailed per case in those sections, not a uniform full-response-equality protocol; for six recoverable synthetic patched artifacts (Section 4.1.2), the malicious side was checked only for the absence of the exploit's response marker, while the legitimate side was checked against real expected content of varying granularity per class. These are bounded observations for the tested inputs, not a guarantee of general patch correctness. Results obtained from simplified reproduction are distinguished from those obtained using actual software, with unsuccessful and inconclusive tests recorded. The findings are intended to help developers judge the evidence supporting an automated vulnerability report or proposed patch, including where that evidence, or the criterion used to produce it, was found to be incomplete.

1.5 Project Phases and Scope Evolution

The project proceeded in four broad phases over the academic year: extending the inherited exploit-confirmation prototype with dynamic execution and self-improvement; building and correcting the patch-acceptance criterion described in Chapter 4; porting and applying the reachability-filtering capability to real free5GC source and extending it to runtime confirmation; and the later multi-model comparisons, real-upstream validation cases, and final evidence freeze. This is a chronological grouping of when work happened over the academic year, not the same four-way split as the Methodology Overview's "four main stages" (Section 3.2), which groups the same underlying work by pipeline component instead. The two do not, and are not intended to, map onto each other one-to-one. The work completed matches this final scope. The project was originally framed around fuzzing-based LLM security; when it became clear during implementation that no pipeline stage performs coverage-guided fuzzing, the framing was changed, with the supervisor's agreement, to LLM-assisted exploit confirmation and patch validation for already-disclosed CVEs — a change to stated framing only, with no technical restructuring and no planned work dropped.

Evaluation subsequently broadened to three further model-access methods beyond the Ollama and Claude CLI comparisons above (a direct Claude API gateway with 10 requested model names, the OpenAI API with 23 model identifiers, and the Codex CLI with 18 model identifiers, together 51 requested model/access combinations across the

same free5GC, OpenEMR, and six-CVE-catalogue targets, not 51 distinct models that were each successfully evaluated: some names overlap across methods, many produced no output at all, and only 4 of the 10 gateway names resolved) summarised in Section 4.1.9 and reported in full in the project repository's `docs/RESULTS_BY_ACCESS_METHOD.md` and `docs/FINAL_EVIDENCE_SUMMARY.md`, rather than reproduced chapter-by-chapter here alongside the original Ollama/Claude CLI comparisons they extend.

1.6 Ethics and Responsible Use

All exploitation and patch testing in this project was carried out against locally hosted, self-controlled targets: either generated reproductions run on a private development machine, or a real upstream package (`jaraco.context`) and two real upstream repositories (`free5gc/udr` and OpenEMR) exercised entirely within isolated local environments the author controlled, never against a public or third-party service. No exploit generated by this project was deployed against, or tested on, any system outside the author's own local infrastructure, and no live production service, public deployment, or third party's data was accessed, probed, or affected at any stage. Every CVE and advisory studied is real and already publicly disclosed (verified against NVD, GHSA, and the relevant upstream project's own advisory or fix commit before use, per Appendix A); CWEs are the weakness classification each advisory carries, not a separate class of disclosed advisory. This project did not discover, disclose, or otherwise handle any previously unknown vulnerability, so no responsible-disclosure obligation to a vendor arose during this work. Local HTTP servers used to serve crafted archives or payloads (for example, the real-upstream `jaraco.context` case, Section 4.1.3) were bound to `127.0.0.1` only and never exposed beyond the local machine. Should this project's methodology be extended to a previously undisclosed finding in future work, the author commits to following standard coordinated/responsible disclosure practice (privately notifying the affected project or vendor, allowing a reasonable remediation window, and withholding public detail until a fix is available) rather than the immediate, open reporting appropriate for the already-published CVEs studied here.

Chapter 2

Literature Review

2.1 Overview

This project sits at the intersection of three bodies of work: agentic AI systems that use large language models (LLMs) to carry out multi-step security tasks, Cyber Reasoning Systems (CRSs) that automate vulnerability discovery and repair at scale, and reachability-based static analysis techniques that narrow the scope of what such systems must examine. This chapter reviews each in turn, moves from isolated per-system description toward the themes that connect them, and closes by identifying the specific gap (evidence-gated confirmation of both exploits and patches against representative targets) that motivates this project's objectives, introduced in Chapter 1.

2.2 Agentic AI for Automated Security Testing

An agent, in the sense used throughout this literature, is a system in which an LLM processes text and code, selects among available tools, and revises its own actions based on feedback from their results, rather than following a fixed script [2]. This feedback loop is what distinguishes an agentic approach from a single-shot LLM query: an agent that generates a candidate exploit can, in principle, run it, observe whether it succeeded, and try again with the failure in hand.

Fang et al. reported that GPT-4 exploited 13 of 15 one-day vulnerabilities within up to five attempts, while performance fell to 1 of 15 without the vulnerability descriptions. Other evaluated models and scanners recorded no successes under their respective test conditions. This demonstrates strong dependence on the supplied advisory information in that benchmark [15]. A follow-up evaluated a hierarchical agent team on 14 post-cutoff vulnerabilities without supplying their descriptions, reporting a 4.3× pass@1 improvement over GPT-4 without descriptions [18]. Weiss and Khayet demonstrated this same loop concretely for vulnerability exploitation, showing that an agent could take a published

CVE's advisory text and generate a working exploit against it in under fifteen minutes [3]. Their pipeline formed the direct basis for AI-exploit-CVE, the prototype this project extends. CVE-GENIE reproduced 428 of 841 selected CVEs and reported an average cost of $2.77 per CVE [19]. These larger-scale results provide context, while differences in case selection, validation and cost accounting prevent a direct performance or efficiency comparison with this project's fully described six-CVE catalogue with selective trace-level audits (Chapter 4).

What Weiss and Khayet's work established, and what it left open, both matter for how this project is scoped: they showed that advisory-to-exploit generation is tractable for an agent, but their evaluation, like much of the broader "AI can hack" literature this project's Introduction opens with [1], centres on the offensive capability itself rather than on how confidently a defender could trust the result. An exploit that an agent reports as successful and an exploit that has actually been shown to work against a representative target are not the same claim, and the literature reviewed here does not consistently distinguish between them.

PoC-Gym quantifies exactly this gap for Java CVEs: of 116 LLM-generated candidates that passed its own runtime validation (completed execution and produced a success signal), only 65 also passed post-hoc verification against the actual vulnerable code location: meaning 51 of 116 runtime-valid candidates failed its annotated-location verification [14]. This project's own dynamic-confirmation stage (Section 3.7.2) is designed against exactly this risk, replacing an earlier design where generated exploits were written to disk but never actually run with one that checks the exploit script's real process exit code; PoC-Gym's result is a reminder that this choice narrows the gap rather than closes it outright.

2.3 Cyber Reasoning Systems and the AIxCC/OSS-CRS Ecosystem

A Cyber Reasoning System generalises the single-exploit agentic loop into a full pipeline: discover an unknown vulnerability in a codebase, triage it, generate a proof of vulnerability, and generate and validate a patch, all without a human specifying the bug in advance. DARPA's AI Cyber Challenge (AIxCC) evaluated seven finalist CRSs (Atlantis, Buttercup, RoboDuck, FuzzingBrain, Bug Buster, Artiphishell, and Lacrosse) against a shared benchmark of synthetic vulnerabilities seeded into real open-source projects, with the finalists collectively discovering 54 of 63 seeded bugs (86%) and patching 43 (68%), per DARPA's own results announcement and, independently, the first systematic peer-reviewed analysis of the competition's design, architectures, and results [4, 17]. The winning system, ATLANTIS, combined LLM-driven reasoning with traditional program-analysis techniques across its discovery, triage, and patch-generation stages [5], and the Open Source Cyber

Reasoning System project (OSS-CRS) subsequently generalised several AIxCC-era systems into a common runtime so they could be pointed at real OSS-Fuzz projects rather than only the competition's own challenge problems [6].

Two things follow from reading AIxCC and OSS-CRS alongside Weiss and Khayet's narrower exploit-generation work, stated as an observation and a hypothesis rather than an established finding. AIxCC's aggregate 86%-discovery/68%-patch split, reported across seven finalist systems on a large competition benchmark, is not directly comparable in task, scale, or denominator to this project's own six-CVE confirmation/patch-validation results (Section 4.2.5), and this project's own patch-validation numbers have themselves been shown, by trace-level inspection, to include at least one false acceptance (Chapter 4): so neither figure should be read as an independently reliable measurement to compare against the other. What both bodies of work do suggest, more cautiously, is that generating a working patch may plausibly be harder than discovering or confirming the underlying bug across genuinely different systems and scales; this project's own results are consistent with that hypothesis without independently proving it holds as a general property of the task. Second, AIxCC and OSS-CRS finalists are primarily full discovery systems (they find vulnerabilities nobody has previously identified) though this is not absolute: FuzzingBrain, one AIxCC finalist, includes a documented mode for assessing externally supplied findings (for example, from static-analysis tools) rather than only its own discoveries [10], which is closer in spirit to a known-finding confirmation task than a pure discovery system. This project's own scope remains narrower still and more specific: it confirms and patches already-published CVE advisories specifically, with dynamic execution evidence for every case, rather than triaging static findings of unstated provenance. This project's scope is distinguished not by an assertion that known-CVE execution confirmation is absent from the field – CVE-GENIE, for instance, explicitly performs it – but by its particular combination: a small, fully described catalogue, documented harness defects, and an investigation of what each evidence tier can and cannot establish.

2.4 Reachability-Filtered Vulnerability Triage

A separate line of work addresses a different bottleneck: even once a codebase is the analysis target, an LLM or static analyser cannot practically reason over every function in a large real-world project. OpenAnt addresses this by decomposing a codebase into a call graph and performing breadth-first reachability analysis from attacker-controlled entry points, reporting scope reductions of up to 97% on real projects including OpenSSL, WordPress, and Flowise, before applying LLM-driven adversarial verification and sandboxed dynamic testing to the reduced candidate set [9]. An independently reported AIxCC finalist system, FuzzingBrain [10] (competition repository name `afc-crs-all-you-need-is-a-fuzzing-brain`), converges on a similar three-stage shape (static reachability partitioning,

LLM-based "suspicious point" triage, then fuzzing-driven verification) arrived at separately from OpenAnt's own design.

Read together, OpenAnt's and FuzzingBrain's independently-arrived-at similarity is at least suggestive that reachability-first filtering is not an idiosyncratic design choice specific to one system, though this observation rests on the small, non-systematic set of sources reviewed for this chapter rather than a comprehensive survey of the field, and should be read with that scope in mind.

Patch validation rigour in this literature varies: FuzzingBrain's own published validation criteria require a patch to compile successfully and to pass a supplied regression-test suite before being accepted [10], which is at least as strong as, and in the regression-testing respect stronger than, this project's own two-check acceptance criterion (Section 4.1.2). A stated criterion is not the same as a reliably enforced one, however, and FuzzingBrain's own paper reports this directly: a missing-parameter bug silently caused its Python validation subprocesses to fail during the competition itself, so that, in the authors' own words, "many patches were submitted without verification against known POVs" [10], discovered only in post-competition analysis. This gap between a patch passing validation and a patch actually being correct is not new to LLM-based repair, and is not unique to this project's own validator failure described in Section 4.1.2 either: Qi, Long, Achour, and Rinard's decade-old analysis of three classical generate-and-validate repair systems (GenProg, RSRepair, and AE) found that errors in the validation infrastructure itself meant most reported patches were not even plausible under their own test suites, and that almost all patches judged plausible were equivalent to deleting the relevant functionality rather than fixing it: establishing that passing a validation suite and being a correct patch have never been the same claim, well before LLMs entered the picture [16].

Two recent studies examine validation using different designs: VulnRepairEval reports low repair performance under exploit-based differential validation – requiring the original PoC to fail against the patched code, not merely that the patch applies – with even the best of twelve evaluated LLMs repairing only 5 of 23 real-world Python CVEs under that criterion [12]. PVBench separately quantifies overestimation by a weaker validation procedure: 42.3% of patch attempts that passed its basic checks (1,250 of 2,952) failed its stronger, developer-authored "PoC+" tests, which encode root-cause and specification intent beyond mere exploit-blocking [13]. This project's own round-5 false-acceptance finding (Section 4.2.2) (a patch accepted by a basic two-check criterion that trace-level inspection later showed was an unrelated crash, not a deliberate fix) is a single, concrete instance of the general validation problem these studies discuss; it does not replicate PVBench's paired comparison or VulnRepairEval's benchmark evaluation.

What distinguishes this project's own reachability work (Chapter 3) is not a general gap in the literature's rigour, but a specific combination: applying reachability-filtered triage to an already-disclosed CVE and verifying the resulting patch by cloning the actual

upstream repository and rebuilding it against that project's real, unmodified dependency graph. This project explicitly records that checkout, patch application, and rebuild step; the OpenAnt paper describes sandboxed exploit tests but does not report this particular rebuild-and-patch-compilation procedure, which supports a statement about what its publication documents, not proof its system never performs the step. This project's free5GC case study demonstrates the combination for one real vulnerability, detailed further in Chapter 3; it is offered as this project's own bounded implementation and validator-failure analysis, not as evidence that the wider literature lacks compile-time verification or known-CVE execution confirmation altogether (CVE-GENIE, for instance, explicitly performs known-CVE reproduction and verification [19]).

2.5 Research Gap

Three observations from the small set of sources reviewed above, taken together, motivate this project's objectives; they are offered as a rationale drawn from a limited, non-systematic review, not as a claim about the full field. First, agentic exploit generation (Weiss and Khayet, and the broader capability the Hugging Face incident illustrates [1]) has been demonstrated as tractable, but the evaluations reviewed here do not consistently separate "the agent reports success" from "the exploit was dynamically confirmed against a representative target": a distinction this project treats as a first-class requirement rather than an afterthought. Second, AIxCC-class systems are primarily oriented toward discovering previously unknown vulnerabilities at competition scale (with FuzzingBrain's external-finding assessment mode a partial exception); this project instead studies a narrower, everyday situation (triaging a dependency's already-disclosed CVE) with a lighter-weight, dynamic-evidence workflow scoped specifically to that task, without claiming from the small set of sources reviewed here that this situation is underserved by the field as a whole. Third, reachability-filtered triage (OpenAnt, FuzzingBrain) is established as an effective scope-reduction technique, with FuzzingBrain's case specifying stringent compile-and-regression-test validation criteria whose enforcement was itself undermined by a documented infrastructure bug, as discussed above; what remains specific to this project is combining that filtering technique with compile verification against a real, live-cloned upstream project's dependency graph for an already-disclosed CVE, rather than a claim that the wider literature omits compile-time verification.

This project studies the following combination under its own stated conditions, distinct from each source reviewed above in a specific, statable way. Building on Weiss and Khayet's own execution-based workflow (their published method already executes generated exploits against vulnerable and patched versions in a sandboxed evaluation loop, not merely generates and describes them statically [3]), this project added dynamic execution to the inherited local prototype it actually extends, AI-exploit-CVE, which had not yet

implemented that step; introduced a two-check patch-acceptance criterion and documented its own validator failures in detail; and evaluated selected real-upstream cases (Chapter 3). Unlike the evaluation described in OpenAnt's own 2026 arXiv paper [9], it verifies a reachability-filtered patch by cloning and rebuilding the actual upstream repository and checking it compiles against that repository's genuine dependency graph (Chapter 3). That comparison is against that specific, dated publication, not against OpenAnt the open-source project's current state, which has continued to develop since that paper. OpenAnt's repository, as of this writing, documents a separate "Auto Patcher" feature that likewise clones a real repository checkout and applies a candidate patch to a temporary copy of it, so "sandbox" is not treated here as the categorical opposite of "real upstream repository" for that current tool. Unlike the AIxCC-aggregate figures, this project reports its own exploit-confirmation and patch-acceptance rates across multiple models and multiple verification rounds on a small, fully described catalogue (Chapter 4), so its own discovery/patch pattern can be inspected directly rather than assumed to match AIxCC's aggregate. Findings for JavaScript and TypeScript, via the ProvTrail integration introduced in Chapter 1 (SARIF-based, [8]), extend this same evidence-gated approach to a second ecosystem.

Chapter 3

Methodology

3.1 Project Context

This project extends an existing single-vulnerability exploit-confirmation prototype, AI-exploit-CVE, into a two-part evidence-gated system for using large language models (LLMs) to secure open-source software: (1) LLM-assisted exploit confirmation and patch validation for already-published CVEs, and (2) reachability-filtered static analysis on real upstream source, applied to a disclosed vulnerability in free5GC, an open-source 5G core network implementation [7]. ATLANTIS and OSS-CRS (Chapter 2) inform this project's stage vocabulary and evidence-gating philosophy rather than being integrated as code: no component of ATLANTIS or OSS-CRS is imported, called, or run by this project, and Appendix A.6 states explicitly where the analogy between this project's stages and theirs holds and where it does not. A secondary integration links the pipeline to ProvTrail, a companion project that statically identifies JavaScript/TypeScript code resembling known-vulnerable implementations; this integration currently consists of SARIF ingestion plumbing (`provtrail_bridge.py`) and one hand-authored, dynamically confirmed JavaScript case (CVE-2024-48910, Prototype Pollution), not a systematic evaluation of ProvTrail's own flagged findings against real scanned projects, and this narrower scope is stated here rather than implied by the architecture description alone. The system falls under the Software System/Application category, with a Data Analytics component in its reachability-filtering and metrics stages.

3.2 Methodology Overview

This project was carried out in four main stages. First, the existing CVE-driven exploit-confirmation pipeline (advisory intake, vulnerability classification, exploit-artifact generation, dynamic execution, self-improvement on failure, and patch generation with regression validation) was extended and hardened against a catalogue of six published CVEs spanning

six vulnerability classes. Next, a reachability-filtering engine (ported from an earlier, standalone prototype developed for the same project before its scope was redirected) was applied to a real, disclosed CVE in free5GC, producing an AST-based call graph reduction and a patch verified to compile against the actual upstream dependency graph. This was followed by the integration of ProvTrail's SARIF/AI-text export as an additional advisory source, allowing the pipeline to be driven by statically located JavaScript/TypeScript findings rather than only by NVD/GHSA feed entries. Finally, the system was evaluated across multiple rounds of live, locally hosted LLM verification (using Ollama-served open-weight models [11]), during which two implementation defects were identified, fixed, and re-verified, and the pipeline's evidentiary claims were confirmed to hold under live model generation as well, not only under stubbed responses.

High-level workflow

1. Advisory intake: fetch a CVE/GHSA advisory, or consume a ProvTrail-flagged finding, as the unit of work.

2. Vulnerability classification: categorise the advisory into one of six classes (SSRF, SQL injection, OS command injection, XSS, path traversal, deserialisation), or, for a memory-safety-class advisory, dispatch to the main pipeline's own dedicated probe (`_probe_memory_safety`), which generates and compiles a minimal C proof-of-vulnerability harness directly; this is a separate mechanism from, and does not call into, the reachability engine described in step 7 below, which operates independently on real upstream Go/C/C++ source rather than on advisory text.

3. Exploit-artifact generation: synthesise a proof-of-concept and a minimal reproduction target from the advisory's described bug pattern.

4. Dynamic execution: run the generated artifact against the reproduction target and record a real process exit code / HTTP response as evidence.

5. Self-improvement: on a genuine, executed failure, attempt a fix via a persisted lesson, then an LLM-generated revision, then a rule-based fallback, bounded to three iterations.

6. Patch generation and validation: generate a candidate patch and accept it only if the original exploit now fails against it and the target's health check still passes. This is the original acceptance criterion as first implemented; Chapter 4 reports a discovered flaw in it and the stronger, four-outcome `patch_verdict` criterion this project uses as its headline patch metric from that chapter onward.

7. Reachability analysis (parallel track): parse real upstream source into an AST-derived call graph, perform breadth-first reachability from stated entry points, and generate and compile-verify a patch against the real dependency graph.

8. Reporting and metrics: aggregate per-CVE outcomes into structured reports and summary metrics (confirmation rate, patch-acceptance rate, reachability reduction, wall-clock time, LLM call count).

3.3 Alternative Approach Considered

Before continuing with the existing advisory-driven architecture, a proposed redesign was evaluated and deliberately not adopted: replacing CVE-driven exploit confirmation with a pipeline in which an LLM reads raw source code with no prior knowledge of any specific advisory, hypothesises a vulnerability from scratch, synthesises a triggering input purely by reasoning rather than by search or mutation, and validates the hypothesis by replaying that input once against an instrumented build. This alternative was rejected for four reasons. First, its own proposed validation plan (a single smoke test against one example file) was judged insufficient grounds to commit to restructuring the project's architecture before that assumption was independently tested. Second, this project's existing exploit-artifact generation is always guided by an advisory's own stated root cause, a materially easier task than zero-shot vulnerability hypothesis generation with no prior knowledge, so this project's own results do not transfer as evidence that the alternative's harder, blind variant would work. Third, the proposal would have introduced a second, disconnected system rather than extending the existing, already-validated pipeline. Fourth, it required setting up new local model infrastructure for a speculative direction while the existing, evidence-gated pipeline was already in a documented, working state. This alternative remains available to revisit as a bounded, separately-evaluated extension, but was not adopted as the basis for this project.

3.4 System Architecture

3.4.1 System Description

The system consists of two loosely coupled subsystems sharing a common advisory-driven design philosophy. The first, the main exploit-confirmation pipeline, is orchestrated by `cve_pipeline.py` and driven by a feed poller (`cve_watcher.py`) that dispatches pipeline runs for newly observed advisories from NVD, GHSA, or ProvTrail. The second, the reachability-filtering engine (`src/reachability/`), operates independently on real upstream source rather than on advisory text, and is invoked directly against a stated set of entry-

point functions. A supporting bridge module (`provtrail_bridge.py`) converts ProvTrail's SARIF output into advisories the main pipeline can consume, and two standalone dynamic-exploitation labs (`ssrf_lab/`, `free5gc_lab/`) provide locally hosted, self-controlled targets for live confirmation where a generic Flask stand-in would not suffice.

3.4.2 Major System Components

Table 3.1: Major system components and their functions.

Component / Module	Function
`cve_pipeline.py`	Orchestrates advisory fetch, classification, artifact generation, dynamic execution, self-improvement, and patch generation/validation for a single CVE.
`cve_watcher.py`	Polls NVD, GHSA, and ProvTrail feeds on a fixed interval and dispatches pipeline runs across parallel workers.
`provtrail_bridge.py`	Converts ProvTrail's SARIF/AI-text export into advisories consumable by the main pipeline, falling back to NVD/GHSA when no scan is available.
`src/reachability/`	Performs tree-sitter-based AST parsing, call-graph construction, breadth-first reachability filtering, adversarial triage, and rule-based or LLM-based patch generation on real upstream source.
`src/pipeline/patch.py`	Generates a candidate patch for a confirmed exploit and validates it via a two-check regression test, the original criterion described here as first implemented; Chapter 4 reports this criterion's own discovered flaw and the four-outcome `patch_verdict` criterion that supersedes it as this project's headline patch metric.
`src/metrics.py`	Aggregates confirmation rate, patch-acceptance rate, wall-clock time, and LLM call count across the report catalogue.
`free5gc_lab/`	A dependency-free Go reproduction of a disclosed free5GC vulnerability, dynamically exploited and patched in isolation from the main pipeline.
`ssrf_lab/`	A local FastAPI target providing genuine live-traffic confirmation for the SSRF vulnerability class.

3.4.3 Architecture Diagram

A system architecture diagram is included as Figure 3.1 below (landscape orientation, for legibility), illustrating the flow from advisory intake through classification, artifact

generation, dynamic execution, self-improvement, and patch validation. Figures 3.2 and 3.3 detail two supporting mechanisms: the interpreter branch that routes Stage 3.6 execution to `python` or `node` depending on target file extension, and the shared live-model backend used by Stages 3.5, 3.7, and 3.8. All three diagrams are rendered directly from this project's own `architecture.html` source, not redrawn.




Figure 3.1: System architecture: advisory-driven exploit confirmation pipeline, from advisory intake through classification, dynamic execution, self-improvement, and patch generation/acceptance.




Figure 3.2: The Stage 3.6 interpreter branch: routes execution to `python` or `node` depending on target file extension.




Figure 3.3: The shared live-model backend used across Stages 3.5, 3.7, and 3.8, including the persisted-lesson store.

3.5 Data Sources and Preprocessing

3.5.1 Advisory and Source Data

Table 3.2: Advisory and source data used in evaluation.

Item	Description
Advisory sources	NVD API v2, the GHSA feed, and ProvTrail's SARIF/AI-text export
Advisory volume (main catalogue)	Six CVEs, spanning six vulnerability classes (SQL injection, OS command injection, XSS, path traversal, deserialisation, SSRF)
free5GC: CVE-2026-40246 (hand-written reproduction)	Evaluated separately as a hand-written Go reproduction (`free5gc_lab/`), dynamically exploited and patched at runtime; a hand-written target, so no upstream commit hash applies to this specific artifact
free5GC: CVE-2026-40245–40248 (real upstream source, four selected handlers)	Evaluated against the real, cloned `free5gc/udr` upstream source at four selected handlers of one file, all sharing one missing-`return` root cause and one shared upstream fix commit, with a documented fix commit and a build check at the pre-fix revision for all four; all four handlers additionally run at runtime against a fuller deployment (a real MongoDB instance and a real free5GC NRF, OAuth2 disabled) (Section 3.8.2). The DELETE handler of this real-source evaluation is CVE-2026-40246's own real-upstream counterpart to the hand-written reproduction above, not a separate CVE from it.
Upstream source data	Real, verbatim free5GC/UDR source (`internal/sbi/api_datarepository.go`), fetched at the commit before and the commit of the disclosed fix, approximately 86 KB, 102 parseable functions

3.5.2 Preprocessing Steps

Advisory text was parsed to extract the vulnerability class, affected package, and any code-diff snippet included in the advisory. Where a code diff was present, it was used for static pattern matching during classification. For the reachability track, the fetched

Go source file was parsed using a tree-sitter grammar into an abstract syntax tree, from which function definitions and call edges were extracted to construct a directed call graph. A stated list of four real HTTP entry-point handlers was then used as the seed set for breadth-first reachability traversal.

3.6 Algorithms and Models Used

3.6.1 Model and Algorithm Selection

Table 3.3: Representative models and algorithms invoked by the pipeline (not the full eight-model comparison, which is reported in full in Table 4.6).

Model / Algorithm	**Purpose**
Claude CLI / pydantic-ai agent backend	Advisory analysis, exploit-artifact generation, and patch generation when a hosted API or CLI session is available
Ollama-served `qwen2.5-coder:7b` (local, no API key)	Live-model verification of exploit-artifact generation and self-improvement revision
Ollama-served `qwen2.5-coder:1.5b` and `mistral:7b` (local)	Comparative live-model backends evaluated across verification rounds
Rule-based heuristics (e.g. `find_missing_return_after_response`)	Deterministic, offline fallback patch generation requiring no LLM call
Tree-sitter AST parsing + breadth-first search	Reachability filtering: construction of a call graph and traversal from stated entry points

The first table row names two distinct backends, not one interchangeable mode. All comparisons reported in Chapter 4 used code-orchestrated model calls with bounded, code-triggered feedback revisions (Stage 3.7), not autonomous tool selection: the Claude CLI calls specifically disabled tool access (`--tools ""`) and session persistence (`--no-session-persistence`) using its own CLI flags, to obtain a single, stateless text completion rather than an agentic session with file or shell access; the other access paths (local Ollama, the OpenAI API, the Codex CLI, and AIxTech) used their own direct API or CLI configurations, not these same Claude-specific flags, and none of them exercised autonomous tool selection either. The separate, optional pydantic-ai agent-backend mode, which can select tools via `RunContext`, instead registers and can call tools spanning advisory

fetch, vulnerability analysis, the live probe, and report compilation (Stages 1 through 4, not only advisory analysis); it is a distinct execution path available when a hosted API key is configured, and its tool-selecting behaviour is not what the Chapter 4 comparisons measured, nor does it extend to the later exploit-artifact or patch-generation stages.

3.6.2 Key Parameters and Settings

Table 3.4: Key parameters and settings.

Parameter	**Value**	**Reason**
Self-improvement iteration bound	3	Prevents unbounded LLM cost or looping past a signature with no known fix
Feed poll interval	60 minutes	Balances advisory freshness against feed rate limits
Parallel workers	2	Bounds concurrent LLM/API load while allowing cross-CVE parallelism
Reachability entry-point set	4 handlers	Four manually selected real HTTP handlers used as BFS seeds, not a proven-complete enumeration of the module's externally reachable surface

3.7 Implementation Details

3.7.1 Programming Environment

Table 3.5 summarises the languages, libraries, and hardware the system was implemented and evaluated with.

Table 3.5: Programming environment.

Item	Details
Programming languages	Python (pipeline orchestration, pydantic data models, reachability engine); Go (free5GC target reproduction and the real upstream module under test)
Libraries / frameworks	pydantic-ai (agent orchestration), tree-sitter (AST parsing), Flask (main-catalogue reproduction targets), FastAPI (`ssrf_lab/`), Go's standard-library `net/http` (dependency-free lab server)
Hardware	13th Gen Intel Core i9-13980HX, 16 GB RAM, NVIDIA GeForce RTX 4060 Laptop GPU (Ollama-served models ran on this GPU); Windows 11 Home, build 10.0.26200. One locally hosted model, `deepseek-coder-v2:16b`, failed to load at all under this configuration: a CPU-side system-RAM allocation failure (requesting a 45 GB buffer against 16 GB available), unrelated to the GPU (`docs/FREE5GC_LLM_MODEL_SWEEP_RESULTS.md`).

3.7.2 Implementation Procedure

The system was implemented incrementally, in the following order. First, the pre-existing exploit-confirmation pipeline was extended with dynamic execution, replacing an earlier design in which generated exploit artifacts were written to disk but never actually run. Self-improvement was then added as a bounded retry loop consulting, in order, a persisted-lesson store, an LLM-generated revision, and a rule-based fallback. Patch generation and validation was implemented next, gated on two simultaneous conditions: the original exploit failing against the patched target, and the target's health check continuing to pass. The reachability engine was subsequently ported from an earlier standalone prototype and re-validated against its own prior results before being applied to real free5GC source, first as an isolated file parse and later against the actual cloned upstream repository to confirm compile-compatibility with its full dependency graph. The ProvTrail bridge and the free5GC dynamic-exploitation lab were implemented as independent, loosely coupled additions, following the same dual vulnerable/patched-mode convention already established elsewhere in the system. Finally, the system was run across successive live-model verification rounds; two defects that surfaced during this process (Section 4.2.1) were each isolated with a targeted test, fixed, and verified via a full-catalogue re-run.

3.8 Testing and Validation

3.8.1 Testing Strategy

The system was tested by executing every generated exploit artifact as a real subprocess against a real, locally deployed target and recording its actual exit code or HTTP response, rather than treating generation as evidence of exploitability by itself. Patch validation was tested by re-running the original, unmodified exploit against the patched target and independently confirming a separate `/health` endpoint still responded correctly, so that a patch which crashed the target process entirely would be rejected. This check does not confirm that the vulnerable route itself still behaves correctly for a legitimate request, only that the application as a whole is still running; Chapter 4 reports a case where this specific gap allowed a patch containing an unrelated crash bug to be marked validated. For the reachability track, the generated patch was tested for compile-compatibility by cloning the actual upstream repository at the pre-fix commit, applying the patch to the real source file, and rebuilding against the module's genuine dependency graph. The DELETE handler (CVE-2026-40246) was first tested at runtime using a minimal local harness. A fuller Docker deployment with a real NRF subsequently extended runtime testing to all four selected handlers (CVE-2026-40245 through CVE-2026-40248, Section 3.8.2).

3.8.2 free5GC Runtime Validation Harness

The four selected handlers analysed in this case study share one missing-`return` root cause and one shared upstream fix commit, but are four separately disclosed CVEs, not four symptoms of a single CVE. Table 3.6 states the mapping used throughout this chapter; it corrects an earlier, imprecise shorthand (retained verbatim in some places this project's earlier work already cited as "CVE-2026-40248, all four handlers") that attributed every handler's behaviour to CVE-2026-40248 specifically.

Table 3.6: free5GC handler-to-CVE mapping (one shared root cause, one shared fix commit, four separate CVE identifiers).

Handler	**CVE**	**CWE(s)**	**GHSA**
Collection GET (empty filter)	CVE-2026-40245	CWE-200, CWE-202, CWE-209	GHSA-wrwh-rpq4-87hf
DELETE subscription	CVE-2026-40246	CWE-285	GHSA-g9cw-qwhf-24jp
Single-record GET	CVE-2026-40247	CWE-285	GHSA-x5r2-r74c-3w28
PUT (create/modify)	CVE-2026-40248	CWE-285, CWE-636	GHSA-jgq2-qv8v-5cmj

Three of the four handlers (DELETE, single-record GET, PUT) are disclosed under CWE-285 (improper authorisation check); the fourth, collection GET, is disclosed as CWE-200/202/209 (information exposure). Section 4.1.7 reports how this project's own rule-based classifier's output compares against these four disclosed labels. The DELETE handler (CVE-2026-40246) is additionally the real-upstream counterpart to this project's separate, hand-written `free5gc_lab/` reproduction of the same CVE: the same CVE validated two ways, at two evidence tiers, not two different CVEs.

The real, cloned `free5gc/udr` module was built twice from source, once at the vulnerable commit and once at its immediate successor, the real upstream fix commit. Both builds require a reachable MongoDB instance to start; a native MongoDB Community Server instance, run locally rather than inside a container, was used, since the experiment's only real infrastructure dependency was UDR's own database connection, not full containerisation. Both builds also require a reachable Network Repository Function (NRF) to complete their own startup: UDR's registration call to the NRF blocks its HTTP server from starting at all if it never succeeds, an infinite retry with no timeout, so a minimal stand-in NRF, answering only the one registration call UDR needs and asserting no broader NF-discovery capability, was required purely to let each build reach the point of serving real HTTP traffic. This stand-in had itself to be implemented as a small compiled Go program communicating over cleartext HTTP/2 (h2c), rather than a simpler HTTP/1.1 script, because free5GC's own NRF client negotiates HTTP/2 unconditionally and rejects an HTTP/1.1 responder outright. With both dependencies satisfied, each build was driven through an identical request sequence over real HTTP: seed a subscription record, issue the CVE's malicious delete request, check whether the record still exists, reseed, issue a legitimate delete request for the same record, and check again: with every request, response, and process log captured as part of the resulting evidence bundle rather than only the final pass/fail outcome.

This minimal harness was subsequently extended to a fuller deployment and to the three remaining reachable handlers, using the official `free5gc-compose` Docker stack rather than the hand-written stand-in above: a real, official MongoDB image and a real, official free5GC NRF image (not a minimal stub), with a custom-built UDR image compiled from the same pinned vulnerable and fixed commits. OAuth2 enforcement, which the real NRF enables by default and which would otherwise require a full OAuth2 client-credentials flow unrelated to the vulnerability under test, was explicitly disabled in the NRF's configuration for this harness; this is a real, supported free5GC configuration option, not a synthetic bypass, but it means this result alone says nothing about whether OAuth2 enforcement would affect an attacker's ability to reach these handlers in a deployment that has it enabled (a later, separate follow-up, Section 4.1.10, closes part of this gap for two of the four handlers' read operations specifically). Under this fuller deployment, all four of the reachability engine's originally-flagged handlers (not only the DELETE handler) were driven through a malicious request and a seeding/setup write, with every request, response, and container log captured; a single explicit benign-request check (a legitimate single-record read with the correct `infIuenceId`) was run once per build and used as this harness's overall benign-path signal, not repeated as a separate, independently content-checked legitimate request for every handler.

This project does not use a training/testing split or k-fold cross-validation; it is not a statistical learning system. Instead, validation ran across five successive live-model rounds of the full CVE catalogue, with each round's failures traced to a specific, named cause before the next round was attempted, rather than accepted as unexplained noise.

3.9 Evaluation Metrics

Table 3.7: Evaluation metrics and their justification.

Metric	**What It Measures**
Confirmation rate	Proportion of catalogued CVEs whose described bug pattern was dynamically confirmed exploitable, varying by round (1/6, 2/6, 1/6, 4/6, 5/6 across rounds 1–5; 5/6 is round 5's own best result, not this metric's fixed value)

continued on next page

Metric	What It Measures
Two-check patch acceptance rate	Count of catalogue cells (CVE–model pairs, out of every cell attempted, confirmed or not) for which a generated patch met both conditions of the pipeline's own `patch_validated` field (the original PoC no longer succeeds, and a separate health endpoint still responds), reported throughout this chapter as accepted/total-cells (e.g. 3/48), not accepted/confirmed-exploits or accepted/patch-attempts, which are smaller, different denominators (3/11 and 3/9 respectively for that same retest) answering a narrower question; first achieved in round 4, after zero acceptances across three prior rounds; this metric does not measure benign-route preservation or repair correctness, and is superseded as this project's headline patch metric by the corrected `patch_verdict` field (Section 4.1.2), retained here and throughout for continuity with earlier rounds
Reachability reduction	Percentage reduction in functions requiring analysis after BFS filtering (96.1%, 102 reduced to 4)
Wall-clock time per CVE	Runtime cost of a full pipeline run, as a practicality indicator

continued on next page

Metric	What It Measures
LLM call count, wall-clock time, and recorded API cost (USD)	Real, per-call figures read directly from the Claude CLI's or Ollama's own token/duration fields. Every Ollama-backend call in this evaluation records $0.0000, a genuine zero *billed API charge* from local, unmetered inference, not zero underlying compute cost, which was not separately measured. Claude CLI calls initially recorded no cost figure at all, since the CLI's plain-text output mode exposes no usage metadata; switching to its structured JSON output mode (Section 4.1.6) exposes a non-zero `total_cost_usd` per call, used directly in Table 4.7. Per Anthropic's own documentation, this figure is computed locally from token counts at list price and is itself labelled an estimate, not a verified billing record; this project did not independently verify it against an account billing ledger

These metrics were selected to mirror the vocabulary used by DARPA's AI Cyber Challenge and the OpenSSF's OSS-CRS project to report cyber-reasoning-system results (bugs confirmed against bugs attempted, proof-of-vulnerability confirmation rate, and patch-acceptance rate) so that this project's results can be read against the same benchmark context introduced in Chapter 1, rather than against an ad hoc scale.

To keep these terms precise across the results reported in Chapter 4, evidence tiers are distinguished explicitly rather than collapsed into a single pass/fail label.

Dynamically confirmed means a recorded subprocess execution outcome, HTTP exchange, or compiled-harness run, each real and not a static description.

Patch accepted by the two-check criterion means the original, unmodified proof-of-concept no longer meets its success condition against the patched local target, while a separate `/health` request still succeeds. This checks exactly one attack input and application liveness; it does not establish that the affected route handles a legitimate request correctly, that other attack inputs are blocked, or that the named upstream package has been repaired. This project does not use the term "plausible patch" or claim "regression-safety" for this flag: Chapter 4 reports a specific case (CVE-2026-78683, round 5) where the tested exploit request crashed the patched route with an unrelated import error, and this satisfied the exact criterion above, which is why a stronger label would overstate what it proves. This criterion is also weaker than the

patch-validation bar used by at least one real AIxCC finalist system, FuzzingBrain, whose own published criteria require a patch to compile, eliminate all known proofs of the vulnerability, and pass a supplied regression-test suite [10]. This project's own two-check criterion does not match that three-part bar, though FuzzingBrain's own stricter bar was itself silently undermined by a validation-infrastructure bug during the competition (Chapter 2 discusses this further), a failure mode of the same general kind this project independently found and corrected in its own pipeline.

A further tier, "correct" patch (one independently checked against the real upstream fix's own intent, or against benign-request and multi-payload behaviour, rather than only against the one exploit that triggered it) is, at this stage of the pipeline, not yet measured by this project across the main catalogue; no second-reader adjudication against the real upstream fix's own intent is performed anywhere in this project, and this project's own patch-validation investigation (Section 4.1.2) shows why that distinction matters in practice. The benign-request half of this gap is later closed, for a bounded set of cases, not left purely as a limitation: Section 4.1.2's content-verified reassessment checks benign-path behaviour against real expected content of varying granularity per class (full JSON equality, a specific field value, or a substring check) for 6 recoverable patched artifacts, and the three real-upstream cases (Sections 4.1.3, 4.1.4, and 3.8.2) use case-specific response-content or state checks against actual software, detailed per case in those sections rather than a uniform full-response-equality protocol. These remain bounded observations for the tested inputs, not a guarantee of general patch correctness, and second-reader adjudication specifically remains unmeasured throughout the whole project.

Diff-similarity scoring is also not purely absent: a separate, later free5GC-specific study (`docs/PATCH_QUALITY_SCORING_RESULTS.md`) line-diffed 14 already-generated free5GC patches for one target function against the real upstream fix's own version of that function, finding 9 of 14 byte-identical and the remaining 5 (all smaller Ollama models) differing by 1–3 lines. Of those 5, 4 passed every recorded runtime check (`confirmed_fix_all_four_handlers`); the fifth, `qwen2.5-coder:1.5b` (95.52% textually similar to the real fix, differing by only 1–2 lines), did not: its own runtime sweep records `collection_get_leak_fixed: false` and `overall_verdict: partial_or_inconclusive`, the same partially-correct patch already discussed in Section B.4 (it appends an unrelated response line rather than the needed `return`). This is a useful illustration in its own right: high textual similarity to the real fix does not by itself establish that the patch is functionally correct. This is a textual-similarity proxy on one narrow, single-statement fix, not a semantic-correctness guarantee or a second-reader adjudication, and does not extend to the main catalogue's patches.

Compile-verified describes the free5GC reachability case study's original compile-only evidence and means `go build` succeeds against the real, live-cloned upstream module with the patch applied: explicitly weaker evidence than dynamic confirmation, and never reported in the same column without this qualification.

Runtime-confirmed All four of that case study's reachable handlers (CVE-2026-40245 through CVE-2026-40248, Table 3.6) were subsequently runtime-confirmed: the real, cloned module was built, run, and exercised over real HTTP for both the vulnerable and fixed commits, first against a minimal MongoDB-only stand-in (Section 3.8.2) for the DELETE handler, then against a fuller deployment (real MongoDB and a real free5GC NRF, OAuth2 disabled) for all four handlers, meeting the same dynamically confirmed bar defined above rather than the weaker compile-verified one.

3.10 Limitations and Assumptions (Method-Related)

The methodology rests on several stated assumptions and bounds, listed here individually rather than run together, so each can be checked on its own terms.

1. **Reproduction versus the real package.** The methodology assumes that a faithful reproduction of an advisory's described bug pattern is representative evidence of that bug class, even where the reproduction target is a minimal stand-in rather than the actual named upstream package. For the six main-catalogue CVEs, the exploited target is a generated Flask application reproducing the described pattern; a confirmed exploit therefore demonstrates that the described pattern is exploitable as written, not that the real, named package is exploitable when actually installed and run. The SSRF probe performs live HTTP and callback checks against a controlled lab reproduction, not the real, named `lmdeploy` package.

2. **Static pattern matching versus dynamic evidence.** Four of the remaining five classes (SQL injection, OS command injection, XSS, deserialisation) rely on static pattern matching at the probe stage, with dynamic evidence instead attributed to the execution step. The fifth, path traversal, is a partial exception at this specific stage: its probe (`_probe_path_traversal`) also runs a generic, target-independent runtime demonstration that a `"../"`-style path genuinely escapes a sandboxed base directory under Python's own path-join semantics, which is a real executed check, not a regex match; it does not execute the named package's own vulnerable function, so it remains distinct from, and weaker than, the execution-step evidence described next.

3. **What the two-check patch-acceptance criterion does and does not show.** A patch accepted by this project's two-check criterion has only been shown to make one known exploit request fail while a separate health endpoint still succeeds; this is not general correctness, not freedom from all other exploitable inputs, and (established by direct trace inspection in Chapter 4) not even reliably regression-safe, since the criterion cannot distinguish a deliberate security fix from an unrelated crash bug in the generated patch, both of which produce the same observable pattern (the exploit request fails, the separate `/health` endpoint still returns 200). Neither check currently confirms that the patched route itself still behaves correctly for a legitimate, non-malicious request (only that the application process as a whole remains alive), which is a concrete direction for strengthening the validation criterion, not merely a hypothetical one, since Chapter 4 reports a case where this exact gap produced a false acceptance. A corrected validator, introduced later in Chapter 4 (Section 4.1.2), strengthens the exploit side of exactly this gap by distinguishing a deliberate rejection from a crash; its own benign-route check, however, was itself found to require only crash-absence rather than correct behaviour, so this limitation is narrowed, not resolved, and the same caution applies to reading its own results.

4. **The free5GC reachability case study's compile-to-runtime progression.** The free5GC reachability case study's four handlers were originally verified only to compile against the real upstream dependency graph, which is a real but bounded result: it does not by itself constitute dynamic confirmation, and one handler is additionally known to be only partially correct under the project's own rule-based patcher (Chapter 4), fully preserving compilation but not fully closing its handler's vulnerability under that generated patch (the real upstream fix used for runtime testing does not share this limitation). All four handlers were subsequently taken further, by a narrower route than a full core-network deployment: neither the minimal MongoDB-only harness nor its fuller successor stands up free5GC's other network functions (AMF, SMF, and the rest), and the fuller deployment's real NRF was run with OAuth2 enforcement disabled, so this remains real dynamic confirmation for this one file's four handlers under that specific configuration, not evidence that free5GC's broader core-network behaviour would confirm the same way under this stronger standard. A later, separate follow-up (Section 4.1.10) closes part of the OAuth2 gap specifically, for two of the four handlers' read operations, finding enforcement does not change their exploitability by a credentialed caller; this does not extend to the write and delete handlers or to the broader core-network question.

5. **Stubbed versus live-model verification.** LLM-dependent pipeline stages were first verified using stubbed model responses to establish that the surrounding

logic functioned correctly, and were subsequently confirmed to operate under live model generation for exploit-artifact generation, self-improvement, and patch generation alike: every patch attempt in the eight-model local catalogue comparison (Section 4.1.5) used real, metered Ollama calls, not a stub; the later 36-run hosted-Claude comparison (Section 4.1.6) and the further OpenAI/Codex/AIxTech sweeps (Section 4.1.9) likewise used real, metered calls to their respective backends, not Ollama.

6. **The free5GC LLM-generated patch sweep's own under-fit cases.** The reachability engine's own separate LLM-based patch fallback was initially verified only via stub, since the free5GC case study's original patches were produced by its rule-based path instead; this was subsequently closed (Section B.4) by asking real local and hosted models to generate the fix for the one handler the rule-based patcher under-fixes, from scratch, with 6 of 8 local models (7 compiled) and 7 of 8 hosted Claude models passing the existing four-handler runtime harness. Two of those 8 local-model outputs illustrate different limitations, one of them not among the 6 passes: `qwen2.5-coder:1.5b`'s patch compiled but did not pass the runtime harness at all, recorded as `partial_or_inconclusive`; `codellama:13b`'s patch did pass the harness and is 98.51% textually similar to the real fix, but closer static inspection shows it still omits the required `return` on the malformed-`snssai` branch, a branch the harness's own request set never exercises (Section B.4). A harness pass should accordingly be read as passing the specific branches this harness exercises, not as an exhaustive repair guarantee for the handler.

Chapter 4

Results and Discussion

4.1 Results

Table 4.1 gives a consolidated view of the major experiments reported in this chapter (the classification ablation and the repeatability checks are not separately rowed): what was exploited or patched, whether the patch came from a real upstream maintainer or a model, what standard of evidence it was checked against, how many cases were run, and the headline outcome, so a reader can locate any number's evidence tier and scale without reconstructing it from the surrounding prose. The detailed, per-round and per-model results each row summarises follow below.

Table 4.1: Consolidated overview of the major experiments reported in this chapter.

Experiment	**Target**	**Patch source**	**Validation standard**	**N**	**Headline outcome**	**Ref.**
Six-CVE catalogue, 5 Ollama rounds	Generated reproduction	Model-generated	Two-check (`patch_validated`)	6×5	Confirmed up to 5/6 per round; patches accepted 0–1/6 per round	4.2.1
Eight-model Ollama comparison + bug-fix retest	Generated reproduction	Model-generated	Two-check	48, 48	Confirmed 17/48, then 11/48; patches accepted 0/48, then 3/48 (uncontrolled for alternate payloads)	4.1.5
Real upstream: `jaraco.context` (CVE-2026-23949)	Real, pinned-version PyPI package	Real upstream maintainer fix	Content-verified, 4-way	1	`confirmed_fix`	4.1.3
Real upstream: OpenEMR (GHSA-q366-cv5v-83w8)	Real, unmodified application	Real upstream maintainer fix	Content-verified, 3-request	1	`confirmed_fix`	4.1.4

continued on next page

Experiment	Target	Patch source	Validation standard	N	Headline outcome	Ref.
free5GC CVE-2026-40246, DELETE handler	Real, cloned upstream source	Real upstream maintainer fix	Runtime-confirmed	1 handler	`confirmed_fix`	3.8.2
free5GC CVE-2026-40245/6/7/8, all 4 handlers (fuller deployment)	Real, cloned upstream source	Real upstream maintainer fix	Runtime-confirmed	4 handlers	`confirmed_fix_all_four_handlers`	3.8.2
36-run hosted-Claude comparison	Generated reproduction	Model-generated	`patch_verdict` (heuristic screening)	36	36/36 exploits confirmed; 27/36 `confirmed_fix` (heuristic)	4.1.6
Content-verified reassessment of 6 survivors	Generated reproduction (surviving artifacts)	Model-generated	Content-verified (malicious: marker-absence only; legitimate: content-checked)	6	6/6 passed bounded checks	4.1.2

continued on next page

Experiment	Target	Patch source	Validation standard	N	Headline outcome	Ref.
free5GC LLM-generated patch sweep (Ollama + Claude CLI)	Real, cloned upstream source	Model-generated, one handler	Compile + runtime (recorded harness checks only)	8, 8	6/8 Ollama, 7/8 Claude confirmed all four handlers	B.4
free5GC adversarial bypass probe (Ollama + Claude CLI)	Real, already-patched upstream deployment	n/a (bypass attempt)	Real HTTP execution against the patched target	8, 11	0 genuine bypasses, either backend	B.5
OpenAI API sweep (free5GC patch/bypass, OpenEMR patch/bypass)	Real upstream source and application	Model-generated	Compile/runtime (free5GC); content-verified (OpenEMR)	23×4	18/23, 0/23, 16/23, 0/23 respectively	4.1.9
Codex CLI sweep (free5GC patch/bypass)	Real, cloned upstream source	Model-generated	Compile + runtime	18, 18	7/18 confirmed all four handlers; 0 genuine bypasses	4.1.9

continued on next page

Experiment	Target	Patch source	Validation standard	N	Headline outcome	Ref.
AIxTech gateway (direct Claude API)	Mixed (free5GC, OpenEMR, catalogue)	Model-generated	Varies by experiment family	4 (10 requested)	4/4 clean gate; 12/12 stable across a 3-run repeatability check	4.1.9
Catalogue XSS browser replay	Generated reproduction	Model-generated bypass proposals	Direct browser execution	33	0/33 genuine browser-execution signal (18/33 raw-marker positive)	4.1.9

4.1.1 Exploit Confirmation Across the CVE Catalogue

The five rounds reported in this section are five evolving pipeline runs, not repeated trials of one constant, held-fixed system: code, prompts, the persisted-lesson store, and (for round 5) sampling parameters all changed between at least some rounds. They should not be read as a controlled model comparison in the way Section 4.1.5's single-protocol, single-snapshot eight-model comparison can be. Table 4.2 shows the number of catalogued CVEs dynamically confirmed exploitable across five successive verification rounds, each run against the same six CVEs under a fixed, single-shot-per-CVE protocol within that round. Throughout this chapter, a "confirmed" flag means the described bug pattern was reproduced and dynamically triggered in a generated stand-in target (Section 3.10); it is not independent evidence the corresponding named upstream package is exploitable when actually installed and run.

Table 4.2: Dynamic confirmation rate by round.

Round	**Confirmed**	**Change from previous round**
Round 1	1/6 (17%)	Baseline (first round)
Round 2	2/6 (33%)	net +1: gained SSRF and XSS, lost SQLi (confirmed round 1)
Round 3	1/6 (17%)	−1 (net; Path Traversal newly confirmed, two prior confirmations lost)
Round 4	4/6 (67%)	+3
Round 5	5/6 (83%)	+1




Figure 4.1: Dynamic confirmation rate across the five catalogue verification rounds (Table 4.2). The non-monotonic dip at Round 3 and the jump at Round 4 are discussed in Section 4.2.1.

Considered across all five rounds rather than any single round in isolation, all six vulnerability classes in the catalogue confirmed dynamically at least once; no class was permanently unconfirmable. Round 4 corrected two implementation defects that had been suppressing round 3's result: an unstripped markdown code fence in model-generated output, present in four of round 3's five unconfirmed cases, and a stale exit-code/confirmation field not reset when a target crashed before its health check. Zero of round 4's and round 5's six reports contained the fence-crash signature, checked programmatically against every execution log.

4.1.2 Patch Generation and Validation

Across rounds 1–3 of the main pipeline's live-LLM catalogue runs, zero of the attempted patches were accepted by both conditions of the two-check criterion (the original exploit failing against the patched target, and the target's health check continuing to pass). Round 4 and round 5 each produced one patch accepted by this criterion, both for CVE-2026-78683 (Insecure Deserialization) and both resulting in the patched target returning HTTP 500 when the original exploit was re-run, satisfying the pipeline's first condition.

Trace-level inspection of both patches found the two HTTP 500 responses have different, and differently trustworthy, causes. Round 4's patched handler deliberately raises `ValueError("Deserialization only allowed for safe classes")` from an added class whitelist, consistent with the patch summary's own description and plausibly a genuine security fix, though this project's evidence for it stops at that trace-level reading.

Round 5's patched handler, by contrast, raises `NameError: name 'io' is not defined`: the generated patch called `io.BytesIO(...)` without importing the `io` module, a plain implementation bug, not a security check of any kind (both traces reproduced in full in Appendix B). Because the pipeline's two-check criterion treats *any* exception on the vulnerable route, deliberate or accidental, identically to a successful block, it could not distinguish these two cases: round 5's `patch_validated: true` flag is a **false acceptance** by trace-level inspection, not a verified repair.

Round 5's patch was genuinely re-probed with its two recorded alternate payloads, each returning "still blocked"; this does not establish the vulnerability was closed. The preserved trace shows the `NameError` occurs in a line constructing the unpickler before any payload-specific branching is reached, consistent with the crash being independent of payload content — a logical inference from the traceback's location, not confirmed by a preserved benign-request trace or the patched source itself (not preserved outside its temporary sandbox path, Appendix D). The two probes therefore ran, but at minimum re-confirm the same crash rather than demonstrating the vulnerability was closed.

A corrected validator

The false-acceptance finding above was addressed directly, not merely documented. The two-check criterion was extended, additively, with two new checks and a headline verdict field on the same underlying report object: `patch_exploit_blocked` (the exploit fails without an unhandled exception in the target's own process log, via a crash-signature pattern), `patch_function_preserved` (a fixed, non-malicious benign request to the same route completes without that same crash-signature pattern; precisely what this field does and does not establish is stated below, since it is weaker than it may first appear), and a headline `patch_verdict` taking one of four outcomes: `confirmed_fix` (blocked and preserved), `regression_broke_route` (blocked but the benign request also now fails), `inconclusive_crash` (the exploit request itself crashed the route), and `not_blocked` (the exploit still succeeds). The pipeline's current source has since relabelled `confirmed_fix` as `heuristic_fix_screened` in new reports; the original `patch_validated` flag is unchanged. Replaying the round 5 false-acceptance trace (Appendix B) through the corrected validator reproduces `patch_validated: true` as before, while the new `patch_verdict` field correctly reads `inconclusive_crash`: the corrected criterion catches, automatically, exactly the case that previously required manual trace inspection.

What `patch_function_preserved` does and does not establish. The benign probe reuses the same generated proof-of-concept script with a fixed, generic non-malicious payload substituted for the exploit's own payload, rather than a class-specific request with a known-correct expected response. `patch_function_preserved` is set to true when that probe's target process executes and the same crash-signature pattern used for

`patch_exploit_blocked` does not appear in its log: it does *not* require the benign request to return HTTP 200, does not require the reused proof-of-concept script to itself report success, and does not check any class-specific expected output. A direct audit of every `confirmed_fix` verdict in the 36-run hosted-Claude comparison (Section 4.1.6), prompted by external review, found that all 27 such verdicts' benign probes were reported as failed by the reused proof-of-concept script's own logic (a generic payload does not trigger that script's exploit-specific success marker), and that only 13 of those 27 returned HTTP 200 on the benign request's final response, with the remaining 14 returning 401, 403, or 400: a clean HTTP-level rejection, not a crash, but also not confirmation that the route handled the legitimate request as intended. Every reading of `patch_verdict` = `confirmed_fix` in this project from Section 4.1.6 onward should accordingly be understood as "the exploit was rejected without a detected crash, and a generic benign request to the same route also completed without a detected crash," not as independent confirmation that the route's legitimate behaviour is correct.

A stronger, content-verified reassessment. This limitation was addressed directly: for each of the six main-catalogue vulnerability classes, a real expected malicious result (its response status, recorded for context) and a real expected legitimate result (a class-specific expected-content assertion), both read from the actual generated target/proof-of-concept source, were defined and re-tested against surviving patched artifacts from the 36-run comparison; the malicious side's own check asserts only marker absence, not the recorded status. Locating those artifacts surfaced a further harness gap: only 6 of the original 36 patched targets were available on disk at the time of the reassessment, one per CVE, since Stage 3.5/3.8's artifact writer saves generated files to a shared, non-model-specific path every model touching the same CVE overwrote. Re-testing those 6 available artifacts under the stronger criterion, every one passed: each malicious request's class-specific check found no response marker (recorded statuses 401, 400, 400, 400, 403, and 200), and each legitimate request's response matched real expected content, ranging per class from full JSON-object equality to a specific field value or an HTML substring check, a materially stronger check than the malicious side's marker-absence test even though it is not uniformly exact full-response equality across all six classes. This reassessment also resolved an apparent contradiction: `claude-opus-4-8`'s surviving CVE-2026-46492 patch, originally recorded `not_blocked`, passed this reassessment because the original multi-payload bypass check's alternate payload triggered the generated target's own vulnerability-signalling self-check without the markup ever being capable of executing in a real browser — a fidelity limitation of the target's signal, not a real bypass. Full methodology and per-CVE values: `reports/patch_reassessment_2026-09-26/RESULTS.md`. This reassessment does not extend to the other 30 of 36 original attempts, whose patched source no longer exists, and the 6 survivors are not a representative sample of the full comparison.

Table 4.3: The six surviving patched artifacts under the stronger, content-verified reassessment: expected vs. actual response on both the malicious and legitimate request.

CVE (class)	**Asserted malicious predicate**	**Expected legitimate outcome**	**Malicious status**	**Legit**	**Verdict**
CVE-2026-42208 (SQLi)	SQLi marker absent	Authenticated JSON response	401	200	`confirmed_fix`
CVE-2026-27602 (OS CmdI)	Command-output marker absent	"Domain created" JSON response	400	200	`confirmed_fix`
CVE-2026-23949 (Path Trav.)	Traversal marker absent	Example-file JSON response	400	200	`confirmed_fix`
CVE-2026-78683 (Deserial.)	RCE marker absent	"Loaded" JSON response	400	200	`confirmed_fix`
CVE-2026-54729 (SSRF)	SSRF marker absent	External fetch succeeds normally	403	200	`confirmed_fix`
CVE-2026-46492 (XSS)	XSS marker absent	Escaped heading/paragraph present (substring check)	200	200	`confirmed_fix`

Each malicious predicate checks only the absence of that class's response marker from the raw text, per Section 4.1.2; the recorded malicious status is contextual, not itself asserted, and process output is suppressed, so marker absence alone does not rule out a request-specific crash.

All 6 surviving patches pass this stronger, content-verified test: each of the six legitimate responses satisfied its stated class-specific content assertion (Table 4.3), a materially stronger, independent check than the malicious side's marker-absence test. The artifacts themselves are not retained in the repository outside their original, now-overwritten scratch paths (Appendix D); the source of record for these six rows is `reports/patch_reassessment_2026-09-26/RESULTS.md`.

A second implementation gap was found while first exercising the corrected validator against live, varied data: a patched target's health check failing entirely left `patch_verdict` blank instead of classified, fixed by explicitly setting `inconclusive_crash` in that branch. This is a further instance of the pattern established in Sections 4.2.1 and 4.2.2: a validation harness's own correctness is established only by exercising it against real, varied failure modes, not merely by writing it.

The corrected validator was then applied to a sixth full-catalogue verification round

(Appendix A), originally intended to compare Ollama against a hosted Claude Code CLI session; that comparison did not succeed, since the CLI's authentication session silently expired and was silently substituted with Ollama, caught only by auditing the `generation_backend` field against the run's stated protocol, then hardened and the round correctly relabelled as a sixth Ollama round. Under the corrected validator, this round's four confirmed exploits each received a patch attempt, and every one failed to close the vulnerability (three `not_blocked`, one `inconclusive_crash`): the same qualitative pattern as round 5, now distinguished explicitly, and zero `confirmed_fix` results.

A separate, dedicated investigation tested whether a patch accepted by the two-check criterion could still be bypassed by a different payload, surfacing and fixing four further implementation defects (an unstripped markdown fence, a patch missing Flask's required `app.run()` block, a diagnostic log discarding the patched process's real standard error, and a `localhost` hostname resolving to two different locally bound services) distinct from the exploit-generation defects in Section 4.1.1. After fixing all four, a full eight-model, six-CVE re-test found 11/48 exploits confirmed, 9/48 patches attempted, and 3/48 accepted, a substantial rise from the 0/48 accepted in the original, pre-fix comparison (Section 4.1.5).

This 3/48 figure requires one further qualification: all three nominally accepted patches had an empty `payload_variants` field, meaning the multi-payload bypass check had no alternate payload to probe them with, because the small model that produced them (`qwen2.5-coder:1.5b`) did not successfully generate the alternate-payload section. A controlled synthetic test independently confirmed the bypass check itself works correctly: a deliberately narrow patch that blocklisted only the literal default payload passed the single-payload check but was correctly rejected once a structurally different payload was tried. The headline for this retest is therefore not "3/48 patches validated," but **0/48 patches in this retest have been validated against more than their own original payload**: the bypass-testing mechanism is proven correct, but no patch here was exercised against it with a real alternate payload. This is narrower than a claim about the whole project: the main catalogue's own round-5 patch genuinely was re-probed with two alternate payloads, though that probe turned out to be uninformative for a different reason (Section 4.1.2).

4.1.3 Real-Upstream Validation: CVE-2026-23949

Every result reported so far in this chapter, aside from the free5GC case study, exploits a generated Flask reproduction of an advisory's described bug pattern, not the actual named upstream package (Section 3.10). One case was carried out instead against the real, pinned-version package, to close part of that gap directly. CVE-2026-23949 (`jaraco.context`, a path-traversal defect in its `tarball()` helper) was selected as a tractable candidate: the advisory names a specific vulnerable range and fixed version, and the vulnerable function's

real behaviour could be exercised without any special deployment beyond a Python virtual environment.

Two isolated virtual environments were built, installing the real, unmodified `jaraco.context==5.3.0` (the advisory's stated vulnerable range) and `==6.1.0` (its stated fixed version) from PyPI. The installed source in both was read directly to confirm the mechanism: `5.3.0`'s `strip_first_component` filter splits a tar member's path on its first `/` and keeps everything after it, including any `../` sequences, while `6.1.0`'s filter composes the same function with Python's standard-library `tarfile.data_filter` (PEP 706), so `strip_first_component` runs first and `data_filter` catches any surviving `../` sequence on the already-stripped member before extraction. A real malicious tar archive (a legitimate entry alongside one crafted to escape the extraction directory by two levels) and a real, non-malicious archive were served from a local, self-controlled HTTP server; the real, unmodified `jaraco.context.tarball()` function was called directly from each environment's own interpreter, with no mocking of the library under test.

Table 4.4 reports the full four-way result. Read against the vocabulary in Section 4.1.2: `patch_exploit_blocked` is true on `6.1.0` because the block is a named, documented standard-library exception (`tarfile.OutsideDestinationError`), not an unrelated crash signature; `patch_function_preserved` is true because the extracted file content was independently read back and confirmed to match on both versions, a stronger, content-verified check than the generic crash-absence probe used elsewhere (Section 4.1.2) — practical here because a tar-extraction function's legitimate-use behaviour has one clear, checkable expected output, unlike every class in the main catalogue. The case reaches `patch_verdict = confirmed_fix` on this project's strongest evidence tier among the Python-based cases, since the "patch" is the real upstream maintainers' own released fix, not an LLM-generated one. This remains one tested legitimate-archive case, not exhaustive proof the fix preserves every legitimate use.

Table 4.4: Real-upstream four-way validation result: CVE-2026-23949 (`jaraco.context`).

Version	**Test**	**Result**
`5.3.0` (vulnerable)	Malicious archive	Escaped: canary file written outside the extraction directory, exit 0
`5.3.0` (vulnerable)	Legitimate archive	Extracts correctly
`6.1.0` (patched)	Malicious archive	Blocked: `tarfile.OutsideDestinationError`, exit 1
`6.1.0` (patched)	Legitimate archive	Extracts identically to the vulnerable version

This result does not generalise to the other five main-catalogue CVEs, whose targets remain generated reproductions, and involves no LLM-generated patch: it validates this project's own *evaluation methodology* independently of whether an LLM can produce a patch this good, the separate, harder question this chapter's other results address.

4.1.4 Real-Upstream Validation: OpenEMR (GHSA-q366-cv5v-83w8)

A third real-upstream case transferred this project's evidence-gating method to a second application domain, healthcare, rather than confirming it again within the same telecom/5G or Python-packaging contexts. GHSA-q366-cv5v-83w8 is an unauthenticated information-disclosure advisory in OpenEMR's `admin.php`, carrying no assigned CVE number (its `cve_id` field is `null`, confirmed via the GitHub API); the real, unmodified OpenEMR source was built and run at its vulnerable commit (`b5313ea`) and the real upstream fix commit (`50f789f`, PR #13133), with no reproduction or stand-in target. The fix is structurally the same class as free5GC's missing-`return` defect: an early-exit opt-in guard returning `403` unless `OPENEMR_ADMIN_PHP_ENABLED` is explicitly set, rather than a rewrite of the underlying disclosure logic.

The real, unmodified OpenEMR checkout was bind-mounted into a minimal Docker deployment (a real, official `mariadb:10.11` image seeded with only the two tables `admin.php`'s read path actually needs, and a minimal `php:8.2-cli` image running PHP's own built-in development server, no Apache and no full OpenEMR setup wizard) the same minimal-dependency-scoping principle already applied to both free5GC harnesses (Section 3.8.2). Table 4.5 reports the full three-request result.

Table 4.5: Real-upstream validation result: GHSA-q366-cv5v-83w8 (OpenEMR `admin.php`).

Request	Expected	Actual (this run)
Vulnerable commit, no env var	`200`, metadata disclosed	`200`: rendered table shows Site ID, DB name, Site Name, and version pulled directly from the seeded database rows
Patched commit, no env var	`403`, metadata blocked	`403`, body exactly `admin.php is disabled by default...`: no site, database, or version data anywhere in the response
Patched commit, `OPENEMR_ADMIN_PHP_ENABLED=1`	`200`, admin page works	`200`, content identical to the vulnerable run's disclosure: confirms the fix is a default-closed gate, not a removal of the underlying function

Read against the vocabulary in Section 4.1.2: the harness's own automated gate checks the patched build's legitimate-use request against its status code and the presence or absence of the page heading, not merely crash-absence; separately, comparing the saved raw response bodies for the vulnerable-default and patched-opt-in runs shows them to be byte-identical, a stronger, exact-content observation not itself asserted by the automated gate. Together these give this case `patch_verdict = confirmed_fix` on this project's strongest, content-verified evidence tier: the real upstream maintainers' own released fix, exercised against the real, unmodified application, matching `jaraco.context`'s standard of evidence rather than the heuristic crash-absence screening used for the main catalogue's LLM-generated patches. Running this harness for real surfaced two further implementation defects, both readiness races (a container or server reporting ready before it genuinely was), consistent with this project's established pattern (Sections 4.2.1, 4.2.2, and 3.8.2); both were fixed by replacing the naive readiness check with the actual evidence-gathering action rather than a weaker proxy for it.

This case does not generalise beyond its own one file and one safe, unauthenticated oracle: it is not a systematic security assessment of OpenEMR, and the minimal two-table schema demonstrates this specific vulnerability's logic without demonstrating anything about OpenEMR's broader behaviour or authentication system. It was subsequently also used, alongside free5GC, as a target for the later LLM patch-generation and adversarial bypass-probe comparisons (Section 4.1.9); those comparisons evaluate LLM-generated patches against this same real OpenEMR target, not this section's own real-upstream

maintainer fix.

4.1.5 Multi-Model Comparison

Table 4.6 summarises results from running the identical, sampling-pinned protocol (temperature = 0, fixed seed) across eight local Ollama-served models, 48 runs in total.

Table 4.6: Confirmation rate by model (6 CVEs each).

Model	Confirmed	Patch accepted	Total LLM call time (s)
qwen2.5-coder:1.5b	3/6*	0/6	37.3
qwen2.5-coder:3b	1/6	0/6	38.4
qwen2.5-coder:7b	5/6	0/6	114.9
llama3.1:8b	2/6	0/6	94.3
mistral:7b	0/6	0/6	106.8
gemma2:9b	0/6	0/6	763.7
codellama:13b	2/6	0/6	1544.1
deepseek-coder-v2:16b	4/6	0/6	176.6

*All three of qwen2.5-coder:1.5b's confirmations came from the pipeline's template fallback path, not from the model's own live-generated output: every one of its six generation attempts was recorded as `llm_live_failed`.

Patch acceptance was 0/48 across every model in this comparison. This run predates four patch-acceptance harness bugs fixed in a dedicated follow-up (Section 4.1.2); a later, separate 48-run re-test with those fixes applied found a different confirmed-exploit count (11/48, not 17/48) and 3/48 nominally accepted patches, though Section 4.1.2 also shows a nominally accepted patch in a separate round was later found to be a false acceptance by trace-level inspection — a finding about the two-check criterion itself, not that one of these 48 records was individually inspected. LLM call time did not scale monotonically with parameter count: codellama:13b's total call time (1544.1s) exceeded deepseek-coder-v2:16b's (176.6s) despite the latter having more parameters, and gemma2:9b recorded one single-CVE call time of 608.7s against a 24.8–40.5s range for its other five runs. This column measures model generation time specifically, not full pipeline wall-clock.

4.1.6 Multi-Model Comparison: Hosted Claude Models

The eight-model comparison above evaluates only locally hosted, open-weight models; no hosted API or CLI session was available in this project's environment at the time. A second, later comparison became possible once a Claude Code CLI session was authenticated, carried out across six named Claude model snapshots (Haiku 4.5, Sonnet 4.6, Sonnet 5,

and Opus 4.6/4.7/4.8) against the same six-CVE catalogue, under the same one-recorded-run-per-cell, isolated-lessons-store protocol as every Ollama round, with the corrected validator's `patch_verdict` (Section 4.1.2) as its headline patch metric from the outset: read throughout this subsection as heuristic patch-screening, not confirmed functional correctness. "One recorded pipeline run" bounds independent trials per cell, not LLM calls within it: two of the 36 cells (Haiku 4.5 on CVE-2026-78683, Sonnet 4.6 on CVE-2026-54729) triggered Stage 3.7's bounded self-improvement loop internally (3 further LLM revision calls total) after an initial attempt genuinely failed — bounded, in-protocol revisions, not repeated trials.

Table 4.7: Confirmation and patch outcomes by hosted Claude model (6 CVEs each, 36 runs total).

Model	**Confirmed**	**Screening pass (`confirmed_fix`)**	**Not blocked**	**Crash**	**Cost (USD)**
Haiku 4.5	6/6	5	1	0	$1.81
Sonnet 4.6	6/6	4	2	0	$4.50
Sonnet 5	6/6	4	2	0	$4.26
Opus 4.6	6/6	4	1	1	$8.04
Opus 4.7	6/6	5	1	0	$5.52
Opus 4.8	6/6	5	1	0	$9.04
Total (36 runs)					**$33.18***

*Computed from each model's unrounded per-call cost, not from summing the rounded cells shown above (which sum to $33.17); the one-cent difference is a rounding artifact, not a data error.

Note on the Screening pass column: as throughout this chapter, `confirmed_fix` here means the corrected, crash-signature-based `patch_verdict` criterion passed, not that the patch was independently verified correct. This is a different, stricter count than this comparison's raw, original `patch_validated` field, true for 28 of the 36 records rather than 27: the two fields disagree on one case, a reminder that even the historical and corrected screening criteria are not interchangeable. Six patched artifacts were available at reassessment time for stronger, content-verified re-testing; the exact historical target files are not preserved for replay (Section 4.1.2 explains why); the counts in this column should be read as heuristic screening results, not as 27 independently confirmed correct patches.




Figure 4.2: Total CLI-reported cost estimate against `confirmed_fix` count for each of the 6 hosted Claude models (Table 4.7). Cost and screening-pass rate are visibly not monotonically related: Haiku 4.5, the cheapest model, ties the best rate.

Every one of the 36 runs dynamically confirmed its assigned exploit, so (unlike the eight-model local comparison, where confirmation rate varied substantially by model) exploit generation is not the differentiator among these six hosted models; passing the heuristic patch-screening criterion is. Two findings stand out beyond the raw `confirmed_fix` counts in Table 4.7, both read under the scope stated in Section 4.1.2 rather than as confirmed patch correctness. First, reported cost and screening-pass rate are not monotonically related: Haiku 4.5, the cheapest model by reported cost, matched the best `confirmed_fix` rate (5/6) at 20–42% of every other model's reported cost, while Opus 4.6 tied Sonnet 4.6 and Sonnet 5 for the lowest pass count at 4/6, distinct among the three by one of its two misses: `inconclusive_crash`, the only crash-class failure across all 36 runs despite Opus 4.6 being neither the cheapest nor fastest model tested; its other miss is `not_blocked`, the same outcome discussed next. Second, Cross-Site Scripting (CVE-2026-46492) was the sole class every model failed even this heuristic screen (`not_blocked` in every case) — a consistent, cross-model finding, though not necessarily a property of the task itself: the later content-verified reassessment (Section 4.1.2) found at least one of these six recorded failures (`claude-opus-4-8`'s surviving patch) was a false-positive exploit signal from the generated target's own response-marker regex, not a genuine patch defect. The cross-model `not_blocked` pattern is therefore a legacy screening result, not independent proof that every model's XSS patch was actually incorrect (Section 5.6 returns to this point).

Table 4.7 reports only per-model totals; Table A.5 in Appendix A gives the full per-CVE breakdown, since a per-model total alone hides real variation within the same model (for example, Opus 4.8's cost per CVE ranges from $0.81 to $2.13, and Sonnet 4.6's wall-clock time ranges from 80.3s to 257.8s, both within a single model's own six runs).

This comparison surfaced its own harness defects, consistent with this project's established pattern of validation issues surfacing only once a harness is exercised against real, varied data. Switching the Claude CLI to its structured JSON output mode exposed real per-call cost and token data for the first time in this project, which is what makes Table 4.7's cost column possible. Two further defects were found and fixed here: the round-6 silent-fallback behaviour (Section 4.1.2) recurred under a genuine rate-limit condition and was hardened at the source, and two models (Opus 4.7/4.8) initially stalled by attempting an interactive file-write tool in this pipeline's non-interactive calling context, resolved by disabling tool use and session persistence. As with the eight-model local comparison, this is one deterministic-in-intent but not sampling-pinned shot per CVE per model (the Claude CLI exposes no temperature or seed control), one data point per model, not a statistically powered ranking.

4.1.7 Reachability Filtering on Real Upstream Source

Applied to a real, 86 KB free5GC/UDR source file, the reachability engine parsed 102 functions and identified 4 as reachable from four HTTP entry-point handlers manually selected for this case study, not the module's complete externally callable surface: the same file defines dozens of other HTTP handlers (for AMF context, authentication status, PFD management, and more) that were not supplied as seeds. The resulting 96.1% reduction is therefore a scope-reduction figure conditional on this seed selection and this one file's own call graph, not a completeness guarantee or a measured wall-clock speedup.

The call graph itself is name-keyed rather than symbol-qualified (two same-named functions or methods on different types are not distinguished, a documented limitation of the parser, `src/reachability/reachability.py`), and its traversal only follows calls visible as direct AST call sites within this one file; neither interface-dispatched calls resolved only at runtime nor calls into other files or packages are part of this specific reduction figure, so the 96.1% bound applies to this file's own internal call graph, not to free5GC's full, cross-package call surface.

All four reachable functions were flagged by the rule-based pattern matcher and classified as CWE-285 (improper authorisation check), checked against each handler's own disclosed advisory (Table 3.6), not confirmed by an independent second reviewer. Three of the four (DELETE, single-record GET, PUT) are disclosed under CWE-285 exactly; the fourth, collection GET, is disclosed as CWE-200/202/209 (information exposure), so this project's CWE-285 label for it is a broad authorisation-related interpretation, not

exact agreement with its actual disclosed CWE.

A patch was generated for all four; applying all four to a live clone of `free5gc/udr` at the pre-fix commit, `go build ./...` completed successfully both before and after. One of the four generated patches is only partially correct: its target handler (`HandleApplicationDataInfluenceDataSubsToNotifyGet`) requires two separate `return` insertions in the real, disclosed fix, while the rule-based patcher inserts only the first match per function body, so that handler's vulnerability is not fully closed even though the module still compiles. This limitation is specific to this project's own rule-based auto-patcher, not to the real upstream fix used for the runtime testing described next, which takes all four handlers beyond this compile-time verification. This failure mode (addressing the fix site first noticed while leaving a structurally identical second site unaddressed) is not an idiosyncrasy of this project's patcher: a large-scale study of incomplete security fixes in the Linux kernel identifies "overlooked similar modules" as one of three recurring root causes of incomplete patches, alongside a developer misled by a crash's superficial symptoms rather than its underlying cause [20]. This one-vs-two insertion difference is a useful bounded comparison between this project's rule-based and model-assisted patchers for this specific defect, but it is not an ablation establishing that an LLM is necessary: a deterministic rule iterating over all matching sites in the function body, rather than stopping at the first match, could potentially close the same narrow defect without any LLM involvement.

The DELETE handler, sharing the same missing-`return` root cause and upstream fix commit as the other three, is disclosed as its own CVE, CVE-2026-40246 (Table 3.6; Appendix A relates this result to the separately-evaluated, hand-written CVE-2026-40246 reproduction in `free5gc_lab/`), and was subsequently taken one evidence tier further using the harness in Section 3.8.2: the real, cloned upstream module was built and run twice (vulnerable and fixed commits) against a real local MongoDB instance, driven with real HTTP requests rather than compiled but never executed.

At the vulnerable commit, the malicious delete request (invalid `influenceId`) received a `404` response, matching the handler's own validation check, but a follow-up read confirmed the targeted record had been deleted regardless: the vulnerable code writes the `404` response but does not `return` afterward, so execution falls through and performs the deletion anyway. At the real fix commit, the identical request again received `404`, but the follow-up read confirmed the record was still present: the added `return` stops execution before the deletion path. A legitimate delete request, with the correct `influenceId`, succeeded and removed the record on both builds, confirming the fix does not break the handler's intended function.

This gives a real, non-inconclusive verdict (`confirmed_fix`) for this one handler, upgrading the free5GC case from compile-time to runtime evidence and giving it, at the time, the project's strongest patch-validation evidence among its compiled, real-upstream

reachability work. The full evidence bundle (process logs, HTTP request/response logs, both commits' build logs, `manifest.json`/`verdict.json`, and the real upstream diff) is in Appendix A. At the time, this remained a single-handler result, not evidence the other three reachable handlers would behave identically; that gap was subsequently closed, as described next.

All three remaining handlers (collection GET, disclosed as CVE-2026-40245; single-record GET, CVE-2026-40247; PUT, CVE-2026-40248; Table 3.6) were then run against the fuller Docker-based deployment described in Section 3.8.2 (real MongoDB, real free5GC NRF, OAuth2 disabled), and were found to share the DELETE handler's exact root cause (the same missing `return` after a non-2xx write), with two of the three found to be more severe than the DELETE case on direct empirical inspection of the raw HTTP response bytes:

1. **Single-record GET.** Queried with an invalid `influenceId`, this handler returns `404 Not Found` with the literal body `"404 page not found"` on the patched build, but on the vulnerable build that same text is immediately followed, in the same response, by the real subscription's JSON content, with one `Content-Length` header sized to both writes combined (confirmed directly against the captured raw response in `evidence/RAW_FINDINGS.md`, not inferred). The mechanism is the missing `return` in the Gin route wrapper: the invalid-`influenceId` branch writes the 404 but does not return, so execution falls through to the processor's own lookup by the separate `subscriptionId` segment, disclosing the real, previously seeded subscription — the invalid-`influenceId` check and the subscription's existence are unrelated checks, and failing the first does not stop the second. The captured response contains both writes in a single body. Writing an error response did not terminate the handler, so later code appended the subscription data.

2. **Collection GET.** Queried with no filter parameters at all (its own documented error condition), this handler shows the same pattern at larger scale: the vulnerable build's `400 Bad Request` error body is followed by a JSON array of *every* subscription record in the system, since an empty filter matches every stored record: a full, unauthenticated collection dump inside what looks like a rejected request.

3. **PUT.** This handler goes further still: the request again returns `404 Not Found`, but a follow-up read confirms the submitted data was genuinely written to the MongoDB-backed subscription store: an unauthorized *write*, not only a read leak.

All three close cleanly on the patched build (the response body contains only the expected error text, and the follow-up read for `PUT` confirms nothing was stored). A legitimate, correct-`influenceId` request was separately verified unaffected on both builds for the single-record `GET` handler, the one case where this deployment's evidence bundle

records a benign-path check; the collection `GET` and `PUT` handlers' legitimate-use behaviour was not separately re-tested here (DELETE's own legitimate path was verified in the earlier minimal harness). Combined with the DELETE result above, this constitutes a full CRUD bypass (unauthorized read of one record, unauthorized read of the entire collection, unauthorized write, and unauthorized delete) through one shared, one-line root cause, confirmed and closed across all four manually selected handlers. This work is recorded at commit `b8a4fe1`, kept isolated from the single-handler result's own evidence bundle; both are cited in Appendix A.

4.1.8 Classification Ablation

A separate ablation isolated Stage 2 (vulnerability classification) from the generation stages evaluated above, testing three conditions against the six-CVE catalogue's ground-truth CWE labels: full advisory content, prose description only, and the CVE identifier alone with no advisory content. Table 4.8 reports class-level match and exact-CWE match as separate metrics, since collapsing them into one accuracy figure would obscure a real, informative difference between the two.

Table 4.8: Stage 2 classification ablation (n=6).

Condition	**Class-level match**	**Exact-CWE match**
Prose description only	5/6	4/6
Full advisory (structured CWE field)	6/6	6/6
CVE identifier only (no content)	0/6 (no classification)	0/6 (no classification)

Prose-only classification correctly identified the vulnerability class for 5 of 6 CVEs, with one full miss (CVE-2026-42208, SQL Injection): its NVD summary describes the mechanism without using the words "SQL" or "injection," so keyword matching returned no classification. Among the 5 correct at the class level, one (CVE-2026-46492) was assigned the wrong exact CWE: prose matching returned the general CWE-79 for any cross-site-scripting pattern, while the actual, analyst-assigned code was the more specific CWE-80. Supplying the structured CWE field already present in the advisory resolved both cases, reaching 6/6; this should be read precisely, since it demonstrates the classifier correctly reads a ground-truth field already present, not independent classification of unseen content — the genuinely informative result is the 5/6 and 4/6 figures under prose-only matching. Micro-averaged precision, recall, and F1 for this condition (Table 4.9), computed by treating a missing classification as a false negative with no corresponding false positive and a wrong classification as both a false negative for the true label and a false positive for the predicted one, only partly track the accuracy figures above: recall equals them exactly (0.833 class-level, 0.667 exact-CWE) at this $n = 6$, but precision

and F1 do not, since they distinguish the two kinds of error accuracy alone does not: the class-level condition's one error is a pure abstention, keeping its precision at 1.000, while the exact-CWE condition adds one misclassification to the shared abstention, lowering precision to 0.800 and recall to 0.667. The CVE-identifier-only condition, with no advisory content at all, correctly produced no classification for any of these six inputs; direct inspection of the classifier's source (`cve_pipeline.py`) confirms it has no CVE-identifier-to-label lookup table, only CWE-field and free-text keyword matching, so this is not merely consistent with but directly rules out identifier-based hardcoding in the tested classifier.

Table 4.9: Prose-only condition: micro-averaged precision, recall, and F1.

Level	**Precision**	**Recall**	**F1**
Class-level (family)	1.000	0.833	0.909
Exact-CWE	0.800	0.667	0.727

A cross-check against GitHub's independent advisory database found CWE agreement with NVD's structured field for all six entries (CVE-2026-46492 lists an additional CWE alongside the matching one), indicating the structured-CWE signal is consistent across both databases, though not independent replication of the underlying analysis, since advisories are commonly shared between the two.

4.1.9 Extended Model-Access Comparison: OpenAI API, Codex CLI, and AIxTech Gateway

After the eight-model Ollama and 36-run hosted-Claude comparisons above, three further model-access methods were evaluated against the same free5GC, OpenEMR, and six-CVE-catalogue targets used throughout this chapter: the OpenAI API (23 model identities), the Codex CLI (18 model identities), and a direct Claude API gateway operated by AI Singapore (AIxTech, 10 requested model names). The full per-model, per-call detail (individual tokens, duration, and cost where a figure exists) is in the project repository (`docs/RESULTS_BY_ACCESS_METHOD.md`, `docs/RESULTS_SUMMARY.md`, `docs/FINAL_EVIDENCE_SUMMARY.md`), not reproduced call-by-call here. Zero genuine bypasses were confirmed by any of these three methods against any already-validated patch, consistent with every earlier comparison in this chapter.

Table 4.10: OpenAI API sweep: all 23 requested model identities, across four experiment families.

Experiment	N	Outcome
free5GC patch generation	23	18 full four-handler validation-pipeline passes (one model-generated handler, three deterministic reachability materialisations); 4 genuine compile failures (`gpt-4-turbo`, `gpt-5.2`, `gpt-5.4`, `gpt-4.1`); 1 generation/API failure (`gpt-3.5-turbo-1106`, deprecated, a 404 on the generation call, so no patch was ever produced to compile). 18+4+1=23, verified against each model's own `compile.compiles`/`generation_outcome` fields.
free5GC adversarial bypass probe	23	0 genuine bypasses against the real, already-patched deployment (19 parseable proposals)
OpenEMR patch generation	23	16 fully working, content-verified gates; the remaining 7 did not reach this standard (per-model detail in `docs/RESULTS_SUMMARY.md`)
OpenEMR adversarial bypass probe	23	0 genuine bypasses against the real, unmodified, patched application (20 parseable proposals)

Table 4.11: Codex CLI sweep: all 18 requested model identities, free5GC target.

Experiment	N	Outcome
Patch generation	18	7 runtime-confirmed across all four handlers (`confirmed_fix_all_four_handlers`); the remaining 11 (5 modern IDs – `gpt-5`, `gpt-4.1`, `gpt-4o`, `o3`, `o4-mini` – plus 6 GPT-3-era legacy IDs) failed before the Codex CLI returned a completion or usage event, recorded as environment-limited rather than model-quality failures, verified against each model's own `generation_outcome` field
Adversarial bypass probe	18	Only 4 of 18 sessions completed far enough to execute a proposal at all; 0 of those 4 produced a genuine bypass

The AIxTech gateway is a structurally different access method from every other Claude-labelled result in this chapter: it calls the real `anthropic` Python SDK directly with a bearer token, rather than shelling out to the `claude` CLI subprocess the way every

other Claude sweep in this project does. Ten model names were requested; only four resolved. All four produced a clean, reachable patch-generation gate, and a targeted repeatability check (3 runs per model) found all 12 resulting calls stable. This gateway's API response never includes a dollar-cost figure, so, unlike every other paid access method here, none is reported for it; real per-call token counts and wall-clock duration were captured for every call, including those rejected by the key's own model-allowlist.

The catalogue's XSS bypass result was also re-evaluated at this stage, replacing the legacy response-marker oracle with direct browser execution. 33 XSS bypass proposals with a usable request (every entry carrying a `proposal` field across every bypass-probe report in this project) had their real HTTP response fetched from the patched local reproduction, then rendered as an instrumented copy of that response body in headless Chrome from a temporary local file (injected dialog/error-capturing instrumentation rather than the response's own original headers); of these, 18 independently re-confirmed the legacy response-marker's raw-positive reading at replay time and 15 did not. Zero of the 33, including all 18 raw-positive proposals, produced a dialog or uncaught-error signal within the observation window. The raw marker result remains preserved for audit.

Two interpretation rules apply to the numbers in this subsection. First, the free5GC headline result is a full pipeline validation outcome, not an independently model-generated one: four manually selected handlers are tested, but one handler change is model-generated and three are deterministic reachability materialisations, so the OpenAI sweep's 18/23 figure is not an 18/23 rate of independently model-generated patches. Second, the investigated failures in these later sweeps were attributed to a specific model's generation quality or a specific environment constraint after the harness corrections already described in this chapter, not asserted to exhaustively rule out every other cause; no access method's weaker results should be read as that access method being unsound on the evidence available.

4.1.10 OAuth2-Enforced Follow-Up and Repeatability Check

Every free5GC runtime result reported above runs with OAuth2 enforcement explicitly disabled on the NRF. A follow-up closed this specific limitation for two of the four handlers: an opt-in compose override enabled OAuth2 without altering the default stack, and re-ran the collection-wide-read and single-record-read checks (plus the benign path) against both the vulnerable and real-fix-patched UDR image, under no credentials and a valid, correctly-scoped bearer token minted with the NRF's own private key for a real, registered network-function identity (not a full client-credentials round-trip, out of scope here). With no credentials, both builds correctly returned HTTP 401 before the underlying CWE-285 bug could matter. With a valid token, the vulnerable build's leaks reproduced exactly as in every OAuth2-disabled result, and the real fix closed both while preserving the legitimate

path. OAuth2 enforcement and the code-level fix are therefore independent, complementary layers: OAuth2 narrows the threat model to credentialed callers but provides no additional protection against this bug once that bar is cleared, so the real fix remains necessary regardless. Full method and raw evidence: `docs/FREE5GC_OAUTH2_ENFORCEMENT_RESULTS.md` and `reports/reachability/free5gc_oauth2_enforcement.json`.

A separate repeatability check, using unique prompt markers per call, targeted the Claude CLI and AIxTech gateway results: all 12 AIxTech calls completed; nine of twelve Claude CLI calls completed, with three Opus calls retained as access failures. A controlled OpenAI repeatability attempt recorded the requested temperature and seed for all twelve runs, but the locally supplied API key was rejected with HTTP 401 before generation — environment-limited evidence, not a model-quality failure.

4.2 Discussion

4.2.1 Interpreting the Confirmation-Rate Progression

The rise from 1/6 in round 1 to 5/6 in round 5 is not evidence of a steadily improving model or pipeline. Round 3's drop to 1/6, despite a genuine bug fix introduced that round, shows a working retry mechanism is not the same as one that reliably finds the correct fix. It is clearer to attribute most of round 4's jump to the two implementation-defect fixes rather than to any change in model capability, given the same model and largely the same prompt were used across rounds 3 and 4, and the improvement coincides precisely with the fence-crash signature disappearing from every report — a correlational reading, not a causal proof. What the records do support is a more general caution, reinforced by the patch-validation false-acceptance finding (Section 4.1.2): a harness defect of this kind can distort a reported result in either direction, so neither a low nor a high raw count in this project's own catalogue should be read as a reliable floor or ceiling without independent trace verification.

The SQL Injection class's behaviour across rounds (confirmed in round 1, unconfirmed in rounds 2–4, confirmed again in round 5) is consistent with the project's own stated caveat that a single-shot, non-averaged protocol can flip for the same CVE between runs, since neither the model's sampling nor the surrounding pipeline state is guaranteed identical run-to-run even with a fixed seed. This is a property of the evaluation protocol, not evidence that any one class is inherently harder than another.

4.2.2 Why Patch Validation Lagged Confirmation

The single most important finding on patch acceptance is not a rate but the design flaw established in Section 4.1.2: the two-check criterion cannot distinguish a deliberate fix

from an unrelated crash bug, as round 5's confirmed false acceptance for CVE-2026-78683 shows directly. This reframes every raw patch-acceptance count in this chapter: a nonzero count means "the automated criterion was satisfied," not "a correct fix was produced," until each case is traced by hand as round 4 and round 5 were here. This is not an idiosyncrasy of this project's own harness: PVBench's independent, 209-case benchmark found over 40% of patches three state-of-the-art automated-repair systems had validated as correct failed its stronger, developer-authored test standard [13], and VulnRepairEval similarly found that, under exploit-based differential validation, the best-performing of twelve evaluated models repaired only 5 of 23 Python CVEs [12]: a low result under that criterion, not a measured before-and-after reduction caused by switching validation standards, since the study does not report re-scoring the same patches under a weaker oracle first. Round 5's single false acceptance is therefore a small-sample instance of a pattern now independently measured at benchmark scale, not a defect unique to this project's own criterion.

Two distinct 48-run datasets are reported in this chapter (Section 4.1.5; Section 4.1.2's four-bug retest) and should not be collapsed into one figure. Given the false-acceptance finding above, even the corrected 3/48 figure should be read cautiously, since the acceptance criterion can still accept a patch whose vulnerable route simply crashes; no overall reliability gain is claimed beyond the specific behavioural changes already listed. Across these two datasets and, separately, round 5's own six-record run: zero patches, across all three, have both passed the original two-check criterion *and* been confirmed correct by trace-level inspection. This is narrower than a claim about every patch in this project: it does not describe the three real-upstream maintainer fixes or the 6 content-verified artifacts reported elsewhere, all of which passed a stronger standard, short of independently confirmed general correctness.

The corrected validator (Section 4.1.2) directly addresses the specific failure mode this subsection describes, but only partially: it distinguishes a deliberate rejection from a crash on the exploit side, but does not close the equivalent gap on the benign side. This is a genuine improvement to exploit-side discrimination — it found zero `confirmed_fix` results on a full sixth catalogue round, and only 4–5 of 6 per model on the later 36-run hosted comparison — but its benign-side check remains a screen for gross regressions, not a correctness proof.

A separate, more procedural finding reinforces the same caution: three of the four harness defects found during the patch-validation investigation were pure implementation bugs, not model failures, and plausibly suppressed some earlier counts, though this project did not re-run those earlier attempts to measure how many. This is consistent with the pattern already observed for exploit confirmation (Section 4.2.1): a nontrivial share of this project's apparent capability gaps has turned out to be harness defects rather than fundamental model limitations, cutting in both directions — a harness defect can suppress

a real success (round 3's markdown-fence crashes) or manufacture a false one (round 5's `NameError`).

4.2.3 Runtime and Model-Size Findings

It is clear from Table 4.6 that confirmation rate did not track parameter count: the 7B qwen2.5-coder model outperformed both the 9B (gemma2, 0/6) and 13B (codellama, 2/6) models. This project's comparison (a single deterministic shot per CVE per model, with differing architectures and qwen2.5-coder:7b carrying prior prompt-tuning exposure the others did not) is not designed to isolate a cause and should not be read as a general-purpose ranking. The codellama:13b and gemma2:9b runtime anomalies (respectively far slower than a larger model, and one 15–25x single-run outlier) were not root-caused in this project; they are reported as observed rather than explained by an unverified guess.

4.2.4 Classification Reliability and the Structured-Data Advantage

It is clear from Table 4.8 that preferring an advisory's own structured CWE field over free-text keyword matching removed every classification error observed in this catalogue, supporting this precedence rule as a deliberate design choice. The one full miss under prose-only matching (CVE-2026-42208) suggests keyword-based classification is fragile when an advisory describes a mechanism without the vulnerability class's own common vocabulary — a gap a structured field sidesteps entirely. The single exact-CWE mismatch points to a narrower limitation: a fixed family-to-representative-CWE mapping cannot reproduce an analyst's more specific subtype judgment (here, CWE-80 assigned instead of the mapping's default CWE-79 for any cross-site-scripting pattern), a property of how the mapping was hand-encoded, not of prose matching as a technique — it does not establish that prose-based classification is unreliable in general, only that a coarse family mapping loses subtype precision a structured field preserves.

4.2.5 Relationship to the AIxCC/OSS-CRS Benchmark Context

The 86% discovery / 68% patch figures introduced in Chapter 1 are DARPA's own aggregate across all seven AIxCC finalist systems, not a per-system figure and not specifically ATLANTIS's own result; the sources consulted here do not report an ATLANTIS-specific patch rate. Direct numerical comparison between that aggregate and this project's own rates would also compare results obtained under materially different tasks, software, and evaluation conditions: AIxCC's finalists discovered previously *unknown* bugs seeded into large, real competition codebases under a shared, adjudicated benchmark, while this project confirms and reproduces *already-published* bugs against six small, generated

stand-in targets. The two results are not on the same scale or denominator, and no numerical comparison between them is drawn here.

What is fair to say is qualitative rather than quantitative: both AIxCC-class systems and this project treat an unverified claim as insufficient on its own and require executable evidence before a discovery or a patch is trusted. FuzzingBrain, a real AIxCC finalist, uses a comparable staged reachability-then-triage architecture and reports that its call-graph analysis narrows a codebase from thousands of functions to a more tractable reachable subset [10], qualitatively consistent with this project's own reachability-filtering result; however, its published paper does not report a specific percentage reduction figure comparable to this project's 96.1%, so no quantitative comparison is drawn here, only the shared qualitative design choice.

4.2.6 Limitations, Trade-offs, and Sources of Uncertainty

The exploit-artifact generation results above were obtained against a generated Flask stand-in reproducing each advisory's described bug pattern, not the actual named upstream package; a confirmed exploit therefore demonstrates that the described pattern is exploitable as reproduced, not that the real package is exploitable when actually installed and run.

This limitation is now partially, not fully, closed: Section 4.1.3 demonstrates the same evidence-gating discipline against a real, pinned-version PyPI package (CVE-2026-23949), reaching this project's strongest evidence tier among the Python-based cases, but this remains one case chosen for tractability out of six, not a claim the remaining five could be validated the same way without comparable effort.

The reachability result avoids the reproduction-vs-real-package limitation by a different route, since it operates on the real, cloned upstream free5GC source, and its original compile-only bound (`go build` succeeding proves syntactic validity, not runtime correctness) has since been closed for all four handlers: runtime confirmation (Section 3.8.2), over real HTTP against both the vulnerable and fixed commits, confirms the fix closes all four handlers' exploitable behaviour while preserving legitimate function for the operations tested — one of three real-upstream, runtime-confirmed cases alongside `jaraco.context` and OpenEMR (Section 4.1.4), and the only one where all four manually selected handlers reached this standard.

Deploying and testing the full free5GC core network stack (AMF, SMF, and the rest) remains out of scope. OAuth2 enforcement, which the fuller deployment's real NRF enables by default, was explicitly disabled in the runtime results described earlier in this chapter to reach the handlers under test; a later follow-up, also reported in this chapter (Section 4.1.10), re-ran a subset of these same checks with OAuth2 enforcement turned on and found it does not change this CVE's exploitability by a credentialed caller, so

this out-of-scope statement applies specifically to the OAuth2-disabled results described earlier, not to this project's evaluation as a whole.

The multi-model comparison's single-shot, non-repeated design (one run per CVE per model, even with sampling pinned) means individual model rankings in Table 4.6 should be read as one data point rather than a statistically powered result: an explicit, acknowledged trade-off made to keep the eight-model, 48-run comparison tractable within the project's timeframe rather than to claim more statistical confidence than the design supports.

4.3 Summary and Implications

Overall, these findings suggest that an evidence-gated, dynamically-confirmed pipeline of this kind can produce useful confirmation evidence on a small, fixed catalogue of already-disclosed vulnerabilities, but that patch generation and validation remain substantially harder to achieve reliably than exploit confirmation does, and harder still to trust once a validation criterion is checked by trace-level inspection rather than taken at its own flag. No numerical comparison to AIxCC finalist systems is drawn here (Section 4.2.5); the two bodies of work share only a qualitative commitment to executable evidence over unverified claims. This may have implications for future work: rather than treating exploit confirmation and patch generation as symmetric problems solvable by the same prompt-and-model combination, the results here suggest patch generation may benefit from separate, class-specific tuning or a larger model tier before it can be trusted as a validated output rather than an experimental one. For practitioners considering a similar system, the reachability-filtering result offers a more immediately transferable takeaway: narrowing an LLM's analysis scope via real, AST-based call-graph reachability produced a large, real scope reduction (96.1%) and an initial patch verified to compile against the genuine upstream dependency graph for all four manually selected handlers, without at that stage requiring dynamic confirmation. Reachability filtering and dynamic confirmation are not mutually exclusive: a minimal, dependency-scoped harness (Section 3.8.2) first added runtime evidence for one filtered-in handler (DELETE) without deploying the full upstream stack, and a fuller Docker-based deployment subsequently extended the same dynamic standard to all four handlers, without ever needing the rest of the free5GC core network stack.

Chapter 5

Conclusion

5.1 Summary of the Project

This project set out to extend an existing exploit-confirmation prototype so that suspected vulnerabilities could be confirmed and candidate fixes evaluated with genuine evidence, rather than accepted on the strength of a plausible-sounding generated artifact alone. Two complementary capabilities were built and evaluated toward this goal. The main pipeline advanced a CVE from advisory intake through classification, exploit-artifact generation, dynamic execution, self-improvement, and patch generation and validation, evaluated across five rounds against a six-CVE catalogue and, separately, across eight locally hosted models. A second, independent capability ported and extended an earlier reachability-filtering prototype to operate on real, disclosed free5GC source, narrowing a real 102-function file to 4 relevant functions and verifying a generated patch against the genuine upstream project; the DELETE handler (CVE-2026-40246) was first runtime-confirmed using a minimal MongoDB-only harness, and a fuller deployment with a real free5GC NRF subsequently extended runtime confirmation to all four selected handlers (CVE-2026-40245 through CVE-2026-40248), rather than compiled but never executed, making free5GC the project's most complete demonstration of the full exploit-confirmation-and-patch-validation methodology against a real, disclosed, compiled upstream vulnerability.

5.2 Objective Closure

Table 5.1 maps this project's stated objectives (Chapter 1) directly onto the evidence that closes each one, so the status of each is stated once, explicitly, rather than left for a reader to reconstruct from Chapter 4's narrative.

Table 5.1: Objective-by-objective closure.

Objective	**Status**	**Evidence**
Dynamic exploit confirmation (six-CVE catalogue)	Met	All six vulnerability classes confirmed at least once across five Ollama rounds; every one of six hosted Claude models confirmed all six exploits (36/36) in the later comparison (Section 4.1.6).
Patch generation and validation	Partially met	The real-upstream `jaraco.context` (Section 4.1.3) and OpenEMR (Section 4.1.4) cases passed the stated real-upstream checks; the 6 recoverable, content-verified synthetic patches (Section 4.1.2) passed bounded, class-specific checks (marker-absence on the malicious side, real content on the legitimate side), short of independently confirmed general correctness; the broader 36-run comparison's `confirmed_fix` rate (4–5/6 per model) remains heuristic patch-screening, not confirmed correctness, at that scale.

continued on next page

Objective	Status	Evidence
free5GC reachability filtering & patch verification	Partially met	102 real functions reduced to 4 reachable (96.1%), three of four classified as the disclosed CWE-285, one (collection GET) classified CWE-285 against a disclosed CWE-200/202/209; all four generated patches verified to compile against the real, live-cloned upstream dependency graph, and all four handlers (CVE-2026-40245 through CVE-2026-40248) subsequently runtime-confirmed via a fuller Docker deployment with a real MongoDB instance and a real free5GC NRF (Section 3.8.2): OAuth2 enforcement was disabled to reach the handlers under test, and no live HTTP exploit was run against a fully deployed free5GC core network (AMF, SMF, and the rest) (Section 3.10).
ProvTrail/SARIF integration	Partially met	SARIF ingestion plumbing (`provtrail_bridge.py`) is functional and one hand-authored JavaScript case (CVE-2024-48910) is dynamically confirmed; this is not a systematic evaluation of ProvTrail's own flagged findings against real scanned projects.
Multi-model comparison under a fixed protocol	Met	Eight locally hosted models (48 runs) and six hosted Claude models (36 runs), both under a frozen, single-protocol comparison with real time accounting and a reported per-call cost estimate.

5.3 Key Findings

Eight findings stand out from the results reported in Chapter 4; full detail and evidence for each is in the cross-referenced section, not repeated here.

1. Dynamic exploit confirmation reached 5/6 CVEs in the best local round, and every

catalogue class confirmed at least once overall (Section 3.10).

2. Two confirmation-rate swings across rounds traced to fixable implementation defects, not model capability: a reported "confirmation rate" is only as trustworthy as its own harness.

3. Patch acceptance lagged confirmation throughout: at most 1/6 per local round, 0/48 then 3/48 across the two 48-run comparisons.

4. This project's single most important finding: the validation criterion behind that "passing" flag was itself found, by trace-level inspection, to accept a patch for the wrong reason at least once, since it cannot distinguish a deliberate block from an unrelated crash. Every raw pass/fail count in this project should accordingly be read as what the harness reported, not an automatically trustworthy verdict (Section 4.1.2).

5. Correcting that criterion into a four-outcome verdict and scaling up (a sixth local round, a 36-run hosted comparison) did not increase heuristic screening passes beyond 4–5/6 per model, under a criterion itself limited to crash-absence; not all remaining failures represent incorrect patches, given the known XSS oracle issue (Section 4.1.2), and reported cost tracked model tier, not pass rate.

6. A real, pinned-version PyPI package (`jaraco.context`) reached this project's full evidence-gating standard against the actual named package, not a reproduction: one case of six (Section 4.1.3).

7. The same standard transferred to a second, unrelated domain: OpenEMR's GHSA-q366-cv5v-83w8, confirmed against the real, unmodified application (Section 4.1.4).

8. A third real-upstream case, free5GC, closed a shared one-line defect enabling unauthorized read, collection-wide read, write, and delete across all four manually selected handlers (the malicious side relying on a heuristic leaked-data signal rather than exact-content matching, Section 3.8.2), while the legitimate path was separately verified for two of the four (single-record read and delete) — this project's most complete end-to-end case.

5.4 Contributions

This project's contributions are as follows. (1) A dynamic-execution and self-improvement extension to an existing exploit-confirmation pipeline, evaluated with real subprocess and HTTP evidence rather than static description. (2) A two-check, evidence-gated patch-acceptance mechanism and a corrected four-outcome verdict (Section 4.1.2), built

specifically in response to a confirmed false acceptance the original criterion could not detect, and itself subsequently audited for what its own benign-route check does and does not establish. (3) A reachability-filtering capability applied in this project to real, disclosed free5GC source, verified by compile and then by runtime confirmation for all four manually selected handlers (CVE-2026-40245 through CVE-2026-40248), finding the underlying bug to be a full CRUD bypass rather than a single-record issue — this project's most complete real-system case. (4) A reproducible, sampling-pinned eight-model comparison and a second, 36-run comparison across six hosted Claude models, under an identical protocol with real token accounting and a reported cost estimate. (5) Two further real-upstream validation cases against actual, unmodified software: a pinned-version PyPI package (Section 4.1.3) and a disclosed OpenEMR advisory in a second, unrelated application domain (Section 4.1.4).

5.5 Limitations

The results in this project should be read within stated bounds. The main pipeline's exploited targets are generated reproductions, not the real named packages, for all six main-catalogue CVEs; a confirmed exploit demonstrates the described pattern is exploitable as reproduced, not that the real package is. One of the six, CVE-2026-23949, additionally has a separate, dedicated experiment against the real, pinned-version package (Section 4.1.3) — a single case selected for tractability, not evidence the remaining five could be validated the same way without comparable effort.

The free5GC reachability result avoids this limitation by a different route, operating on real, cloned source: all four manually selected handlers' patches were verified to compile, and all four (CVE-2026-40245 through CVE-2026-40248) were additionally confirmed at runtime, without deploying the rest of the core network stack or enabling OAuth2 enforcement on the real NRF used in the fuller deployment.

The eight-model local comparison used a single deterministic shot per CVE per model, and its strongest-confirming model carried prior prompt-tuning exposure the others did not, a real confound; the 36-run hosted comparison shares this single-shot design and adds its own, since the Claude CLI exposes no temperature or seed control at all. Patch generation and validation remained the main unresolved engineering challenge: the hosted comparison recorded 4–5 of 6 heuristic screening passes per model, and known XSS oracle errors prevent interpreting all remaining failures as incorrect patches; whether per-class prompt tuning would close it further was not tested.

The extended-access comparison, the OAuth2-enforced follow-up, and the prompt/cache repeatability check (Sections 4.1.9 and 4.1.10) are reported in Chapter 4 alongside the results they extend, not repeated here: in summary, OAuth2 enforcement and the code-level fix are independent, complementary layers, and every repeatability

attempt's limits were environment-specific, not evidence of model-quality failure.

5.6 Future Work

Five directions follow directly from the limitations above.

1. The cross-model `not_blocked` result for Cross-Site Scripting (Section 4.1.6) is a heuristic screening result, not confirmed patch incorrectness: at least one recorded failure was a false-positive marker signal in the generated target rather than a genuine patch defect (Section 4.1.2). Repairing the XSS oracle first — so that it checks actual rendered HTML output rather than only for marker absence — is a prerequisite before any per-class tuning pass on XSS patching can be meaningfully interpreted.

2. Patch generation would benefit from the same bounded, per-class tuning process already applied successfully to exploit-artifact generation in this project, starting with Cross-Site Scripting once the oracle repair above is in place. Any such tuning should be evaluated on held-out CVEs not seen during prompt development, since repeatedly tuning and scoring on the same six cases demonstrates engineering fit to those cases, not generalisation to unseen tasks.

3. The free5GC reachability work's runtime validation (Section 3.8.2), now confirmed for all four of its handlers (CVE-2026-40245 through CVE-2026-40248) under a fuller deployment with a real NRF, has since been extended with OAuth2 enforcement turned on (Section 4.1.10): the question of whether OAuth2 changes these CVEs' exploitability is answered in the negative for the three ported checks under the tested bearer-token conditions, but that follow-up only ported 3 of the original 5 runtime checks and minted its bearer token directly with the NRF's own private key rather than through a live client-credentials HTTP round-trip against NRF's own `/oauth2/token` endpoint. Porting the remaining unauthorized-write and confirmed-delete checks to the OAuth2-enabled harness, implementing the full client-credentials flow rather than a directly-minted token, and standing up additional network functions (AMF, SMF, and the rest) to test behaviour beyond UDR's own component boundary all remain future work, unifying the reachability engine's real-source analysis with the main pipeline's dynamic-confirmation discipline at greater scope.

4. The main pipeline's exploited targets could be moved from generated reproductions toward the actual named upstream packages for a larger subset of the catalogue than the one case demonstrated here, extending Section 4.1.3's methodology to the remaining five classes.

5. The hosted-model comparison could be extended with sampling controls once the Claude CLI (or an equivalent hosted interface) exposes them, and repeated across multiple shots per CVE per model to move from one data point per model toward a statistically powered ranking.

Bibliography

[1] "The Hugging Face incident and the road ahead," OpenAI, Aug. 26, 2026. https://openai.com/index/hugging-face-incident-and-the-road-ahead/ (accessed Sep. 22, 2026).

[2] E. Schluntz and B. Zhang, "Building effective AI agents," Anthropic Engineering, Dec. 19, 2024. https://www.anthropic.com/engineering/building-effective-agents (accessed Sep. 22, 2026).

[3] E. Weiss and N. Khayet, "Can AI weaponize new CVEs in under 15 minutes?," Efi Weiss, Aug. 21, 2025. https://valmarelox.substack.com/p/can-ai-weaponize-new-cves-in-under (accessed Sep. 22, 2026).

[4] Defense Advanced Research Projects Agency, "AIxCC Final Competition Results," DARPA, 2025. https://www.darpa.mil/news/2025/aixcc-results (accessed Sep. 25, 2026).

[5] T. Kim et al., "ATLANTIS: AI-driven threat localization, Analysis, and Triage intelligence system," arXiv (Cornell University), Sep. 2025, doi: 10.48550/arxiv.2509.14589.

[6] "OSS-CRS — Cyber Reasoning Systems for Open source software | OSS-CRS." https://oss-crs.openssf.org/ (accessed Sep. 22, 2026).

[7] The Linux Foundation, "World's Leading Open Source Mobile Packet Core, free5GC, Moves Under Linux Foundation to Provide Open Source Alternatives Across 5G Deployments," THE LINUX FOUNDATION, Sep. 16, 2024. https://www.linuxfoundation.org/press/worlds-leading-open-source-mobile-packet-core-free5gc-moves-under-linux-foundation-to-provide-open-source-alternatives-across-5g-deployments (accessed Sep. 22, 2026).

[8] M. C. Fanning and L. J. Golding, "Static Analysis Results Interchange Format (SARIF) version 2.1.0." Mar. 27, 2020. [Online]. Available: https://docs.oasis-open.org/sarif/sarif/v2.1.0/os/sarif-v2.1.0-os.html

[9] N. Korda and G. Evron, "OpenAnt: LLM-Powered Vulnerability Discovery Through Code Decomposition, Adversarial Verification, and Dynamic Testing," arXiv preprint arXiv:2606.19149 (2026). https://arxiv.org/abs/2606.19149

[10] Z. Sheng, Q. Xu, J. Huang, M. Woodcock, H. Huang, A. F. Donaldson, G. Gu, and J. Huang, "All You Need Is A Fuzzing Brain: An LLM-Powered System for Automated Vulnerability Detection and Patching," arXiv preprint arXiv:2509.07225, 2025. https://arxiv.org/abs/2509.07225. Competition repository (organisation `fuzzingbrain`, formerly listed as `o2lab`): https://github.com/fuzzingbrain/afc-crs-all-you-need-is-a-fuzzing-brain.

[11] Ollama. https://ollama.com/ (accessed Sep. 2026).

[12] W. Wang, W. Ma, Q. Hu, Y. Zhang, J. Sun, B. Wu, Y. Liu, G. Xu, and L. Jiang, "VulnRepairEval: An Exploit-Based Evaluation Framework for Assessing Large Language Model Vulnerability Repair Capabilities," arXiv preprint arXiv:2509.03331, Sep. 2025. https://arxiv.org/abs/2509.03331.

[13] Z. Yu, W. Shi, X. Sun, Z. Feng, M. Xu, and X. Xing, "Patch Validation in Automated Vulnerability Repair," arXiv preprint arXiv:2603.06858, Mar. 2026. https://arxiv.org/abs/2603.06858.

[14] D. Gezgin, A. Das, S. Kim, Z. Huang, N. Stojkovic, and C. Wang, "PoC-Gym: Towards More Reliable LLM-Assisted Proof-of-Concept Exploit Generation," arXiv preprint arXiv:2602.04165, Feb. 2026. https://arxiv.org/abs/2602.04165.

[15] R. Fang, R. Bindu, A. Gupta, and D. Kang, "LLM Agents can Autonomously Exploit One-day Vulnerabilities," arXiv preprint arXiv:2404.08144, Apr. 2024. https://arxiv.org/abs/2404.08144.

[16] Z. Qi, F. Long, S. Achour, and M. Rinard, "An Analysis of Patch Plausibility and Correctness for Generate-and-Validate Patch Generation Systems," in Proceedings of the 2015 International Symposium on Software Testing and Analysis (ISSTA), 2015. doi: 10.1145/2771783.2771791.

[17] C. Zhang et al., "SoK: DARPA's AI Cyber Challenge (AIxCC): Competition Design, Architectures, and Lessons Learned," arXiv preprint arXiv:2602.07666, Feb. 2026. https://arxiv.org/abs/2602.07666.

[18] Y. Zhu, A. Kellermann, A. Gupta, P. Li, R. Fang, R. Bindu, and D. Kang, "Teams of LLM Agents can Exploit Zero-Day Vulnerabilities," arXiv preprint arXiv:2406.01637, Jun. 2024. https://arxiv.org/abs/2406.01637.

[19] S. Ullah, P. Balasubramanian, W. Guo, A. Burnett, H. Pearce, C. Kruegel, G. Vigna, and G. Stringhini, "From CVE Entries to Verifiable Exploits: An Automated Multi-Agent Framework for Reproducing CVEs," arXiv preprint arXiv:2509.01835, Sep. 2025. https://arxiv.org/abs/2509.01835.

[20] Q. Liu, W. Zhang, M. Jiang, L. Wu, and Y. Zhou, "Characteristics, Root Causes, and Detection of Incomplete Security Bug Fixes in the Linux Kernel," arXiv preprint arXiv:2511.17799, Nov. 2025. https://arxiv.org/abs/2511.17799.

Appendix A

Reproducibility Details

A.1 Full CVE Catalogue

Table A.1: All eleven CVEs used across this project's evaluation: six in the main catalogue (Chapter 4), four in the free5GC work (Chapter 3, Table 3.6), and one in the ProvTrail integration (Chapter 3). A twelfth case, OpenEMR's GHSA-q366-cv5v-83w8 (Section 4.1.4), carries no CVE number and so is not listed below.

CVE	**Package**	**Class**	**CWE**	**Real source or reproduction**
CVE-2026-42208	litellm	SQL Injection	CWE-89	Reproduction (`target_app.py`)
CVE-2026-27602	modoboa	OS Command Injection	CWE-78	Reproduction
CVE-2026-23949	jaraco.context	Path Traversal	CWE-22	Reproduction
CVE-2026-78683	nltk	Insecure Deserialization	CWE-502	Reproduction
CVE-2026-54729	dssrf (npm)	SSRF	CWE-918	Reproduction
CVE-2026-46492	md-fileserver	XSS	CWE-80	Reproduction

continued on next page

CVE	Package	Class	CWE	Real source or reproduction
CVE-2026-40246	free5GC/udr	Improper Auth.	CWE-285	Reproduction (`free5gc_lab/`) *and* real upstream source (DELETE handler, runtime-confirmed)
CVE-2026-40245	free5GC/udr	Info. Disclosure	CWE-200/202/209	Real upstream source (collection-GET handler, compile- and runtime-confirmed)
CVE-2026-40247	free5GC/udr	Improper Auth.	CWE-285	Real upstream source (single-record GET handler, compile- and runtime-confirmed)
CVE-2026-40248	free5GC/udr	Improper Auth.	CWE-285, CWE-636	Real upstream source (PUT handler, compile- and runtime-confirmed)
CVE-2024-48910	dompurify (npm)	Prototype Pollution	CWE-1321	Reproduction (`provtrail_js_lab/`)

Every entry above was independently verified against GitHub's advisory API or commit API before use, not taken from a search-result summary. The table contains four distinct groups, not one uniform set: six CVEs (litellm through XSS) evaluated as local Python reproductions in the main catalogue (Chapter 4); CVE-2026-40246 evaluated *both* as a separate, hand-written Go reproduction (`free5gc_lab/`, no fix commit documented for that specific artifact) *and* against the real, cloned upstream source (its DELETE handler, with the real documented fix commit); CVE-2024-48910 demonstrated as a hand-authored JavaScript reproduction; and CVE-2026-40245/40247/40248, the three remaining cases where the real, cloned upstream `free5gc/udr` source itself was analysed and patched, each with its own documented fix commit (the same shared commit across all four CVEs): all four compile-verified, and additionally runtime-confirmed under a fuller Docker deployment (Section 3.8.2, Appendix A). An earlier internal correction (documented in `docs/FREE5GC_RUNTIME_VALIDATION_PLAN.md`) had relabelled the DELETE handler's real-upstream result from CVE-2026-40246 to CVE-2026-40248 for internal consistency with this project's own earlier reachability work, which had itself only checked the shared fix commit against one of the four disclosed advisories; checking all four

advisories directly against their own GHSA records (Table 3.6) shows this was incorrect, and the DELETE handler's real-upstream result is CVE-2026-40246's own result, not a fifth data point for CVE-2026-40248. The four CVEs share one root cause and one fix commit but are not one shared source-file-and-fix-commit experiment under a single identifier. CVE-2026-23949 additionally carries a second, separate evaluation not reflected in its table row above: alongside its main-catalogue reproduction, its real, pinned-version PyPI package (`jaraco.context`, versions `5.3.0` and `6.1.0`) was independently validated against a real exploit and the real published fix (Section 4.1.3); the two evaluations use different artifacts under different evidence standards and are reported separately throughout Chapter 4, exactly as CVE-2026-40246's two artifacts are.

A.2 free5GC Runtime Validation Evidence Bundle

The minimal, single-handler (DELETE) runtime validation of CVE-2026-40246 described first in Section 3.8.2 and its results is reproducible from the following artifacts, all committed to the `fyp` remote (`https://github.com/J-Dheeraj/Final-Year-Project`) under `free5gc_runtime_case/`, at commit `70281e5` (which supersedes commit `f09de67`, itself a correction of an initial CVE-identifier mislabelling introduced at commit `4524193`; both corrections are documented in `docs/FREE5GC_RUNTIME_VALIDATION_PLAN.md`, and the harness was re-run after each to confirm an identical result before this report was written). These committed artifacts themselves still record the identifier as CVE-2026-40248, per that same correction; this report uses the handler's actual disclosed identifier, CVE-2026-40246 (Table 3.6), which the raw stored files have not yet been re-generated to reflect:

Table A.2: free5GC runtime validation evidence bundle (`free5gc_runtime_case/`).

File	Contents
`run_harness.py`	The harness itself: builds the vulnerable and fixed commits, starts the stub NRF, drives the seed/malicious-delete/benign-delete request sequence, and writes every file below.
`stub_nrf/main.go`	The minimal HTTP/2-cleartext (h2c) stand-in NRF, built with the `golang.org/x/net/http2` and `golang.org/x/net/http2/h2c` packages (the extended `x/net` module, not Go's standard library), required only because free5GC's own NRF client negotiates h2c unconditionally and rejects an HTTP/1.1 responder.
`udrcfg.yaml`	The real UDR configuration used for both builds (local MongoDB URL, local NRF URI, cleartext SBI scheme).
`manifest.json`	Structured record of both runs: commit hashes, component/handler identifiers, services used, and the full per-run result objects.
`verdict.json`	The pipeline's own final verdict: whether the exploit was blocked, whether legitimate behaviour was preserved, the overall four-outcome verdict, and whether the vulnerable run confirmed the exploit.
`patch.diff`	The real, unmodified diff between the vulnerable and fixed commits for the affected source file.
`vulnerable_response.log`, `patched_response.log`	Full per-run HTTP status/body evidence for every request in the sequence (seed, pre-check, malicious delete, post-malicious check, reseed, benign delete, post-benign check).
`vulnerable_process.log`, `patched_process.log`	Raw stdout/stderr from each UDR process, including the diagnostic NRF-registration retry evidence that led to the stub-NRF fix.
`build_vulnerable.log`, `build_patched.log`	Full build output for both commits.
`vulnerable_commit.txt`	The exact vulnerable commit hash used (the fix commit's direct parent).

`docs/FREE5GC_RUNTIME_VALIDATION_PLAN.md` in the same repository documents the case selection rationale and the exact vulnerable/fixed commit hashes. It also documents two genuine implementation blockers found only by running the harness for real rather than

by reading source (UDR's NRF registration being a blocking infinite retry rather than "logged and non-fatal" as an earlier, shallower reading concluded; and the first, HTTP/1.1 stub NRF attempt failing with a client-side `http2: frame too large` error before the h2c requirement was identified), along with the CVE-identifier correction referenced above. `docs/PROJECT_STATUS.md`'s dated session-log entries for 2026-09-27 record the same work chronologically, including the correction, as this project's established multi-session coordination record.

The fuller-deployment extension covering all four handlers, described in the second half of Section 3.8.2, was developed and committed at `b8a4fe1` (2026-09-28), kept isolated from the single-handler bundle above so the two would remain distinguishable. Its evidence bundle, under `free5gc_full_deployment/evidence/`, follows the same schema. `manifest.json` and `verdict.json` record all four handlers' vulnerable- and patched-build outcomes (`overall_verdict: "confirmed_fix_all_four_handlers"`). `vulnerable_response.json` and `patched_response.json` record the full raw HTTP status, headers, and body for every request (including the collection-GET and single-PUT requests whose raw response bytes are the direct evidence for the stronger CRUD-bypass finding). `vulnerable_process.log`/`patched_process.log` record the real UDR container logs, including successful registration with the real free5GC NRF. `docs/FREE5GC_FULL_DEPLOYMENT_RESULTS.md` documents the deployment (real, official MongoDB and NRF images; a custom-built UDR image compiled from the same pinned commits as the single-handler case; OAuth2 explicitly disabled on the NRF, stated as an explicit limitation rather than omitted) and a caught-and-corrected mistake (an unrelated case study's commit hashes were briefly, and unsuccessfully, used for this build before the correct ones were substituted). This evidence is present on `main`, and this report source and its compiled PDF (`free5gc_full_deployment/FYP_Report_main_upgraded.tex`, `.pdf`) are likewise maintained on `main`: this is this project's single, current version, not a pending candidate for one. For precision: commit `b8a4fe1` is where the fuller-deployment evidence bundle and its harness were first established; this report's own narrative was subsequently updated to describe the all-four-handlers finding at commit `16d9b63`.

A.3 Model and Sampling Configuration

Table A.3: Exact configuration values used across the live-LLM evaluation (Chapter 4), read directly from `cve_pipeline.py`.

Parameter	Value
Default local model	`qwen2.5-coder:7b` (env override: `OLLAMA_MODEL`)
Sampling (round 5 onward)	`temperature=0`, `seed=42`, pinned specifically because round 1 vs. round 2 of the live-LLM run were not directly comparable without it (identical CVE and prompt flipped confirmed/unconfirmed between runs)
Per-call generation timeout	180 seconds
Self-improvement iteration bound	3
Ollama host	`http://127.0.0.1:11434` explicitly (fixed after an IPv4/IPv6 `localhost` ambiguity was found to silently flip availability checks)
Eight-model comparison set	`qwen2.5-coder:1.5b/3b/7b`, `llama3.1:8b`, `mistral:7b`, `gemma2:9b`, `codellama:13b`, `deepseek-coder-v2:16b`
Hosted Claude comparison set	`claude-haiku-4-5`, `claude-sonnet-4-6`, `claude-sonnet-5`, `claude-opus-4-6`, `claude-opus-4-7`, `claude-opus-4-8`; no temperature/seed control exposed by the CLI
Hosted comparison generation timeout	300 seconds (raised from the 180-second default specifically for two of the six models, found to genuinely exceed the shorter budget on realistic prompts)

Exact prompt wording is versioned directly in `cve_pipeline.py` and `src/pipeline/patch.py` in the source repository (Appendix D); it is not reproduced verbatim here for space. The pinned commit's source files document the prompts as they stand in that final, pinned snapshot of the pipeline; the prompts changed across the five development rounds described

in Chapter 4, and the exact wording used in any one specific earlier round is not separately preserved outside that round's own commit history. Table A.4 maps each round to the commit(s) where its own protocol and any code changes it depended on were introduced, so an examiner can check out the closest recorded code and prompt state for a specific round rather than only the final pinned snapshot; as that table notes, round 5's exact execution working tree was not independently captured, so "closest recorded" is not a guarantee of an exact match for that round specifically.

Table A.4: Round-to-commit mapping for the live-LLM catalogue runs (Chapter 4).

Round	Commit(s)	What changed at this point
1	`390c316`	First full six-CVE catalogue run under the frozen prompt; `qwen2.5-coder:7b` via local Ollama.
2	`4c1a386`	Fixed a schemeless-URL bug found in round 1's PoCs; re-ran the full catalogue.
3	`5ecd4d0` `6f932b4`	Ran with Stage 3.7 (self-improvement) newly wired to the live backend; `6f932b4` documents the markdown-fence and stale-exit-code bugs this round surfaced, before they were fixed.
4	`b05b45d` `9711fe5`	`b05b45d` fixes the two bugs found in round 3; `9711fe5` is the round-4 catalogue run itself, with the first patch accepted by the two-check criterion.
5	`348eea0` (code) `f5958d0` (results)	Ran after `56449a2` merged a parallel session's independent live-LLM work (multi-payload validation, pinned sampling) into `main`. `348eea0` is the parent of the results commit and the closest recorded pre-results code snapshot; the preserved raw log does not itself record a commit hash or a clean-working-tree check at execution time, so this is the closest available snapshot, not an independently verified exact match. `f5958d0` ("round 5 - full catalog on reconciled main, 5/6 confirmed") is the commit that adds all six JSON reports, `RAW_LOG.txt`, and this round's section of the live-run record.
6	`78fbaf0` (validator) `fd3d22f` (relabel)	`78fbaf0` introduces the corrected validator (Section 4.1.2) and the real-upstream CVE-2026-23949 case (Section 4.1.3). This round was launched intending a Claude Code CLI comparison, silently ran on Ollama instead due to an expired CLI session, and was relabelled as a sixth Ollama round in `fd3d22f` once the mislabelling was found by auditing `generation_backend` against the run's own stated protocol.
Hosted	`6fa5a3a` `6f159d6` `139240d` `289d8f3` `2075671`	The 36-run hosted-Claude comparison (Section 4.1.6) is not a numbered round of the main six-CVE catalogue sequence; these five commits add real cost/token capture, the silent-fallback fix, the extended-timeout option, the agentic-tool/session-persistence fix, and the completed 36-cell results, in that order.

An examiner wanting a specific round's prompt should check out that round's commit from Table A.4 rather than relying on the pinned snapshot's current source, keeping in mind the round-5 caveat stated there.

A.4 Hosted Claude Comparison: Per-CVE Cost and Time

Table A.5 gives the individual, per-CVE cost and wall-clock time underlying Table 4.7's per-model totals in Section 4.1.6. Cost is the sum of that run's generation, self-improvement, and patch-generation calls, read directly from the Claude CLI's own `total_cost_usd` field per call, itself an estimate computed from token counts at list price (per Anthropic's own documentation) rather than a verified billing record. Time is the pipeline's own recorded end-to-end wall-clock duration for that CVE, including advisory/analysis/probe stages, dynamic execution, and patch validation, not model generation time alone.

Table A.5: Per-CVE cost (USD) and wall-clock time (s) for every model–CVE cell in the hosted Claude comparison (36 cells total).

Model	**CVE**	**Verdict**	**Cost**	**Time (s)**
Haiku 4.5	42208	confirmed_fix	0.26	112.3
Haiku 4.5	27602	confirmed_fix	0.26	119.0
Haiku 4.5	23949	confirmed_fix	0.24	90.6
Haiku 4.5	78683	confirmed_fix	0.55	323.0
Haiku 4.5	54729	confirmed_fix	0.26	120.4
Haiku 4.5	46492	not_blocked	0.24	84.3
Sonnet 4.6	42208	confirmed_fix	0.73	130.3
Sonnet 4.6	27602	confirmed_fix	0.34	80.3
Sonnet 4.6	23949	confirmed_fix	0.74	130.8
Sonnet 4.6	78683	not_blocked	0.80	173.5
Sonnet 4.6	54729	confirmed_fix	1.14	257.8
Sonnet 4.6	46492	not_blocked	0.74	141.0
Sonnet 5	42208	confirmed_fix	0.68	104.0
Sonnet 5	27602	confirmed_fix	0.69	99.8
Sonnet 5	23949	confirmed_fix	0.65	88.6
Sonnet 5	78683	not_blocked	0.87	123.8

Model	CVE	Verdict	Cost	Time (s)
Sonnet 5	54729	confirmed_fix	0.70	134.0
Sonnet 5	46492	not_blocked	0.67	104.5
Opus 4.6	42208	inconclu-sive_crash	1.24	187.7
Opus 4.6	27602	confirmed_fix	1.47	185.2
Opus 4.6	23949	confirmed_fix	1.36	259.8
Opus 4.6	78683	confirmed_fix	1.39	285.4
Opus 4.6	54729	confirmed_fix	1.28	189.4
Opus 4.6	46492	not_blocked	1.31	237.1
Opus 4.7	42208	confirmed_fix	0.77	85.6
Opus 4.7	27602	confirmed_fix	0.70	70.5
Opus 4.7	23949	confirmed_fix	0.79	106.8
Opus 4.7	78683	confirmed_fix	1.71	150.1
Opus 4.7	54729	confirmed_fix	0.73	83.7
Opus 4.7	46492	not_blocked	0.82	128.2
Opus 4.8	42208	confirmed_fix	1.74	170.2
Opus 4.8	27602	confirmed_fix	2.05	247.2
Opus 4.8	23949	confirmed_fix	0.81	189.3
Opus 4.8	78683	confirmed_fix	2.13	249.2
Opus 4.8	54729	confirmed_fix	0.95	256.8
Opus 4.8	46492	not_blocked	1.38	258.5

CVE identifiers above are abbreviated to their final five digits (e.g. `42208` = CVE-2026-42208); the class each maps to is given in Table A.1 in Section A. Raw per-cell reports: `reports/model_comparison_pilot_2026-09-25/<model>/<CVE-ID>.json`.

Summing the 36 individually-rounded cost cells shown above gives $33.19, one cent more than Table 4.7's stated $33.18 total, which is itself one cent more than that table's own per-model cells summed ($33.17). All three figures are internally consistent, not contradictory. Each is the same underlying unrounded cost, accumulated and rounded in a different order (36 roundings here, 6 roundings there, versus one rounding of the true unrounded grand total, $33.1790536, independently recomputed by summing each report's own `generation_cost_usd` and `patch_gen_cost_usd` fields plus every `refinement_history` entry's `revision_cost_usd` field, not read from a single pre-aggregated total). This is an ordinary cascading-rounding artifact, not a data discrepancy; its size depends on where in the calculation rounding occurs, not simply on how many addends are rounded, since

individual rounding errors can also partially cancel.

A.5 Validation Criteria (Quick Reference)

Full definitions, caveats, and audited scope for every term below are given once, in Section 3.9 and Section 4.1.2; this list restates only the term and its one-line gist for lookup convenience.

- **Dynamically confirmed**: a recorded subprocess execution outcome, HTTP exchange, or compiled-harness run, each real and not merely described.
- **Patch accepted by the two-check criterion** (raw `patch_validated` field): exploit fails and `/health` still returns 200; cannot distinguish a deliberate fix from an unrelated crash (Section 4.1.2); superseded by `patch_verdict` below.
- `patch_verdict` (Section 4.1.2): `confirmed_fix` (the historical label used by every report this thesis cites; renamed `heuristic_fix_screened` in newly generated reports), `regression_broke_route`, `inconclusive_crash`, or `not_blocked`, distinguishing a crash on the exploit side from one on the benign side.
- **Correct patch / stronger bounded validation**: the strict sense (independent second-reader adjudication) is not measured anywhere in this project; a stronger bounded-validation sense was established for three real-upstream cases and 6 recoverable LLM-generated artifacts (Section 4.1.2 states the exact, non-uniform malicious- and legitimate-side checks used for each), short of general correctness.
- **Compile-verified** (free5GC, original evidence tier): `go build` succeeds against the real, live-cloned upstream module; weaker than dynamic confirmation, since superseded by runtime confirmation.
- **Runtime-confirmed** (free5GC, all four handlers): the real, cloned module built, run, and exercised over real HTTP for both commits (Section 3.8.2); meets the **Dynamically confirmed** standard above.

A.6 Relationship to AIxCC/OSS-CRS Vocabulary (Condensed)

This project's stages line up with AIxCC/OSS-CRS vocabulary as follows, condensed from this project's own internal mapping document. Stage 1 (advisory fetch) corresponds to OSS-CRS's `prepare` phase, except that it pulls an already-known advisory rather than

preparing to discover one. Stage 3.5 (exploit-artifact generation) corresponds to `build-target`, except that it generates a minimal reproduction rather than compiling the real upstream project (the single biggest structural gap versus a real CRS, per Section 3.10). Stages 2, 3, 3.6, and 3.7 together correspond to the `run` phase's triage-and-verify loop. The two capabilities are best framed as complementary but partial: (1) the confirm-and-patch back half of a real CRS's loop, evaluated one known CVE at a time, and (2) a real, AST-based scope-reduction front half (`src/reachability/`) proven against one real, disclosed free5GC vulnerability. Neither claims the hardest capability a full CRS needs (discovering an *unknown* bug in an unmodified codebase) which this project does not attempt.

Appendix B

Selected Trace Excerpts

B.1 The False-Acceptance Case: CVE-2026-78683, Round 4 vs. Round 5

Both traces below are quoted directly from the corresponding round's raw JSON report, reformatted only for line length.

Round 4 (plausibly a genuine fix: deliberately raised exception):

```
 File "...target_app.iter1.v0.patched.py", line 20, in vulnerable
 raise ValueError("Deserialization only allowed for safe classes")
ValueError: Deserialization only allowed for safe classes
127.0.0.1 - - [23/Sep/2026 23:28:27] "POST /vulnerable HTTP/1.1" 500 -
=== poc.py (exit 1) ===
[-] FAILED
```

Round 5 (confirmed false acceptance: unrelated crash bug):

```
 File "...target_app.iter1.v0.patched.py", line 26, in vulnerable
 safe_unpickler = SafeUnpickler(io.BytesIO(data))
 ^^
NameError: name 'io' is not defined. Did you mean: 'id'? Or did you forget to import 'io'?
127.0.0.1 - - [24/Sep/2026 09:34:51] "POST /vulnerable HTTP/1.1" 500 -
=== poc.py (exit 1) ===
[-] FAILED
```

Both were recorded by the pipeline as `patch_validated: true`. Only the first is plausibly correct; the second is a crash the validation criterion could not distinguish from a fix (Section 4.1.2).

B.2 The Markdown-Fence Crash (Round 3)

Four of round 3's five unconfirmed CVEs crashed identically because a model-generated revision's `target_app.py` still contained a literal, unstripped ```` ```python ```` fence, making the file invalid Python:

```
 File "target_app.py", line 1
 ```python
 ^
SyntaxError: invalid syntax
```

Fixed in commit `b05b45d` via a dedicated `_strip_code_fence` helper; zero of round 4 or round 5's twelve reports contain this signature, checked programmatically.

B.3 free5GC Upstream Compile Verification

Output from applying all four generated patches directly to a live clone of `github.com/free5gc/udr` at the pre-fix commit and rebuilding against its real dependency graph:

```
=== Baseline: real vulnerable commit, unmodified ===
 [baseline (unpatched)] go build ./... -> OK
Applied 4/4 patches: [...]
=== After applying auto-generated patches to the REAL module ===
 [patched (real module)] go build ./... -> OK
```

B.4 free5GC LLM-Generated Patch: Multi-Model Comparison

The free5GC result reported above uses the real upstream maintainers' own fix commit, checked out directly, not a model-generated artifact. A separate, later experiment instead asked a real LLM to *write* the fix itself, for the one handler, `HandleApplicationDataInfluenceDataSubsToNotifyGet`, that the reachability engine's deterministic rule-based patcher is already documented to under-fix: that patcher inserts only one of the two `return` statements the handler's two separate early-exit validation blocks each need, since both share the identical missing-`return` bug pattern. The handler tests whether the generated patch repairs both known early-exit sites, including the site missed by the current deterministic patcher.

A local model (`qwen2.5-coder:7b`, via Ollama, zero recorded API charge; electricity and hardware use were not separately measured) correctly inserted `return` after both occurrences, a strict improvement over the rule-based patch. It was verified at the same two evidence tiers used throughout this chapter: compiled against a live clone of the real `free5gc/udr` module, then runtime-confirmed against the same real MongoDB and free5GC NRF deployment described in Section 3.8.2, yielding `overall_verdict: "confirmed_fix_all_four_handlers"`.

This was then extended to a comparison across every model locally available and across eight named hosted Claude models, keeping the target handler, the rule-based
```

patches for the other three handlers, and the two-tier verification method fixed, varying only the model asked to patch the one handler.

Table B.1: free5GC LLM-generated patch: eight locally-hosted models (Section B.4). *Pass* = `confirmed_fix_all_four_handlers`; *Partial* = `partial_or_inconclusive`.

Model	**Compiles**	**Applied/4**	**Runtime verdict**
`deepseek-coder-v2:16b`	Not reached: OOM	0/4	not reached
`codellama:13b`	Yes	4/4	Pass
`gemma2:9b`	Yes	4/4	Pass
`mistral:7b`	Yes	4/4	Pass
`llama3.1:8b`	Yes	4/4	Pass
`qwen2.5-coder:7b`	Yes	4/4	Pass
`qwen2.5-coder:3b`	Yes	4/4	Pass
`qwen2.5-coder:1.5b`	Yes	4/4	**Partial**

Six of eight local models compiled and were runtime-confirmed. `deepseek-coder-v2:16b` never produced a patch at all: it failed to load under this machine's available memory (a 45 GB buffer allocation request), a hardware limit, not evidence about that model's patching ability. `qwen2.5-coder:1.5b` is the more informative negative result. Its patch *compiled cleanly* but did not fix the bug: instead of the needed `return` statements, it appended an unrelated, syntactically valid response line after the function's existing logic. The runtime harness caught this precisely (`collection_get_leak_fixed: false`). A compile-only check, as used for the main free5GC evidence elsewhere in this chapter, would have reported this patch as equally successful as the other six models that genuinely compiled and ran (`deepseek-coder-v2:16b` never reached compilation at all, so it is not a seventh comparator here). This is a direct, concrete illustration of why this project's reachability track treats compile verification as strictly weaker evidence than runtime confirmation.

Even runtime confirmation under this specific harness is not exhaustive, however: `codellama:13b`'s patch, recorded as `confirmed_fix_all_four_handlers` and 98.51% textually similar to the real upstream fix (the closest match of any model that did not reproduce the fix byte-for-byte), was found on direct static inspection of the saved patched source to still omit the required `return` after the malformed-`snssai` deserialization error branch, the second of the two sites CVE-2026-40245's own advisory identifies as needing the fix. This branch is not exercised by this harness's own request sequence (which sends only an empty-query collection GET, not a request with a malformed `snssai` parameter), so the harness correctly reports every request it actually sent as handled, while remaining unable

to detect this specific, real, uncovered gap. The 6/8 pass count above should accordingly be read as six models passing the specific branches this harness exercises, not as six fully repaired handlers; extending the harness to exercise the malformed-`snssai` branch, and a legitimate filtered collection-GET request, would be needed to close this specific gap, and has not been done for this report.

Table B.2: free5GC LLM-generated patch: eight hosted Claude models, CLI-reported cost estimate (Section B.4). *Pass* = `confirmed_fix_all_four_handlers`.

Model	**Compiles**	**Cost (USD)**	**Runtime verdict**
`claude-haiku-4-5`	Yes	$0.2138	Pass
`claude-sonnet-5-5`	Yes	$1.1334	Pass
`claude-opus-5-5`	Yes	$0.1644	Pass
`claude-sonnet-4-6`	Yes	$0.1494	Pass
`claude-sonnet-5`	**Not reached: refusal**	$1.1130	not reached
`claude-opus-4-6`	Yes	$0.2477	Pass
`claude-opus-4-7`	Yes	$0.3427	Pass
`claude-opus-4-8`	Yes	$0.3460	Pass

Seven of eight hosted Claude models (accessed via the `claude` CLI's own authenticated session rather than a separate API key, mirroring the mechanism this project's main pipeline already uses when a raw key is not configured) compiled and were runtime-confirmed, for a combined CLI-reported cost of $2.60 for those seven models; the `claude-sonnet-5` refusal carries a separate $1.11 diagnostic cost, bringing the sweep's reported total to $3.71 (this excludes the separately reported $5.49 in preliminary smoke tests). `claude-sonnet-5` is the remaining negative result, and a different kind from `qwen2.5-coder:1.5b`'s. The CLI's own usage report identifies it with a 1,000,000-token context window and a `firstParty` provider tag, distinct metadata from the other models in this comparison, though this project does not independently verify that this metadata corresponds to genuinely distinct underlying model weights. The recorded diagnostic response attributed the refusal to Sonnet 5's safeguards and directed the account to the Cyber Verification Program. This project did not independently identify the trigger terms or the internal decision mechanism. The refusal itself still carried a nonzero reported cost figure. This is an observed access limitation for this request and authenticated CLI route, alongside its reported nonzero diagnostic cost.

Two further robustness issues were found and fixed directly as a consequence of this comparison, both in the shared patch-generation code path used by every model and provider in this project, not specific to any one model. First, the patch-generation prompt

template was originally written for a C target and retained its C-specific framing and code-fence language even when applied to free5GC's Go source; a language-aware system prompt and fence selection, keyed on the target file's extension, was added. Second, one hosted model twice ignored an explicit "no commentary" instruction in two different ways across two separate attempts (once appending an explanation after a closing code fence, once with no fence at all). In both cases the underlying fix was logically correct, but trailing prose corrupted the surrounding Go source and caused a compile failure unrelated to the fix itself. This was resolved by truncating the model's response at the target function's own final, unindented closing brace unconditionally, rather than relying on fence detection, since every target in this comparison is syntactically a single complete function.

This comparison does not control for training-data memorisation: the real, public fix commit may appear in some models' training data, and a model reproducing it from memory is, in this experimental design, indistinguishable from one genuinely re-deriving it from the function body and vulnerability description alone. Each model was also run once; `qwen2.5-coder:7b` was observed to produce a textually different but semantically identical patch on a repeat run, a direct, if harmless, demonstration that single-run results in this comparison do not capture run-to-run variance.

B.5 free5GC Adversarial Bypass-Probe: Can a Model Find a Way Past the Real Fix?

The comparison above asks whether a model can *write* the fix. A separate, later experiment asks the opposite question: given the real, already-deployed upstream fix, can a model find an HTTP-request-level trick (encoding, case, path manipulation, headers, trailing or duplicate path segments) that still reaches the protected resource? The upstream fix closes the known missing-return fall-through paths. This bounded probe asks whether the selected models can propose a request-level way around that fix. Each of the eight locally-hosted models and eleven named hosted Claude models was asked to propose one concrete HTTP request. The historical prompt described the patched handlers as having no remaining code-path gap. This was a framing assumption supplied to the models, not an exhaustive property established by the experiment. The result is interpreted here only as a bounded request-level probe of the known fix. Each successfully parsed, valid proposal was then *actually executed* against the real, already-built upstream-fix image (`free5gc-udr-custom:patched`) running on the same real MongoDB and free5GC NRF deployment used throughout this chapter, not evaluated by inspection.

Result: zero genuine bypasses were found, across every model tested, local or hosted.

A real defect in this experiment's own classifier was found and fixed before any result was reported. The first version flagged three models as having found a successful bypass purely because their proposed request returned a 200 response containing the protected data, without checking whether that request actually differed from the ordinary, fully authorised request. Two of the three proposals were, after inspection, byte-for-byte identical to the correct, legitimate path; a third used URL encoding (`%2F`) that decodes back to the identical canonical path. None of these are bypasses of anything (they are the intended request, which obviously returns 200), and two of the implicated models' own stated reasoning (a claimed trailing-dot trick, a claimed case variation) did not even match the request they actually issued, itself a finding about model reliability on this task rather than about the target. The classifier was corrected to require that a proposal's URL-decoded form differ from the canonical, fully authorised path before it can count as a genuine attempt at all; every result below reflects that corrected check, re-derived from the already-captured request and response data with no model re-queried.

Table B.3: free5GC bypass-probe: eight locally-hosted models against the real fix (Section B.5).

Model	**Genuine attempt**	**Bypass confirmed**
`deepseek-coder-v2:16b`	Not reached (out-of-memory)	Not tested
`codellama:13b`	No: restated the correct path	No
`gemma2:9b`	Yes	No
`mistral:7b`	Yes	No
`llama3.1:8b`	Yes	No
`qwen2.5-coder:7b`	No: `%2F`-encoding of the correct path	No
`qwen2.5-coder:3b`	No: restated the correct path	No
`qwen2.5-coder:1.5b`	No: restated the correct path	No

Only three of the seven models that produced a response (`gemma2:9b`, `mistral:7b`, `llama3.1:8b`) proposed a request that was genuinely distinct from the legitimate one despite every model being explicitly asked for one; all three were correctly rejected by the real fix with a `400` or `404` response, and none altered the protected record.

Table B.4: free5GC bypass-probe: eleven named hosted Claude models against the real fix, CLI-reported cost estimate (Section B.5).

Model	Genuine attempt	Cost (USD)	Bypass confirmed
`claude-haiku-4-5`	Yes	$0.2321	No
`claude-sonnet-4-5`	Yes	$0.6539	No
`claude-sonnet-4-6`	No: restated the correct path	$0.6540	No
`claude-sonnet-5`	CLI failure; cause unrecorded	Not recorded	Not tested
`claude-sonnet-5-5`	Failed to resolve (`unrecognized_model`)	Not recorded	Not tested
`claude-opus-4-6`	No: restated the correct path	$1.0744	No
`claude-opus-4-7`	Yes	$1.4122	No
`claude-opus-4-8`	No: restated the correct path	$1.4235	No
`claude-opus-4-9`	Failed to resolve (`unrecognized_model`)	Not recorded	Not tested
`claude-opus-5`	**Refused the task**	$4.2345	Not tested
`claude-opus-5-5`	**Refused the task**	$1.9371	Not tested

The Claude run's total reported cost estimate was $11.62, reported here as this specific bypass sweep's own cost figure (the largest reported for a single sweep script invocation in this project; the hosted 36-run patch-generation comparison's own total, $33.18, is larger still). Two results stand out beyond the headline zero-bypasses finding. First, `claude-opus-5` and `claude-opus-5-5` declined to produce an exploit payload at all, even under the same authorised-red-team framing every other model in this chapter, local or hosted, accepted without objection; both refusals still carried a nonzero reported cost figure, with `claude-opus-5`'s refusal alone reporting a higher cost than any other single call recorded in this bypass sweep. This is a materially different provider-labelled response from `claude-sonnet-5`'s refusal on the patch-generation prompt reported above, which referred to safeguards and the Cyber Verification Program; this project does not independently verify the internal mechanism of either refusal. Second, two model identifiers explicitly recorded `unrecognized_model` (`claude-sonnet-5-5` and `claude-opus-4-9`), and `claude-sonnet-5` recorded an exit-1 CLI failure with no recorded cause – three untested outcomes in total. `claude-sonnet-5-5` had compiled and been runtime-confirmed without issue earlier the same day under the patch-generation prompt (Section B.4); this inconsistency is reported as observed, not explained, given the cost already incurred investigating it further.

As with the patch-generation comparison, this result bounds what it shows: it is evidence the real fix holds against this specific, bounded set of request-level tricks attempted by these particular models in one run each, not a formal proof that no bypass exists, and a model's refusal to attempt a bypass is evidence about that model's willingness to perform the task, not about the target's security.

B.6 Classification Ablation: NVD/GHSA Ground-Truth Cross-Check

Table B.5: Ground-truth CWE cross-check between NVD and GitHub Security Advisories (Section 4.1.8).

CVE	NVD CWE	GHSA CWE(s)
CVE-2026-42208	CWE-89	CWE-89
CVE-2026-27602	CWE-78	CWE-78
CVE-2026-23949	CWE-22	CWE-22
CVE-2026-78683	CWE-502	CWE-502
CVE-2026-54729	CWE-918	CWE-918
CVE-2026-46492	CWE-80	CWE-80, CWE-87

Agreement across all six entries indicates the structured-CWE signal is consistent across both databases, though this is not independent replication of the underlying analysis, since advisories are commonly shared or ingested between the two sources.

Appendix C

Verbatim Prompts (Representative Sample)

Appendix D's results-location table points to the source files holding every prompt used in this project rather than reproducing all of them here. This appendix reproduces one representative pair verbatim (the reachability track's patch- generation system and user prompts (`src/reachability/patch.py`)) so a reader can see this project's actual prompting style without opening the repository.

```
SYSTEM PROMPT (Go target; a near-identical C/kernel variant is
selected when the target file is not Go):

You are a Go backend developer writing a minimal security fix for an
HTTP handler. Output ONLY the complete corrected function body (same
signature, same style), no markdown fences, no commentary. Keep the
change as small as possible - do not refactor or rename anything not
required by the fix.

USER PROMPT TEMPLATE:

CWE: {cwe}
Vulnerability: {explanation}

Fix this function. Preserve its exact signature and behavior for
valid inputs; only add the missing bounds/validation/sanitization
needed to close the reported issue.

```{lang}
{body}
```
```

When a prior exploit attempt crashed the target, one further paragraph is appended to the user prompt, grounding the fix in that confirmed failure rather than only the triage stage's prose description:

````
A generated proof-of-vulnerability harness confirmed this exact bug
crashes the original code:
```
{last 1000 characters of the crash log}
```
The fix must make this exact harness survive without crashing.
````

Appendix D

Repository and Artifact Access

The tracked reports, session logs, prompts, and source code referenced in this thesis are version-controlled and publicly accessible rather than reproduced in full here; some individual generated artifacts (for example, a specific run's exploit or target file written to a temporary sandbox directory during a single evaluation session) are referenced by the machine path recorded at the time and are not themselves preserved in the repository, only the structured JSON report summarising that run. This appendix, together with Appendices A and B, is intended to support an audit trail for this thesis's specific claims; full verification of a specific raw response, log, or generated artifact not reproduced here still requires the cited repository records, since some individual artifacts are referenced by path rather than preserved, per the caveat above. The repository itself is offered for anyone wanting to go further (re-run a case, inspect a full prompt, read a session log in full), with that same caveat for any artifact an examiner may want that was not itself committed.

- **Repository**: `https://github.com/J-Dheeraj/Final-Year-Project`
- **Pinned commit**: `ea062ab4d13b5d3e3f40b275d31d01979244ca1c` (the commit this thesis's claims were checked against as of this update, following several rounds of review and correction; `ed00551d6a5a5a13348c2cea9d12ce6374810869` was the pinned commit for the results predating Section 4.1.2). The full chain of superseded pins, and what each round corrected, is in this repository's own commit history (`git log`) rather than repeated here. The `bb96fdb`/`ed00551` hashes were updated on 2026-10-10 after a history rewrite removed an accidentally committed, already-revoked API credential from an unrelated environment-template file; the rewrite changed every commit's hash but not its content, so each of those two hashes still points to the same commit content the original pin identified. As with every prior pin in this project, `git tag -l 'fyp-rd-freeze-*'` lists any newer freeze tag superseding this one.

Table D.1: Where each result reported in this thesis lives in the repository.

Result	Repository path
Original template-mode baseline catalogue	`reports/CVE_CATALOG.md`
Live-LLM catalogue runs, rounds 1–6	`reports/LIVE_LLM_CATALOG_RUN.md`
Eight-model comparison (initial, 48 runs)	`reports/MULTI_MODEL_COMPARISON.md`
Patch-validation investigation and retest	`reports/PATCH_VALIDATION_INVESTIGATION.md`
Corrected validator (implementation)	`src/pipeline/patch.py`
Real-upstream validation (CVE-2026-23949)	`real_upstream_case/CVE-2026-23949/RESULTS.md`
Real-upstream validation (GHSA-q366-cv5v-83w8, OpenEMR)	`docs/OPENEMR_TRANSFER_RESULTS.md`, `openemr_transfer_case/`
Hosted Claude 6-model comparison (36 runs)	`reports/model_comparison_pilot_2026-09-25/RESULTS.md`
Stronger, content-verified patch reassessment	`reports/patch_reassessment_2026-09-26/RESULTS.md`
Consolidated session record for this update	`docs/SESSION_2026-09-25_MULTI_AGENT_COMPARISON.md`
Benchmark protocol and classification ablation	`docs/BENCHMARK_PROTOCOL.md`
Reachability engine and free5GC case study	`docs/REACHABILITY.md`, `src/reachability/`
free5GC LLM-generated patch, single-model + sweeps (Section B.4)	`docs/FREE5GC_LLM_PATCH_RESULTS.md`, `docs/FREE5GC_LLM_MODEL_SWEEP_RESULTS.md`, `docs/FREE5GC_LLM_CLAUDE_SWEEP_RESULTS.md`

continued on next page

Result	Repository path
free5GC adversarial bypass-probe (Section B.5)	`docs/FREE5GC_BYPASS_PROBE_RESULTS.md`, `docs/FREE5GC_CLAUDE_BYPASS_PROBE_RESULTS.md`
free5GC dynamic-exploitation lab	`docs/FREE5GC_LAB.md`, `free5gc_lab/`
Full scope and limitations statement	`docs/SCOPE_AND_LIMITATIONS.md`
Alternative approach considered and rejected	`docs/CONSIDERED_DIRECTIONS.md`
AIxCC/OSS-CRS stage mapping (full)	`docs/CRS_MAPPING.md`
Full development session log	`docs/PROJECT_STATUS.md`
Pipeline orchestration and exact prompts	`cve_pipeline.py`, `src/pipeline/patch.py`