

## Pressure measurements

JMO Massey<sup>†</sup>, F Cabrera-Booman, T Jaroslowski, JC Klewicki, BJ McKeon


Center for Turbulence Research  
Stanford University

October 2, 2025

Thanks to DARPA for funding this work.




1. Focus on 50psi ph calibration signals
2. Show the raw signals
  - ▶ Show loglog for 3 cases.
  - ▶ No noise, w. background noise, white noise ?
3. Show the spectra
4. Show with HP filtering
5. Apply transfer function and show the TF
6. Determine whether a LP filter can be applied at  $f = 2kHz$ 
  - ▶  $T^+ \equiv Tu_\tau^2/\nu$
  - ▶ at 50psi  $Re_\tau \approx 5000$   $u_\tau \approx 0.51$ ,  $\nu \approx 1.43$
  - ▶  $T^+ = 20 \rightarrow f = 948Hz$
- 7.

# Raw signals




**Top left:** white noise, **top right:** *only* facility noise, **bottom:** white noise + facility noise


# Raw Spectra



## Does the noise add up?




## Does the noise add up?




Yes, it does! Does this mean we can subtract the facility noise from all of the calibration cases?

# TF reconstructed spectra



Filter at 0.1Hz and 2kHz corresponding to LP cutoff of  $T^+ = 10$  at 50psi





## Raw Spectra with HP filter: no difference in the calibration signal

