Determine pinhole size

J. M. O. Massey

September 22, 2025

1 Introduction

In the measurement of wall pressure fluctuations in a turbulent boundary layer, we use a microphone cap with a pinhole (PH) to avoid spatial attenuation and aliasing effects. To reconstruct the measured pressure, we must callibrate the treated microphone setup and determine a transfer function (H) that maps PH \mapsto NKD, where NKD is the known pressure measurement. If the PH is too small, the suppression of the signal is too much and H is ill-posed.

Past data has shown that an inner- and outer-scaled part of the premultiplied wall-pressure spectra exist, with the inner-scaled part being invariant to frictional Reynold's number ($\delta^+ \equiv \delta u_\tau/\nu$) (Massey et al., 2025). Figure 1 shows that the peak of the inner-function sits at

$$T^{+} \approx 20,\tag{1}$$

where the \bullet^+ superscript denotes normalisation by viscous length ν/U_{τ} . With this region of known behaviour, we can determine the size of the pinhole and correct accordingly.

2 Spatial approximation using Taylor's frozen turbulence hypothesis

Convection velocity can be used to convert temporal fluctuations into spatial structures such that

$$c_x^+ \equiv \frac{\omega^+}{k_x^+} \stackrel{\omega^+ = 2\pi f^+}{\longleftrightarrow} \frac{c_x^+}{\lambda_x^+} = f^+. \tag{2}$$




Figure 1: Inner-scaled, pre-multiplied wall-pressure spectra in inner-(left) and outer-scaled (right) coordinates for a range of Reynolds numbers. The region $T^+ \leq 20$ is highlighted in green. Data from Eitel-Amor *et al.* (2014); Fritsch *et al.* (2020, 2022)

Propagating the equality-acknowledging the relationship $T^+ \equiv 1/f^+$ -established in (1) leads to

$$\frac{\lambda_x^+}{c_x^+} < 20 \tag{3}$$

In this context, $\lambda_x^+ \equiv \frac{\ell u_\tau}{\nu}$ is the wavelength of the attenuated structures and c_x^+ is the convection velocity of the structures. The convection velocity of the pressure fluctuations is not constant throughout the boundary-layer (Willmarth & Wooldridge, 1962; Corcos, 1964), but a widely adopted approximation is $c_x^+ \approx 10$ leading to

$$\frac{\ell u_{\tau}}{\nu} < 200. \tag{4}$$

3 Viscous scales in the Stanford wind tunnel

The plan is to deploy three pinholes, the largest is geared to the atmospheric conditions, the smallest to the highest δ^+ , maximum pressure, and one in between. For this study, the boundary-layer thickness is fixed at $\delta = 0.035$ m and the free-stream velocity is fixed at $U_{\rm CL} = 14~{\rm ms}^{-1}$.

δ^+	$\nu/u_{\tau} \; [\mu \mathrm{m}]$	$\ell_{\rm max} \ [{ m mm}]$
1500	29.00	5.80
4300	7.97	1.59
8200	4.00	0.80

References

CORCOS, G. M. 1964 The structure of the turbulent pressure field in boundary-layer flows. *J. Fluid Mech.* 18 (03), 353.

EITEL-AMOR, GEORG, ÖRLÜ, RAMIS & SCHLATTER, PHILIPP 2014 Simulation and validation of a spatially evolving turbulent boundary layer up to. *International Journal of Heat and Fluid Flow* 47, 57–69.

FRITSCH, DANNY, VISHWANATHAN, VIDYA, DUETSCH-PATEL, JULIE, GARGIULO, ALDO, LOWE, KEVIN T. & DEVENPORT, WILLIAM J. 2020 The Pressure Signature of High Reynolds Number Smooth Wall Turbulent Boundary Layers in Pressure Gradient Family. In AIAA AVIATION 2020 FORUM. VIRTUAL EVENT: American Institute of Aeronautics and Astronautics.

FRITSCH, DANIEL J., VISHWANATHAN, VIDYA, TODD LOWE, K. & DEVENPORT, WILLIAM J. 2022 Fluctuating Pressure Beneath Smooth Wall Boundary Layers in Nonequilibrium Pressure Gradients. *AIAA Journal* **60** (8), 4725–4743.

MASSEY, JONATHAN M. O., SMITS, ALEXANDER J. & McKeon, Beverley J. 2025 Eddy population based model for the wall-pressure spectrum at high Reynolds number. ArXiv:2507.23098 [physics].

WILLMARTH, W. W. & WOOLDRIDGE, C. E. 1962 Measurements of the fluctuating pressure at the wall beneath a thick turbulent boundary layer. *J. Fluid Mech.* 14 (2), 187–210.