

Pressure signal processing


JMO Massey[†], F Cabrera-Booman, T Jaroslawski, J Klewicki, BJ McKeon

Center for Turbulence Research
Stanford University

August 20, 2025

Thanks to DARPA for funding this work.

Going from raw data to clean spectra

Raw measurements from pinhole (PH) mic.  Cleaned pressure spectra.








Figure: Complete pressure processing pipeline for measurement of the WPFs through a pinhole microphone.
similar to Tsuji et al. (2007)


Microphone calibration: Nose Cone (NC)



Microphone calibration: Pinhole (PH)



Corrected signals



Calibration algos

Algorithm 1 H Transfer-Function Estimation

Require: $x[n]$ (ref), $y[n]$ (treated), f_s , Welch (N_{seg} , N_{ov} , w)

Ensure: $f[k]$, $H[k]$, $\gamma^2[k]$

- 1: Compute $S_{xx}[k]$, $S_{yy}[k]$ (Welch)
 - 2: Compute $S_{xy}[k]$ (same settings)
 - 3: $H[k] \leftarrow S_{xy}[k]/S_{xx}[k]$
 - 4: $\gamma^2[k] \leftarrow |S_{xy}[k]|^2/(S_{xx}[k]S_{yy}[k])$
 - 5: **return** $(f[k], H[k], \gamma^2[k])$
-

Algorithm 2 Coherence-weighted Wiener inverse

Require: y_r , f_s , grid f , $H(f)$, $\gamma^2(f)$

Ensure: y

- 1: $y_r \leftarrow y_r - \text{mean}(y_r)$
 - 2: $\hat{y}_r \leftarrow \mathcal{F}(y_r, N_{\text{fft}})$
 - 3: $m \leftarrow |H|$, $\phi \leftarrow \text{unwrap}(\angle H)$
 - 4: Interp m, ϕ, γ^2 to FFT grid $\Rightarrow m_i, \phi_i, \gamma_i^2$
 - 5: $H_i \leftarrow m_i e^{j\phi_i}$; $\varepsilon \leftarrow \text{machine epsilon}$
 - 6: $H_{\text{inv}} \leftarrow \gamma_i^2 H_i^*/\max(m_i^2, \varepsilon)$
 - 7: $H_{\text{inv}}[0] \leftarrow 0$ (& Nyquist if present)
 - 8: $y \leftarrow \Re\{\mathcal{F}^{-1}(\hat{y}_r \cdot H_{\text{inv}})[0:N]\}$
 - 9: **return** y
-

References

TSUJI, Y., FRANSSON, J. H. M., ALFREDSSON, P. H. & JOHANSSON, A. V. 2007 Pressure statistics and their scaling in high-Reynolds-number turbulent boundary layers. *J. Fluid Mech.* **585**, 1–40.