

DSA Introduction >

Data Structures (I) >

Data Structures (II) >

Tree based DSA (I) >

Tree based DSA (II) >

Graph based DSA >

Sorting and Searching Algorithms ^

Bubble Sort

Selection Sort

Insertion Sort

Merge Sort

Quicksort

Counting Sort

Radix Sort

Bucket Sort

Heap Sort

Shell Sort

Linear Search

Binary Search

Greedy Algorithms >

Dynamic Programming >

Other Algorithms >

Related Topics

Selection Sort Algorithm

Bubble Sort

Shell Sort Algorithm

Counting Sort Algorithm

Radix Sort Algorithm

Quicksort Algorithm



Simplify software development with the One DevOps Platform. Start your free 30 day trial today!

ADS VIA CARBON

Insertion Sort Algorithm

In this tutorial, you will learn about insertion sort algorithm and its implementation in C, C++, Java and Python.

Insertion sort is a [sorting algorithm](#) that places an unsorted element at its suitable place in each iteration.

Insertion sort works similarly as we sort cards in our hand in a card game.

We assume that the first card is already sorted then, we select an unsorted card. If the unsorted card is greater than the card in hand, it is placed on the right otherwise, to the left. In the same way, other unsorted cards are taken and put in their right place.

A similar approach is used by insertion sort.

Working of Insertion Sort

Suppose we need to sort the following array.


9 5 1 4 3

Initial array

1. The first element in the array is assumed to be sorted. Take the second element and store it separately in `key`.

Compare `key` with the first element. If the first element is greater than `key`, then `key` is placed in front of the first element.

step = 1




If the first element is greater than key, then key is placed in front of the first element.

2. Now, the first two elements are sorted.

Take the third element and compare it with the elements on the left of it. Placed it just behind the element smaller than it. If there is no element smaller than it, then place it at the beginning of the array.



step = 2



Place 1 at the beginning

3. Similarly, place every unsorted element at its correct position.

step = 3



Insertion Sort Algorithm

```
InsertionSort(array)
  mark first element as sorted
  for each unsorted element X
    'extract' the element X
    for j <- lastSortedIndex down to 0
      if current element j > X
        move sorted element to the right by 1
    break loop and insert X here
  end InsertionSort
```

Insertion Sort in Python, Java, and C/C++

```
Python Java C C++

// Insertion sort in Java
import java.util.Arrays;

class InsertionSort {

  void insertionSort(int array[]) {
    int size = array.length;

    for (int step = 1; step < size; step++) {
      int key = array[step];
      int j = step - 1;

      // Compare key with each element on the left of it until an element smaller than
      // it is found.
      // For descending order, change key<array[j] to key>array[j].
      while (j >= 0 && key < array[j]) {
        array[j + 1] = array[j];
        --j;
      }

      // Place key at after the element just smaller than it.
      array[j + 1] = key;
    }
  }

  // Driver code
  public static void main(String args[]) {
    int[] data = { 9, 5, 1, 4, 3 };
```

Insertion Sort Complexity

Time Complexity	
Best	$O(n)$
Worst	$O(n^2)$
Average	$O(n^2)$
Space Complexity	
	$O(1)$
Stability	
	Yes

Time Complexities

- **Worst Case Complexity:** $O(n^2)$

Suppose, an array is in ascending order, and you want to sort it in descending order. In this case, worst case complexity occurs.

Each element has to be compared with each of the other elements so, for every n th element, $(n-1)$ number of comparisons are made.

Thus, the total number of comparisons = $n*(n-1) \sim n^2$

- **Best Case Complexity:** $O(n)$

When the array is already sorted, the outer loop runs for n number of times whereas the inner loop does not run at all. So, there are only n number of comparisons. Thus, complexity is linear.

- **Average Case Complexity:** $O(n^2)$

It occurs when the elements of an array are in jumbled order (neither ascending nor descending).

Space Complexity

Space complexity is $O(1)$ because an extra variable `key` is used.

Insertion Sort Applications

The insertion sort is used when:

- the array is has a small number of elements
- there are only a few elements left to be sorted

Similar Sorting Algorithms

1. [Bubble Sort](#)
2. [Quicksort](#)
3. [Merge Sort](#)
4. [Selection Sort](#)

Previous Tutorial:
[Selection Sort](#)

Next Tutorial:
[Merge Sort](#)

Share on:



Did you find this article helpful?



Related Tutorials

DS & Algorithms

Selection Sort Algorithm

DS & Algorithms

Bubble Sort

DS & Algorithms

Shell Sort Algorithm

DS & Algorithms

Counting Sort Algorithm

Programiz

Join our newsletter for the latest updates.

Enter Email Address*

Join



Tutorials

[Python 3 Tutorial](#)
[JavaScript Tutorial](#)
[SQL Tutorial](#)
[C Tutorial](#)
[Java Tutorial](#)
[Kotlin Tutorial](#)
[C++ Tutorial](#)
[Swift Tutorial](#)
[C# Tutorial](#)
[Go Tutorial](#)
[DSA Tutorial](#)

Examples

[Python Examples](#)
[JavaScript Examples](#)
[C Examples](#)
[Java Examples](#)
[Kotlin Examples](#)
[C++ Examples](#)

Company

[About](#)
[Advertising](#)
[Privacy Policy](#)
[Terms & Conditions](#)
[Contact](#)
[Blog](#)
[Youtube](#)

Apps

[Learn Python](#)
[Learn C Programming](#)
[Learn Java](#)

