A: 1:N error tradeoff by dataset and enrollment type. N = 1600000 individuals

B: Dependence of error rates on T by number enrolled identities, N, for Mugshot natural images

C: FPIR vs. Selectivity for mugshot images, N = 1600000 subjects enrolled with one recent mate

D: FPIR dependence on T by probe type for N = 1600000 subjects

E: DET for Mugshot natural images and various N. Links connect points of equal threshold.

F: Mugshot natural images, identification mode: FNIR(N, L+1, T) vs. most accurate (sensetime_004)

G: Datasheet

Algorithm: 3divi_3

Developer: 3Divi

Submission Date: 2018_06_19

Template size: 512 bytes

Template time (2.5 percentile): 486 msec

Template time (median): 610 msec

Template time (97.5 percentile): 826 msec

Frontal mugshot investigation rank 203 –– FNIR(1600000, 0, 1) = 0.0833 vs. lowest 0.0010 from sensetime_004

natural investigation rank 178 –– FNIR(1600000, 0, 1) = 0.2060 vs. lowest 0.0067 from sensetime_003

natural investigation rank 84 –– FNIR(1600000, 0, 1) = 0.1407 vs. lowest 0.0014 from visionlabs_009

natural investigation rank 92 –– FNIR(1600000, 0, 1) = 0.4742 vs. lowest 0.0694 from cib_000

Frontal mugshot identification rank 197 –– FNIR(1600000, T, L+1) = 0.3999 vs. lowest 0.0018 from sensetime_004

natural identification rank 178 –– FNIR(1600000, T, L+1) = 0.6257 vs. lowest 0.0122 from sensetime_003

natural identification rank 79 –– FNIR(1600000, T, L+1) = 0.6066 vs. lowest 0.0059 from sensetime_004

natural identification rank 71 –– FNIR(1600000, T, L+1) = 0.8221 vs. lowest 0.1129 from visionlabs_009

H: Investigational mode: FNIR(N, 1, 0) vs. most accurate (yitu_4)

I: Investigational mode: FNIR(1600000, R, 0) by probe type

Template duration; search duration vs. N. The blue and pink ribbon covers 95 percent of observed measurements. The template generation time is independent of N. The log and power−law models are fit to the first two (N,T) observations