

A: Datasheet

Algorithm: vigilantsolutions_008

Developer: Vigilant Solutions

Submission Date: 2021_07_23

Template size: 1544 bytes

Template time (2.5 percentile): 403 msec

Template time (median): 403 msec

Template time (97.5 percentile): 441 msec

Investigation:

Frontal mugshot ranking 70 (out of 288) -- FNIR(1600000, 0, 1) = 0.0029 vs. lowest 0.0009 from sensetime_006

Mugshot webcam ranking 78 (out of 250) -- FNIR(1600000, 0, 1) = 0.0171 vs. lowest 0.0057 from sensetime_006

Mugshot profile ranking 136 (out of 219) -- FNIR(1600000, 0, 1) = 0.9126 vs. lowest 0.0550 from sensetime_006

Immigration visa-border ranking 91 (out of 177) -- FNIR(1600000, 0, 1) = 0.0142 vs. lowest 0.0009 from sensetime_006

Immigration visa-kiosk ranking 94 (out of 174) -- FNIR(1600000, 0, 1) = 0.1778 vs. lowest 0.0568 from cloudwalk_hr_000

Identification:

Frontal mugshot ranking 48 (out of 288) -- FNIR(1600000, T, L+1) = 0.0204, FPIR=0.001000 vs. lowest 0.0018 from sensetime_004


Mugshot webcam ranking 59 (out of 248) -- FNIR(1600000, T, L+1) = 0.0767, FPIR=0.001000 vs. lowest 0.0122 from sensetime_003

Mugshot profile ranking 144 (out of 218) -- FNIR(1600000, T, L+1) = 0.9988, FPIR=0.001000 vs. lowest 0.1331 from cloudwalk_hr_000


Immigration visa-border ranking 90 (out of 176) -- FNIR(1600000, T, L+1) = 0.1035, FPIR=0.001000 vs. lowest 0.0039 from sensetime_006

Immigration visa-kiosk ranking 82 (out of 171) -- FNIR(1600000, T, L+1) = 0.5183, FPIR=0.001000 vs. lowest 0.0925 from sensetime_006


B: Mugshot natural images, identification mode: FNIR(N, L+1, T) vs. most accurate (nec_004)




C: Evolution of accuracy for VIGILANTSOLUTIONS algorithms on three datasets 2018 – present




D: 1:N error tradeoff by dataset and enrollment type. N = 1600000 individuals




E: Dependence of error rates on T by number enrolled identities, N, for Mugshot natural images



F: FPIR vs. Selectivity for mugshot images, N = 1600000 subjects enrolled with one recent mate




G: FPIR dependence on T by probe type for N = 1600000 subjects



H: Reduced length candidate lists for human review


Dataset is border–border with time–lapse [10,15] YRS with N = 1600000. Probes are 10–15 years later than enrollment image




I: FNIR and FPIR dependence on threshold

Dataset is border-border with time-lapse [10,15] YRS with N = 1600000. Probes are 10-15 years later than enrollment image


False {Negative | Positive} Identification Rate




J: DET for Mugshot natural images and various N. Links connect points of equal threshold.




K: Investigational mode: FNIR(N, 1, 0) vs. most accurate (sensetime_006)





L: Investigational mode: FNIR(1600000, R, 0) by probe type



M: Template duration; search duration vs. N. The blue and pink ribbon covers 95 percent of observed measurements. The template generation time is independent of N. The log and power-law models are fit to the first two (N,T) observations




O: FNIR(T, N = 1.6 million) by sex, age and time-lapse. The top row gives investigational rank-1 miss rates. The bottom panels give high threshold for more lights-out identification with low FPIR.



P: FPIR(N = 1.6 million) by sex and age. It is typical for false positive identification rates to be higher in women except in their teens.

Algorithm: vigilantsolutions_008, Dataset: Border-Crossing Ageing
Threshold: 0.828639 set to achieve FPIR(30–45, Male) = 0.001

Color encodes log(FPIR)



Q: Identification FNIR(N, T, L+1) and Investigational FNIR(N, 0, R) under ageing

Dataset: 2018 Mugshot N = 3068801

