




A: 1:N error tradeoff by dataset and enrollment type. N = 1600000 individuals




B: Dependence of error rates on T by number enrolled identities, N, for Mugshot natural images




C: FPIR vs. Selectivity for mugshot images, N = 1600000 subjects enrolled with one recent mate




D: FPIR dependence on T by probe type for N = 1600000 subjects



E: DET for Mugshot natural images and various N. Links connect points of equal threshold.



F: Mugshot natural images, identification mode: FNIR(N, L+1, T) vs. most accurate (sensetime\_004)



## G: Datasheet

Algorithm: microsoft\_1

Developer: Microsoft

Submission Date: 2018\_02\_12

Template size: 1024 bytes

Template time (2.5 percentile): 341 msec

Template time (median): 348 msec

Template time (97.5 percentile): 362 msec

Frontal mugshot investigation rank 49 --- FNIR(1600000, 0, 1) = 0.0035 vs. lowest 0.0010 from sensetime\_004

natural investigation rank 44 --- FNIR(1600000, 0, 1) = 0.0083 vs. lowest 0.0014 from visionlabs\_009


natural investigation rank 44 --- FNIR(1600000, 0, 1) = 0.1351 vs. lowest 0.0694 from cib\_000

Frontal mugshot identification rank 53 --- FNIR(1600000, T, L+1) = 0.0417 vs. lowest 0.0018 from sensetime\_004

natural identification rank 43 --- FNIR(1600000, T, L+1) = 0.0662 vs. lowest 0.0059 from sensetime\_004


natural identification rank 26 --- FNIR(1600000, T, L+1) = 0.2766 vs. lowest 0.1129 from visionlabs\_009

H: Investigational mode: FNIR(N, 1, 0) vs. most accurate (yitu\_4)





I: Investigational mode: FNIR(1600000, R, 0) by probe type



Template duration; search duration vs. N. The blue and pink ribbon covers 95 percent of observed measurements. The template generation time is independent of N. The log and power-law models are fit to the first two (N,T) observations

