

A: Datasheet

Algorithm: 3divi_4

Developer: 3Divi

Submission Date: 2018_06_19

Template size: 4096 bytes

Template time (2.5 percentile): 489 msec

Template time (median): 614 msec

Template time (97.5 percentile): 838 msec

Investigation:

Frontal mugshot ranking 169 (out of 279) -- FNIR(1600000, 0, 1) = 0.0175 vs. lowest 0.0009 from sensetime_005

Mugshot webcam ranking 171 (out of 241) -- FNIR(1600000, 0, 1) = 0.0621 vs. lowest 0.0062 from sensetime_005

Immigration visa-border ranking 105 (out of 168) -- FNIR(1600000, 0, 1) = 0.0354 vs. lowest 0.0013 from visionlabs_010

Immigration visa-kiosk ranking 110 (out of 165) -- FNIR(1600000, 0, 1) = 0.2788 vs. lowest 0.0568 from cloudwalk_hr_000

Identification:


Frontal mugshot ranking 180 (out of 279) -- FNIR(1600000, T, L+1) = 0.1686, FPIR=0.001000 vs. lowest 0.0018 from sensetime_004

Mugshot webcam ranking 177 (out of 236) -- FNIR(1600000, T, L+1) = 0.3426, FPIR=0.001000 vs. lowest 0.0122 from sensetime_003


Immigration visa-border ranking 107 (out of 167) -- FNIR(1600000, T, L+1) = 0.2776, FPIR=0.001000 vs. lowest 0.0047 from idemia_008

Immigration visa-kiosk ranking 83 (out of 162) -- FNIR(1600000, T, L+1) = 0.6075, FPIR=0.001000 vs. lowest 0.0996 from cloudwalk_hr_000


B: Mugshot natural images, identification mode: FNIR(N, L+1, T) vs. most accurate (sensetime_004)




C: Evolution of accuracy for 3DIVI algorithms on three datasets 2018 – present




D: 1:N error tradeoff by dataset and enrollment type. N = 1600000 individuals




E: Dependence of error rates on T by number enrolled identities, N, for Mugshot natural images




F: FPIR vs. Selectivity for mugshot images, N = 1600000 subjects enrolled with one recent mate




G: FPIR dependence on T by probe type for N = 1600000 subjects




J: DET for Mugshot natural images and various N. Links connect points of equal threshold.




K: Investigational mode: FNIR(N, 1, 0) vs. most accurate (sensetime_005)



L: Investigational mode: FNIR(1600000, R, 0) by probe type



M: Template duration; search duration vs. N. The blue and pink ribbon covers 95 percent of observed measurements. The template generation time is independent of N. The log and power-law models are fit to the first two (N,T) observations



Q: Identification FNIR(N, T, L+1) and Investigational FNIR(N, 0, R) under ageing

Dataset: 2018 Mugshot N = 3068801

