




A: 1:N error tradeoff by dataset and enrollment type. N = 1600000 individuals




B: Dependence of error rates on T by number enrolled identities, N, for Mugshot natural images




C: FPIR vs. Selectivity for mugshot images, N = 1600000 subjects enrolled with one recent mate




D: FPIR dependence on T by probe type for N = 1600000 subjects



E: DET for Mugshot natural images and various N. Links connect points of equal threshold.



F: Mugshot natural images, identification mode: FNIR(N, L+1, T) vs. most accurate (sensetime\_004)



## G: Datasheet

Algorithm: vigilantsolutions\_1

Developer: Vigilant Solutions

Submission Date: 2018\_02\_14

Template size: 2056 bytes

Template time (2.5 percentile): 726 msec

Template time (median): 735 msec

Template time (97.5 percentile): 783 msec

Frontal mugshot investigation rank 226 -- FNIR(1600000, 0, 1) = 0.2017 vs. lowest 0.0010 from sensetime\_004


natural investigation rank 261 -- FNIR(1600000, 0, 1) = 0.9395 vs. lowest 0.0492 from paravision\_005

natural investigation rank 261 -- FNIR(1600000, 0, 1) = 0.9395 vs. lowest 0.0492 from paravision\_005

Frontal mugshot identification rank 220 -- FNIR(1600000, T, L+1) = 0.6359 vs. lowest 0.0018 from sensetime\_004


natural identification rank 142 -- FNIR(1600000, T, L+1) = 0.9995 vs. lowest 0.1020 from sensetime\_004

H: Investigational mode: FNIR(N, 1, 0) vs. most accurate (yitu\_4)





I: Investigational mode: FNIR(1600000, R, 0) by probe type



Template duration; search duration vs. N. The blue and pink ribbon covers 95 percent of observed measurements. The template generation time is independent of N. The log and power-law models are fit to the first two (N,T) observations

