

A: Datasheet

Algorithm: quantasoft\_1

Developer: Quantasoft

Submission Date: 2018\_10\_30

Template size: 2048 bytes

Template time (2.5 percentile): 367 msec

Template time (median): 386 msec

Template time (97.5 percentile): 467 msec

Investigation:


Frontal mugshot ranking 254 (out of 279) -- FNIR(1600000, 0, 1) = 0.2177 vs. lowest 0.0009 from sensetime\_005

Mugshot webcam ranking 235 (out of 241) -- FNIR(1600000, 0, 1) = 0.7266 vs. lowest 0.0062 from sensetime\_005


Identification:

Frontal mugshot ranking 247 (out of 279) -- FNIR(1600000, T, L+1) = 0.6382, FPIR=0.001000 vs. lowest 0.0018 from sensetime\_004


B: Mugshot natural images, identification mode: FNIR(N, L+1, T) vs. most accurate (sensetime\_004)



C: Evolution of accuracy for QUANTASOFT algorithms on three datasets 2018 – present




D: 1:N error tradeoff by dataset and enrollment type. N = 1600000 individuals




E: Dependence of error rates on T by number enrolled identities, N, for Mugshot natural images


N    00640000    01600000    03000000    12000000




F: FPIR vs. Selectivity for mugshot images, N = 1600000 subjects enrolled with one recent mate



G: FPIR dependence on T by probe type for N = 1600000 subjects




J: DET for Mugshot natural images and various N. Links connect points of equal threshold.







K: Investigational mode: FNIR(N, 1, 0) vs. most accurate (sensetime\_005)



L: Investigational mode: FNIR(1600000, R, 0) by probe type



M: Template duration; search duration vs. N. The blue and pink ribbon covers 95 percent of observed measurements. The template generation time is independent of N. The log and power-law models are fit to the first two (N,T) observations



Q: Identification FNIR(N, T, L+1) and Investigational FNIR(N, 0, R) under ageing

Dataset: 2018 Mugshot N = 3068801

