




A: 1:N error tradeoff by dataset and enrollment type. N = 1600000 individuals




B: Dependence of error rates on T by number enrolled identities, N, for Mugshot natural images




C: FPIR vs. Selectivity for mugshot images, N = 1600000 subjects enrolled with one recent mate




D: FPIR dependence on T by probe type for N = 1600000 subjects



E: DET for Mugshot natural images and various N. Links connect points of equal threshold.



F: Mugshot natural images, identification mode: FNIR(N, L+1, T) vs. most accurate (sensetime_004)



G: Datasheet

Algorithm: rankone_006

Developer: Rank One Computing

Submission Date: 2019_06_03

Frontal mugshot investigation rank 72 --- $\text{FNIR}(1600000, 0, 1) = 0.0050$ vs. lowest 0.0010 from sensetime_004


natural investigation rank 137 --- $\text{FNIR}(1600000, 0, 1) = 0.6418$ vs. lowest 0.0492 from paravision_005

natural investigation rank 137 --- $\text{FNIR}(1600000, 0, 1) = 0.6418$ vs. lowest 0.0492 from paravision_005


Frontal mugshot identification rank 49 --- $\text{FNIR}(1600000, T, L+1) = 0.0370$ vs. lowest 0.0018 from sensetime_004

natural identification rank 42 --- $\text{FNIR}(1600000, T, L+1) = 0.9404$ vs. lowest 0.1020 from sensetime_004

H: Investigational mode: FNIR(N, 1, 0) vs. most accurate (yitu_4)



I: Investigational mode: FNIR(1600000, R, 0) by probe type



Template duration; search duration vs. N. The blue and pink ribbon covers 95 percent of observed measurements.
The template generation time is independent of N. The log and power-law models are fit to the first two (N,T) observations

Search Duration (milliseconds)

Enrolled population size, N, one image per person