

A: Datasheet

Algorithm: microsoft\_5

Developer: Microsoft

Submission Date: 2018\_10\_29

Template size: 1024 bytes

Template time (2.5 percentile): 637 msec

Template time (median): 659 msec

Template time (97.5 percentile): 900 msec

Investigation:

Frontal mugshot ranking 24 (out of 259) -- FNIR(1600000, 0, 1) = 0.0019 vs. lowest 0.0009 from sensetime\_005

Mugshot webcam ranking 18 (out of 221) -- FNIR(1600000, 0, 1) = 0.0109 vs. lowest 0.0062 from sensetime\_005

Mugshot profile ranking 11 (out of 190) -- FNIR(1600000, 0, 1) = 0.1438 vs. lowest 0.0591 from sensetime\_005

Immigration visa-border ranking 12 (out of 142) -- FNIR(1600000, 0, 1) = 0.0030 vs. lowest 0.0014 from visionlabs\_009

Immigration visa-kiosk ranking 20 (out of 139) -- FNIR(1600000, 0, 1) = 0.0987 vs. lowest 0.0694 from cib\_000

Identification:

Frontal mugshot ranking 42 (out of 259) -- FNIR(1600000, T, L+1) = 0.0255, FPIR=0.001000 vs. lowest 0.0018 from sensetime\_004


Mugshot webcam ranking 34 (out of 219) -- FNIR(1600000, T, L+1) = 0.0704, FPIR=0.001000 vs. lowest 0.0122 from sensetime\_003

Mugshot profile ranking 10 (out of 189) -- FNIR(1600000, T, L+1) = 0.5867, FPIR=0.001000 vs. lowest 0.1733 from sensetime\_005


Immigration visa-border ranking 19 (out of 139) -- FNIR(1600000, T, L+1) = 0.0268, FPIR=0.001000 vs. lowest 0.0059 from sensetime\_004

Immigration visa-kiosk ranking 12 (out of 134) -- FNIR(1600000, T, L+1) = 0.1809, FPIR=0.001000 vs. lowest 0.1048 from sensetime\_005


B: Mugshot natural images, identification mode: FNIR(N, L+1, T) vs. most accurate (sensetime\_004)




C: Evolution of accuracy for MICROSOFT algorithms on three datasets 2018 – present




D: 1:N error tradeoff by dataset and enrollment type. N = 1600000 individuals




E: Dependence of error rates on T by number enrolled identities, N, for Mugshot natural images




F: FPIR vs. Selectivity for mugshot images, N = 1600000 subjects enrolled with one recent mate



G: FPIR dependence on T by probe type for N = 1600000 subjects




H: DET for Mugshot natural images and various N. Links connect points of equal threshold.







I: Investigational mode: FNIR(N, 1, 0) vs. most accurate (sensetime\_005)



J: Investigational mode: FNIR(1600000, R, 0) by probe type




Template duration; search duration vs. N. The blue and pink ribbon covers 95 percent of observed measurements. The template generation time is independent of N. The log and power-law models are fit to the first two (N,T) observations



M: Identification FNIR(N, T, L+1) and Investigational FNIR(N, 0, R) under ageing

Dataset: 2018 Mugshot N = 3068801



# N: Decline of genuine scores with ageing

