

A: Datasheet

Algorithm: scanovate_001

Developer: Scanovate Ltd

Submission Date: 2020_09_10

Template size: 2048 bytes

Template time (2.5 percentile): 646 msec

Template time (median): 675 msec

Template time (97.5 percentile): 703 msec

Investigation:

Frontal mugshot ranking 81 (out of 259) — FNIR(1600000, 0, 1) = 0.0053 vs. lowest 0.0009 from sensetime_005

Mugshot webcam ranking 128 (out of 221) — FNIR(1600000, 0, 1) = 0.0401 vs. lowest 0.0062 from sensetime_005

Mugshot profile ranking 58 (out of 190) — FNIR(1600000, 0, 1) = 0.5849 vs. lowest 0.0591 from sensetime_005

Immigration visa–border ranking 76 (out of 142) — FNIR(1600000, 0, 1) = 0.0310 vs. lowest 0.0014 from visionlabs_009

Immigration visa–kiosk ranking 66 (out of 139) — FNIR(1600000, 0, 1) = 0.1782 vs. lowest 0.0694 from cib_000

Identification:

Frontal mugshot ranking 112 (out of 259) — FNIR(1600000, T, L+1) = 0.0813, FPIR=0.001000 vs. lowest 0.0018 from sensetime_004


Mugshot webcam ranking 130 (out of 219) — FNIR(1600000, T, L+1) = 0.2268, FPIR=0.001000 vs. lowest 0.0122 from sensetime_003

Mugshot profile ranking 31 (out of 189) — FNIR(1600000, T, L+1) = 0.9115, FPIR=0.001000 vs. lowest 0.1733 from sensetime_005


Immigration visa–border ranking 79 (out of 139) — FNIR(1600000, T, L+1) = 0.1924, FPIR=0.001000 vs. lowest 0.0059 from sensetime_004

Immigration visa–kiosk ranking 51 (out of 134) — FNIR(1600000, T, L+1) = 0.4055, FPIR=0.001000 vs. lowest 0.1048 from sensetime_005


B: Mugshot natural images, identification mode: FNIR(N, L+1, T) vs. most accurate (sensetime_004)




C: Evolution of accuracy for SCANOVATE algorithms on three datasets 2018 – present




D: 1:N error tradeoff by dataset and enrollment type. N = 1600000 individuals




E: Dependence of error rates on T by number enrolled identities, N, for Mugshot natural images




F: FPIR vs. Selectivity for mugshot images, N = 1600000 subjects enrolled with one recent mate




G: FPIR dependence on T by probe type for N = 1600000 subjects




H: DET for Mugshot natural images and various N. Links connect points of equal threshold.




I: Investigational mode: FNIR(N, 1, 0) vs. most accurate (sensetime_005)



J: Investigational mode: FNIR(1600000, R, 0) by probe type




Template duration; search duration vs. N. The blue and pink ribbon covers 95 percent of observed measurements. The template generation time is independent of N. The log and power-law models are fit to the first two (N,T) observations



M: Identification FNIR(N, T, L+1) and Investigational FNIR(N, 0, R) under ageing

Dataset: 2018 Mugshot N = 3068801



N: Decline of genuine scores with ageing

