A: Datasheet

Algorithm: vigilantsolutions_5

Developer: Vigilant Solutions

Submission Date: 2018_10_30

Template size: 1544 bytes

Template time (2.5 percentile): 757 msec

Template time (median): 762 msec

Template time (97.5 percentile): 861 msec

Investigation:

Frontal mugshot ranking 121 (out of 265) −− FNIR(1600000, 0, 1) = 0.0092 vs. lowest 0.0009 from sensetime_005

Mugshot profile ranking 115 (out of 196) −− FNIR(1600000, 0, 1) = 0.9199 vs. lowest 0.0591 from sensetime_005

Identification:

Frontal mugshot ranking 207 (out of 265) −− FNIR(1600000, T, L+1) = 0.3861, FPIR=0.001000 vs. lowest 0.0018 from sensetime_004

Mugshot profile ranking 176 (out of 195) −− FNIR(1600000, T, L+1) = 0.9999, FPIR=0.001000 vs. lowest 0.1331 from hr_000


B: Mugshot natural images, identification mode: FNIR(N, L+1, T) vs. most accurate (sensetime_004)
False negative identification rate, FNIR(N)
0.500
0.300
0.200
0.100
0.070
0.050
0.030
0.020
0.010
0.007
0.005
0.003
0.002
1e+06
3e+06
1e+07
Enrolled population size, N
Dataset:
2018 Mugshot
FNIR@FPIR = 0.001
sensetime_004
vigilantsolutions_5
enrolment_style
recent

C: Evolution of accuracy for VIGILANTSOLUTIONS algorithms on three datasets 2018 − present




D: 1:N error tradeoff by dataset and enrollment type. N = 1600000 individuals
Immigration visa−border
Immigration visa−kiosk
Mugshot natural
sensetime_004
vigilantsolutions_5
False negative identification rate, FNIR(T)
0.700
0.500
0.300
0.200
0.100
0.070
0.050
0.030
0.020
0.010
0.007
0.005
0.003
0.002
0.001
1e−04
3e−04
1e−03
3e−03
1e−02
3e−02
1e−01
3e−01
1e+00
False positive identification rate, FPIR(T)
enrolment_style
random−ONE−MATE
recent−ONE−MATE


E: Dependence of error rates on T by number enrolled identities, N, for Mugshot natural images
N
00640000
01600000
recent
FNIR
FPIR
Identification Error rate, FPIR(T) or FNIR(T)
0.700
0.500
0.300
0.200
0.100
0.070
0.050
0.030
0.020
0.010
0.007
0.005
0.003
0.002
7e−01
5e−01
3e−01
2e−01
1e−01
7e−02
5e−02
3e−02
2e−02
1e−02
7e−03
5e−03
3e−03
2e−03
1e−03
7e−04
5e−04
3e−04
2e−04
1e−04
7e−05
0.7
0.8
0.9
1.0
Threshold


F: FPIR vs. Selectivity for mugshot images, N = 1600000 subjects enrolled with one recent mate
Selectivity, SEL(T)
7e+01
5e+01
3e+01
2e+01
1e+01
7e+00
5e+00
3e+00
2e+00
1e+00
7e−01
5e−01
3e−01
2e−01
1e−01
7e−02
5e−02
3e−02
2e−02
1e−02
7e−03
5e−03
3e−03
2e−03
1e−04
3e−04
1e−03
3e−03
1e−02
3e−02
1e−01
3e−01
False Positive Idenification Rate, FPIR(T)
Enrolled images:
recent
N = 1600000
Mugshot
natural


G: FPIR dependence on T by probe type for N = 1600000 subjects
False Positive Idenification Rate, FPIR(T)
7e−01
5e−01
3e−01
2e−01
1e−01
7e−02
5e−02
3e−02
2e−02
1e−02
7e−03
5e−03
3e−03
2e−03
1e−03
7e−04
5e−04
3e−04
2e−04
1e−04
7e−05
5e−05
0.7
0.8
0.9
1.0
Threshold
enrolment_style
random
recent
Enrolled image:
random
N = 1600000
Mugshot
natural
Mugshot
profile


H: DET for Mugshot natural images and various N. Links connect points of equal threshold.
False negative identification rate, FNIR(T)
0.700
0.500
0.300
0.200
0.100
0.070
0.050
0.030
0.020
0.010
0.007
0.005
0.003
0.002
1e−04
3e−04
1e−03
3e−03
1e−02
3e−02
1e−01
3e−01
1e+00
False positive identification rate, FPIR(T)
2018 Mugshot
Enrolled image:
recent
00640000
01600000


I: Investigational mode: FNIR(N, 1, 0) vs. most accurate (sensetime_005)
Immigration visa−border
Immigration visa−kiosk
Mugshot natural
Mugshot webcam
False negative identification rate, FNIR(N)
0.100
0.070
0.050
0.030
0.020
0.010
0.007
0.005
0.003
0.002
0.001
1e+06
3e+06
1e+07
Enrolled population size, N
FNIR@Rank = 1
sensetime_005
vigilantsolutions_5
enrolment_style
random
recent


J: Investigational mode: FNIR(1600000, R, 0) by probe type
sensetime_005
vigilantsolutions_5
False negative identification rate, FNIR(N)
0.100
0.070
0.050
0.030
0.020
0.010
0.007
0.005
0.003
0.002
0.001
1
3
10
30
Rank, R
enrolment_style
random
recent
FNIR(R)
N = 1600000
Immigration visa−border
Immigration visa−kiosk
Mugshot natural
Mugshot webcam

Template duration; search duration vs. N. The blue and pink ribbon covers 95 percent of observed measurements.
The template generation time is independent of N. The log and power−law models are fit to the first two (N,T) observations




M: Identification FNIR(N, T, L+1) and Investigational FNIR(N, 0, R) under ageing
Dataset: 2018 Mugshot N = 3068801
(00,02]
(02,04]
(04,06]
(06,08]
(08,10]
(10,12]
(12,14]
(14,18]
FPIR
Rank
False negative identification rate (FNIR)
0.700
0.500
0.300
0.200
0.100
0.070
0.050
0.030
0.020
0.010
0.007
0.005
0.003
0.002
0.001
1e−04
3e−04
1e−03
3e−03
1e−02
3e−02
1e−01
3e−01
1e+00
1
3
10
30
50
False positive identification rate, FPIR or Rank, R
sensetime 005