

A: Datasheet

Algorithm: hik\_1

Developer: Hikvision Research Institute

Submission Date: 2018\_02\_12

Template size: 1808 bytes

Template time (2.5 percentile): 815 msec

Template time (median): 820 msec

Template time (97.5 percentile): 842 msec

Investigation:

Frontal mugshot ranking 144 (out of 259) -- FNIR(1600000, 0, 1) = 0.0147 vs. lowest 0.0009 from sensetime\_005


Mugshot profile ranking 136 (out of 190) -- FNIR(1600000, 0, 1) = 0.9517 vs. lowest 0.0591 from sensetime\_005

Identification:


Frontal mugshot ranking 140 (out of 259) -- FNIR(1600000, T, L+1) = 0.1173, FPIR=0.001000 vs. lowest 0.0018 from sensetime\_004

Mugshot profile ranking 73 (out of 189) -- FNIR(1600000, T, L+1) = 0.9902, FPIR=0.001000 vs. lowest 0.1733 from sensetime\_005


B: Mugshot natural images, identification mode: FNIR(N, L+1, T) vs. most accurate (sensetime\_004)




C: Evolution of accuracy for HIK algorithms on three datasets 2018 – present




D: 1:N error tradeoff by dataset and enrollment type. N = 1600000 individuals




E: Dependence of error rates on T by number enrolled identities, N, for Mugshot natural images




F: FPIR vs. Selectivity for mugshot images, N = 1600000 subjects enrolled with one recent mate



G: FPIR dependence on T by probe type for N = 1600000 subjects




H: DET for Mugshot natural images and various N. Links connect points of equal threshold.






# I: Investigational mode: FNIR(N, 1, 0) vs. most accurate (sensetime\_005)





Template duration; search duration vs. N. The blue and pink ribbon covers 95 percent of observed measurements. The template generation time is independent of N. The log and power-law models are fit to the first two (N,T) observations



M: Identification FNIR(N, T, L+1) and Investigational FNIR(N, 0, R) under ageing

Dataset: 2018 Mugshot N = 3068801

