

A: Datasheet

Algorithm: pixelall\_003

Developer: Guangzhou Pixel Solutions Co Ltd

Submission Date: 2019\_11\_05

Template size: 2560 bytes

Template time (2.5 percentile): 696 msec

Template time (median): 704 msec

Template time (97.5 percentile): 770 msec

Investigation:

Frontal mugshot ranking 30 (out of 259) -- FNIR(1600000, 0, 1) = 0.0021 vs. lowest 0.0009 from sensetime\_005

Mugshot webcam ranking 33 (out of 221) -- FNIR(1600000, 0, 1) = 0.0140 vs. lowest 0.0062 from sensetime\_005

Mugshot profile ranking 44 (out of 190) -- FNIR(1600000, 0, 1) = 0.5155 vs. lowest 0.0591 from sensetime\_005

Immigration visa-border ranking 38 (out of 142) -- FNIR(1600000, 0, 1) = 0.0062 vs. lowest 0.0014 from visionlabs\_009

Immigration visa-kiosk ranking 58 (out of 139) -- FNIR(1600000, 0, 1) = 0.1505 vs. lowest 0.0694 from cib\_000

Identification:

Frontal mugshot ranking 35 (out of 259) -- FNIR(1600000, T, L+1) = 0.0218, FPIR=0.001000 vs. lowest 0.0018 from sensetime\_004


Mugshot webcam ranking 37 (out of 219) -- FNIR(1600000, T, L+1) = 0.0724, FPIR=0.001000 vs. lowest 0.0122 from sensetime\_003

Mugshot profile ranking 144 (out of 189) -- FNIR(1600000, T, L+1) = 0.9996, FPIR=0.001000 vs. lowest 0.1733 from sensetime\_005


Immigration visa-border ranking 33 (out of 139) -- FNIR(1600000, T, L+1) = 0.0374, FPIR=0.001000 vs. lowest 0.0059 from sensetime\_004

Immigration visa-kiosk ranking 63 (out of 134) -- FNIR(1600000, T, L+1) = 0.5551, FPIR=0.001000 vs. lowest 0.1048 from sensetime\_005


B: Mugshot natural images, identification mode: FNIR(N, L+1, T) vs. most accurate (sensetime\_004)




C: Evolution of accuracy for PIXELALL algorithms on three datasets 2018 – present




D: 1:N error tradeoff by dataset and enrollment type. N = 1600000 individuals




E: Dependence of error rates on T by number enrolled identities, N, for Mugshot natural images




F: FPIR vs. Selectivity for mugshot images, N = 1600000 subjects enrolled with one recent mate



G: FPIR dependence on T by probe type for N = 1600000 subjects




H: DET for Mugshot natural images and various N. Links connect points of equal threshold.







# I: Investigational mode: FNIR(N, 1, 0) vs. most accurate (sensetime\_005)



J: Investigational mode: FNIR(1600000, R, 0) by probe type




Template duration; search duration vs. N. The blue and pink ribbon covers 95 percent of observed measurements. The template generation time is independent of N. The log and power-law models are fit to the first two (N,T) observations



M: Identification FNIR(N, T, L+1) and Investigational FNIR(N, 0, R) under ageing

Dataset: 2018 Mugshot N = 3068801



# N: Decline of genuine scores with ageing

