

A: Datasheet

Algorithm: sensetime_006

Developer: Sensetime Group

Submission Date: 2021_07_26

Template size: 1032 bytes

Template time (2.5 percentile): 928 msec

Template time (median): 930 msec

Template time (97.5 percentile): 970 msec

Investigation:

Frontal mugshot ranking 1 (out of 288) -- FNIR(1600000, 0, 1) = 0.0009

Mugshot webcam ranking 1 (out of 250) -- FNIR(1600000, 0, 1) = 0.0057

Mugshot profile ranking 1 (out of 219) -- FNIR(1600000, 0, 1) = 0.0550

Immigration visa--border ranking 1 (out of 177) -- FNIR(1600000, 0, 1) = 0.0009

Immigration visa--kiosk ranking 3 (out of 174) -- FNIR(1600000, 0, 1) = 0.0635 vs. lowest 0.0568 from cloudwalk_hr_000

Identification:

Frontal mugshot ranking 2 (out of 288) -- FNIR(1600000, T, L+1) = 0.0018, FPIR=0.001000 vs. lowest 0.0018 from sensetime_004


Mugshot webcam ranking 2 (out of 248) -- FNIR(1600000, T, L+1) = 0.0122, FPIR=0.001000 vs. lowest 0.0122 from sensetime_003

Mugshot profile ranking 136 (out of 218) -- FNIR(1600000, T, L+1) = 0.9981, FPIR=0.001000 vs. lowest 0.1331 from cloudwalk_hr_000


Immigration visa--border ranking 1 (out of 176) -- FNIR(1600000, T, L+1) = 0.0039, FPIR=0.001000

Immigration visa--kiosk ranking 1 (out of 171) -- FNIR(1600000, T, L+1) = 0.0925, FPIR=0.001000


B: Mugshot natural images, identification mode: FNIR(N, L+1, T) vs. most accurate (nec_004)




C: Evolution of accuracy for SENSETIME algorithms on three datasets 2018 – present




D: 1:N error tradeoff by dataset and enrollment type. N = 1600000 individuals




E: Dependence of error rates on T by number enrolled identities, N, for Mugshot natural images



F: FPIR vs. Selectivity for mugshot images, N = 1600000 subjects enrolled with one recent mate




G: FPIR dependence on T by probe type for N = 1600000 subjects




H: Reduced length candidate lists for human review

Dataset is border–border with time–lapse [10,15] YRS with N = 1600000. Probes are 10–15 years later than enrollment image




I: FNIR and FPIR dependence on threshold


Dataset is border-border with time-lapse [10,15] YRS with N = 1600000. Probes are 10-15 years later than enrollment image




J: DET for Mugshot natural images and various N. Links connect points of equal threshold.




K: Investigational mode: FNIR(N, 1, 0) vs. most accurate (sensetime_006)




L: Investigational mode: FNIR(1600000, R, 0) by probe type



M: Template duration; search duration vs. N. The blue and pink ribbon covers 95 percent of observed measurements. The template generation time is independent of N. The log and power-law models are fit to the first two (N,T) observations




O: FNIR(T, N = 1.6 million) by sex, age and time-lapse. The top row gives investigational rank-1 miss rates. The bottom panels give high threshold for more lights-out identification with low FPIR.



P: FPIR(N = 1.6 million) by sex and age. It is typical for false positive identification rates to be higher in women except in their teens.

Algorithm: sensetime_006, Dataset: Border-Crossing Ageing
Threshold: 0.883483 set to achieve FPIR(30–45, Male) = 0.001

Color encodes log(FPIR)



Q: Identification FNIR(N, T, L+1) and Investigational FNIR(N, 0, R) under ageing

Dataset: 2018 Mugshot N = 3068801

