

A: Datasheet

Algorithm: fujitsulab_000

Developer: [**Developer name**]

Submission Date: 2021_10_12

Template size: 1032 bytes

Template time (2.5 percentile): 914 msec

Template time (median): 945 msec

Template time (97.5 percentile): 998 msec


Investigation:

Mugshot webcam ranking 62 (out of 269) — FNIR(1600000, 0, 1) = 0.0137 vs. lowest 0.0057 from sensetime_006


Identification:

Mugshot webcam ranking 50 (out of 267) — FNIR(1600000, T, L+1) = 0.0560, FPIR=0.001000 vs. lowest 0.0122 from sensetime_003


B: Mugshot natural images, identification mode: FNIR(N, L+1, T) vs. most accurate (nec_004)




C: Evolution of accuracy for FUJITSULAB algorithms on three datasets 2018 – present




D: 1:N error tradeoff by dataset and enrollment type. N = 1600000 individuals




F: FPIR vs. Selectivity for mugshot images, N = 1600000 subjects enrolled with one recent mate




G: FPIR dependence on T by probe type for N = 1600000 subjects




K: Investigational mode: FNIR(N, 1, 0) vs. most accurate (sensetime_006)



L: Investigational mode: FNIR(1600000, R, 0) by probe type



M: Template duration; search duration vs. N. The blue and pink ribbon covers 95 percent of observed measurements. The template generation time is independent of N. The log and power-law models are fit to the first two (N,T) observations



Q: Identification FNIR(N, T, L+1) and Investigational FNIR(N, 0, R) under ageing

Dataset: 2018 Mugshot N = 3068801

