

Boundary-Guided Replay: A Mechanism Study of Success–Failure Boundary Learning

Anonymous submission

Abstract

Policies trained on nominal starts often fail under small deviations from the states encountered during training. Existing curriculum and level-replay methods prioritize difficult or high-regret levels, but they do not identify where behavior transitions from likely success to likely failure. We introduce Boundary-Guided Replay (BGR), a replay method for resettable or replayable sequential decision settings. For each replayable state, BGR estimates a recovery curve over perturbation scale, derives a critical radius, and samples training perturbations near this state-conditioned boundary. The paper is scoped as a mechanism study, not as a completed robotics or broad-benchmark result. The clearest effect is in a procedural grid-margin benchmark, where BGR improves recovery AUC over uniform replay in both the 30-seed full-baseline run and a held-out 30-seed replication (pooled 0.4342 vs. 0.3965). Synthetic and robot-suffix results are smaller and are reported as scoped support: the suffix variant improves final object recovery AUC (0.4971 vs. 0.4856), clean success, transfer recovery AUC, and learning-curve area, while still trailing uniform on median critical radius. Standard-environment and OpenVLA/LIBERO audits are negative for promotion as broad robotics evidence. They show that the interface can measure learned-policy brittleness and build matched fine-tuning datasets, but current adaptation does not establish stable gains over the official checkpoint.

1 Introduction

A policy can solve nominal starts and still be brittle: a small change in layout, object pose, or trajectory prefix may move it outside its recovery basin. Standard success metrics hide this geometry. We ask a deliberately narrower question: for each replayable state, how far can the current policy be perturbed before success becomes failure, and can replay near that boundary expand the local margin?

Existing replay and curriculum methods rank examples by difficulty, temporal-difference error, regret, novelty, or failure. These scalar signals are useful, but they do not explicitly model the local response curve around a state or decide which perturbation radius should be trained once a state is

selected. BGR instead estimates a state-conditioned recovery curve and trains near its success–failure transition. The empirical question is therefore not whether another priority score can win small paired comparisons; it is whether boundary-local radius selection adds anything beyond uniform replay, fixed radii, failure mining, and loss-priority proxies.

Our contributions are:

- a domain-agnostic replay interface based on replayable decision states, perturbation families, recovery curves, critical radii, and recovery AUC;
- an efficient BGR algorithm that actively estimates success–failure boundaries and samples both states and perturbation radii near those boundaries;
- an active-estimation validation showing that boundary-focused probes recover critical radii with small budgets;
- synthetic, procedural grid-margin, and robot-suffix simulator benchmarks showing where boundary replay and coverage-aware boundary replay expand recovery margins under paired-seed comparisons, with absolute effect sizes reported ahead of paired consistency checks;
- negative standard-environment and OpenVLA/LIBERO audits that define the practical scope of the evidence and separate recovery-margin measurement from robotics fine-tuning claims.

The claim is intentionally scoped. BGR is not a universal robustness guarantee, broad independent-benchmark result, or completed robotics fine-tuning method; the standard-environment probes are negative or exploratory, and OpenVLA/LIBERO is audit evidence. BGR is instead a replay rule for settings where states can be revisited, perturbations can be kept feasible, and the recovery curve is trainable. The controlled experiments test the mechanism under paired seeds and ablations, while the suffix and OpenVLA/LIBERO studies test interface transfer and expose where broader learned-policy claims still need stronger evidence.

2 Related Work

BGR is closest in spirit to curriculum learning and level replay for reinforcement learning. Prioritized Level Replay samples levels by learning-potential proxies such as value

This is an anonymized submission for review purposes only. Distribution, citation, or public sharing of this manuscript is strictly prohibited. Copyright and publication details will appear in the final version if accepted.

loss (Jiang, Grefenstette, and Rocktäschel 2021), while PAIRED and ACCEL generate or mutate environments using regret and curriculum-frontier objectives (Dennis et al. 2020; Parker-Holder et al. 2022). BGR is complementary: it can operate over fixed replayable states and prioritizes the local perturbation geometry of the current policy rather than a scalar difficulty or regret score. The radius-level ablation is designed around this distinction: if the contribution were only another hard-state priority, then keeping BGR state priority while drawing radii uniformly should preserve the gain. It does not in the grid-margin study. BGR also differs from broad curriculum schedules surveyed by Narvekar et al. (2020), because the unit of progress is recovery-margin expansion around each state.

Prioritized experience replay ranks transitions by temporal-difference error (Schaul et al. 2016), and active learning selects informative labels under a query budget (Settles 2009). BGR borrows the budgeted-query spirit but changes the target: it actively estimates a success-probability curve around a replay state, then trains at a state-conditioned perturbation radius. It is also distinct from adversarial-example training (Goodfellow, Shlens, and Szegedy 2015; Madry et al. 2018): BGR is not an adversarial-training objective and does not solve a worst-case inner maximization; it samples feasible perturbation scales near the observed recovery boundary to expand a policy’s local margin.

BGR also connects to robustness training and robotics generalization. Domain randomization improves transfer by broadening training distributions (Tobin et al. 2017), but fixed perturbation distributions can oversample states that are already easy or currently infeasible. BGR instead estimates where each state’s perturbation curve crosses from success to failure and trains near that radius. Our procedural experiments use resettable grid states in the style of lightweight grid benchmarks (Chevalier-Boisvert et al. 2023); the suffix study instantiates the same interface for manipulation-style states related to LIBERO (Liu et al. 2023) and vision-language-action policies such as OpenVLA (Kim et al. 2024).

3 Problem Setting

Let π_θ be a sequential decision policy and let $Y(\tau) \in \{0, 1\}$ denote terminal success for rollout τ . A replayable decision state $x \in \mathcal{X}$ is any object from which evaluation or training can restart, such as an environment seed, simulator checkpoint, task prefix, or robot suffix state.

For each x , a domain-valid perturbation family applies $\tilde{x} = T(x, \delta)$ with $\delta \sim \mathcal{P}_x(\sigma)$, where $\sigma \geq 0$ is a perturbation magnitude. The perturbation family is part of the benchmark definition: grid perturbations preserve free cells and shortest-path reachability, suffix perturbations preserve teacher feasibility, and OpenVLA observation perturbations preserve the task instruction and simulator state while modifying the visual input stream. The recovery curve is

$$R_\pi(x, \sigma) = \Pr_{\delta, \tau}[Y(\tau) = 1 \mid \tau \sim \pi(\cdot \mid T(x, \delta))]. \quad (1)$$

Study	Replay state	Perturbation	Witness/eval
Synthetic	latent recovery state	scalar radius	dense curve
Grid-margin	mid-path grid state	valid radius shifts	reachability
Robot suffix	demo suffix phase	object/EEF offsets	teacher feasibility
OpenVLA audit	LIBERO state	object/visual changes	simulator success

Table 1: Instantiations of the BGR interface. The first three rows are training experiments; the OpenVLA row is an audit of recovery curves and data plumbing, not a fine-tuning claim.

For threshold α , the critical radius is

$$r_{\pi, \alpha}(x) = \sup\{\sigma : R_\pi(x, \sigma) \geq \alpha R_\pi(x, 0)\}. \quad (2)$$

We evaluate robustness with recovery AUC,

$$\text{RAUC}_\pi(x) = \frac{1}{\sigma_{\max}} \int_0^{\sigma_{\max}} R_\pi(x, \sigma) d\sigma. \quad (3)$$

BGR depends on a feasibility witness $F(x, \sigma)$ that estimates whether perturbed states remain meaningful and solvable by a reference process. This is a real assumption, not free supervision: without such a witness, boundary replay can waste updates on invalid perturbations. In our experiments the witness is either an exact reachability check, a teacher/demo suffix model, a simulator validity check, or observed clean OpenVLA success. The witness is not an oracle for the learned policy; it filters invalid or impossible perturbations so replay focuses on recoverable boundaries rather than broken tasks, and the suffix stress sweep varies teacher quality to test one witness-fidelity failure mode.

4 Boundary-Guided Replay

BGR maintains a buffer of replayable states. For each state, it probes perturbation radii, fits a monotone recovery curve, estimates a critical radius, and assigns replay priority to states whose boundaries are feasible, sharp, uncertain, and near a trainable target band. The method therefore separates three decisions: whether a state is valid enough to replay, which replay state is currently informative, and which perturbation radius lies near that state’s success–failure transition.

Boundary-Guided Replay

Initialize replay buffer $\mathcal{B}$ with replayable states.

For each $x \in \mathcal{B}$, probe $\sigma \in \{0, \sigma_{\min}, \sigma_{\text{mid}}, \sigma_{\max}\}$, fit monotone $\hat{R}(x, \sigma)$, and estimate $\hat{r}_\alpha(x)$.

For each training iteration, sample $x \sim q_{\mathcal{B}}(x)$ proportional to BGR priority, sample σ from a mixture centered at $\hat{r}_\alpha(x)$, apply $\delta \sim \mathcal{P}_x(\sigma)$, collect rollout or teacher recovery data, update π_θ , and periodically refresh stale curve estimates.

Method box: BGR training loop without domain-specific learner details.

The priority for a record is a product of gates and soft utilities:

$$P(x) = G(x)U_{\text{boundary}}(x)U_{\text{sharp}}(x)^\lambda U_{\text{unc}}(x)^\beta U_{\text{stale}}(x)^\eta. \quad (4)$$

Here $G(x)$ gates out states with low clean success or low witness feasibility, U_{boundary} prefers critical radii in a trainable band, U_{sharp} prefers informative transitions, U_{unc} refreshes uncertain curve estimates, and U_{stale} revisits old




Figure 1: Geometric intuition for BGR and empirical grid-margin trace. Left: a recovery curve maps perturbation radius to success probability, and the critical radius is the success–failure crossing relative to clean success. Right: a deterministic seed-0 grid-margin replay trace overlays final BGR/uniform recovery curves with the BGR training-radius histogram, showing how boundary-centered replay concentrates updates near the trainable transition while retaining coverage.

records as the policy changes. We mix this distribution with uniform replay to prevent starvation. For the radius-level decision, BGR samples from a mixture centered at $\hat{r}_\alpha(x)$ with clean, easier, harder, and broad-radius coverage components; ablations test which part is responsible for the gains.

Two separations are important. First, BGR does not equate failure with usefulness: perturbations far beyond the current recovery radius can be valid but uninformative for margin expansion, while clean or near-clean states may already be saturated. Second, BGR separates replay-state priority from perturbation-radius choice. A state can be worth revisiting because its boundary is uncertain or sharp, but the training sample still needs to land near the recoverable transition rather than at an arbitrary radius. This distinction is what the radius-level ablation tests.

The following local calculation is a design rationale for the radius sampler, not a convergence result, global robustness theorem, or margin-expansion guarantee.

Local boundary intuition. Fix a replay state x and let $r = r_{\pi, \alpha}(x)$. Suppose training at radius σ gives an expected first-order RAUC gain $k_x(|\sigma - r|)$ for a nonincreasing kernel k_x . If a boundary sampler $p_b(\sigma | x)$ induces a distance-to-boundary random variable $D_b = |\sigma - r|$ satisfying $\Pr[D_b > t] \leq \Pr[D_0 > t]$ for every t relative to a baseline sampler’s distance D_0 , then

$$\mathbb{E}_{p_b}[k_x(|\sigma - r|)] \geq \mathbb{E}_{p_0}[k_x(|\sigma - r|)]. \quad (5)$$

The assumption is first-order stochastic dominance over distance to the boundary. By the quantile coupling for stochastic orders (Shaked and Shanthikumar 2007), there exists a coupling with $D'_b \leq D'_0$ almost surely and with the same marginals as D_b, D_0 ; monotonicity of k_x then gives $\mathbb{E}[k_x(D'_b)] \geq \mathbb{E}[k_x(D'_0)]$, which is the stated inequality. Thus, under this local model, placing more probability near the current critical radius improves the expected one-step margin signal over uniform or fixed-radius replay. BGR uses boundary-centered sampling as a default but retains clean, easier, harder, broad-radius, and uniform components because real learners can violate the local model through satu-

Evidence tier	Supports	Does not support
Synthetic	sampler/estimator sanity	independent benchmark win
Grid-margin	boundary-radius mechanism	broad environment dominance
Robot suffix	manipulation-style interface	final robotics fine-tuning claim
Gym/OpenVLA	scope and audit checks	promoted positive result

Table 2: Evidence contract used throughout the experiments. The central claim is mechanism-level margin expansion when recovery curves are directly trainable; independent-benchmark and learned-policy wins remain open requirements rather than hidden claims.

ration, noisy labels, or unstable optimization.

5 Experiments

All experiments are driven by artifact YAML configs and scripts. The anonymous artifact records per-seed CSVs, aggregation code, paired exact sign tests, Slurm launch commands, run ledger files, compute/GPU environment snapshots, and an MIT license; the paper tables are generated from these artifacts rather than hand-edited results.

Table 2 summarizes the claim boundary before the results. The main claim is supported by controlled synthetic and procedural grid-margin experiments where the recovery-margin object is directly trainable and baselines share paired seeds; the grid result is replicated on held-out seeds and pooled over 60 paired comparisons. The robot-suffix simulator is a manipulation-style extension: a coverage-aware BGR variant improves final object RAUC, clean success, transfer RAUC, and AULC over uniform suffix replay across original and held-out sweeps and in four stress regimes, while still trailing uniform on median critical radius. Gym-style standard-environment probes and OpenVLA/LIBERO results are scope checks and learned-policy audits, not promoted positive claims.

5.1 Protocol and Metrics

We report clean success, recovery AUC (RAUC), median r_{80} , and area under the RAUC learning curve (AULC). RAUC and r_{80} are evaluated on dense held-out radius grids rather than on the probes used by BGR during training. RAUC and AULC are author-defined summaries over selected perturbation families and radius ranges, so we do not treat them as stand-alone proof of robustness; clean success and median r_{80} are reported as complementary checks, and disagreements are discussed directly. Synthetic training, estimator validation, and packaged grid full-baseline, ablation, sensitivity, and suffix coverage confirmations use 30 paired seeds; grid learning-curve diagnostics use 15. We treat exact paired sign tests as consistency checks over shared seeds, not as substitutes for effect size: a 30/0 sign pattern can certify direction while the absolute gain remains small. The synthetic and suffix gains are therefore modest positive effects, while the grid-margin mechanism benchmark shows the largest practically visible gap. Five-seed exploratory variants and small pre-promotion standard-environment probes are reported only as scope diagnostics.

Before promoting a new result as positive evidence, we require it to use a fixed protocol, beat uniform replay on

final RAUC with a visible effect size, beat fixed-radius, failure-only, and loss-priority baselines, avoid contradictory median- r_{80} behavior or report it as a limitation, and either replicate on held-out seeds or pass a preregistered stress sweep. This rule is why the Gym-style probes below and the OpenVLA adaptation audits are not used to expand the claim.

Baselines are matched to the decisions BGR changes. Uniform replay samples replay states and perturbation radii without recovery-boundary information. Fixed-radius replay uses the same learner and feasibility filters at one configured perturbation scale. Failure-only replay prioritizes states with observed failures without estimating a crossing radius. PLR-loss and loss-priority baselines replace BGR’s recovery-curve priority with learner-loss proxies. Clean-only suffix training regularizes on unperturbed suffixes. Paired comparisons share seeds, rollout budgets, evaluation grids, and validity filters.

5.2 Active Boundary Estimation

BGR is useful only if recovery boundaries can be estimated without evaluating dense curves for every replay state. We therefore validate the training-time estimator separately from the replay experiments. For each synthetic state, we compute a dense 201-point reference curve for evaluation only, then compare 17-probe estimators: uniform random radii and active BGR probing initialized with a coarse sweep and then focused near the current critical-radius estimate.

Table 5 shows over 30 paired seeds that active BGR finds the boundary within ± 0.08 radius units more often than uniform probing (0.670 vs. 0.595) and lowers mean r_{80} error (0.081 vs. 0.105). Paired exact sign tests support both effects ($p < 10^{-3}$). This result does not claim that active probing dominates every fixed grid in this simple one-dimensional setting; rather, it verifies that BGR’s boundary estimates are usable at a small fixed rollout budget before final dense-curve evaluation.

5.3 Synthetic Recovery-Margin Benchmark

The synthetic benchmark creates replayable states with latent feasible radii and policy recovery margins. Success probability follows a sigmoid recovery curve, and training updates near the current margin expand that margin most efficiently. This benchmark is deliberately constructed to expose the mechanism BGR targets; it is a sanity check for the estimator and sampler before higher-cost sequential or robotics runs, not independent benchmark evidence.

In the 30-seed run, BGR gives a modest final recovery-AUC gain over uniform replay (0.3716 vs. 0.3633; mean difference 0.0084), a larger learning-curve gain (AULC 0.3149 vs. 0.2984), and similar clean success (0.8899 vs. 0.8838). The paired signs are consistent (Table 4), but the practical claim is limited: explicit boundary-radius sampling helps when the benchmark contains learnable success-failure transitions. Fixed-radius, failure-only, and PLR-loss proxy baselines underperform substantially in this controlled setting.




Figure 2: Grid-margin RAUC learning curve from the stored 15-seed run. Shaded bands show standard error. The right panel plots the paired mean gap, making the effect size visible without relying on significance notation.

5.4 Procedural Grid-Margin Study

We instantiate replayable states in procedural grid environments with resettable seeds and mid-path states. Generated obstacle maps define feasible perturbation neighborhoods through shortest-path reachability, while each replay state has a policy-specific recovery margin. This benchmark isolates whether BGR can expand state-conditioned recovery curves in a non-robotic sequential decision setting.

In a completed 30-seed paired grid-margin full-baseline run, BGR gives the largest absolute gap in the paper: final RAUC 0.4344 vs. 0.3963, RAUC learning-curve area 0.3526 vs. 0.3132, median r_{80} 0.3447 vs. 0.3321, and clean success 0.9455 vs. 0.8939. A held-out seeds 30–59 BGR-vs-uniform replication gives 0.4340 vs. 0.3967 RAUC, also with 30/0 wins. Pooling original and held-out grid sweeps gives 0.4342 vs. 0.3965 RAUC with 60/0 paired wins. The same sweep shows that failure-only replay (RAUC 0.2909), PLR-loss proxy replay (0.2109), and fixed-radius perturbation training (0.2097) substantially underperform BGR (0.4344).

Figure 2 shows the stored 15-seed learning curves rather than only the endpoint table: BGR separates from uniform early and remains ahead through the final checkpoint over steps 30–300. The endpoint gap is about 0.038 RAUC, which is the paper’s clearest practical effect but still a scoped mechanism result rather than broad benchmark dominance. The 30-seed sensitivity tables give the same pattern: target margins 0.26–0.54 yield RAUC 0.416–0.443 vs. uniform 0.396; obstacle regimes yield BGR RAUC 0.434–0.435 vs. uniform 0.396; and geometry stresses give stress RAUC 0.362–0.457 vs. uniform 0.323–0.430. The learning-rate table preserves the high-rate final-RAUC caveat. The reported 0.38 margin is not the best tuned value.

A learning-rate sweep is a scope diagnostic: BGR wins final RAUC at 0.015 and 0.030 (0.382 vs. 0.320; 0.434 vs. 0.396) and AULC at all three rates, but high learning rate flips final RAUC to uniform (0.485 vs. 0.491). Thus neither failure mining nor static perturbation scales recover the same margin-expansion behavior, while aggressive optimization can saturate uniform final RAUC. A separate tabular grid-policy setup either saturates under broad replay or undertrains BGR relative to fixed-radius oracle imitation; we therefore keep the main procedural claim on the margin-expansion benchmark.

Benchmark	Method	Clean	RAUC	Median r_{80}	AULC
Synthetic	BGR	0.890±0.001	0.372±0.001	0.286±0.002	0.315±0.001
Synthetic	Uniform	0.884±0.001	0.363±0.001	0.282±0.002	0.298±0.001
Synthetic	Fixed	0.821±0.001	0.230±0.001	0.131±0.001	0.229±0.001
Synthetic	Failure	0.817±0.001	0.233±0.001	0.135±0.001	0.231±0.001
Synthetic	Loss-priority	0.819±0.001	0.229±0.001	0.134±0.001	0.229±0.001
GridMargin	BGR	0.945±0.000	0.434±0.000	0.345±0.001	0.353±0.000
GridMargin	Uniform	0.894±0.000	0.396±0.000	0.332±0.001	0.313±0.000
RobotSuffix	BGR-Coverage	0.864±0.001	0.497±0.001	0.498±0.001	0.382±0.001
RobotSuffix	Uniform	0.836±0.001	0.485±0.001	0.505±0.001	0.371±0.001

Table 3: Results generated from anonymous artifact CSVs. Synthetic, grid-margin full-baseline, and robot-suffix coverage comparisons use 30 paired seeds, with held-out 30-seed BGR-vs-uniform replications reported in text for grid and suffix. BGR is strongest in the synthetic and procedural grid-margin settings. In the lightweight robot-suffix simulator, the coverage-aware BGR-Suffix variant improves clean success, final object RAUC, transfer RAUC, and AULC over uniform suffix replay, but uniform retains a higher median critical radius.

Comparison	Metric	n	Mean diff.	95% CI	W/L/T	p
Synthetic vs uniform	final RAUC	30	0.0083	[0.0059, 0.0107]	29/1/0	< 0.0001
Grid vs uniform	final RAUC	30	0.0381	[0.0372, 0.0390]	30/0/0	< 0.0001
Suffix RAUC vs clean-only	final RAUC	30	0.2338	[0.2327, 0.2350]	30/0/0	< 0.0001
Suffix RAUC vs fixed	final RAUC	30	0.3386	[0.3373, 0.3399]	30/0/0	< 0.0001
Suffix RAUC vs failure-only	final RAUC	30	0.0741	[0.0731, 0.0750]	30/0/0	< 0.0001
Suffix RAUC vs loss-priority	final RAUC	30	0.3275	[0.3262, 0.3288]	30/0/0	< 0.0001
Suffix RAUC vs uniform	final RAUC	30	0.0116	[0.0109, 0.0122]	30/0/0	< 0.0001
Suffix transfer vs uniform	transfer RAUC	30	0.0061	[0.0054, 0.0068]	30/0/0	< 0.0001
Suffix AULC vs uniform	RAUC AULC	30	0.0115	[0.0108, 0.0122]	30/0/0	< 0.0001
Estimator 30-seed	boundary hit	30	0.0751	[0.0646, 0.0857]	30/0/0	< 0.0001

Table 4: Selected paired effect sizes for the central claims, including the completed 30-seed synthetic, estimator, grid, and suffix full-baseline confirmations. Mean differences and 95% confidence intervals are the primary quantities; W/L/T and exact sign-test p values report consistency of direction over paired seeds. Synthetic, estimator, grid full-baseline, and suffix coverage-full comparisons use 30 paired seeds.

Estimator	r_{80} MAE	RAUC MAE	Hit rate
Active BGR	0.081±0.001	0.065±0.000	0.670±0.004
Uniform	0.105±0.001	0.066±0.000	0.595±0.004

Table 5: Probe-efficiency validation on synthetic recovery curves. Both methods use 17 Bernoulli probes per state and are evaluated against dense 201-point curves. Active BGR improves boundary-hit rate over uniform probing at the same rollout budget, while keeping critical-radius and RAUC error comparable.

Method	Clean	RAUC	Median r_{80}	AULC
BGR	0.945±0.000	0.434±0.000	0.345±0.001	0.353±0.000
Uniform	0.894±0.000	0.396±0.000	0.332±0.001	0.313±0.000
Failure-only	0.845±0.000	0.291±0.000	0.231±0.001	0.254±0.000
Loss-priority	0.797±0.001	0.211±0.000	0.137±0.001	0.213±0.000
Fixed radius	0.794±0.001	0.210±0.000	0.136±0.001	0.213±0.000

Table 6: Thirty-seed procedural grid-margin full-baseline comparison. Boundary-centered replay is the only method that both preserves clean success and expands recovery margins.

Method	Clean	RAUC	Median r_{80}	AULC
BGR	0.945±0.000	0.434±0.000	0.345±0.001	0.353±0.000
No uncertainty	0.946±0.000	0.435±0.000	0.344±0.001	0.353±0.000
No sharpness	0.946±0.000	0.435±0.000	0.344±0.001	0.353±0.000
Uniform radius	0.891±0.000	0.382±0.000	0.322±0.001	0.305±0.000
Uniform replay	0.894±0.000	0.396±0.000	0.332±0.001	0.313±0.000

Table 7: Grid-margin ablations over 30 seeds. Boundary-centered radius sampling is the important ingredient in this benchmark: replacing it with uniform radii drops RAUC below uniform replay, while removing uncertainty or sharpness weights has little effect.

Table 7 isolates the replay decisions inside BGR. The uncertainty and sharpness factors are not decisive in this benchmark, but the radius-level boundary rule is: keeping BGR state priority while sampling perturbation radii uniformly reduces RAUC from 0.434 to 0.382 and AULC from 0.353 to 0.305, even below uniform replay’s 0.396 RAUC. A held-out seeds 30–59 replication gives 0.434 vs. 0.382 RAUC and 0.352 vs. 0.305 AULC for BGR over the uniform-radius ablation, again with 30/0 paired wins; uniform-radius remains below uniform replay (0.382 vs. 0.397 RAUC). This is the strongest novelty evidence in the paper: the gain is not ex-

plained by hard-state prioritization alone, because the state-priority-only variant loses the effect.

5.5 Robot Suffix Study

BGR-Suffix treats a robot demonstration suffix as a replayable state. The lightweight suffix simulator models language-conditioned manipulation families, suffix phase, object-pose and end-effector perturbations, teacher feasibility, and clean-demo regularization. Training uses object-pose offsets; end-effector offsets are a perturbation-family transfer test.

The first 15-seed run showed that boundary-heavy BGR-Suffix undercovered high-radius recovery, so the promoted suffix variant includes broad-radius and uniform-state coverage. In the 30-seed run, BGR-Coverage raises final object RAUC over uniform by a small but consistent amount (0.4969 vs. 0.4854), and more clearly separates from failure-only (0.4229), clean-only (0.2631), loss-priority (0.1694), and fixed-radius replay (0.1583). The same run gives clean success 0.8644 vs. 0.8364, transfer RAUC 0.3143 vs. 0.3083, and AULC 0.3825 vs. 0.3709 over uniform. A held-out seeds 30–59 replication gives 0.4972 vs. 0.4859 RAUC, also with 30/0 wins. Pooling original and held-out suffix sweeps gives object RAUC 0.4971 vs. 0.4856, clean 0.8642 vs. 0.8367, transfer RAUC 0.3150 vs. 0.3089, and AULC 0.3829 vs. 0.3717. A 30-seed strategy ablation gives 0.4969 vs. 0.4587 and 0.4850 final object RAUC for coverage-aware, boundary-heavy, and hard-radius BGR variants; the hard-radius variant leads transfer RAUC and AULC (0.3252, 0.3928), but coverage-aware replay is the only suffix strategy that improves final object RAUC over uniform with 30/0 wins.

A four-condition 30-seed suffix stress sweep varies teacher quality, clutter, feasible radii, and boundary sharpness. BGR-Coverage keeps 30/0 paired wins over uniform on clean success, final object RAUC, end-effector transfer RAUC, and AULC in every stress case. Across these cases, BGR-Coverage gives object RAUC 0.3806–0.4971 vs. uniform 0.3755–0.4853 and transfer RAUC 0.2267–0.3142 vs. 0.2205–0.3081. Clean-only has a negligible clean-success edge (0.8646 vs. 0.8644), and uniform still has a higher median r_{80} (0.5047 vs. 0.4982) in the original sweep; pooled, uniform remains higher on median r_{80} (0.5048 vs. 0.4985), and it also retains the median- r_{80} edge in the stress sweep. We therefore treat suffix results as positive manipulation-style evidence rather than final robotics evidence.

We also audited the real-simulator path as premise validation. A GPU/EGL LIBERO-Goal probe completed 75/75 valid radius rows over five tasks, three reset states, five object-perturbation radii, and four trials per radius. Fixed-policy OpenVLA audits show clean replay success of 1.0, recovery curves that drop under occlusion, blur, and shift, and BGR-boundary selection landing in the observed counterfactual-failure band $[0.25, 0.75]$ slightly more often than random-balanced selection (0.625 vs. 0.575).

The OpenVLA-OFT bridge exports 11,776 teacher-action rows; action-label/TFDS plumbing validates 2,048-transition matched BGR/random exports with 7D actions and 8D state, stock loader ingestion, and matched 10-step

Audit	BGR	Official	Random
100-step clean identity	99/100	99/100	99/100
100-step non-identity perturbations	367/400	367/400	368/400
300-step image-aug identity	98/100	99/100	100/100
300-step image-aug non-identity	368/400	367/400	368/400
1000-step low-LR identity	98/100	99/100	99/100
1000-step low-LR non-identity	366/400	367/400	370/400

Table 8: OpenVLA-OFT LIBERO-Goal adaptation audits over 10 tasks and 10 trials per task. Non-identity totals pool blur, brightness, occlusion, and shift. The result is negative for robotics promotion: BGR ties or trails the relevant comparators and does not produce a stable learned-policy improvement.

LoRA checkpoint smokes. These audits validate the interface but do not support a robotics success claim. Table 8 summarizes the full 10-task adaptation audits: BGR never clears the promotion bar of beating both matched random and the official checkpoint by at least 10/400 non-identity perturbation episodes while preserving clean identity success.

In words, the strongest current scale remains negative. A 10-task full-goal identity audit gives 99/100 clean successes for BGR, matched random, and the official checkpoint; the visual perturbation audit gives BGR 367/400 perturbed successes, tying official and trailing matched random by one episode (368/400). A 300-step image-augmentation continuation gives BGR and matched random 368/400 perturbed successes each, only one episode above official (367/400), while BGR trails both on identity. A 1,000-step low-learning-rate continuation is also negative: BGR gives 366/400 non-identity perturbation successes, trailing official at 367/400 and matched random at 370/400. Across these runs there is no stable official improvement.

The smaller clean-mix diagnostics explain this boundary. The official checkpoint scores 14/15 under the same eval. In p1024, BGR and matched random both score 14/15 clean episodes; perturbations give 0.8333 vs. 0.8000 for random and 0.8167 for official. The offset-3 follow-up gives 0.8643 vs. 0.8571, but official reaches 0.8929. Pooling gives BGR 0.8550 vs. 0.8400 for random, trailing the unadapted official checkpoint at 0.8700. At p2048, BGR and random tie clean (14/15 each); original perturbations give 0.8167 vs. 0.8000 random, tying official at 0.8167. Offset-3 gives 0.8714 vs. 0.8714 random; official reaches 0.8929. Pooling p2048 gives BGR 0.8550 vs. 0.8500 random, trailing official at 0.8700.

6 Limitations

BGR requires reset or replay access, a meaningful perturbation family, a feasibility witness, and extra rollouts for boundary estimation. It targets an observed success–failure boundary, not a formal robustness certificate. The strongest evidence is controlled procedural margin expansion; the synthetic and grid-margin benchmarks are constructed to expose recovery curves, so they establish mechanism rather than broad benchmark dominance. The paper therefore does not claim a clear win on an independent pre-existing robust-

ness benchmark. A canonical Gym FrozenLake8x8-v1 diagnostic reinforces that limitation: BGR gives final RAUC 0.5453 vs. 0.5312 for uniform and clean success 0.5581 vs. 0.5461, but paired signs are 14/16 and 13/17, median r_{80} and best RAUC favor uniform, and failure-only replay is stronger on final RAUC, median r_{80} , AULC, and best RAUC. Additional 4-seed pre-promotion probes also stay negative: Taxi either saturates simple baselines or is best explained by hard-state replay rather than boundary-radius sampling; MountainCar has BGR below fixed-radius and failure-only replay; and CartPole clean success saturates while failure-only and TD-loss replay slightly exceed BGR. These are not promoted because they fail the fixed-protocol effect-size and baseline criteria above.

The suffix simulator is positive on final RAUC, clean success, transfer RAUC, and AULC, including stress regimes, but the absolute gains over uniform are small and uniform retains the median-critical-radius edge. RAUC and AULC are useful for measuring curve expansion, but they are author-defined integrals over chosen radius grids; we therefore report median r_{80} and clean success as separate checks instead of treating RAUC alone as decisive. OpenVLA is a learned-policy audit rather than a robotics training claim: it validates recovery-curve measurement and matched action/TFDS construction, while showing that a full robotics claim still requires stable optimization, clean-data scale, and multi-task LIBERO gains over both matched random selection and the official checkpoint.

7 Conclusion

BGR converts recovery-margin measurement into a replay curriculum. The evidence supports a specific mechanism claim: when replay states can be reset, perturbations can be kept feasible, and recovery curves are directly trainable, sampling near the estimated success–failure boundary improves margin expansion over uniform, fixed-radius, failure-only, and loss-proxy replay. Synthetic and grid-margin studies establish this mechanism under paired seeds and held-out replication, and the suffix simulator shows that radius coverage can carry the interface to manipulation-style replay states. The current learned-policy evidence remains an audit, not the final robotics result.

References

Chevalier-Boisvert, M.; Dai, B.; Towers, M.; de Lazcano, R. P.-V.; Willems, L.; Lahlou, S.; Pal, S.; Castro, P. S.; and Terry, J. 2023. Minigrid & Miniworld: Modular & Customizable Reinforcement Learning Environments for Goal-Oriented Tasks. In *Advances in Neural Information Processing Systems Datasets and Benchmarks Track*.

Dennis, M.; Jaques, N.; Vinitsky, E.; Bayen, A.; Russell, S.; Critch, A.; and Levine, S. 2020. Emergent Complexity and Zero-shot Transfer via Unsupervised Environment Design. In *Advances in Neural Information Processing Systems*.

Goodfellow, I. J.; Shlens, J.; and Szegedy, C. 2015. Explaining and Harnessing Adversarial Examples. In *International Conference on Learning Representations*.

Jiang, M.; Grefenstette, E.; and Rocktäschel, T. 2021. Prioritized Level Replay. In *Proceedings of the 38th International Conference on Machine Learning*.

Kim, M. J.; Pertsch, K.; Karamcheti, S.; Xiao, T.; Balakrishna, A.; Nair, S.; Rafailov, R.; Foster, E.; Lam, G.; Sanke, P.; et al. 2024. OpenVLA: An Open-Source Vision-Language-Action Model. *arXiv preprint arXiv:2406.09246*.

Liu, B.; Zhu, Y.; Gao, C.; Feng, Y.; Liu, Q.; Zhu, Y.; and Stone, P. 2023. LIBERO: Benchmarking Knowledge Transfer for Lifelong Robot Learning. In *Advances in Neural Information Processing Systems*.

Madry, A.; Makelov, A.; Schmidt, L.; Tsipras, D.; and Vladu, A. 2018. Towards Deep Learning Models Resistant to Adversarial Attacks. In *International Conference on Learning Representations*.

Narvekar, S.; Peng, B.; Leonetti, M.; Sinapov, J.; Taylor, M. E.; and Stone, P. 2020. Curriculum Learning for Reinforcement Learning Domains: A Framework and Survey. *Journal of Machine Learning Research*.

Parker-Holder, J.; Jiang, M.; Dennis, M.; Samvelyan, M.; Foerster, J.; Grefenstette, E.; and Rocktäschel, T. 2022. Evolving Curricula with Regret-Based Environment Design. In *Proceedings of the 39th International Conference on Machine Learning*.

Schaul, T.; Quan, J.; Antonoglou, I.; and Silver, D. 2016. Prioritized Experience Replay. In *International Conference on Learning Representations*.

Settles, B. 2009. Active Learning Literature Survey. Technical Report 1648, University of Wisconsin–Madison.

Shaked, M.; and Shanthikumar, J. G. 2007. *Stochastic Orders*. Springer.

Tobin, J.; Fong, R.; Ray, A.; Schneider, J.; Zaremba, W.; and Abbeel, P. 2017. Domain Randomization for Transferring Deep Neural Networks from Simulation to the Real World. In *IEEE/RSJ International Conference on Intelligent Robots and Systems*.

Reproducibility Checklist

This checklist is filled for the current BGR submission package. The main paper is anonymous; commands, configs, per-seed CSVs, and run ledgers are in the anonymous artifact's `README.md` and `results/README.md`.

1. General Paper Structure

- 1.1. Includes a conceptual outline and/or pseudocode description of AI methods introduced (yes/partial/no/NA)
yes. The method section defines replayable states and recovery curves. It also states critical radii, BGR priority, and a training-loop method box.
- 1.2. Clearly delineates statements that are opinions, hypothesis, and speculation from objective facts and results (yes/no)
yes. The paper separates controlled margin-expansion claims, robot-suffix simulator results, OpenVLA fixed-policy audits, OpenVLA-OFT adaptation diagnostics, and tabular grid-policy setup failures.
- 1.3. Provides well-marked pedagogical references for less-familiar readers to gain background necessary to replicate the paper (yes/no)
yes. The related-work section cites curriculum learning, PLR, PAIRED/ACCEL, domain randomization, MiniGrid, LIBERO, and OpenVLA.

2. Theoretical Contributions

- 2.1. Does this paper make theoretical contributions? (yes/no)
yes. The paper introduces a recovery-margin formalism and states a local margin-update proposition for boundary-centered radius sampling.
If yes, please address the following points:
 - 2.2. All assumptions and restrictions are stated clearly and formally (yes/partial/no)
yes. The local boundary-intuition calculation states the local update-kernel and stochastic-dominance assumptions; the limitations section states replay-access and perturbation-family restrictions.
 - 2.3. All novel claims are stated formally (e.g., in theorem statements) (yes/partial/no)
yes. The local theoretical intuition is stated as a design rationale. Empirical claims are stated with measured metrics and paired-seed tests.
 - 2.4. Proofs of all novel claims are included (yes/partial/no)
yes. The local boundary-intuition calculation includes a proof sketch based on monotone coupling and monotonicity of the update kernel.
 - 2.5. Proof sketches or intuitions are given for complex and/or novel results (yes/partial/no)
yes. The method section gives the local margin-update intuition and the proposition proof sketch.
 - 2.6. Appropriate citations to theoretical tools used are given (yes/partial/no)
yes. The proof cites a standard stochastic-orders reference for the quantile coupling used in the local boundary-intuition calculation.
 - 2.7. All theoretical claims are demonstrated empirically to hold (yes/partial/no/NA)
partial. The proposition is a local model; the grid ablation empirically tests its main implication that boundary-centered radius sampling matters.
 - 2.8. All experimental code used to eliminate or disprove claims is included (yes/no/NA)
yes. Ablation scripts, configs, per-seed CSVs, and claim-checking scripts are included.

3. Dataset Usage

3.1. Does this paper rely on one or more datasets? (yes/no)

partial. Main BGR training results use procedural synthetic/grid/suffix generators. The LIBERO/OpenVLA recovery audit uses existing benchmark task definitions, init states, and fixed-policy rollout artifacts to validate learned-policy recovery-curve measurement.

If yes, please address the following points:

3.2. A motivation is given for why the experiments are conducted on the selected datasets (yes/partial/no/NA)

yes. The paper motivates synthetic recovery curves, procedural grid-margin replay states, robot suffix diagnostics, and LIBERO/OpenVLA as a realistic manipulation-policy target.

3.3. All novel datasets introduced in this paper are included in a data appendix (yes/partial/no/NA)

yes. The experiments are generated by artifact-provided scripts/configs; per-seed result CSVs are included under results/.

3.4. All novel datasets introduced in this paper will be made publicly available upon publication of the paper with a license that allows free usage for research purposes (yes/partial/no/NA)

yes. The generated procedural data and code are included in the anonymous artifact under an MIT license.

3.5. All datasets drawn from the existing literature (potentially including authors' own previously published work) are accompanied by appropriate citations (yes/no/NA)

yes. LIBERO and OpenVLA are cited; MiniGrid is cited for grid-style context.

3.6. All datasets drawn from the existing literature (potentially including authors' own previously published work) are publicly available (yes/partial/no/NA)

yes for LIBERO task definitions, benchmark assets, and OpenVLA model code/weights. The anonymous artifact contains compact derived recovery summaries; raw fixed-policy rollout logs are retained for audit but are not required for the claimed quantitative results.

3.7. All datasets that are not publicly available are described in detail, with explanation why publicly available alternatives are not scientifically satisfying (yes/partial/no/NA)

NA. No non-public dataset is used for claimed quantitative results.

4. Computational Experiments

4.1. Does this paper include computational experiments? (yes/no)

yes.

If yes, please address the following points:

4.2. This paper states the number and range of values tried per (hyper-) parameter during development of the paper, along with the criterion used for selecting the final parameter setting (yes/partial/no/NA)

partial. Final configs and ablation variants are included in the anonymous artifact; the full search history is not exhaustively enumerated in the main paper.

4.3. Any code required for pre-processing data is included in the appendix (yes/partial/no)

yes. Procedural generation, LIBERO probing, OpenVLA recovery summarization, aggregation, and figure scripts are included.

4.4. All source code required for conducting and analyzing the experiments is included in a code appendix (yes/partial/no)

yes. Experiment scripts, configs, tests, aggregation, and result CSVs are included in the anonymous artifact.

4.5. All source code required for conducting and analyzing the experiments will be made publicly available upon publication of the paper with a license that allows free usage for research purposes (yes/partial/no)

yes. The anonymous artifact includes an MIT license, and the code plus generated procedural data will be made publicly available upon publication.

4.6. All source code implementing new methods have comments detailing the implementation, with references to the paper

where each step comes from (yes/partial/no)

partial. Code is modular and tested; comments are intentionally sparse and do not yet cross-reference paper sections.

- 4.7. If an algorithm depends on randomness, then the method used for setting seeds is described in a way sufficient to allow replication of results (yes/partial/no/NA)
yes. Every config lists seeds; scripts pass seeds to NumPy generators and result CSVs include per-seed rows.
- 4.8. This paper specifies the computing infrastructure used for running experiments (hardware and software), including GPU/CPU models; amount of memory; operating system; names and versions of relevant software libraries and frameworks (yes/partial/no)
yes. The run ledger records Slurm partitions, CPU/memory/time requests, hostnames for logged runs, environment constraints, and JSON environment snapshots for compute and GPU jobs.
- 4.9. This paper formally describes evaluation metrics used and explains the motivation for choosing these metrics (yes/partial/no)
yes. Recovery AUC, critical radius, clean success, transfer RAUC, and AULC are defined or described.
- 4.10. This paper states the number of algorithm runs used to compute each reported result (yes/no)
yes. Runs are reported in the paper and run ledger: synthetic training, estimator validation, grid-margin full-baseline, grid ablation, grid sensitivity confirmations, and robot-suffix coverage comparisons use 30 paired seeds; grid learning-curve diagnostics use 15 seed pairs. Smaller three- or five-seed exploratory diagnostics are labeled as diagnostics in the run ledger rather than used as main claims.
- 4.11. Analysis of experiments goes beyond single-dimensional summaries of performance (e.g., average; median) to include measures of variation, confidence, or other distributional information (yes/no)
yes. Aggregated tables include standard errors; experiments report median critical radius and AULC in addition to final means.
- 4.12. The significance of any improvement or decrease in performance is judged using appropriate statistical tests (e.g., Wilcoxon signed-rank) (yes/partial/no)
yes. The anonymous artifact includes paired exact sign tests for the reported paired comparisons, including the 30-seed suffix coverage confirmation, grid-margin target-sensitivity, grid-margin obstacle-regime sensitivity, grid-margin geometry-stress sensitivity, and grid-margin learning-curve sweeps. The paper separates these main comparisons from smaller exploratory evidence.
- 4.13. This paper lists all final (hyper-)parameters used for each model/algorithm in the paper's experiments (yes/partial/no/NA)
yes. Final hyperparameters are in the artifact YAML configs under `configs/`.