Smishing Triage — Technical Writeup

BC3415 AI in Accounting & Finance · Individual Assignment (Option A)
Jonathan Low Seng Kian · U2321652C · 22 October 2026

Summary. A three-way classifier separates legitimate messages, marketing spam and smishing (phishing by SMS), served as a forward-it-to-check bot for a Singapore bank's customers.

- **Test performance:** catches 76.1% of smishing (95% CI 56.3–89.3%) at 78.3% precision. 19 of the 109 test scams are called spam, so the user is still warned; 7 are called legitimate, and all 7 are sent to a person by the review rule.
- **False alarms:** flags 0.21% of ordinary Singaporean personal messages (18 of 8,547). That figure comes from personal chat collected before 2015, close to the training ham, and was used as a selection guardrail. Genuine bank and SingPost notices fare far worse: all 5 were flagged.
- **Main gap:** on 60 real scams sent to people in Singapore it catches 60% and warns on 68%. Scams with a link are mostly caught; chat-style scams without one mostly are not. 19 of the 60 get a "no scam signals found" reply.
- **Human in the loop:** the bot hands a message to a person when the expected cost of its verdict exceeds the cost of a review (section 9). That sends 10.0% of test messages to a person, and they include every one of the 26 test scams the bot missed; with review, 54 of the 60 local scams are either caught or checked by a person.
- **How it got here:** the first version reported 95% smishing recall, partly by testing on copies of its own training campaigns. The final method splits the data by near-copy cluster, which keeps such copies out of the test without deleting any real training data (section 6).
- **Recommendation:** not ready for customers. Fund a three-month pilot, about S$9,000 of staff time, more than half of it labelling local data, with explicit go/no-go criteria (section 1). Flagging genuine bank notices is a no-go blocker that the prototype currently fails.

1. Problem and business case

Smishing Triage is a forward-it-to-check scam detector for a Singapore bank's customers. A customer forwards a suspicious text, or a screenshot of one, and within seconds gets a verdict (scam, marketing spam, or no scam signals) along with the words that triggered it. This section makes the case for funding a pilot.

The problem, in money. Scams cost people in Singapore S$913.1 million across 37,308 cases in 2025, about S$24,500 per case [1], and S$410.6 million in the first half of 2026 alone [2]. Most scams start with a message: messaging platforms (53.5% WhatsApp, 37.9% Telegram) were the contact method in 9,355 cases in 2025, second only to social media (10,448). SMS itself was the contact method in only 450, after telco filtering and the protected `gov.sg` sender ID took effect [1]. The checker therefore accepts any forwarded text, not only SMS. Its training data is SMS, and the Singapore scam set used to test it (section 5) is mostly SMS and WhatsApp messages, with a few from Carousell chat and Telegram.

Where it fits. The government's ScamShield app filters suspicious SMS, and its WhatsApp bot checks forwarded messages against police reports and a classifier [4]. Smishing Triage is a complement, not a replacement. It is the bank's own layer: it runs in the bank's channel, separates marketing spam from scams, and shows the customer *which words* raised the flag. Every check also stays with the bank's fraud team, which sees new scam wording first.

Why it matters to the bank. Since 16 December 2024, the MAS–IMDA Shared Responsibility Framework has allocated phishing losses in order. The bank bears the loss if it breached one of its specified anti-phishing

duties. The telco bears it, for scams sent by SMS, if the bank complied and the telco did not. Otherwise the customer bears it [3]. A voluntary checker does not discharge any of those duties, and it does not move liability. What it does is reduce how often customers are phished at all. That means fewer losses to dispute, less exposure wherever a control does fall short, and fewer customers who lose money with no one else liable. A customer who sees *why* a message was flagged also learns to spot the next one unaided.

Why three classes, not two. A standard spam filter puts a marketing blast and a credential-harvesting message in the same class. For the customer, one wastes three seconds and the other can empty an account. Separating them turns an inbox tidier into a fraud control, so success is measured by how many scams are caught (smishing recall), not by accuracy. On messages that are 83% legitimate, a model that calls everything legitimate scores 83% accuracy and catches nothing.

What the prototype delivers today, and what it does not. On held-out test data it catches 76% of scam messages, and every test scam it misses is sent to a person by the review rule (section 9). It runs on a laptop; a small server costs a few hundred dollars a year. It is not ready for customers. On 60 real local scams it catches 60% and warns on 68%, and all 5 genuine bank and SingPost notices were flagged. Both gaps have one cause in the public training data: its scams are British and Indian, mostly premium-rate prize texts, and its legitimate messages are personal chat (partly Singaporean) with almost no transactional SMS.

The pilot. Three months, with the money going mostly to local data. Costs are estimates.

Phase	Work	Estimated cost
Months 1–2: local data	Label about 3,000 local messages from the bank's fraud reports, customer forwards and its own genuine transactional SMS (OTPs, alerts), each checked twice: about 100 analyst-hours	about S$5,000 (at S$50 per hour)
Month 3: retrain and trial	Retrain with this pipeline (minutes), test on a fresh held-out local set, then a staff-only trial in the bank's channel	server a few hundred S$ a year
Throughout: staff time	An engineer to connect `predict()` to the bank's channel and run the trial (about 60 hours), and the fraud team reviewing the trial's verdicts (about 20 hours)	about S$4,000 (80 hours at S$50 per hour)
Throughout: scam-type labels	From a paid-tier or self-hosted LLM: customer messages cannot go to a free tier that may train on them	usage-based; small at pilot volumes
Total		**about S$9,000**, plus server and LLM usage

Go/no-go criteria, measured on a fresh local test set never used in training:

- catch at least 80% of local scams as smishing, and warn on at least 90%;
- flag at most 1% of the bank's own genuine transactional messages;
- reply within 10 seconds, and store no message bodies.

The prototype fails these today, and one failure is a blocker by itself. It flagged all 5 genuine SingPost and bank notices in the Singapore set. A checker that calls a bank's own alerts scams teaches customers to ignore warnings, and the bank's own messages too. Until the bank's genuine messages pass the 1% criterion, the answer is no-go, whatever the scam catch rate.

An illustrative yearly benefit. Every input below is an assumption, stated so it can be replaced with the pilot's measurements:

Assumption	Value
Messages customers forward to check, per year	50,000
Share that are scams (people forward what already looks suspicious)	40%
Share of scams caught: today on local scams / at the pilot target	60% / 80%
Share of caught scams that would otherwise have led to a loss	1%
Average loss per scam case [1]	S$24,500
Losses avoided per year: 50,000 × 40% × caught × 1% × S$24,500	**S$2.9m today / S$3.9m at target**

The figure scales in proportion to each input, and the least certain is the 1% that would have lost money. The S$24,500 average is also a mean, which a few very large losses pull up, so a typical case costs less. Even at a tenth of that, avoided losses (about S$290,000 a year today) are many times the pilot's cost. The pilot costs less than one average scam loss, so it breaks even if it prevents a single loss. Under the Shared Responsibility Framework most of these losses would fall on customers rather than the bank, so for the bank the benefit is mainly customer trust and fewer disputed claims. The pilot exists to measure the first four inputs, so the case can be re-made with real numbers before any wider rollout.

How it maps to the brief. The brief's example combines review text, customer images and a joint flag. This project follows the same pattern. Text classification produces the verdict, as review sentiment does. The image channel is a screenshot, as the customer's photo is, although here OCR extracts its text rather than an image classifier labelling it. A second LLM stage names the scam type, so each flagged message, like a flagged order, carries both a verdict and the kind of problem it resembles. The brief's image channel is a classifier of defect photos. A scam-screenshot classifier would need labelled scam images, and no public labelled set was found, so here the image channel reads the screenshot's text and the trained text classifier judges it.

2. Data

Of the public corpora found, only one of real messages separates commercial spam from smishing, and after deduplication it holds 546 real smishing messages. That class is the project's binding constraint. Each source has a fixed role so that none can leak into the wrong place.

Source	Messages (raw)	After dedup.	Role
Mendeley SMS Phishing	5,971 (4,844 ham, 489 spam, 638 smishing)	5,823	Core three-class set; the only real source of smishing
UCI SMS Spam Collection	5,574 (ham, spam)	184	Extra ham and spam; almost all of it is already in Mendeley
NUS SMS Corpus (Singapore senders)	10,116 ham	8,948	Held out to measure false alarms on local personal messages
Mendeley balanced (published as LLM-generated)	10,191 (3,397 each of ham, spam, smishing)	3,302	Excluded from training (below)
Singapore scam set (collected)	60 scams, 5 legitimate	65	Evaluation only (section 5)

The fourth corpus, published as LLM-generated messages, turned out to be mostly reworded copies of the other corpora. Over repeated splits it shows no reliable benefit, so it is excluded (section 6).

Deduplication across the corpora removed 13,595 of 31,852 rows: they are built on each other (Mendeley re-labels UCI, and UCI absorbed part of NUS). 303 identical messages carry different labels, almost all `uci=spam` against `mendeley=smishing`. That is the spam/smishing conflation this project exists to undo. Conflicts are resolved by source priority, and Mendeley ranks above UCI, so the finer Mendeley label wins. Some conflicts sit inside a single corpus; there the row that sorts first is kept, which leaves 16 messages that one source called smishing labelled spam (12 in training, 2 in validation, 2 in test).

The Singapore scam set was collected from Singapore Police Force advisories (43 scams, all 5 legitimate messages), Mothership (8) and archived ScamAlert stories (9), dated 2018 to 2026. Most sources publish these as screenshots, so 51 of the 60 scam texts were transcribed from the screenshots with AI assistance. The `notes` column marks each one as transcribed from a screenshot.

3. Preprocessing pipeline

The pipeline makes sure the model is never tested on a message, or a near-copy of a message, that it trained on, without throwing real training data away to do it. It runs in five steps (`src/preprocess.py`).

1. **Load and unify.** One loader per corpus emits the same three columns: `text`, `label`, `source`. All files are read as UTF-8; latin-1 would turn every "£" into "Â£", a cue no real incoming message carries.
2. **Deduplicate before splitting.** Messages are matched on a key that ignores case, spacing and punctuation, and conflicting labels are resolved by source priority (Mendeley over UCI).
3. **Normalise, keeping two representations.** `text_clean` replaces URLs, emails, phone numbers (including 8-digit Singapore numbers), amounts and numbers with placeholder tokens for word features, because their presence is predictive even when the value is not. The raw text is kept for character features, since digits, case and punctuation are what obfuscation abuses (`DB5`, `acc0unt`).
4. **Cluster near-copies, then split whole clusters at random.** Scam campaigns send one template many times with a different number or amount, or reword a phrase ("it has been resent" against "it ingest been resent"). Exact deduplication keeps every variant. So two messages are linked if they share a template (identical normalised text) or their character n-gram similarity is 0.7 or more, on the raw or the number-blanked text (cosine over 3–5 character TF-IDF, with weights fitted once on the whole corpus). At that level most pairs inspected were the same message with a word or number changed; some are merely similar. Linked messages form clusters, and a chain of links can join different short messages: the 6,007 real messages fall into 4,956 clusters, most of them single messages, the largest holding 40 short legitimate replies. Over-grouping only makes the split stricter. Whole clusters are then shuffled and assigned to training, validation or test by scikit-learn's `StratifiedGroupKFold`, which balances the labels: one in five to test, then one in seven of the rest to validation. This is still a random split; the unit shuffled is the campaign, not the message. It is standard practice for groups of dependent samples [6], such as several X-rays from one patient [7]. No copy of a campaign can sit on both sides, and validation and test are kept apart from each other too. An independent check with its own weights finds no pair above 0.75 across any boundary (ignoring messages under 20 characters, whose similarity swings with the weights; none is a scam).
5. **Keep the rest clear.** The LLM-generated rows can only ever join training, so those that nearly copy a validation or test message are dropped (1,096 of 3,302). The same check removes any Singapore shift or scam message that resembles a training message, so both local sets measure unseen text.

Split	Messages	Ham	Spam	Smishing
Train (real)	4,118	3,402	342	374
Validation	687	567	57	63
Test	1,202	993	100	109
Singapore shift (NUS)	8,547	8,547	0	0

With 109 smishing messages in test, one misclassification moves recall by almost a point, so smishing recall is always reported with a bootstrap confidence interval. The bootstrap resamples clusters, not messages. The 109 test scams come from only 43 clusters (the largest holds 21), and copies of one campaign are one piece of evidence, not several.

4. Models and selection

The served model is a calibrated linear SVM on character n-grams. Its validation macro F1 is within noise of the best model's, and it is the only model that flags under 1% of ordinary Singaporean messages. Four models were fitted, cheapest first, and scored on validation only; the selected model's test evaluation ran once. The split study (section 6) and the review analysis (section 9) also report test figures, but neither chose the model.

Model	Features	Val. macro F1	Smishing recall	Smishing precision	False alarms on SG ham
Multinomial Naive Bayes	word counts	0.790	0.603	0.844	1.9%
Logistic regression	word TF-IDF (1–2 grams)	0.807	0.619	0.867	2.6%
Logistic regression	word + character TF-IDF	0.832	0.651	0.891	1.2%
Calibrated linear SVM	**character TF-IDF (2–5 grams)**	**0.806**	**0.619**	**0.830**	**0.21%**

- **Selection rule.** Highest validation macro F1, with smishing recall as the tie-break, among models that flag at most 1% of the Singapore shift set, applied in code. The four models are within about 0.04 macro F1 of each other, inside the noise of 63 validation smishing messages (one message moves recall by 1.6 points), but differ up to twelvefold on false alarms, which macro F1 cannot see. The 1% cap was set under an earlier split, with that split's validation results in view.
- **Class imbalance.** Every model except Naive Bayes uses balanced class weights, so errors on the rare smishing class count as much in training as errors on the common classes.
- **Why characters.** Smishing hides in spellings, digits and link shapes that word tokens destroy; character n-grams keep them, and misspellings such as "DB5" and "acc0unt" are still caught (section 5).
- **Calibration.** The SVM is wrapped in sigmoid calibration so it outputs probabilities: the bot shows a confidence, and both the operating-point comparison and the review rule need one.

Operating point: argmax. The model outputs three probabilities, and a decision rule turns them into one verdict. Argmax takes the most probable class; min-cost takes the class with the lowest expected cost under the project's cost matrix, where a missed scam costs 20 and a false scam alarm costs 2. Both were compared on validation and the Singapore shift set before the test set was touched.

Rule	Macro F1	Smishing recall	Smishing precision	False alarms on SG ham
Argmax (served)	**0.806**	**0.619**	**0.830**	**0.21%**
Min-cost	0.729	0.905	0.633	0.64%

Min-cost would catch 18 more of the 63 validation scams, but precision falls to 0.63 and false alarms on real local messages triple, a cost the matrix has no term for. For a checker people must trust, the served rule is argmax (`config.yaml`). A cost matrix is only as good as the costs it leaves out. All 18 scams that min-cost would add are sent to a person by the human-review rule instead (section 9), so they are not lost, and no verdict shown to a customer becomes less trustworthy.

5. Results

On the held-out test set the model catches 76.1% of smishing at 78.3% precision. On real scams sent to people in Singapore it catches 60%, and that gap is the project's most important finding.

Test metric	Value
Smishing recall	**0.761 (95% CI 0.563–0.893, by cluster)**
Smishing precision	0.783
Macro F1	0.813
Accuracy	0.943
Brier score (0 is perfect)	0.079
False alarms on Singaporean ham (NUS)	0.21% (18 of 8,547)

True ↓ / predicted →	Ham	Spam	Smishing
Ham (993)	988	3	2
Spam (100)	16	63	21
Smishing (109)	7	19	83

Most error sits on the spam/smishing boundary. A scam called spam still reaches the user with a warning. The costly miss, a scam marked safe, happened 7 times in 109; all 7 are sent to a person by the review rule (section 9).

The interval is wide, and the validation split is the outlier. Validation recall (0.619) is lower than test (0.761). Over six repeated cluster splits of the non-test data, the same model's recall ranges from 0.75 to 0.90 and averages 0.80 (`reports/ablation_repeated.csv`), so the single validation split, whose 63 scams fall in only 27 clusters, is unusually hard. The 95% interval on test recall, 0.56 to 0.89, is the honest summary: 109 scams in 43 clusters is not much evidence.

Confidence is reliable at the extremes on familiar text. Of test messages given about 94% smishing probability, 90% were smishing, and of those given about 1%, 1% were. The middle bins hold only 20–31 messages each and are noisier (`reports/calibration_test.csv`). This calibration holds for text like the training data, not for real local scams, where the model is often confidently wrong.

Real Singapore scams

The Singapore scam set (section 2) was never used to train or tune the model. It is, however, one of the yardsticks in the split study (section 6), so it informed the choice of split method. The model catches 36 of 60

scams (60%) and warns on 41 (68%).

Link-based scams are more often caught; chat-style scams mostly pass



`reports/sg_scams_predictions.csv` · 60 scam messages, 2018–2026

- **The model learned what a scam SMS with a link looks like.** Scams carrying a link were caught 26 times out of 32; scams without one, 10 out of 28. A link here means one the pipeline's URL pattern recognises; it misses one scam's `s.id` short link and one redacted link.
- **Conversational scams pass as chat.** Carousell fake buyers, job recruiters and a kidnap threat read like personal messages, and personal messages are what the training ham is made of. 15 of the 28 scams without a link get "no scam signals found".
- **Legitimate local transactional messages are flagged.** All 5 genuine SingPost notices and bank OTPs were called spam or smishing. The training ham is almost entirely personal chat, so an official OTP looks more like a scam than like ham. Five messages is a small sample, but the direction is clear.

Robustness probes

Constructed variants of a message test behaviour the test set cannot (`src/robustness.py`). They are reported as behaviour, not accuracy: 7 of 12 get the verdict a user would want. Three failures are link-related, and two are chat-style scams with no link at all.

Probe	Example	Verdict (p smishing)
Misspelling	Y0ur DB5 acc0unt has been l0cked. Verify now at http://dbs-sg-verify.top	Smishing (0.97) ✓
Link with `http://`	Your parcel is held at customs. Pay the fee at http://sgpost-clear.co/pay	Smishing (0.94) ✓
Same link, bare domain	…Pay the fee at sgpost-clear.co/pay	No scam signals (0.09) ✗
Same lure, no link	Your parcel is held at customs. Reply with your card number to pay the fee	No scam signals (0.39) ✗
Harmless news link	check out this article https://www.straitstimes.com/singapore/abc	Smishing (0.76) ✗
Chat-style scam	Hi mum this is my new number, my phone broke. Can you PayNow me $500 urgently	No scam signals (0.04) ✗
Job scam	Hi, I am Jessica from Lazada HR. Part time job, earn $300-$800 daily. Interested?	No scam signals (0.02) ✗

6. How the project got here: what was tried, and what was dropped

The first version of this classifier reported 95.4% smishing recall. The final one reports 76.1%. Most of that fall came from making the test harder to cheat on: early versions were partly tested on copies of campaigns they had trained on. The third version closed that leak by deleting training data; the final version closes it without deleting anything. The earlier versions are kept in the project's git history.

Version	How the data was split	Trained on	Accuracy	Macro F1	Smishing recall	Real SG scams caught
1 (8 Oct)	By message, at random	Real + LLM-generated (2,329 smishing, 371 real)	0.978	0.923	0.954	not yet collected
2 (13 Oct)	By template	Real + LLM-generated (2,324 smishing, 366 real)	0.973	0.904	0.891	38 of 60
3 (20 Oct)	By template, then near-copies deleted from training	Real only (199 smishing)	0.953	0.825	0.733	29 of 60
4 (22 Oct, final)	**By near-copy cluster**	**Real only (374 smishing)**	**0.943**	**0.813**	**0.761**	**36 of 60**

- **Version 1 → 2: the message-level split leaked.** Scam campaigns send one template many times with a different number or amount. Splitting message by message put 27% of test smishing beside a training message with exactly the same template, and about two-thirds once near-copies are counted too (split study, below). The model was partly being tested on campaigns it had already seen. Version 2 also fixed the text-encoding bug (below) and made the character features case-sensitive.
- **Version 2 → 3: templates were not enough, and the fix was too blunt.** Reworded copies and the same campaign with a different phone number still crossed the boundary. Version 3 deleted every training message within 0.7 similarity of a validation or test message: 2,317 rows, 1,807 of them LLM-generated

(55% of that corpus, against 12.5% of real rows). The test became honest, but training lost real scams (199 left). The Singapore catch fell from 38 to 29, but that change mixes two causes (the deletions and dropping the generated corpus), and the split study below shows that differences of this size are within the variation between random seeds.

- **Version 3 → 4: cluster first, then split.** The question that led here was a fair one: wouldn't a plain random split be better, since the model would learn every pattern? The answer came from testing it, below. Version 4 links near-copies into clusters before splitting and assigns whole clusters at random, so near-copies always land on the same side and nothing has to be deleted. Training keeps 374 real scams and the test stays free of twins. It catches 36 Singapore scams, but averaged over three seeds the three split methods catch about the same number (below).
- **The LLM-generated corpus was dropped.** On the one validation split it adds +9.5 points of smishing recall. A single split of 63 scams is noisy, so the comparison was repeated over six cluster splits of the non-test data. There the corpus showed no reliable benefit: −1.7 points on average (better in 1, tied in 1, worse in 4), and +2.1 under version 3's split (better in 4 of 6). It has been excluded since version 3, and the final model trains on real messages only. Its apparent gains in versions 1 and 2 (+9.1 and +3.8 points on one validation split each) were probably partly leakage.
- **The cost-matrix operating point was rejected.** Choosing the cheapest class under the cost matrix raised validation smishing recall from 0.62 to 0.90. But precision fell from 0.83 to 0.63 and false alarms on Singaporean messages tripled (section 4).
- **Selection on macro F1 alone was replaced.** The four models are within noise on macro F1 but differ up to twelvefold on false alarms. Picking purely on macro F1 would choose the word-and-character logistic regression, which flags 1.2% of ordinary Singaporean messages. The 1% false-alarm guardrail selects the character SVM (0.21%).
- **The first explainer did not work.** It removed one word at a time and measured the change. On a 99%-confident prediction no single word moves the score, so it returned no red flags at all. It was replaced by LIME (section 7).
- **A text-encoding bug was found and fixed.** Reading the corpora as latin-1 turned every "£" into "Â£", a cue no real incoming message carries, in over two thousand messages. All files are now read as UTF-8.
- **Not attempted: a transformer model.** The binding constraints are 374 real training scams and the gap to local scams, which a larger model trained on the same British and Indian corpora would not close. The pilot's local data is the better use of effort.

Testing the split itself

Why not split message by message at random, as a textbook regression example does? A random split assumes each row is independent. Here they are not: one campaign produces many near-identical rows. scikit-learn's guidance is that "the i.i.d. assumption is broken if the underlying generative process yields groups of dependent samples", and it provides group-aware splitters for this case [6]. CheXNet, a well-known pneumonia model, split its X-rays at random but ensured "there is no patient overlap between the sets" [7]. Splitting by record instead of by person "often massively overestimates the prediction accuracy" [8]. Duplicates across a split inflated reported metrics "by up to 100%" in models of code [9].

The argument was tested rather than assumed (`src/split_study.py`). The same real messages were split three ways and the same model trained on each, for three seeds. "Twin" means a test scam with a near-copy or the same template in training. The 60 real Singapore scams never enter any training set, so they measure how good each trained model really is.

Split method	Real scams trained on	Test scams with a twin in training	Test smishing recall	...on twins / on new campaigns	Real SG scams caught (average)
Random, by message	371	73–81 of 109	0.81–0.89	0.91–0.95 / 0.53–0.86	31–35 of 60 (33.7)
By template, near-copies deleted (version 3)	199–209	0	0.73–0.80	— / 0.73–0.80	29–35 of 60 (32.7)
By near-copy cluster (final)	**373–375**	**0**	**0.76–0.84**	**— / 0.76–0.84**	**31–36 of 60 (34.0)**

`reports/split_study.csv` · ranges over seeds 42, 1 and 2 · the final pipeline uses seed 42 · the delete method's test sets hold 99–105 scams, so its test recall is not directly comparable

What the study shows, and what it does not. A random split makes the test score untrustworthy. Two-thirds of its test scams are near-twins of training messages, recalled at over 90% against 53–86% for new campaigns, and a test score of 0.89 sits beside a real-world catch of 35 in 60 (58%). On real Singapore scams, though, the three methods are within seed noise of each other (33.7, 32.7 and 34.0 of 60 on average), so the study does not show that any split trains a better model. The cluster split is chosen on principle. Like deleting near-copies, it gives a test free of twins; like a random split, it keeps every real training message.

7. Explainability

A spam or scam verdict comes with the words that drove it, found by LIME and shown to the user as red flags. When every cue is a filtered token (a function word or a bare number), the verdict is shown without flags. A user who sees why a message was flagged learns to spot the next one unaided, which makes the explanation part of the product, not just a report figure.

LIME deletes random subsets of words from the message, re-scores each variant with the real model, and fits a small weighted linear model to those scores; each word's weight is its estimated push towards the verdict. Deleting many words at once lets it explain a 95%-confident prediction, where removing any single word moves nothing.

Message	Verdict	Red flags (LIME)
Your DBS account is locked. Verify at http://bit.ly/x9	Likely scam (98%)	http://bit.ly/x9, account, Verify
URGENT! You have won a 1 week FREE membership in our £100,000 Prize Jackpot! Txt the word: CLAIM to No: 81010	Likely scam (94%)	£100,000, URGENT, Prize, CLAIM, won
WIN a FREE iPhone! Txt WIN to 85233 now. T and Cs apply	Marketing / spam (99%)	FREE, Txt, WIN, apply, T
Eh you reaching already? I order first ah	No scam signals found (96%)	none, plus a reminder that this is not a guarantee

Tokens are split on whitespace so a link stays whole and is shown as one flag. Function words such as "your" and "our", and bare numbers such as an OTP, are filtered out. Explanations are seeded, so the same message always yields the same flags, and they take under half a second. LIME explains the model's behaviour, not ground truth: a weak token such as "T" or "apply" can appear when it co-occurs with the real cue.

What the model relies on overall. The SVM's averaged linear weights give the global picture (`reports/top_features.csv`). The strongest smishing cues are digit fragments of UK premium-rate numbers

("08…", "09…", "00") and "http". The model has learned what a scam SMS in these mostly British and Indian corpora looks like, which explains both the robustness results and the gap on Singapore scams.

8. The application

The product is a forward-it-to-check bot: a user forwards a suspicious message, or a screenshot with or without a caption, and gets a verdict, a confidence and the red flags back within seconds. Telegram is the demo channel because a bot there needs no business verification. A deployment would put the same `predict()` behind the bank's app or WhatsApp Business, where ScamShield's bot already runs.



serving path · `app/bot.py`, `src/ocr.py`, `src/predict.py`, `src/review.py`, `src/scam_type.py`

Only the highlighted step is evaluated. The trained classifier makes every decision. A zero-shot Gemini call runs only on messages the classifier already called smishing, and adds a likely scam type (parcel, bank impersonation, job offer…) with the phrases that indicate it. Scam-type labels do not exist as public labelled data, so this stage is advisory and no metric depends on it. As a spot check, on the 36 Singapore scams the classifier caught, the Gemini label matched the hand label 30 times (`reports/scam_type_eval.csv`; an LLM's answers can vary between runs). The misses were near neighbours, such as an online-seller scam labelled as a parcel scam, and three involved scams hand-labelled "other". The gate lives inside `scam_type.enrich()`, not in the caller, and a test checks that a legitimate message never reaches it. Each model is given 15 seconds before a fallback model is tried, and the verdict is sent whether or not Gemini answers.

- **No false all-clear.** A message with no scam signals is never called "safe". The reply says it is not a guarantee and tells the user to check any request for money, a code or a login with the sender on a number they already trust, because about a third of real local scams (19 of 60) get this verdict. When even this verdict carries enough risk, the reply says a person should check it instead (section 9).
- **Screenshots.** Users forward screenshots more readily than they retype. Tesseract reads the image, chat furniture (timestamps, "Delivered") is stripped, and the text, together with any caption, goes through the same `predict()`.
- **Privacy.** The bot logs a label, a confidence and a message length, never the message body or the bot token. Legitimate messages never leave the machine. Flagged messages do go to Google, and on the free tier Google may use them to improve its models; a billed account or a locally hosted model would close that gap.
- **Degrades, never fails.** Without a Gemini key the bot still answers with the classifier's verdict; without Tesseract it uses the caption or asks the user to paste text instead.

9. Human in the loop

The classifier answers in seconds, but some of its answers should not stand alone. People come into the system at four points. The first, deciding which messages a person should check, is built into the prototype and measured; the other three are how a deployment would run.

When the bot should hand a message to a person

Not below a flat confidence such as 60%. A single cut-off treats every mistake as equally costly, and this project's mistakes are not. Under the cost matrix a missed scam costs 20, while calling a legitimate message spam costs 1. Take a message the model calls legitimate with 96% confidence and a 4% chance of being a scam. Letting that verdict stand has an expected cost of 20 × 0.04 = 0.8. Now take a message split 55/45

between legitimate and marketing spam. Its confidence is far lower, but the worst mistake it can make costs almost nothing. The first deserves a human more than the second.

The rule. This is a cost-sensitive form of Chow's reject option [5]: send a message to a person when the expected cost of the bot's verdict standing alone exceeds the cost of a review. The expected cost is the verdict's cost under the cost matrix, averaged over the model's three probabilities. The rule lives in `src/review.py`, and `predict()` applies it to every message.

The review cost, 0.5, is 1/40 of a missed scam. In money, a two-minute analyst review at S$50 an hour costs S$1.67. That is 1/40 of a missed scam if a missed scam's expected loss is S$67, which holds if about 0.27% of missed scams end in an average S$24,500 loss. Section 1's benefit estimate assumed 1%, which would put the review cost at 0.14; a tenth of that assumption would put it at 1.4. The value 0.5 sits between them. It was fixed under the previous split (version 3), while that split's validation and test figures were both on screen, and was not revisited for the final split. The table shows every candidate on every set, so a reader can see how the figures move with the choice.

What it means in confidence terms. At a review cost of 0.5, a "no scam signals" verdict stands alone only if the model is at least 97.5% sure the message is not a scam. A "spam" verdict needs it to be roughly 95% sure the message is not a scam, and a "likely scam" verdict roughly 75% sure it is not legitimate. The second and third are approximate because smaller doubts add to the cost: 6 of the 120 test reviews come from those combinations. Pure doubt between legitimate and marketing spam never needs a person at this cost. A single flat threshold would be wrong in both directions: too lax where a scam could slip through, too strict where nothing is at stake.

Review cost	Val.: share reviewed	Val.: missed scams reviewed	Test: share reviewed	Test: missed scams reviewed	SG set: share reviewed	SG set: missed scams reviewed
0.14	40.9%	24 of 24	42.7%	26 of 26	89.2%	22 of 24
0.5 (served)	**9.8%**	**21 of 24**	**10.0%**	**26 of 26**	**41.5%**	**18 of 24**
1	6.8%	19 of 24	5.2%	25 of 26	23.1%	14 of 24
2	4.2%	16 of 24	4.0%	22 of 26	16.9%	11 of 24

`reports/human_review.csv` · "missed scams" are scams the bot called spam or legitimate · SG set = the 65-message Singapore set

- **On test, 10.0% of messages go to a person, and they include all 26 scams the bot missed,** among them the 7 it called legitimate. Counting scams the bot caught plus missed ones a person sees, all 109 test scams are handled.
- **On real Singapore scams the gap narrows most.** The bot catches 36 of 60, and the rule sends 18 of the other 24 to a person, including 13 of the 19 the bot called legitimate. With review, 54 of 60 local scams are either caught or checked by a person.
- **The review rate among scams is itself an alarm.** Test scams go to review 25% of the time, real Singapore scams 37%. Local personal messages go slightly less often than test ones (3.5% against 4.1%), so the difference comes from the scams. Reviewed messages get labels, so a rising review rate among confirmed scams is an early sign that scams no longer look like the training data. A rising overall rate can also simply mean more scams.
- **What the user sees.** A reviewed "no scam signals" verdict is marked ❔ instead of ✅ and adds: "There is still enough chance this is a scam, so a person should check it. Until then, treat it as suspicious: don't click links, pay, or share codes." Reviewed spam and scam verdicts open the same line with "I'm not certain

about this one". For example, "Hi mum this is my new number… PayNow me $500 urgently" is called legitimate with 95% confidence. Its 4% scam probability is still enough to send it to a person (the robustness probe in section 5).

- **Capacity.** Section 1 assumes 50,000 checks a year, 40% of them scams. At the test review rates (4.1% of legitimate messages, 25% of scams) that is about 12% reviewed: 17 a day, roughly 35 minutes of analyst time, or about S$10,000 a year at S$50 an hour. At the rates seen on local messages (3.5% and 37%) it is about 17%: 23 a day and about S$14,000 a year, until the model is retrained on local data. The real figure is one more thing the pilot measures.

The other three points

- **Labelling.** Every reviewed message gets a human label. Those labels are the local training data the pilot pays for (section 1), so the review queue and the fix for the local gap are the same work.
- **Release sign-off.** A retrained model never deploys itself. A person checks it against the go/no-go criteria on a held-out local test set before it replaces the current one.
- **The customer decides.** The bot advises and never calls a message "safe". The customer, warned and shown the red flags, makes the final call.

Reviewers would read customers' messages, so a deployment must say so when the customer forwards a message, and should show reviewers only messages the rule selects.

10. Limitations, risks and scope

The largest risk is that the training smishing is not Singaporean: it is British and Indian in phrasing, brands and phone-number formats, and no public local smishing corpus was found. Section 5 measures what that costs on real local scams.

- **False reassurance.** About a third of real local scams (19 of 60) get "no scam signals found", often with high confidence. The reply carries a warning, and the review rule sends 13 of those 19 to a person (section 9), but only where a reviewer exists. A user may still read the verdict as an all-clear; this is the main reason the prototype is not ready for customers.
- **Small smishing class.** 546 real smishing messages remain after deduplication: 374 to train on, 63 for validation and 109 for test. The 95% confidence interval on test recall runs from 0.56 to 0.89: the 109 test scams are effectively 43 independent campaigns.
- **Selection on one small validation split.** There is no hyperparameter search, and the models are within noise of each other. Recall on the single validation split (0.62) sits below the 0.75–0.90 range seen over six repeated splits. The 1% false-alarm cap and the review cost were set under an earlier split with results in view, so the Singapore false-alarm rate is a guardrail rather than an untouched estimate.
- **The false-alarm figure is for personal chat.** The 0.21% comes from Singaporeans' personal messages collected before 2015, and it is closer to the training data than it looks: UCI's legitimate messages were partly drawn from the same NUS corpus. Transactional messages, the kind a bank's customers actually receive, were flagged in all 5 cases.
- **Adversarial evasion.** Character n-grams catch misspellings like "DB5", but a scam link without `http://` evades the model, so does the same lure asking for a card number with no link, and an ordinary message with a news link is flagged.
- **Concept drift.** Scam wording changes faster than any static training set. A deployment would need periodic retraining on newly reported scams and monitoring of the verdict mix and the review rate (section 9).
- **OCR errors land upstream of the classifier.** A misread character becomes a feature the model never trained on; dark mode and low resolution make this worse.

- **Debatable labels on the boundary.** Some source labels between spam and smishing are themselves arguable (premium-rate prize texts are smishing in Mendeley and spam in UCI).
- **Privacy.** Flagged messages are sent to Google for the scam-type label (section 8). A scam checker that ships users' messages to a third party has a tension in it, which should be stated to users.

Next version. The fix for the local gap is local training data: conversation-stage scams labelled smishing, and genuine transactional messages from banks and SingPost labelled ham. Public data of this kind is very small: most local scam examples are published only as screenshots, many chat scams circulate in Chinese, and genuine bank notifications are rarely published at all. A bank's own fraud reports are the natural source, which is what the pilot in section 1 pays for. Any such data must be kept separate from the Singapore scam set, which has to stay unseen to remain a fair test. Once evaluation is complete, the shipped model could also be retrained on every labelled message, including validation and test, since the reported figures only need the held-out split while measuring.

Out of scope, deliberately: email phishing (headers, SPF/DKIM and attachments are a different feature space), phishing website detection, voice and in-person scams, live WhatsApp interception (no read API), and automatic on-device SMS filtering.

11. Reproducing the results

The model and evaluation results in this writeup are regenerated by one command, `python main.py --skip-download`, from the corpora shipped in `data/raw/`, with the exceptions listed here. Background figures (scam statistics, pilot costs) come from the cited sources and stated assumptions, the 27% message-split figure is from an earlier version of the pipeline, and section 6's figures for versions 1 to 3 (their metrics, training counts, ablation gains and Singapore catches) come from those versions in the project's git history, which is not part of the submission. A few descriptive counts were computed with one-off checks on the shipped files rather than printed by the pipeline: the per-corpus counts after deduplication, the link/no-link split, and the first two LIME examples. The scam-type spot check (30 of 36) calls Gemini: it needs `GEMINI_API_KEY` and `python -m src.scam_type --evaluate`, and an LLM's answers can vary between runs. `python -m src.train` alone regenerates the model results from the shipped `data/processed/` splits. All settings (labels, paths, split ratios, seed, near-copy threshold, cost matrix, selection cap, operating point, review cost) live in `config.yaml`; no module hardcodes a top-level path. `requirements-lock.txt` pins the exact library versions the saved model was trained with.

Command	What it does
`python -m src.download`	Fetches UCI, NUS and the OCR language data; lists the Mendeley files that must be downloaded by hand
`python -m src.preprocess`	Deduplicates, normalises, clusters near-copies and writes the cluster splits
`python -m src.train`	Fits the four models, selects on validation, evaluates test once, saves `artifacts/model.joblib`
`python -m src.ablation`	Compares training with and without the excluded corpus, on validation and over six repeated splits
`python -m src.split_study`	Compares random, delete and cluster splits on the same messages (section 6)
`python -m src.robustness`	Runs the constructed probes: misspellings, link form, harmless links, chat-style scams
`python -m src.review`	Applies the human-review rule at several review costs on every evaluation set
`python -m src.predict "message"`	One verdict with confidence and red flags
`python -m src.ocr screenshot.png`	Reads a screenshot, then classifies it
`python -m src.scam_type --evaluate`	Compares the Gemini scam type with the hand labels on the caught Singapore scams (needs `GEMINI_API_KEY`)
`python -m app.bot`	Runs the Telegram bot (keys in `.env`; see `.env.example`)
`python -m pytest tests`	19 checks, including that an independent near-copy check finds nothing shared across training, validation and test on the real splits, that the LLM never sees an unflagged message, and that a screenshot's caption is classified

`notebooks/walkthrough.ipynb` walks through the same pipeline with tables and figures; `python build_notebook.py` regenerates and executes it. The code is reusable through one entry point, `predict()`, which returns a label, a confidence, per-class scores, red flags and whether a person should review it; the bot, the OCR path and the notebook all call it.

References

1. Singapore Police Force (2026). *Annual Scam and Cybercrime Brief 2025.* https://www.police.gov.sg/-/media/SPF/Advisories/Scams/Annual-Scam-and-Cybercrime-Brief-2025.pdf
2. Singapore Police Force (2026). *Mid-Year Scam and Cybercrime Brief 2026.* https://www.police.gov.sg/-/media/SPF/Media-Room/Statistics/Mid-Year-Scam-and-Cybercrime-Brief-2026/Mid-Year-Scam-and-Cybercrime-Brief-2026.pdf
3. Monetary Authority of Singapore and Infocomm Media Development Authority (2024). *Guidelines on Shared Responsibility Framework*, effective 16 December 2024, paragraphs 6.2–6.7. https://www.mas.gov.sg/regulation/guidelines/guidelines-on-shared-responsibility-framework
4. ScamShield (n.d.). *About the ScamShield Bot.* https://www.scamshield.org.sg/about-bot
5. Chow, C. K. (1970). On optimum recognition error and reject tradeoff. *IEEE Transactions on Information Theory*, 16(1), 41–46.
6. scikit-learn developers. *Cross-validation: evaluating estimator performance*, section 3.1.2.4, "Cross-validation iterators for grouped data". scikit-learn 1.9 User Guide. https://scikit-learn.org/stable/modules/cross_validation.html

7. Rajpurkar, P., Irvin, J., Zhu, K., et al. (2017). CheXNet: Radiologist-level pneumonia detection on chest X-rays with deep learning. arXiv:1711.05225.
8. Saeb, S., Lonini, L., Jayaraman, A., Mohr, D. C., & Kording, K. P. (2017). The need to approximate the use-case in clinical machine learning. *GigaScience*, 6(5), gix019.
9. Allamanis, M. (2019). The adverse effects of code duplication in machine learning models of code. *Onward! 2019*. arXiv:1812.06469.