

# PERFORMANCE EVALUATION AND DIMENSIONING OF NETWORKS AND SYSTEMS

METI

---

Lab Report [EN]

---

**Authors:**

José Oliveira (103771)

Tiago Videira (116069)

Afonso Mendes (116024)

[jose.novais.oliveira@tecnico.ulisboa.pt](mailto:jose.novais.oliveira@tecnico.ulisboa.pt)

[tiago.g.videira@tecnico.ulisboa.pt](mailto:tiago.g.videira@tecnico.ulisboa.pt)

[afonsofmenDES@tecnico.ulisboa.pt](mailto:afonsofmenDES@tecnico.ulisboa.pt)

2026/2027 – 1<sup>st</sup> Semester

# Contents

|          |                                                                   |          |
|----------|-------------------------------------------------------------------|----------|
| <b>1</b> | <b>Introduction</b>                                               | <b>2</b> |
| <b>2</b> | <b>A. Random number generators</b>                                | <b>3</b> |
| 2.1      | Exercise 1 . . . . .                                              | 3        |
| 2.2      | Exercise 2 . . . . .                                              | 3        |
| <b>3</b> | <b>B. Generation of random variables and stochastic processes</b> | <b>4</b> |
| 3.1      | Exercise 3 . . . . .                                              | 4        |
| 3.2      | Exercise 4 . . . . .                                              | 6        |
| 3.3      | Exercise 5 . . . . .                                              | 8        |
| <b>4</b> | <b>C. Programming discrete event simulators</b>                   | <b>8</b> |
| 4.1      | Exercise 6 . . . . .                                              | 8        |
| 4.2      | Exercise 7 . . . . .                                              | 8        |
| <b>5</b> | <b>D. Estimation of probabilities</b>                             | <b>8</b> |
| 5.1      | Exercise 8 . . . . .                                              | 8        |
| <b>6</b> | <b>E. Revisions of statistics</b>                                 | <b>8</b> |
| 6.1      | Exercise 9 . . . . .                                              | 8        |
| 6.2      | Exercise 10 . . . . .                                             | 8        |
| 6.3      | Exercise 11 . . . . .                                             | 8        |
| <b>7</b> | <b>F. Output data analysis</b>                                    | <b>8</b> |
| 7.1      | Exercise 12 . . . . .                                             | 8        |
| 7.2      | Exercise 13 . . . . .                                             | 8        |
| 7.3      | Exercise 14 . . . . .                                             | 8        |
| <b>8</b> | <b>Conclusion</b>                                                 | <b>8</b> |

# 1 Introduction

Text for the introduction here.


## 2 A. Random number generators

### 2.1 Exercise 1

**Objective:** Generate 1000 random numbers uniformly distributed in  $[0, 1]$  using `runif()` and plot their histogram with `hist()`, to check informally whether the generator behaves as expected.

**Approach:** The following R script generates the sample and plots the histogram.

```
numbers <- runif(10000, min = 0, max = 1)
hist(numbers, main = "Histogram", xlab = "Value", ylab = "Samples",
      col = "lightblue", border = "black")
```



**Figure 1:** Histogram of 10000 samples generated with `runif()`.

**Conclusion:** As shown in Figure 1, the samples are approximately evenly distributed across all bins in  $[0, 1]$ , with no systematic bias toward any sub-interval. This is consistent with the expected behavior of a uniform distribution, confirming that `runif()` is generating numbers as intended.

### 2.2 Exercise 2

**Objective:** Verify, using `runif()`, that the sequence generated by a pseudo-random number generator is in fact deterministic, i.e., that it can be reproduced exactly.


**Approach:** The `set.seed()` function fixes the internal state of R's random number generator. By setting the same seed before two separate calls to `runif()`, the two resulting sequences can be compared with `identical()` to check whether they match exactly. As a control, a third sequence is generated without resetting the seed, so it is expected to differ.

```
set.seed(123)
seq1 <- runif(5)

seq_random <- runif(5) # generated without resetting the seed

set.seed(123)
seq2 <- runif(5)

identical(seq1, seq2)
```



```
> seq1 <- runif(5)
>
> seq_random <- runif(5)
>
> set.seed(123)
> seq2 <- runif(5)
>
> identical(seq1, seq2)
[1] TRUE
>
```

**Figure 2:** R console output confirming that `seq1` and `seq2` are identical.

**Conclusion:** As shown in Figure 2, `identical(seq1, seq2)` returns `TRUE`, confirming that `seq1` and `seq2` are exactly the same sequence, even though they were generated by separate calls to `runif()`. This happens because `set.seed()` resets the internal state of the generator to the same fixed value before each call, so the pseudo-random number generator produces identical output whenever it starts from the same seed. This demonstrates that the sequence is not truly random but deterministic, fully determined by the seed. In contrast, `seq_random`, generated without resetting the seed, follows on from the generator's state after `seq1` and therefore differs from both.

## 3 B. Generation of random variables and stochastic processes

### 3.1 Exercise 3

**Objective:** Develop an R script to generate Bernoulli distributed numbers from a uniform random number generator (`runif()`), and plot a histogram of 1000 samples to informally check that the generator behaves correctly.

**Approach:** A Bernoulli random variable with success probability  $p$  can be generated from a uniform random variable  $U \sim \text{Unif}(0, 1)$  by setting the outcome to 1 if  $U < p$  and 0 otherwise, using the `ifelse()` function. Here  $p = 0.7$  and  $n = 1000$  samples were generated.


```
p <- 0.7 # success probability
n_samples <- 1000 # number of samples

u <- runif(n_samples)

bernoulli_numbers <- ifelse(u < p, 1, 0)

hist(bernoulli_numbers,
     breaks = c(-0.5, 0.5, 1.5),
     main = "Bernoulli Numbers Histogram (p = 0.7)",
     xlab = "Outcome",
     ylab = "Frequency",
     col = "lightblue",
     xaxt = "n")

axis(1, at = c(0, 1))
```



**Figure 3:** Histogram of 1000 Bernoulli samples with  $p = 0.7$ .

**Conclusion:** As shown in Figure 3, out of 1000 samples approximately 700 outcomes are 1

and 300 are 0, matching the expected proportions for  $p = 0.7$ . This confirms that thresholding a uniform random variable at  $p$  is a valid method for generating Bernoulli distributed samples, since  $P(U < p) = p$  for  $U \sim \text{Unif}(0, 1)$ .

### 3.2 Exercise 4

**Objective:** Develop an R script to generate exponentially distributed numbers from a uniform random number generator (`runif()`), and plot a histogram of 10000 samples superposed with the theoretical pdf, to informally check that the generator behaves correctly.

**Approach:** Exponentially distributed samples can be generated from a uniform random variable  $U \sim \text{Unif}(0, 1)$  via the inverse transform method: since the exponential CDF is  $F(x) = 1 - e^{-\lambda x}$ , setting  $U = F(X)$  and solving for  $X$  gives  $X = -\ln(1 - U)/\lambda$ . The histogram is plotted with `prob=TRUE` so that its area is normalized to 1, making it directly comparable to the theoretical pdf obtained with `dexp()`, which is superposed using `lines()`. Here  $\lambda = 1.5$  and  $n = 10000$  samples were generated.


```
lambda <- 1.5 # rate of the exponential distribution
n_samples <- 10000 # number of samples

u <- runif(n_samples)
exp_numbers <- -log(1 - u) / lambda

hist(exp_numbers,
      breaks = 50,
      prob = TRUE,
      main = "Exponential Distribution (lambda = 1.5)",
      xlab = "Value",
      ylab = "Density",
      col = "lightgray",
      border = "white")

x_vals <- seq(0, max(exp_numbers), length.out = 500)
pdf_vals <- dexp(x_vals, rate = lambda)

lines(x_vals, pdf_vals, col = "red", lwd = 2)
```



**Figure 4:** Histogram of 10000 exponentially distributed samples ( $\lambda = 1.5$ ) with the theoretical pdf (red line) superposed, with and without density normalization.

**Conclusion:** Figure 4 shows why the `prob=TRUE` option is essential for this comparison. In Figure 4a (`prob=FALSE`), the histogram bars represent raw counts per bin, whose total sums to  $n = 10000$ , while the `dexp()` curve has area 1 by definition; the two are on completely different scales, so the pdf line appears flat against the axis and gives no useful comparison. In Figure 4b (`prob=TRUE`), the histogram is rescaled so that the total area of the bars is also 1, matching the normalization of the theoretical pdf, and the empirical histogram now closely follows the red curve. This confirms that the inverse transform method correctly generates exponentially distributed samples from uniform random numbers, and that density normalization is a necessary condition for a visual histogram-vs-pdf comparison to be meaningful.



### **3.3 Exercise 5**

## **4 C. Programming discrete event simulators**

### **4.1 Exercise 6**

### **4.2 Exercise 7**

## **5 D. Estimation of probabilities**

### **5.1 Exercise 8**

## **6 E. Revisions of statistics**

### **6.1 Exercise 9**

### **6.2 Exercise 10**

### **6.3 Exercise 11**

## **7 F. Output data analysis**

### **7.1 Exercise 12**

### **7.2 Exercise 13**

### **7.3 Exercise 14**

## **8 Conclusion**

Text for the conclusion here.