

Co-Formation Games — Unifying Network Formation and Opinion Dynamics

Jens Friedel

*School of Engineering Mathematics
and Technology
University of Bristol
Bristol, United Kingdom
jens.friedel@bristol.ac.uk*

Richard Pettigrew

*Department of Philosophy
University of Bristol
Bristol, United Kingdom
richard.pettigrew@bristol.ac.uk*

Martin Bullinger

*School of Engineering Mathematics
and Technology
University of Bristol
Bristol, United Kingdom
martin.bullinger@bristol.ac.uk*

Abstract—This report proposes a novel model combining network creation studies and opinion dynamics. After introducing each Network Formation Games (NFGs) and Social Influence Models (SIMs), we compose a model allowing for co-evolution of opinions and networks and containing both NFGs and SIMs as special cases. Other sections consider basic dynamics, optimal states, and research directions of these Co-Formation Games (CFGs), as well as showcase an Julia module implementing CFGgames. Overall, the model offers a promising basis for future research projects, while broadening the perspective of NFGs and SIMs.

Index Terms—Collective dynamics, Game theory, Network formation games, Network theory (graphs)

I. INTRODUCTION

Network dynamics plays an ever-important role in describing the modern world, with connective plasticity and local optimizations enabling the emergence of global order. Since this framework can describe a vast variety of phenomena, researchers employed numerous approaches — often multi-disciplinary ones — to analyze these systems. Specifically, networks of human-like agents have been subject of studies ranging from mostly theoretical analysis to phenomenological social science works [1], [2].

Even as the sheer numerosity has inspired some authors to question each model’s marginal benefit, considering strands of research showcases a lack of holistic perspectives [1]: As a subfield of game theory, Network Formation Games (NFGs) study how self-interested agents create and drive the structure of networks [3]. In contrast, Social Influence Models (SIMs) focus on inner states of nodes (opinions) diffusing through it [2]. In the case of social networks, this raises a tension: As opinion propagation and network formation can both be dynamic and influence each other, results from studies regarding only NFG or SIM do not necessarily generalize to the case of simultaneous dynamics.

This is an important caveat, as real social network behaviour rarely reduces to the semi-static treatment implied by NFGs and SIMs. Yet, even though there are works trying to combine some aspects of the other’s influence, they often do so as a small part of the original model’s main mechanism (e.g., [4], [5], [6]). Moreover, there is still no work unifying both approaches in a way sheltering results from both disciplines.

This report explores a model which allows topology and opinions to influence each other, while including NFGs and SIMs as special cases. After presenting NFGs and SIMs, this work presents and justifies each building block of the model, before assessing some basic traits with regard to possible dynamics, optimality and a simulation module implemented in the Julia programming language.

II. BACKGROUND

A. Network Formation Games

Introduced as a subfield of Game Theory, Network Formation Games (NFGs) consider agents acting strategically to maximize personal utilities / minimize costs [3]. In NFGs, the action agents can decide on is whether or not to sponsor connections to an other agent. An action profile a — storing every single agent i ’s decisions a_i — consequently produces a graph $G(a)$ in which nodes represent agents and edges [7].

(Since agents are always treated as part of a graph, the following text uses *agent*, *node* and *vertex* interchangeably, unless noted otherwise.)

The cost function $c(a_i)$ which each agent wishes to minimize imposes costs α_c on each connection sponsored, but encourages connectedness by punishing a distance measure of i in the graph, $c_i^d(G)$. When agent i sponsors an edge to j , we set $a_{ij} = 1$, and $a_{ij} = 0$ otherwise, so that

$$c_i^{\text{NFG}}(a_i) = c_i^d(G) + \alpha_a \|a_i\| \quad (1)$$

returns the cost an agent incurs, with $\|\cdot\|$ being the L1 norm.

The function $c_i^d(G)$ conventionally depend on the choice of laterality and directedness [7]. Whereas (bi-)unilaterality implies edge creation to need one (both) nodes’ sponsorship, (un)directed networks let one (both) nodes use a single edge to traverse paths. Commonly, $c_i^d(G)$ uses the shortest-path distances or the number of reachable nodes, but depends on network choices made later in this report. Thus, the definition of the distance costs is provided when our model is introduced in section Section III.

Because agents are unaware of the other game participants’ actions when deciding on an action — knowledge of a and the resulting network $G(a)$ is only implicit in (1) — there is no room for coordination. Instead, step-wise adaptations of a_i are taken to reduce costs, until there is no single sponsorship

change left which improves costs. These final states a^* are so-called Nash equilibria (NEs). They correspond to the concept of local stability, and a big portion NFG-related research devotes itself to analyzing the set of NEs and NE traits.

Since costs are minimised locally and step-wise, a configuration which minimizes the total cost

$$c(a) = \sum_{i=1}^n c_i(a_i) = c_d(G) + \alpha_c \|a\| \quad (2)$$

may be unreachable:

$$a^{\text{opt}} = \arg \min_a c(a) \leq \arg \min_{a^*} c(a^*). \quad (3)$$

This relates to the Price of Anarchy, which presents how costly selfish strategies end up being relative to game Γ 's optimum costs profile,

$$\text{PoA}(\Gamma) = \max_{a^*} \frac{C(a^*)}{C(a^{\text{opt}})}. \quad (4)$$

Overall, while there are many studies regarding optimality considerations for NFGs in terms of topology [7], [8] and some research weighing costs by categorical opinions [4], NFGs are yet to include explicit information propagation their dynamics.

B. Social Influence Models

Social Influence Models (SIMs) investigate how agents interacting with each other may adapt their behaviour due to those interaction, given some theoretical simplifications. While rooted in social sciences [9], the field captured some interest from the hard science theorists, who borrowed models and tools for the interdisciplinary field they call *sociophysics* or opinion modelling [1].

After exhausting hopes of physic's "hard-science" reductionist models inspiring correct descriptions of human interactions, the field underwent a shift towards Agent-based models (ABMs) [1], which identify humans as agents following an algorithm to exchange and update information.

Next to defining the domain opinions are drawn from (numerical/categorical, dimensionality), an update rule describing how to adapt held opinions given an interaction is at the core of ABMs. The deGroot model is an established choice, boiling down to interactions leading to averaging of continuous numerical opinions [9]. As perfect averaging eventually makes opinions converge and disregards human biases, other approaches let updates depend on proximity of opinions, which enables polarized stable states (e.g., [10], [5]). While richer dynamics and patterns ensue, it is not trivial how much, if any, practical utility such models offer. Hence, multiple reviews stress the necessity of exercising caution to properly justify the introduction of novel update mechanisms.

Regarding the network structure, most ABMs assume either communication to take place by random chance or place agents in a fixed topology [1]. As a middle-ground, some incorporate homophily (the preference to contact similar agents) by biasing communication rates towards others with similar opinions [5]. Overall, though, contact structures are either seen as fixed or only change as the consequence of social influences. Therefore, models are incapable of deducing

social topologies from first principles per se (i.e., in scenarios without explicit communication).

todo

- Rather, see "opinion" as label for local information connected to edge; "social" as nodes influence each other due to "personal" information.

III. CO-FORMATION GAMES MODEL

This section summarizes the model choices we made for our Co-Formation Games (CFG) after reviewing both NFG and SIM literature.

Firstly, edges are undirected, as communication commonly involves bidirectional information flow [2]. Similarly, unilateral sponsorship suffices for edge creation in the model to account for the fact that communication can be initiated by one party in SIMs. Obviously, there are scenarios which are better covered by alternative choices. Next to intuition, though, undirected and unilateral games are a simple choice, which seemed appropriate given the projects short time frame.

The distance cost function then, following the conventional choice for unilateral, undirected NFGs [7], becomes the negated total distance,

$$c_i^d(G) = \sum_{j \neq i} d_{ij}, \quad (5)$$

with d_{ij} being the shortest pairwise distance. Note that unconnected graphs will suffer infinite costs.

Furthermore, it is worth mentioning that undirected, unilateral NFGs optimal configurations contain only the fully connected and star graphs for positive edge costs $\alpha_c \neq 2$. One goal of our model, then, can be to find new optimal networks.

Let us now regard decisions on opinion dynamics, for which simplicity was an important factor, as choosing a well-understood SIM eases the attribution and understanding of results to stem from CFGs' co-evolution dynamic. We define an opinion to be a real number which, when updated, gets averaged with the neighbours' opinions. This follows the classical deGroot mechanism [9]. While bound to converge, this guarantees stability of the opinion landscape, which is a necessary condition for overall stability in a CFG.

We denote agent i 's opinion as x_i , which then gives the deGroot opinion update as

$$x_i^{\text{new}} = \frac{x_i + \langle x_j \rangle_{K_i}}{2}. \quad (6)$$

where

$$K_i = \{j\}_{d_{ij}=1} \quad (7)$$

is the set of i 's neighbours.

Further, the opinion profile x refers to the collection of all opinions $\{x_i\}_{i=1,\dots,n}$.

To incorporate SIM into the NFG, we introduce an opinion-based cost term

$$c^x(x, G) = \frac{1}{\|K_i\|} \sum_{j \in K_i} |x_i - x_j|. \quad (8)$$

and define the overall cost function to consist out of

$$c_i^{\text{CFG}}(a, x) = c_i^d(G) + c_i^a(a_i) + c_i^x(x, G) \\ = \sum_{j \neq i} d_{ij} + \alpha_a \|a_i\| + \frac{1}{\|K_i\|} \sum_{j \in K_i} |x_i - x_j| \quad (9)$$

for a single agent, and system-wides costs

$$c^{\text{CFG}}(a, x) = \sum_{i=1}^n c_i^{\text{CFG}}(a, x). \quad (10)$$

It follows that nodes have to balance their original NFG goal with the minimisation of neighborhood polarisation.

Note how, whereas distance costs foster sponsorship and edge costs imply sparsity, the opinion term's effect can be ambiguous and context-sensitive. Sometimes dropping a connection to a disagreeing agent may minimise costs, while denser neighborhoods (when dropping a single edge makes little difference) can lead to sponsorships to other agreeing nodes. Also, the probability of a node extending or reducing their sponsorships depends on the network-wide opinion profile x for agents happy to choose any cost-reducing step: If the majority of other agents disagree, there are few worthwhile edges whose creation reduced c_i , and vice versa.

Moreover, considering the case of total opinion convergence $|x_i - x_j| = 0 \forall i, j$ leads to the original NFG costs. This implies

A. Definitions & Equations

TABLE I
LIST OF VARIABLES USED IN THIS DOCUMENT

Variable	Symbol	Domain
Number of nodes	n	$\mathbb{N}$
Node of concern	i	$\{1, \dots, n\}$
Set of i 's neighbours	K_i	$\mathbb{N}^{ K_i }$
Network graph	G	$\{0, 1\}^{n \times n}$
Opinion	x_i	$\mathbb{R}$
Opinion profile	x	$\mathbb{R}^n$
Action	a_i	$\{0, 1\}^n$
Action profile	a	$\{0, 1\}^{n \times n}$
Distance costs	c^d	$\mathbb{Z}^-$
Pairwise distance	d_{ij}	$\mathbb{N}$
Sponsorship costs	c^a	$] - \infty, 0[$
Costs per edge	α_c	$]0, \infty[$
Opinion costs	c^x	$] - \infty, 0[$
Opinion range	α_x	$\mathbb{R}^+$
Set of i 's neighbours	K_i	$\mathbb{N}$
Communication rate	r_c	$]0, \infty[$
Action rate	r_a	$\{0, 1\}$
Convergence threshold	ε	$]0, \alpha_c]$

where a norm $\|\cdot\|$ is the L0 norm, returning the count of non-zero elements.

a) Equations:

- Network expenses:

b) Algorithm:

TABLE II
THE PLANETS OF THE SOLAR SYSTEM AND THEIR AVERAGE DISTANCE FROM THE SUN

Planet	Distance (million km)
Mercury	57.9
Venus	108.2
Earth	149.6
Mars	227.9
Jupiter	778.6
Saturn	1,433.5
Uranus	2,872.5
Neptune	4,495.1

```

1 Initialise  $t = 1, G, a, x, \Delta c$ 
2 while  $(t < t_{\max} \wedge \varepsilon < \Delta c)$ 
3   if  $\text{mod}(t, r_c) = 0$  then
4     select random node  $i$ 
5      $x_i$  arrow.l get opinion update  $x_i^u$ 
6   end if
7   if  $r_f = 1$  then
8     select random node  $i$ 
9      $a_i$  arrow.l get action update  $a_i^u$ 
10  end if
11   $t += 1$ 
12   $c(t)$  arrow.l get new costs  $c_t$ 
13   $\Delta c = c_{t-1} - c(t)$ 
14 end while

```

Algorithm 1. Dynamics of our synchronous move game

IV. INTRODUCTORY EXAMPLES

A. Cost function behaviour

- Copy some of your paper drawings

B. New optimal costs

- Examples of chains vs star

C. Some simulations

V. OLD STUFF FROM THE TEMPLATE



Fig. 1. A circle representing the Sun.

In Fig. 1 you can see a common representation of the Sun, which is a star that is located at the center of the solar system.

In Table II, you see the planets of the solar system and their average distance from the Sun. The distances were calculated with (8) that we presented in

REFERENCES

- [1] P. Sobkowicz, “Whither Now, Opinion Modelers?,” in *Frontiers of Physics*, 2020. [Online]. Available: <https://api.semanticscholar.org/CorpusID:226981914>
- [2] A. Flache *et al.*, “Models of Social Influence: Towards the Next Frontiers,” *J. Artif. Soc. Soc. Simul.*, vol. 20, 2017, [Online]. Available: <https://api.semanticscholar.org/CorpusID:3433103>
- [3] A. Fabrikant, A. Luthra, E. N. Maneva, C. H. Papadimitriou, and S. Shenker, “On a network creation game,” in *ACM SIGACT-SIGOPS Symposium on Principles of Distributed Computing*, 2003. [Online]. Available: <https://api.semanticscholar.org/CorpusID:5263612>
- [4] M. Bullinger, P. Lenzner, and A. Melnichenko, “Network creation with homophilic agents,” *Social Choice and Welfare*, vol. 64, pp. 915–959, 2022, [Online]. Available: <https://api.semanticscholar.org/CorpusID:248476098>
- [5] F. Baumann, P. Lorenz-Spreen, I. M. Sokolov, and M. Starnini, “Modeling echo chambers and polarization dynamics in social networks,” *Physical review letters*, p. 48301, 2019, [Online]. Available: <https://api.semanticscholar.org/CorpusID:195750744>
- [6] A. Nigam *et al.*, “ONE-M: Modeling the Co-evolution of Opinions and Network Connections,” in *ECML/PKDD*, 2018, [Online]. Available: <https://api.semanticscholar.org/CorpusID:51695921>
- [7] D. Parkes and S. Seuken, “Algorithmic economics: A design approach.” Cambridge University Press, UK, 2020.
- [8] D. Bilò and P. Lenzner, “On the Tree Conjecture for the Network Creation Game,” *Theory of Computing Systems*, vol. 64, pp. 422–443, 2017, [Online]. Available: <https://api.semanticscholar.org/CorpusID:3593099>
- [9] M. H. Degroot, “Reaching a Consensus,” *Journal of the American Statistical Association*, vol. 69, pp. 118–121, 1974, [Online]. Available: <https://api.semanticscholar.org/CorpusID:120077293>
- [10] N. E. Friedkin and E. C. Johnsen, “Social Influence Network Theory: A Sociological Examination of Small Group Dynamics,” 2011. [Online]. Available: <https://api.semanticscholar.org/CorpusID:143209972>