1. Can you tell at least 5 common rules of assembly language?
   Five common rules of assembly language include:
   - Syntax: Follow specific syntax for instructions and operands.
   - Labels: Use labels to define locations for instructions and data.
   - Operands: Ensure operands match the expected types and formats.
   - Comments: Use comments to annotate and explain code.
   - Directives: Use directives to control the assembly process and memory allocation.
2. Explain 3 major fields in an instruction: the operation field, the address field and the mode field
   Operation Field: Specifies the operation to be performed.
   Address Field: Contains the address of the operand or data.
   Mode Field: Indicates the addressing mode or how the address should be interpreted.
3. Explain types of micro-operations(Register transfer, Shift, Logic, Arithmetic) with examples.
   Arithmetic Micro-Operations: Perform basic arithmetic operations like addition and subtraction.
   Ex: MOV AL, 5 ;
   ADD AL, 10 ;
   Logic Micro-Operations: Perform logical operations such as AND, OR, and NOT.
   Ex: MOV AL, 0xF0 ;
   MOV BL, 0x0F ;
   AND AL, BL ;
   Shift Micro-Operations: Shift the bits of a register left or right.
   Ex: MOV AL, 0x01 ;
   SHL AL, 1 ;
   Transfer Micro-Operations: Move data from one register to another.
   Ex: MOV AL, 0x55 ;
   MOV BL, AL ;
4. What is a horizontal microcode? Why do we use it?
   Horizontal microcode is a micro coding technique where each microinstruction directly specifies the control signals needed for the operation, allowing for more complex and flexible control but requiring more memory.
5. Explain 3 major types of busses - address, data and control bus with an example.
   a. Data Bus: Transfers data between components.
   b. Address Bus: Carries addresses to locate data in memory.
   c. Control Bus: Sends control signals to manage data transfer and operations.



6. Give one example of the below instructions
   a. Arithmetic instructions.

MOV AL, 5 ;
ADD AL, 10 ;

b. Branch instructions
   JMP label ; Jump to the location marked by 'label'
c. Data transfer instructions
   MOV AL, 25 ; Load the value 25 into the AL register
d. Logic instructions
   MOV AL, 0x0F ;
   AND AL, 0xF0 ;
e. Bit-oriented instructions
   MOV AL, 0x01 ;
   SHL AL, 1 ;