

User Guide

JALoP over BEEP (v1.x)

31 October 2025

This Page is Intentionally Left Blank

Contents

1	JALoPv1.x.....	6
2	Download/Clone Source Code	6
3	Build and Install C Publisher (jald) & C Subscriber (jal_subscribe)	6
3.1	System Provisioning.....	6
3.1.1	Install Rust Dependencies	6
3.1.2	RHEL 7 / CentOS 7	7
3.1.3	RHEL 8 / CentOS 8	8
3.1.4	RHEL 9.....	9
3.2	Build and Install C Publisher & C Subscriber.....	10
3.3	Configure C Publisher	10
3.4	Configure JAL-Local-Store.....	12
3.5	Configure C Subscriber	15
3.6	Configure LMDB (Optional)	18
4	Build and Install BeepCore Java	19
4.1	System Provisioning.....	19
4.2	Clone “beepcore-java” repository from GitHub.....	19
4.3	Install BeepCore Java from pre-built jar files	20
5	Build and Install Java Subscriber and Publisher (jnl_test-*.jar)	20
5.1	Clone “jjnl” repository from GitHub	20
5.2	Build and Install Java Subscriber (jnl_test)	20
5.3	Configure jnl_test-*.jar as a Subscriber.....	21
5.4	Configure jnl_test-*.jar as a Publisher.....	22
6	Run Publisher and Subscriber to Transfer JAL Records	23
6.1	Disable SELinux or set to Permissive (For Testing Only).....	23
6.2	Stop Firewall (For Testing Only)	23
6.3	Start JAL-LOCAL-STORE.....	24
6.4	Insert Records into JAL-Local-Store	24
6.4.1	Insert Log Records	24
6.4.2	Insert Audit Records.....	24
6.4.3	Insert Journal Records.....	24
6.5	Check for Inserted Records in JAL-Local-Store	25
6.6	Start Rust Inline Filter (Recommended)	25

6.7	Start C Publisher	26
6.8	Start Subscriber	26
6.9	Purge Records from Local Store	27
6.10	Run Java Publisher and Java Subscriber	27
6.10.1	Add Records to Java Publisher.....	27
6.10.2	Insert Log Records.....	27
6.10.3	Insert Audit Records	27
6.10.4	Insert Journal Records	27
6.10.5	Check for Java Publisher Records	27
6.10.6	Start Java Publisher.....	27
6.10.7	Start Java Subscriber.....	28
6.11	Run C Publisher (jald) with GDB	28
6.12	Run C Publisher (jald) with Valgrind	28
7	JALoP Data-Taps.....	28
7.1	jalop-coreutils.....	28
7.1.1	Build & Install	28
7.1.2	Run tee and tail	29
7.2	jalop-jalauditd.....	29
7.2.1	Build & Install	29
7.2.2	Configure jalauditd.....	30
7.2.3	Run jalauditd	30
7.3	jalop-rsyslog.....	30
7.3.1	Build & Install	30
7.3.2	Configure omjal plugin	31
7.3.3	Install omjal plugin	32
7.4	jalop-log4cxx.....	33
7.4.1	Build & Install	33
7.4.2	Create, Build & Run a Test Executable	33
7.5	jalop-jaljournald.....	35
7.5.1	Build & Install	35
7.5.2	Configure jaljournald.....	35
7.5.3	Run jaljournald	36

This Page is Intentionally Left Blank

1 JALoPv1.x

JALoPv1.x is JALoP over BEEP. It has a C Publisher/Subscriber, a Java Publisher/Subscriber, and several data-taps. The Publisher usually resides on a CDS system to securely and reliably transfer journal, audit, and log records generated by the CDS to one or more remote Subscribers.

2 Download/Clone Source Code

Create a top-level ‘jalop’ directory to store all JALoP repositories. This will be referred to as <jalop_root> throughout this document.

```
% mkdir jalop
% cd jalop/
```

JALoP Publisher and Subscriber repositories are available on GitHub at this URL – <https://github.com/JALoP>

Clone “JALoP” and “jjnl” repositories using git –

```
% git clone https://github.com/JALoP/JALoP.git
% cd JALoP/
% git checkout -t origin/1.x.x.x

% git clone https://github.com/JALoP/jjnl.git
% cd jjnl/
% git checkout -t origin/1.x.x.x
```

The “jjnl” repository requires Java BEEP Core, which is also available on GitHub.

```
% git clone https://github.com/JALoP/beepcore-java.git
```

Initialize Git Large File storage (LFS) for the JALoP git repo

```
% sudo yum install git-lfs
% cd <jalop_root>/JALoP/
% git lfs install
% git lfs env
% git lfs pull
```

3 Build and Install C Publisher (jald) & C Subscriber (jal_subscribe)

The C Publisher (jald) is the process that negotiates with the Subscriber(s) and sends JAL records to them. This is in “jalop” (or “JALoP” if cloned from GitHub) repository. Clone the repository as mentioned above, if not done yet.

3.1 System Provisioning

3.1.1 Install Rust Dependencies

NOTE: This section can be skipped if the pre-built JALoP-rust-deps-*.rpm are present under <jalop_root>/3rd-party/rust/RHEL{7,8,9}.

JALoP uses Rust and requires the following steps to set up the required dependencies. These steps must be run on a RHEL 9 machine/VM first, with the resulting generated dependency tar.gz files copied to RHEL 7 or RHEL 8 if desired to build on these RHEL versions.

- Install EPEL
 - `$ sudo yum install epel-release # if it is not installed already.`
- Run the following script in <jalop_root>/JALoP/ to package all of the rust dependencies needed on RHEL 7/8/9.
 - `$ cd <jalop_root>/JALoP`
 - `$ sudo sh create_cargo_vendor_files.sh`
- Transfer the resulting “vendor-cargo-<rhel version>.tar.gz” file to the <jalop_root>/JALoP/ dir on the machine running the specific RHEL version of RHEL. Note: This step can be skipped on RHEL 9, as the previous step already generated the RHEL 9 version of the JALoP rust dependencies in <jalop_root>/JALoP/.
- Run the following script in <jalop_root>/JALoP/
 - `$ cd <jalop_root>/JALoP`
 - `$ sudo sh install_cargo_vendor_files.sh`

3.1.2 RHEL 7 / CentOS 7

The following instructions will allow a CentOS 7 minimal install to be provisioned to build and run the JALoP C implementation:

- Install EPEL
 - `$ sudo yum install epel-release`
- Install JALoP dependencies available from repos
 - `$ sudo yum install @development libxml2-devel libconfig-devel libuuid-devel openssl-devel xmlsec1-openssl-devel python2-scons lcov libtool-ltdl-devel doxygen libseccomp-devel systemd-devel libcap-devel libcap-ng-devel lmdb-devel boost-devel`
- Install bundled JALoP dependencies from provided RPMs
 - Navigate into your cloned JALoP repo
 - Install axl RPM
 - `$ sudo yum install 3rd-party/axl/RHEL7/*.x86_64.rpm`
 - Install vortex RPM
 - `$ sudo yum install 3rd-party/vortex/RHEL7/*.x86_64.rpm`
 - Install JALoP Rust dependency RPM (if present)
 - `$ sudo yum install 3rd-party/rust/RHEL7/*.x86_64.rpm`
- Download and install test-dept unit test library.
 - `$ git clone https://github.com/norrby/test-dept.git`
 - `$ cd test-dept`
 - `$ ./bootstrap`
 - `$ ./configure`
 - `$ sudo make install`
- NOTE: axl/vortex build steps below are only needed if these dependencies were not already installed via the provided RPMs in the steps above.
- Build and install axl
 - `$ git clone https://github.com/ASPLes/libaxl.git`
 - `$ cd libaxl`
 - `$ ./autogen.sh`
 - `$ sudo make install`
- Build and install vortex
 - `$ git clone https://github.com/ASPLes/libvortex-1.1.git`

- `$ cd libvortex-1.1`
- `$ ./autogen.sh --disable-{sasl,websocket,xml-rpc,tunnel,pull,http,alive}-support --disable-{py,lua}-vortex --disable-vortex-client`
- `$ sudo make install`

3.1.3 RHEL 8 / CentOS 8

The following instructions will allow a RHEL 8/CentOS Stream 8 minimal install to be provisioned to build and run the JALoP C implementation:

- RHEL 8: Enable CodeReady Builder
 - `$ sudo subscription-manager repos --enable codeready-builder-for-rhel-8-x86_64-rpms`
- CentOS 8: Enable Powertools (unbranded version of RHEL's CodeReady Builder)
 - `$ sudo dnf config-manager --set-enabled powertools`
- Install JALoP dependencies available from repos
 - `$ sudo dnf install @development libxml2-devel libconfig-devel loglibuuid-devel openssl-devel xmlsec1-openssl-devel libtool-ltdl-devel apr-util-devel libcurl-devel doxygen lcov libseccomp-devel systemd-devel libcap-devel libcap-ng-devel lmdb-devel boost-devel`
- Install bundled JALoP dependencies from provided RPMs
 - Navigate into your cloned JALoP repo
 - Install axl RPM
 - `$ sudo yum install 3rd-party/axl/RHEL8/*.x86_64.rpm`
 - Install vortex RPM
 - `$ sudo yum install 3rd-party/vortex/RHEL8/*.x86_64.rpm`
 - Install JALoP Rust dependency RPM (if present)
 - `$ sudo yum install 3rd-party/rust/RHEL8/*.x86_64.rpm`
- Build and install test-dept
 - `$ git clone https://github.com/norrby/test-dept.git`
 - `$ cd test-dept`
 - `$ ./bootstrap`
 - `$ ./configure`
 - `$ sudo make install`
- NOTE: axl/vortex build steps below are only needed if these dependencies were not already installed via the provided RPMs in the steps above.
- Build and install axl
 - `$ git clone https://github.com/ASPLes/libaxl.git`
 - `$ cd libaxl`
 - `$ ./autogen.sh --disable-py-axl`
 - `$ sudo make install`
- Build and install vortex
 - `$ git clone https://github.com/ASPLes/libvortex-1.1.git`
 - `$ cd libvortex-1.1`
 - `$ ./autogen.sh --disable-{sasl,websocket,xml-rpc,tunnel,pull,http,alive}-support --disable-{py,lua}-vortex --disable-vortex-client`
 - `$ sudo make install`
- Install python36-scons
 - `$ sudo yum install python36-scons`
 - `$ sudo pip3 install scons`
- Use python36 as python
 - `$ sudo alternatives --config python`

- Enter the number for the /usr/bin/python36 selection
- Ensure /usr/local/lib is in the dynamic linker path
 - `$ echo /usr/local/lib | sudo tee /etc/ld.so.conf.d/usr-local-lib.conf`
 - `$ sudo ldconfig`

3.1.4 RHEL 9

The following instructions will allow a RHEL 9 minimal install to be provisioned to build and run the JALoP C implementation:

- RHEL 9: Enable CodeReady Builder
 - `$ sudo subscription-manager repos --enable codeready-builder-for-rhel-9-x86_64-rpms`
- Install JALoP dependencies available from repos
 - `$ sudo dnf install @development libxml2-devel libconfig-devel libuuid-devel openssl-devel xmlsec1-openssl-devel libtool-ltdl-devel apr-util-devel libcurl-devel doxygen lcov libseccomp-devel systemd-devel libcap-devel libcap-ng-devel lmbd-devel boost-devel`
- Install bundled JALoP dependencies from provided RPMs
 - Navigate into your cloned JALoP repo
 - Install axl RPM
 - `$ sudo yum install 3rd-party/axl/RHEL9/*.x86_64.rpm`
 - Install vortex RPM
 - `$ sudo yum install 3rd-party/vortex/RHEL9/*.x86_64.rpm`
 - Install JALoP Rust dependency RPM (if present)
 - `$ sudo yum install 3rd-party/rust/RHEL9/*.x86_64.rpm`
- Build and install test-dept
 - `$ git clone https://github.com/norrby/test-dept.git`
 - `$ cd test-dept`
 - `$ ./bootstrap`
 - `$ ./configure`
 - `$ sudo make install`
- NOTE: axl/vortex build steps below are only needed if these dependencies were not already installed via the provided RPMs in the step above.
- Build and install axl
 - `$ git clone https://github.com/ASPLes/libaxl.git`
 - `$ cd libaxl`
 - `$ ./autogen.sh --disable-py-axl`
 - `$ sudo make install`
- Build and install vortex
 - `$ git clone https://github.com/ASPLes/libvortex-1.1.git`
 - `$ cd libvortex-1.1`
 - `$ ./autogen.sh --disable-{sasl,websocket,xml-rpc,tunnel,pull,http,alive}-support --disable-{py,lua}-vortex --disable-vortex-client`
 - `$ sudo make install`
- Install python3-scons
 - `$ sudo yum install python3-scons`
- Ensure /usr/local/lib is in the dynamic linker path
 - `$ echo /usr/local/lib | sudo tee /etc/ld.so.conf.d/usr-local-lib.conf`
 - `$ sudo ldconfig`

3.2 Build and Install C Publisher & C Subscriber

The “jalop” (or “JALoP” if cloned from GitHub) repository builds the following applications –

- “jald” (the JALoP C Publisher)
- “jal-local-store” (the JAL-Local-Store)
- “jaldb_tail”
- “jal_dump”
- “jal_purge”
- “jalp_test” (a test Producer)
- “jal_subscribe” (the JALoP C Subscriber)
- “jaldb_inline_filter” (the JALoP Rust Inline Filter)

It also builds the following shared libraries –

- “libjal-common.so”
- “libjal-db.so”
- “libjal-network.so”
- “libjal-producer.so”
- “libjal-utils.so”

Follow the instructions below to build and install the above-mentioned components -

- Change to the jalop top directory –
 - `% cd <jalop_root>/jalop/` (or, `cd <jalop_root>/JALoP/`, if cloned from github).
- Checkout the “1.x.x.x” branch of jalop (if not already checked out. Check “git branch” output) -
 - `% git checkout 1.x.x.x`
- Clean up jalop -
 - `% scons -c` # to clean up.
- Build jalop and install publisher and subscribers using the LMDB database
 - `% scons`
 - `sudo ./install_rhel_x86_64.sh`

3.3 Configure C Publisher

Make a copy of <jalop_root>/jalop/test-input/jald.cfg and adjust according to your Subscriber’s IP, port, etc. This is to avoid changing the sample configuration file in the git source tree. Here is an example of jald.cfg file –

```
# The path to the private key, used for TLS.
private_key =
"/etc/jalop/TLS_CA_Signed/server/jal_publisher_v1_server.key.pem";

# The path to the public cert, used for TLS.
public_cert =
"/etc/jalop/TLS_CA_Signed/server/jal_publisher_v1_server.cert.pem";

# The file containing the certificates for the remote peers.
```

```

remote_cert_dir =
"/etc/jalop/TLS_CA_Signed/server/jal_publisher_v1_server_trusted_cert
s";

# The path to the root of the database.
db_root = "/var/log/jalop";

# The port the Publisher will listen on.
port = 1234L;

# The IP address (interface) the Publisher will listen on, or 0.0.0.0
to listen on all.
host = "127.0.0.1";

# How long to wait, in seconds, before polling for records after
finding no records
poll_time = 1L;

# file storing PID of jald when daemonized.
#pid_file = "/var/log/jalop/jald-pid.txt";

# Log directory of jald when daemonized.
log_dir = "./";

# A list of supported digest algorithms. These algorithms should be
ordered by preference
# in a single double-quoted string with a space separating the
algorithms.
# Valid values are "sha256", "sha384", and "sha512"
digest_algorithms = "sha256";

# List of allowed Subscriber peer configurations
peers = ( {
    hosts = ("192.168.137.130");
    subscribe_allow = ("journal", "audit", "log");
} );

# seccomp will restrict the jal-local-store process to the defined
system calls.
# When the process is in the setup phase, at startup, it will be
restricted to the
# initial_seccomp_rules, both_seccomp_rules and final_seccomp_rules
system call sets. After the setup phase and before the process
# is doing its routine work, it will be further restricted to only
the both_seccomp_rules and final_seccomp_rules system call set.
enable_seccomp = false;
seccomp_debug = false;
# Use these rules for RHEL8/9
initial_seccomp_rules =
["arch_prctl", "bind", "brk", "execve", "getcwd", "getrlimit", "ioctl", "lis

```

```

ten","lstat","newfstatat","prctl","readlink","sysinfo","seccomp","set
_tid_address","statfs","writev"];
both_seccomp_rules =
["access","clone","clone3","close","epoll_create","fcntl","fstat","fu
tex","getsockname","lseek","mmap","mprotect","munmap","open","read","
rseq","rt_sigaction","rt_sigprocmask","set_robust_list","setsockopt",
"socket","stat","write"];
final_seccomp_rules =
["accept","clock_nanosleep","epoll_ctl","epoll_wait","exit","exit_gro
up","fdatasync","flock","ftruncate","getpeername","getpid","getrandom
","getuid","madvise","nanosleep","openat","poll","pread64","prlimit64
","pwrite64","recvfrom","rt_sigreturn","sched_getaffinity","sched_yie
ld","select","sendto","shutdown"];
# RHEL7 doesn't recognize some of the syscalls that are invoked on
RHEL9 so it is
# necessary to use a variant set of syscalls
#initial_seccomp_rules =
["arch_prctl","bind","brk","execve","getcwd","getrlimit","ioctl","lis
ten","lstat","newfstatat","prctl","readlink","sysinfo","seccomp","set
_tid_address","statfs","writev"];
#both_seccomp_rules =
["access","clone","close","epoll_create","fcntl","fstat","futex","get
sockname","lseek","mmap","mprotect","munmap","open","read","rt_sigact
ion","rt_sigprocmask","set_robust_list","setsockopt","socket","stat",
"write"];
#final_seccomp_rules =
["accept","clock_nanosleep","epoll_ctl","epoll_wait","exit","exit_gro
up","fdatasync","flock","ftruncate","getpeername","getpid","getrandom
","getuid","madvise","nanosleep","openat","poll","pread64","prlimit64
","pwrite64","recvfrom","rt_sigreturn","sched_getaffinity","sched_yie
ld","select","sendto","shutdown"];

filter_socket_basename = "jald filter socket"

```

Check the section “Run the Publisher and Subscriber to Transfer JAL Records” below.

3.4 Configure JAL-Local-Store

The JAL-Local-Store (jal-local-store) is a process that receives and stores JAL Data sent from the JAL Producer applications. It has a Lightning Memory-Mapped Database (LMDB) to store and process the JAL records. The jal-local-store process must be started before the Publisher process (jald).

Make a copy of <jalop_root>/jalop/test-input/local_store.cfg and update accordingly. This is to avoid changing the sample configuration file in the git source tree. Here is an example local store configuration file –

```

# The path to a PEM formatted private key that jal-local-store
# will use to sign all system metadata documents. This is optional.
private_key_file = "/etc/jalop/rsa_key";

```

```

# The path to a PEM formatted certificate file that jal-local-store
# will append to the system metadata document. This is optional.
public_cert_file = "/etc/jalop/cert";

# A UUID in the form "xxxxxxxx-xxxx-xxxx-xxxx-xxxxxxxxxxxx" where
each 'x' is a
# hexadecimal character (0-9a-fA-F). jal-local-store
# will include this in the system metadata document as the HostUUID
element.
# This is required.
system_uuid = "34c90268-57ba-4d4c-a602-bdb30251ec77";

# A friendly name to identify the host. This is added to the system
metadata as
# the Hostname element. This is optional, jal-local-store
# will generate a hostname if it is not included in the configuration
file.
hostname = "test.jalop.com";

# This identifies where jal-local-store should store all the records.
# This is optional and defaults to /var/lib/jalop/db/ .
db_root = "/var/log/jalop";

# The jal-local-store process, at startup, will check if it is
# running under systemd along with a systemd socket unit file
configuration.
# If so, there is no need to define any socket parameters below, they
will be ignored.
# Systemd will create the socket file for jal-local-store.
#
# If there is no systemd socket, jal-local-store will attempt to
create it.
# Enter the file system path where the socket file will be created
# socket_owner and socket_group will default to the user and group
# the jal-local-store process is running as and socket mode will
default to 0666.
socket = "./jal.sock";

# Uncomment to define a socket_owner other than the default (the user
the process is running as)
# The username used must exist on the system.
#socket_owner = "jalls";

# Uncomment to define a socket_group other than the default (the
group the process user belongs to).
# The groupname used must exist on the system.
#socket_group = "jalproducer";

# Uncomment to define socket_mode other than the default (0666).
# This must be a string representing exactly 4 digits.
# Each digit must be in the range of 0-7.

```

```

#socket_mode = "0420";

# example socket file listing after being created
# sr--w----.  1 jalls jalproducer  0 Jan 23 13:15
/var/run/jalop/jal.sock

# run db_recover before opening the DB
db_recover = false;

# Process will cd to / (root directory),fork, and will run as a
daemon.
# When running the process as daemon, and even though the jal-local-
store
# will resolve relative paths for you, it is always safer to use
# absolute paths for configurations in this file that require file
system paths.
daemon = true;

# Generate a signature block within the system metadata of each
record
# This has significant performance implications, and is rarely used
sign_sys_meta = false;

# Embed a digest (a.k.a. Manifest) in the system metadata
# May impact performance
manifest_sys_meta = false;

# Algorithm to use for generating the Manifest
# Available algorithms: sha256, sha384, sha512
sys_meta_dgst_alg = "sha256";

# Flow control functionality turned off if accept_delay_thread_count
set to zero.
# Below are the default values if not set.
#accept_delay_thread_count = 10;
#accept_delay_increment = 100;
#accept_delay_max = 10000000;

# File storing PID of jal-local-store when daemonized.
pid_file = "/var/log/jalop/jls-pid.txt";

# Log directory of jal-local-store when daemonized.
log_dir = "/var/log/jalop";

# seccomp will restrict the jal-local-store process to the defined
system calls.
# When the process is in the setup phase, at startup, it will be
restricted to the
# initial_seccomp_rules and final_seccomp_rules system call sets.
After the setup phase and before the process

```

```
# is doing its routine work, it will be further restricted to only
the final_seccomp_rules system call set.
#
enable_seccomp = false;
seccomp_debug = false;
# Use these rules for RHEL8/9
initial_seccomp_rules =
["arch_prctl", "bind", "capget", "capset", "chdir", "chmod", "chown", "dup2",
"execve", "faccessat2", "flock", "getcwd", "getdents", "getdents64", "geteuid", "getgid", "getrlimit", "ioctl", "listen", "lstat", "prctl", "prlimit64", "readlink", "rename", "seccomp", "select", "set_tid_address", "setsid", "statfs", "sysinfo"];
both_seccomp_rules =
["brk", "newfstatat", "poll", "rseq", "rt_sigaction", "rt_sigprocmask"];
final_seccomp_rules =
["accept", "access", "clone", "clone3", "close", "connect", "exit", "exit_group", "fcntl", "fdatasync", "fstat", "futext", "getpid", "getppid", "getrandom", "getsockopt", "gettid", "getuid", "kill", "lseek", "madvise", "mkdir", "mmap", "mprotect", "munmap", "open", "openat", "pread64", "pselect6", "pwrite64", "read", "recvmsg", "rt_sigreturn", "sched_yield", "sendto", "set_robust_list", "socket", "stat", "unlink", "write"];

# RHEL7 doesn't recognize some of the syscalls that are invoked on
RHEL9 so it is
# necessary to use a variant set of syscalls
#initial_seccomp_rules =
["arch_prctl", "bind", "capget", "capset", "chdir", "chmod", "chown", "dup2",
"execve", "flock", "getcwd", "getdents", "getdents64", "geteuid", "getgid",
"getrlimit", "ioctl", "listen", "lstat", "prctl", "prlimit64", "readlink",
"rename", "seccomp", "select", "set_tid_address", "setsid", "statfs", "sysinfo"];
#both_seccomp_rules =
["brk", "newfstatat", "poll", "rt_sigaction", "rt_sigprocmask"];
#final_seccomp_rules =
["accept", "access", "clone", "close", "connect", "exit", "exit_group", "fcntl", "fdatasync", "fstat", "futext", "getpid", "getppid", "getrandom", "getsockopt", "gettid", "getuid", "kill", "lseek", "madvise", "mkdir", "mmap", "mprotect", "munmap", "open", "openat", "pread64", "pselect6", "pwrite64", "read", "recvmsg", "rt_sigreturn", "sched_yield", "sendto", "set_robust_list", "socket", "stat", "unlink", "write"];
```

3.5 Configure C Subscriber

Make a copy of <jalop_root>/jalop/test-input/jal_subscribe.cfg and update accordingly. This is to avoid changing the sample configuration file in the git source tree. Here is an example C subscriber configuration file –

```
# The path to the private key, used for TLS.
private_key =
"/etc/jalop/TLS_CA_Signed/client/jal_subscriber_v1_client.key.pem";
```

```

# The path to the public cert, used for TLS.
public_cert =
"/etc/jalop/TLS_CA_Signed/client/jal_subscriber_v1_client.cert.pem";

# File containing the certificates for the remote peers.
remote_cert =
"/etc/jalop/TLS_CA_Signed/client/jal_subscriber_v1_client_trusted_cer
ts";

# The path to the root of the database.
db_root = "/var/log/jalop";

# The port to connect on.
port = 1234L;

# The hostname or IP address of the Publisher to subscribe to.
host = "192.168.137.133";

# The supported record types.
data_class = [ "audit", "log", "journal" ];

# Mode to request data in. May be "archive" or "live".
mode = "archive";

# For subscribe, the maximum number of records to send before sending
a 'digest-challenge' message.
pending_digest_max = 1L;

# For subscribe, the maximum number of seconds to wait, before
sending a 'digest-challenge' message.
pending_digest_timeout = 10L;

# The time before jal_subscribe ends (HH:MM:SS). Specify 00:00:00 to
run continuously.
session_timeout = "00:00:00";

# This window size for the beep channels created
# will be set to this number * 1024 (1k)
# Beep recommends a minimal size of 4k
window_size = 4;

# A list of supported digest algorithms. These algorithms should be
ordered by preference
# in a single double-quoted string with a space separating the
algorithms.
# Valid values are "sha256", "sha384", and "sha512"
digest_algorithms = "sha256";

# Specify the threshold size at which a journal resume is
"worthwhile"

```



```

# If a partial journal resume record is found during session init
that exceeds this threshold
# then a journal resume will be performed
# If the partial record is less than this size, the resume will be
skipped and the record will be transferred from scratch.
# The special value 0 means always resume
# Any negative number disables resume entirely
journal_resume_threshold_size = 1048576L; #1024*1024 = 1MB (1,048,576
bytes)

# seccomp will restrict the jal-local-store process to the defined
system calls.
# When the process is in the setup phase, at startup, it will be
restricted to the
# initial_seccomp_rules, both_seccomp_rules and final_seccomp_rules
system call sets. After the setup phase and before the process
# is doing its routine work, it will be further restricted to only
the both_seccomp_rules and final_seccomp_rules system call set.
#
enable_seccomp = false;
seccomp_debug = false;
# Use these rules for RHEL8/9
initial_seccomp_rules =
["access", "arch_prctl", "bind", "brk", "execve", "faccessat2", "flock", "fs
tat", "fstatfs", "getcwd", "lstat", "prctl", "recvmsg", "readlink", "rt_sigp
rocmask", "seccomp", "set_tid_address"]
both_seccomp_rules =
["clone", "clone3", "close", "fcntl", "getpid", "ioctl", "lseek", "mmap", "mp
rotect", "munmap", "newfstatat", "open", "openat", "prlimit64", "read", "rse
q", "rt_sigaction", "set_robust_list", "stat", "write"]
final_seccomp_rules =
["clock_nanosleep", "connect", "epoll_create", "epoll_ctl", "epoll_wait",
"exit", "exit_group", "fdatasync", "fsync", "ftruncate", "futex", "getdents
", "getdents64", "getpeername", "getppid", "getrandom", "getrlimit", "getti
d", "getuid", "getsockname", "madvise", "mkdir", "nanosleep", "poll", "pread
64", "pwrite64", "recvfrom", "rename", "rt_sigreturn", "sched_getaffinity",
"sched_yield", "select", "sendto", "setsockopt", "shutdown", "socket", "sy
sinfo"]
# RHEL7 doesn't recognize some of the syscalls that are invoked on
RHEL9 so it is
# necessary to use a variant set of syscalls
#initial_seccomp_rules =
["access", "arch_prctl", "bind", "brk", "execve", "flock", "fstatfs", "getcw
d", "lstat", "prctl", "recvmsg", "readlink", "rt_sigprocmask", "seccomp", "s
et_tid_address"]
#both_seccomp_rules =
["clone", "close", "fcntl", "fstat", "getpid", "ioctl", "lseek", "mmap", "mpr
otect", "munmap", "newfstatat", "open", "openat", "prlimit64", "read", "rt_s
igaction", "set_robust_list", "stat", "write"]
#final_seccomp_rules =
["clock_nanosleep", "connect", "epoll_create", "epoll_ctl", "epoll_wait",

```

```
"exit","exit_group","fdatasync","fsync","ftruncate","futex","getdents",
,"getdents64","getpeername","getppid","getrandom","getrlimit","gettid",
,"getuid","getsockname","madvise","mkdir","nanosleep","poll","pread",
,"pread64","pwrite64","recvfrom","rename","rt_sigreturn","sched_getaffinity",
,"sched_yield","select","sendto","setsockopt","shutdown","socket","sysinfo"]
```

3.6 Configure LMDB (Optional)

Optionally, a file named LMDB_CONFIG can be placed at the <db_root> directory to override LMDB specific configuration settings. The two configuration settings that can be overridden are database_option and lmbd_map_size. If the LMDB_CONFIG file is not present and/or does not contain these settings, then default values are used. For lmbd_map_size, which sets the maximum allowed size of the lmbd database, the default is 120 gigabytes. For database_option, the default is LMDB performance level 2 (JDB_LMDB_PERFORMANCE_LEVEL2). These settings are global across all JAL applications.

Make a copy of <jalop_root>/jalop/test-input/LMDB_CONFIG into the db root directory (which is the directory specified by the db_root config setting in the local store configuration file) and update accordingly. Here is an example LMDB_CONFIG configuration file:

```
#Valid settings for the database_option config setting are the
following:
#JDB_NONE - No LMDB db flags are set.
#    This is the slowest, but most reliable setting to prevent data
loss or db corruption
#JDB_LMDB_PERFORMANCE_LEVEL1 - Sets MDB_NOMETASYNC
#    Faster than JDB_NONE. No risk of db corruption, but could lose
last transaction.
#JDB_LMDB_PERFORMANCE_LEVEL2 - Sets MDB_NOMETASYNC | MDB_NOSYNC
#    This is the recommended setting and is much faster than
JDB_LMDB_PERFORMANCE_LEVEL1.
#    No risk of db corruption if filesystem preserves write order
otherwise db corruption is possible. Also could lose last
transaction.
#JDB_LMDB_PERFORMANCE_LEVEL3 - Sets MDB_NOMETASYNC | MDB_NOSYNC |
MDB_WRITEMAP | MDB_MAPASYNC
#    WARNING!!! This setting is faster than
JDB_LMDB_PERFORMANCE_LEVEL2
#    However there is a very high risk of db corruption and data
loss in case of a crash or power outage. Also if this setting is
used, all other JAL processes
#    must use this exact same setting. Overall this setting is not
recommended to be used if the risk of db corruption is not
acceptable.
#This is optional and will default to JDB_NONE if not present.
database_option = "JDB_LMDB_PERFORMANCE_LEVEL2";
```

```
#lmbd_map_size is in gigabytes (GB) and is the maximum database size
allowed.

#This value can be increased if lmbd map_full errors are occurring.
Valid values are 1 (1GB) to 25000 (25 TB)

lmbd_map_size = 200
```

4 Build and Install BeepCore Java

4.1 System Provisioning

BeepCore Java is a Java implementation of BEEP (RFC3080 and RFC3081) and is required by JJNL.

Install the following packages (if not done already) –

- Java 8 or newer
- Ant
- Maven

```
% sudo yum install java-1.8.0-openjdk-devel ant maven
```

4.2 Clone “beepcore-java” repository from GitHub

```
% cd <jalop_root>/
% git clone https://github.com/JALoP/beepcore-java.git
```

Build and Install BeepCore JavaBuild –

```
% cd <jalop_root>/beepcore-java/
% ant dist-tgz
```

Install –

```
% cd build/beepcore-0.9.20/lib/
% ./install_jars.sh
```

This should install 3 JAR files to ~/.m2/repository/ as shown in the example output below –

```
[INFO] Installing /home/marefin/jalop/beepcore-java/beepcore.jar to
/home/marefin/.m2/repository/org/beepcore-
java/beepcore/0.9.20/beepcore-0.9.20.jar
```

```
[INFO] Installing /home/marefin/jalop/beepcore-java/beeptls-jsse.jar
to /home/marefin/.m2/repository/org/beepcore-java/beeptls-
jsse/0.9.20/beeptls-jsse-0.9.20.jar
```

```
[INFO] Installing /home/marefin/jalop/beepcore-java/concurrent.jar to
/home/marefin/.m2/repository/EDU/oswego/cs/dl/util/concurrent/1.3.4/co
ncurrent-1.3.4.jar
```

Verify that the 3 JAR files mentioned above are successfully installed; if for some reason those are not installed, manually install (copy) them to intended destination as shown above.

4.3 Install BeepCore Java from pre-built jar files

Extract –

```
% cd <jalop_root>/jjnl/3rd-Party/beepcore-java/0.9.20
% tar -xvzf beepcore-0.9.20.tgz
```

Install –

```
% cd ./beepcore-0.9.20/lib/
% sh ./install_jars.sh
```

This should install 3 JAR files to ~/.m2/repository/ as shown in the example output below –

```
[INFO] Installing /home/marefin/jalop/beepcore-java/beepcore.jar to
/home/marefin/.m2/repository/org/beepcore-
java/beepcore/0.9.20/beepcore-0.9.20.jar
```

```
[INFO] Installing /home/marefin/jalop/beepcore-java/beeptls-jsse.jar
to /home/marefin/.m2/repository/org/beepcore-java/beeptls-
jsse/0.9.20/beeptls-jsse-0.9.20.jar
```

```
[INFO] Installing /home/marefin/jalop/beepcore-java/concurrent.jar to
/home/marefin/.m2/repository/EDU/oswego/cs/dl/util/concurrent/1.3.4/co
ncurrent-1.3.4.jar
```

Verify that the 3 JAR files mentioned above are successfully installed; if for some reason those are not installed, manually install (copy) them to intended destination as shown above.

5 Build and Install Java Subscriber and Publisher (jnl_test-*.jar)

5.1 Clone “jjnl” repository from GitHub

This is the “jjnl” repository. Clone the repository as below (if not done already) –

```
% cd <jalop_root>/
% git clone https://github.com/JALoP/jjnl.git
% cd jjnl
% git checkout -t origin/1.x.x.x
```

5.2 Build and Install Java Subscriber (jnl_test)

- Build -
 - % cd <jalop_root>/jjnl/jnl_parent/
 - % mvn clean
 - % mvn package

- Install (optional) -
 - `% cd <jalop_root>/jjnl/jnl_lib/`
 - `% mvn install`

Note that “jnl_test-*.jar” can be configured and run either as a Subscriber or as a Publisher, as described in the subsequent sections.

5.3 Configure jnl_test-*.jar as a Subscriber

```
% cd <jalop_root>/jjnl/jnl_test/
```

Copy `./src/test/resources/sampleSubscriber.json` here and update accordingly. This is to avoid changing the sample config file in git source tree. If not running with TLS, comment out or remove the “ssl” section below.

An example of `sampleSubscriber.json` given below –

```
{
  "address": "127.0.0.1",
  "port": 8444,
  "subscriber": {
    "sessionTimeout": "00:00:00",
    "dataClass": [ "audit", "log", "journal" ],
    "digestAlgorithms": [ "SHA256", "SHA384", "SHA512" ],
    "pendingDigestMax": 1,
    "pendingDigestTimeout": 120,
    "output": "./output",
    "mode": "archive",
  }
  "ssl": {
    "Key Algorithm": "SunX509",
    "Key Store Passphrase": "changeit",
    "Key Store Data Type": "file",
    "Key Store": "./certs/server.jks",

    "Trust Algorithm": "SunX509",
    "Trust Store Passphrase": "changeit",
    "Trust Store Data Type": "file",
    "Trust Store": "./certs/remotes.jks",
  }
}
```

Check the section “Run the Publisher and Subscriber to Transfer JAL Records” below.

5.4 Configure jnl_test-*.jar as a Publisher

Known Limitation: The jnl_test-*.jar Java Publisher does not support batching of digest-challenge. Therefore, set the batch size (`pendingDigestMax`) to 1 as shown below.

```
{
  "address": "192.168.90.1",
  "port": 1234,
  "configureTLS": "on",
  "listener": {
    "pendingDigestMax": 1,
    "pendingDigestTimeout": 120,
    "input" : "../input",
    "output" : "../output",
    "peers": [
      { "hosts": ["192.168.90.5"],
        "publishAllow": ["audit", "journal", "log"],
        "subscribeAllow": ["audit", "journal", "log"]
      }
    ]
  }
}
"ssl": {
  "Key Algorithm": "SunX509",
  "Key Store Passphrase": "changeit",
  "Key Store Data Type": "file",
  "Key Store":
"./certs/TLS_CA_Signed/server/jal_publisher_v1_server.jks",

  "Trust Algorithm": "SunX509",
  "Trust Store Passphrase": "changeit",
  "Trust Store Data Type": "file",
  "Trust Store":
"./certs/TLS_CA_Signed/server/jal_publisher_v1_server-remotes.jks",
}
}
```

6 Run Publisher and Subscriber to Transfer JAL Records

Follow the steps below to run the C Publisher and Java Subscriber to transfer JAL records.

6.1 Disable SELinux or set to Permissive (For Testing Only)

=====

Permanent: have "SELINUX=disabled" or "SELINUX=permissive" in
"/etc/selinux/config" file, then restart VM.

Temporary: Enter the command "/usr/sbin/setenforce 0"

6.2 Stop Firewall (For Testing Only)

=====

RHEL/CentOS 6.x

Stop: % sudo service iptables stop

Disable: % sudo chkconfig iptables off

```
RHEL/CentOS 7.x, 8.x, 9.x
    Stop: % sudo service firewalld stop
    Or,   % sudo systemctl stop firewalld
    Disable: % sudo systemctl disable firewalld
```

6.3 Start JAL-LOCAL-STORE

```
=====
# May need to clean up the first time. Make sure no jal-local-store is
running. For examples -
$ cd <jalop_root>/jalop/
$ pkill jal-local-store
$ sudo rm -rf ./jal.sock      # remove old JAL socket, if any.
$ sudo rm -rf /root/testdb   # clean up existing <db_root>/ directory.
$ sudo mkdir /root/testdb    # For the first time, create <db_root>/
```

Make a copy of ./test-input/local_store.cfg here and update accordingly. This is to avoid changing the sample configuration file in the git source tree.

```
$ sudo ./release/bin/jal-local-store --debug --no-daemon -c
./local_store.cfg &
```

6.4 Insert Records into JAL-Local-Store

```
$ cd <jalop_root>/jalop/
```

6.4.1 Insert Log Records

```
=====
$ sudo ./release/bin/jalp_test -j ./jal.sock -a ~/jalop/jalop/test-
input/sample2.cfg -p ~/jalop/jalop/test-input/big_payload.txt -n 100 -
t l
```

6.4.2 Insert Audit Records

```
=====
$ sudo ./release/bin/jalp_test -j ./jal.sock -a ~/jalop/jalop/test-
input/sample2.cfg -p ~/jalop/jalop/test-input/big_payload.txt -n 100 -
t a
```

6.4.3 Insert Journal Records

```
=====
$ sudo ./release/bin/jalp_test -j ./jal.sock -a ~/jalop/jalop/test-
input/sample2.cfg -p ~/jalop/jalop/test-input/big_payload.txt -n 100 -
t j
```

Note: Use "-t f" instead of "-t j" if you want JAL Producer to send journal file descriptor through the Unix Domain Socket (instead of the payload bytes) to JAL-Local-Store. Passing file descriptor may perform better for larger journal payloads (e.g., in the order of megabytes).

6.5 Check for Inserted Records in JAL-Local-Store

```
=====
$ sudo ./release/bin/jaldb_tail -n 100 -h /root/testdb/ -t l | wc -l
$ sudo ./release/bin/jaldb_tail -n 100 -h /root/testdb/ -t a | wc -l
$ sudo ./release/bin/jaldb_tail -n 100 -h /root/testdb/ -t j | wc -l
```

Or,

```
$ sudo ./release/bin/jal_purge -h /root/testdb -b 2030-11-11T11:11:11
-x -t l | wc -l
$ sudo ./release/bin/jal_purge -h /root/testdb -b 2030-11-11T11:11:11
-x -t a | wc -l
$ sudo ./release/bin/jal_purge -h /root/testdb -b 2030-11-11T11:11:11
-x -t j | wc -l
```

6.6 Start Rust Inline Filter (Recommended)

```
=====
$ cd <jalop_root>/jalop/
```

NOTE: If verbose logging is desired optionally run the following command below.

```
$ export RUST_LOG=trace
```

```
$ sudo rm -f jald_filter_socket_*
```

```
$ sudo ./release/bin/jaldb_inline_filter -d /var/log/jalop -force -rx-
socket-path ./jald_filter_socket_request -tx-socket-path
./jald_filter_socket
```

Note: If digest batching is being used by any subscriber (pending_digest_max greater than 1 in any subscriber config file), and slow record transfer is experienced when using the jaldb_inline_filter, then the -socket-buffer-size parameter for the inline filter can be increased. The default is 256 which should be adequate for normal use cases. This must be equal or greater than the total of all the pending_digest_max settings of all connected subscribers.

Ex: pending_digest_max is set to 100 for three subscribers, then -socket-buffer-size must be set to 300 or higher. If slow record transfer is experienced, this number can be increased further.

```
sudo ./release/bin/jaldb_inline_filter -d /var/log/jalop -force -rx-
socket-path ./jald_filter_socket_request -tx-socket-path
./jald_filter_socket -socket-buffer-size 300
```

Enter “./release/bin/jaldb_inline_filter -h” for help.

6.7 Start C Publisher

```
=====
$ cd <jalop_root>/jalop/
```

Make a copy of ./test-input/jald.cfg here and update accordingly. This is to avoid changing the sample configuration file in the git source tree.

```
$ sudo ./release/bin/jald -f -d -c ./jald.cfg --no-daemon 2>&1 | tee publisher.log
```

NOTE: To run jald without using the inline filter use the following command below instead (no -f option). It is not recommended to run jald publisher without the inline filter.

```
$ sudo ./release/bin/jald -d -c ./jald.cfg --no-daemon 2>&1 | tee publisher.log
```

Enter "man jald" for help.

6.8 Start Subscriber

```
=====
Java subscriber (jnl_test)
=====
$ cd <jalop_root>/jjnl/jnl_test/
```

Make a copy of ./jnl_test/target/test-classes/sampleHttpSubscriber.json here and update accordingly. This is to avoid changing the sample configuration file in the git source tree.

```
java -jar target/jnl_test-1.1.0.1.jar ./sampleSubscriber.json 2>&1 | tee subscriber.log
```

```
=====
or C subscriber (jal_subscribe)
=====
$ cd <jalop_root>/jalop
```

Make a copy of ./test-input/jal_subscribe.cfg here and update accordingly. This is to avoid changing the sample configuration file in the git source tree. If running on same machine as publisher, you need to specify a different location for the database. The publisher and subscriber need to use separate databases.

```
sudo ./release/bin/jal_subscribe -d -c ./jal_subscribe.cfg 2>&1 | tee subscriber.log
```

Enter "man jal_subscribe" for help.

6.9 Purge Records from Local Store

```
=====
$ sudo ./release/bin/jal_purge -h ./testdb/ -d -f -c -b 2030-11-
11T11:11:11 -t l
$ sudo ./release/bin/jal_purge -h ./testdb/ -d -f -c -b 2030-11-
11T11:11:11 -t a
$ sudo ./release/bin/jal_purge -h ./testdb/ -d -f -c -b 2030-11-
11T11:11:11 -t j
```

OR,

```
$ now=$(date -u "+%Y-%m-%dT%H:%M:%S.%N")
$ sudo ./release/bin/jal_purge -h ./testdb/ -d -f -c -b "$now" -t l
$ sudo ./release/bin/jal_purge -h ./testdb/ -d -f -c -b "$now" -t a
$ sudo ./release/bin/jal_purge -h ./testdb/ -d -f -c -b "$now" -t j
```

6.10 Run Java Publisher and Java Subscriber

=====

Follow the steps below to run the Java Publisher and Java Subscriber to transfer JAL records.

6.10.1 Add Records to Java Publisher.

```
$ cd <jjnl_root>/
$ mkdir input
```

6.10.2 Insert Log Records

=====

```
$ python generate_records.py log input/ 100 ~/jalop/jalop/test-
input/sample2.cfg ~/jalop/jalop/test-input/big_payload.txt
```

6.10.3 Insert Audit Records

=====

```
$ python generate_records.py audit input/ 100 ~/jalop/jalop/test-
input/sample2.cfg ~/jalop/jalop/test-input/big_payload.txt
```

6.10.4 Insert Journal Records

=====

```
$ python generate_records.py journal input/ 100 ~/jalop/jalop/test-
input/sample2.cfg ~/jalop/jalop/test-input/big_payload.txt
```

6.10.5 Check for Java Publisher Records

=====

```
$ ls <jjnl_root>/input/audit
$ ls <jjnl_root>/input/journal
$ ls <jjnl_root>/input/log
```

6.10.6 Start Java Publisher

=====

```
$ cd <jjnl_root>/jnl_test/
```

Make a copy of `./src/test/resources/sampleListener.json` here and update accordingly. This is to avoid changing the sample configuration file in the git source tree.

```
$ java -jar jnl_test-1.1.01.jar sampleListener.json
```

6.10.7 Start Java Subscriber

```
=====
```

```
$ cd <jalop_root>/jjnl/jnl_test/
```

Make a copy of `./jnl_test/target/test-classes/sampleSubscriber.json` here and update accordingly. This is to avoid changing the sample configuration file in the git source tree.

```
java -jar target/jnl_test-1.1.0.1.jar ./sampleSubscriber.json 2>&1 | tee subscriber.log
```

6.11 Run C Publisher (jald) with GDB

```
=====
```

```
$ export LD_LIBRARY_PATH="/home/marefin/jalop/jalop/debug/lib/"  
$ gdb -ex=r --args ./debug/bin/jald -d -c ./jald.cfg --no-daemon
```

6.12 Run C Publisher (jald) with Valgrind

```
=====
```

```
$ valgrind --tool=memcheck --leak-check=full --verbose --track-origins=yes --log-file=valgrind_out.txt ./debug/bin/jald -d -c ./jald.cfg --no-daemon
```

7 JALoP Data-Taps

The JALoP data-taps capture and send JAL records to the JALoP Local Store (`jal-local-store`). Each data-tap depends on JALoP libraries, so JALoP v1 or v2 libraries must be build and installed prior to building a data-tap repository. Generally, each of the data-taps requires the JALoP `socket` and `db_root` addresses that `jal-local-store` (JLS) uses. Note that `jal-local-store` must be already running for any data-tap to send JAL records to it via the `socket`.

7.1 jalop-coreutils

Available on IntelLink and JALoP development Git Server.

This has the JALoP version of GNU `tail` and GNU `tee` commands.

7.1.1 Build & Install

```
% cd <jalop_root>/jalop-coreutils/  
% autoreconf -fiv #for RHEL7  
% ./bootstrap --skip-po #for RHEL8/RHEL9  
% ./configure --disable-gcc-warnings  
% make -j
```

```
% make check
% [[ -e /tmp/install ]] || mkdir /tmp/install
% make install DESTDIR=/tmp/install
% cp /tmp/install/usr/local/bin/{tee,tail} /usr/local/bin
```

7.1.2 Run tee and tail

Note that the `jal-local-store (JLS)` process must be running already to receive and insert records.

```
# Based on <db_root> location, user may need 'sudo' in the
following instructions.

% echo "This is a test message to tee into JLS" | tee -j --
path=<path to JALoP socket> --schema-root=<path to JALoP schema
directory>
% echo -e "Test message1\nTest message2" > file_to_tail
$ tail -j --path=<path to JALoP socket> --schema-root=<path to
JALoP schema directory> ./file_to_tail
```

Use `jaldb_tail` to check for newly inserted records -

```
% jaldb_tail -t 1 -h <db_root>
```

Use `jal_dump` to verify that the log records came from auditd -

```
% jal_dump -u <UUID found using jaldb_tail> -h <db_root> -t 1 -d
z
```

7.2 jalop-jalauditd

Available on the NCDSMO IntelLink site and JALoP development Git Server. This is also available at [GitHub.com/JALoP/JALoP-Auditd-Plugin](https://github.com/JALoP/JALoP-Auditd-Plugin).

7.2.1 Build & Install

Note that JALoP v1 or v2 must be built and installed before attempting to build this data tap.

```
% cd <jalop_root>/jalop-jalauditd (or JALoP-Auditd-Plugin)
% make clean
% make
% sudo make install
```

This shall install the followings –

- The binary `/sbin/jalauditd` (or `/usr/sbin/jalauditd`)
- The configuration files for RHEL7 and RHEL8/RHEL9 go into different directories. Make install will install the configuration files in the following locations and will need to be copied to appropriate directory:
 - `/etc/jalauditd/jalauditd.conf`
 - `/etc/audit/plugins.d/audisp-jalauditd.conf`
- For RHEL7 the configuration files should be:
 - `/etc/audisp/jalauditd.conf`
 - `/etc/audisp/plugins.d/audisp-jalauditd.conf`

- For RHEL8/RHEL9 the configuration files should be:
 - `/etc/jalauditd/jalauditd.conf`
 - `/etc/audit/plugins.d/audisp-jalauditd.conf`
- The `jalauditd.conf` file is initially empty; you will need to edit this file, see below.

7.2.2 Configure jalauditd

The configuration file `jalauditd.conf` is initially empty. There can be 4 settings in this file as shown below.

```
socket = "/path/to/jalop/socket";
schemas = "/path/to/schemas/root";
keypath = "/path/to/key";
certpath = "/path/to/cert";
```

If the `socket` and `schemas` locations are not specified above, default locations specified by the JAL Producer Library (JPL) will be used. Below are the default socket and schemas locations –

```
socket = "/var/run/jalop/jalop.sock"
schemas = "/usr/share/jalop/schemas"
```

If `keypath` or `certpath` are not specified, no key or cert will be used for signing.

IMPORTANT: These settings must be consistent with the `jal-local-store` configuration file.

7.2.3 Run jalauditd

Note that the `jal-local-store` (JLS) process must run to receive and insert records sent by `jalauditd` via the socket.

Restarting (as root or sudo) `auditd` automatically runs the `jalauditd` child process.

```
% service auditd restart (or, systemctl restart auditd)
```

Use `jaldb_tail` to check for newly inserted records -

```
% sudo jaldb_tail -f -t 1 -h <db_root>
```

Use `jal_dump` to verify that the log records came from `auditd` -

```
% sudo jal_dump -u <UUID found using jaldb_tail> -h <db_root> -t 1
-d z
```

See `<jalop_root>/jalop-jalauditd/README` file for more details.

7.3 jalop-rsyslog

Available on IntelLink and JALoP development Git Server.

7.3.1 Build & Install

Note that JALoP must be built and installed before attempting to build the rsyslog plugin.

```
$ sudo yum install git automake libtool libestr-devel
```

If you have access to a libfastjson-devel package, you can install that and skip to **Error! Reference source not found.**

```
$ sudo yum install libfastjson-devel
```

7.3.1.1 *Libfastjson headers*

If you cannot install libfastjson-devel, the libfastjson headers must be made available to the rsyslog plugin in another way.

```
$ git clone https://github.com/rsyslog/libfastjson.git
$ cd libfastjson
$ sudo mkdir /usr/include/libfastjson
$ sudo cp ./*.h /usr/include/libfastjson
$ sudo ln -s /usr/lib64/libfastjson.so.4
/usr/lib64/libfastjson.so
```

On RHEL 7 / CentOS 7:

```
$ export JSON_C_FLAGS="-g"
$ export JSON_C_LIBS="/usr/lib64/libfastjson.so"
```

On RHEL 8 / CentOS Stream 8:

```
$ export LIBFASTJSON_CFLAGS="-g"
$ export LIBFASTJSON_LIBS="/usr/lib64/libfastjson.so"
```

7.3.1.2 *Build omjal plugin*

Build the omjal plugin:

```
$ cd jalop-rsyslogd
$ export CPPFLAGS="-I/usr/include/libfastjson"
$ sh autogen.sh
$ make
```

7.3.2 *Configure omjal plugin*

Add the following configuration section to `/etc/rsyslog.conf`:

```
$ModLoad omjal # calls JAL for rsyslog pass through to JALoP
$ActionOmjalSocket /var/run/jalop/jalop.sock
$ActionOmjalSchemas /usr/share/jalop/schemas
$ActionOmjalKey <path_to_key> # Optional
$ActionOmjalCert <path_to_key> # Optional
*. * :omjal:
```

`$ModLoad omjal`

States that the omjal plugin shall be loaded

`$ActionOmjalSocket /var/run/jalop/jalop.sock`

Specifies the socket to be used to forward the messages to the JALoP local store. If this option is omitted from the file, it will use the default value specified in the JALoP library.

`$ActionOmjalSchemas /usr/share/jalop/schemas`

Specifies the directory where the schema information is located. If this option is omitted from the file, it will use the default value specified in the JALoP library.

`$ActionOmjalKey <path_to_key>`

Specifies the path to the key to be used for signing. If this option is omitted from the file, then no key will be used.

`$ActionOmjalCert <path_to_key>`

Specifies the path to the certificate to be used for signing. If this option is omitted from the file, then no certificate will be used.

`*.* :omjal;;logJAL`

`<msg_filter_expression>:<output_module>:<parameters>;<template_name>`

`*.*` specifies that all messages will be sent to this module. If, for example, you wanted to handle mail messages, `mail.*` would handle that.

See <https://www.rsyslog.com/doc/v8-stable/configuration/filters.html> for more information.

7.3.3 Install omjal plugin

Install the omjal plugin:

```
$ cd jalop-rsyslogd
$ make install
```

The rsyslog package installs libraries to `/usr/lib64/rsyslog`. If your environment uses a different location, either manually copy the library from `.libs/omjal.so` or change the `libdir` flag in `autogen.sh`

After installation, and after starting the ***jal-local-store***, restart the rsyslog service:

```
$ sudo systemctl restart rsyslog
```

To ensure that rsyslogd is connecting to jal-local-store, you can run jal-local-store with the debug (`-d`) flag. When jal-local-store is ready, the message `Thread_count: 1` will appear. After rsyslogd is connected, the message `Thread_count: 2` will appear.

To create messages in rsyslogd, the logger command can be used. For example:

```
logger "This is your message content."
```

Use `jaldb_tail` to check for newly inserted records -

```
% sudo jaldb_tail -f -t 1 -h <db_root>
```

Use `jal_dump` to verify that the log records came from auditd -


```
% sudo jal_dump -u <UUID found using jaldb_tail> -h <db_root> -t  
l -d z
```

7.4 jalop-log4cxx

Available on IntelLink and JALoP development Git Server.

7.4.1 Build & Install

Note that JALoP must be built and installed before attempting to build the jalop-log4cxx library.

```
$ sudo yum install apr-util-devel
```

On RHEL 7 / CentOS 7:

```
$ sudo yum install cmake3  
$ sudo yum install centos-release-scl  
$ sudo yum install devtoolset-8-gcc-c++ --  
enablerepo='centos-sclo-rh'  
$ sudo scl enable devtoolset-8 'bash'
```

On RHEL 8 / CentOS 8/ RHEL 9:

```
$ sudo yum install cmake
```

Build the library:

On RHEL 7 / CentOS 7:

```
$ cd jalop-log4cxx  
$ cmake3 -D CMAKE_CXX_COMPILER=/opt/rh/devtoolset-  
8/root/usr/bin/g++ -D CMAKE_INSTALL_PREFIX=/usr CMakeLists.txt  
$ make
```

On RHEL 8 / CentOS 8 / RHEL 9:

```
$ cd jalop-log4cxx  
$ cmake -D CMAKE_INSTALL_PREFIX=/usr CMakeLists.txt  
$ make
```

Install the library:

```
$ sudo make install
```

To uninstall the library:

```
$ sudo make uninstall
```

7.4.2 Create, Build & Run a Test Executable

An example test executable is created during the CMake build at /path/to/jalop-log4cxx/src/examples/cpp/jalp-appender. To test using this executable, skip ahead to the instructions on starting the jal_local_store and running the executable.

To create a new test executable, do the following:

Create a separate folder for the test executable. This can be separate from the jalop-log4cxx folder:

```
$ mkdir ~/log4cxx-test
$ cd ~/log4cxx-test
```

Copy required files from jalop-log4cxx:

```
$ cp /path/to/jalop-log4cxx/src/main/cpp/jalpappender.cpp .
```

Create a main.cpp for the text executable. Use the following as an example:

```
#include <log4cxx/logger.h>
#include <log4cxx/propertyconfigurator.h>
#include <log4cxx/jalpappender.h>

using namespace log4cxx;

LoggerPtr logger(Logger::getLogger("Test"));

int main(int argc, char **argv)
{
    PropertyConfigurator::configure(argv[1]);
    LOG4CXX_INFO(logger, "qwerty")
    return 0;
}
```

Build the test executable:

```
$ g++ main.cpp jalpappender.cpp -llog4cxx -ljaval-producer -o
log4cxx-test
```

Create a configuration file for the test executable. Use the following as a starting point:

```
log4j.rootLogger=DEBUG,A1

log4j.appender.A1=org.apache.log4j.JalpAppender

log4j.appender.A1.layout=org.apache.log4j.PatternLayout
log4j.appender.A1.layout.ConversionPattern=%-4r [%t] %-5p %c %x -
%m%n
```

The following are optional parameters than can be added to the log4cxx config file:

After starting the ***jal-local-store***, run the test executable:

```
$ ./log4cxx-test path/to/test.cfg
```

This will send one record to jal-local-store before closing the connection. Verify the record with the following:

```
$ jaldb_tail -h /path/to/testdb -t 1 -d a
```

```
log4j.appender.A1.PATH - The path to jalop.sock
log4j.appender.A1.HOSTNAME - The hostname of the machine that the
JALoP local store is on
log4j.appender.A1.APPNAME - The name of the process that is logging
data
log4j.appender.A1.SCHEMA_ROOT - The path to the JALoP schemas
log4j.appender.A1.KEY_PATH - The path to the RSA key used for signing
log4j.appender.A1.CERT_PATH - The path to the Certificate used for
signing
```

This will print the app metadata for the records. The record inserted by the test executable does not create a payload from the string in LOG4CXX_INFO. It ends up in the message tag in the app metadata.

7.5 jalop-jaljournalld

Available on NCDSMO IntelLink site and JALoP development GitLab Server.

7.5.1 Build & Install

Dependencies: JALoP v1 or v2 shared libraries must be built and installed.

- /usr/lib64/<jalop shared object files>
- /usr/include/<jalop headers>
- systemd-devel rpm

```
% cd <jalop_root>/jalop-jaljournalld
% make clean
% make
% sudo make install
```

This shall install the followings –

- The binary /bin/jaljournalld
- The jaljournalld configuration file /etc/jalop/jaljournalld.cfg. This file initially has some default values; you will need to edit this file, see below.

7.5.2 Configure jaljournalld

The jalauditd configuration file /etc/jalauditd/jalauditd.conf initially has some default values; The settings in this file as shown below.

```
# verbose logging
debug = false;

# Start collecting logs from head, boot, or tail. Default: tail
# head: will get all journal logs available from multiple boots
```

```

#         and then continuously poll to get all logs as they arrive
# boot: will get all logs from current boot and then continuously
#         poll to get all logs as they arrive.
# tail: will continuously poll to get all logs as they arrive.
init_point = "tail";

# collect all journal fields. Default: MESSAGE only
metadata = false;

# socket path that jal-local-store will be listening.
socket = "/path/to/jalop/socket";

# jalop schema path
schemas = "/path/to/schemas/root";

# hostname to record in log
hostname = "localhost";

# appname to record in log
appname = "jalop-journald";

# poll delay between checking for new journal logs
# in milliseconds 1000 = 1 second
delay = 1000;

```

If the `socket` and `schema_path` locations are not specified above, default locations specified by the JAL Producer Library (JPL) will be used. Below are the default `socket` and `schema_path` locations –

```

socket = "/var/run/jalop/jalop.sock"
schema_path = "/usr/share/jalop/schemas"

```

IMPORTANT: These settings must be consistent with the `jal-local-store` configuration file.

7.5.3 Run `jaljournald`

Note that the `jal-local-store` (JLS) process must run to receive and insert records sent by `jaljournald` via the `socket`. Also, make sure the `jal-local-store` `socket` path matches the `jaljournald` `socket` path and you have write permissions on that `socket` path.

Example command-line

```
% jaljournald -c <path-to-config> --debug --metadata
```

Use `jaldb_tail` to check for newly inserted records -

```
% sudo jaldb_tail -f -t 1 -h <db_root>
```

Use `jal_dump` to verify that the log records came from `journald` -

```
% sudo jal_dump -u <UUID found using jaldb_tail> -h <db_root> -t 1
-d z
```