JAMES FRANCIS E D EGUZMAN

Getting Ready for the Stack Simulator

CC104 – Data Structures | Answered Guide Questions

1. Match each job to the correct technology.

a. Defines the heading, input, and buttons: **HTML**

b. Sets the custom block width to 50px: **CSS**

c. Supplies btn-success and bg-primary: **Bootstrap**

d. Stores the values and implements push(): **JavaScript Stack class**

e. Selects #stack and inserts visible blocks: **jQuery**

2. What does #stack select? Does the starter Push button have an id?

Answer: #stack selects the element with id="stack", which is the stack display container. No, the starter Push button does not have an id attribute.

3. After all four insertion statements run, write the displayed values from top to bottom and give the stack size. Which value would Pop remove first?

Answer: The displayed values from top to bottom are **400, 300, 200, 100**. The stack size is **4**. Pop would remove **400** first because a stack follows Last In, First Out (LIFO).

4. Does the visible 500 prove that the program has performed Pop? Explain.

Answer: No. The 500 is already written in the HTML as a sample block in the “Deleted from Stack” area. No pop() call placed it there, and 500 is not one of the four values stored in the stack.

5. Write one question about connecting the input or buttons to the stack that you want answered during the demonstration.

Answer: How can we connect the Push button to the stack so it adds the value typed in the input box?