

Indicators of Network Attacks

- DDoS
 - High network bandwidth utilization
 - Inbound traffic
 - Can't access network service
 - Website
 - Cloud
 - Servers
 - Can't access Network
 - Overloaded network appliances
 - DDoS attacks can be used to crash firewalls and IDS/IPS
- DNS attacks
 - Domain Takeover/Hijacking
 - Domain Spoofing/Poisoning
 - Static DNS Entries
 - Static DNS set for Network Adapter in Windows
 - `hosts` file
 - `resolv.conf` file
 - Poisoned DNS Cache
 - `ipconfig /all`
 - `ipconfig /displaydns`
- Wireless
 - Poor network performance over wifi
 - Unauthorized devices on network
 - Check list of connected hosts using admin console
 - Changes to AP/Router settings
 - SSID
 - Password/PSK
 - DNS
 - Firewall rules
 - Inability to connect to wifi
 - Disassociation and/or Deauthentication attack
 - Jamming
 - Rogue APs and/or Evil Twins
 - Unusual requests for network creds
- MiTM/On-Path
 - Anything strange with SSL/TLS
 - Warnings
 - Mismatch
 - Check cert for the site in question for oddities
 - Unexpected login prompts
 - Strange emails
 - Responses to emails you never sent
 - Odd responses to emails you did send
 - Unexpected SMS Verifications
- Credential Replay

- Unexpected account lockouts
 - Attacker might be trying to reuse creds repeatedly, tripping a logout
- Unusual login activity
 - Email notifications that a new login has occurred
 - Email contains details such as
 - Device Type
 - OS
 - IP
 - Geolocation
 - Login time
- Suspicious Account Changes
 - Phone numbers
 - Backup accounts
 - Signed-In Devices
- Malicious Code
 - Known C2 Traffic
 - Data Exfiltration