

ITP20003 Java Programming

Array

(Chapter 7)

This slide is primary taken from the instructor's resource of Java: Introduction to Problem Solving and Programming, 7th ed. by Savitch and then edited partly by Shin Hong

Creating and Accessing Arrays


- An array is a special kind of object
- Think of as collection of variables of same type
- Creating an array with 7 variables of type double

```
double[] temperature = new double[7];
```

- To access an element use
 - The name of the array
 - An index number enclosed in braces
- Array indices begin at zero

Creating and Accessing Arrays

- Figure 7.1 A common way to visualize an array



- Note [sample program](#), listing 7.1
class ArrayOfTemperatures

```

import java.util.Scanner;
public class ArrayOfTemperatures
{
    public static void main (String [] args)
    {
        double[] temperature = null ;

        temperature = new double [7];

        System.out.println(temperature[0]) ;

        Scanner keyboard = new Scanner (System.in);
        System.out.println ("Enter 7 temperatures:");
        double sum = 0;
        for (int index = 0 ; index < 7 ; index++)
        {
            temperature [index] = keyboard.nextDouble ();
            sum = sum + temperature [index];
        }
        double average = sum / 7;
        System.out.println ("The average temperature is " + average);
        System.out.println ("The temperatures are");
        for (int index = 0 ; index < 7 ; index++)
        {
            if (temperature [index] < average)
                System.out.println (temperature [index] + " below average.");
            else if (temperature [index] > average)
                System.out.println (temperature [index] + " above average.");
            else //temperature[index] == average
                System.out.println (temperature [index] + " the average.");
        }
        System.out.println ("Have a nice week.");
    }
}

```

Creating and Accessing Arrays

Enter 7 temperatures:

32

30

25.7

26

34

31.5

29

The average temperature is 29.7428

The temperatures are

32.0 above average

30.0 above average

25.7 below average

26.0 below average

34.0 above average

31.5 above average

29.0 below average

Have a nice week.

Sample
screen
output

Array Details

- Syntax for declaring an array with **new**

```
Base_Type[] Array_Name = new Base_Type[Length];
```

- The number of elements in an array is its length
- The type of the array elements is the array's base type

Square Brackets with Arrays

- With a data type when declaring an array

```
int [ ] pressure;
```

- To enclose an integer expression to declare the length of the array


```
pressure = new int [100];
```

- To name an indexed value of the array

```
pressure[3] =  
keyboard.nextInt();
```

Array Details

- Figure 7.2 Array terminology



The Instance Variable **length**

- As an object an array has only one public instance variable
 - Variable **length**
 - Contains number of elements in the array
 - It is final, value cannot be changed
- Note [revised code](#), listing 7.2
class ArrayOfTemperatures2

More About Array Indices

- Index of first array element is 0
- Last valid Index is **arrayName.length - 1**
- Array indices must be within bounds to be valid
 - When program tries to access outside bounds, run time error occurs
- OK to "waste" element 0
 - Program easier to manage and understand
 - Yet, get used to using index 0

Initializing Arrays

- Possible to initialize at declaration time

```
double[] reading = {3.3, 15.8, 9.7};
```

- Also may use normal assignment statements
 - One at a time
 - In a loop

```
int[] count = new int[100];  
for (int i = 0; i < 100; i++)  
    count[i] = 0;
```

Indexed Variables as Method Arguments

- Indexed variable of an array
 - Example ... **a[i]**
 - Can be used anywhere variable of array base type can be used
- View [program](#) using indexed variable as an argument, listing 7.5
class ArgumentDemo

Entire Arrays as Arguments

- Note – array parameter in a method heading does not specify the length
 - An array of any length can be passed to the method
 - Inside the method, elements of the array can be changed
- When you pass the entire array, do not use square brackets in the actual parameter

Arguments for Method main

- Recall heading of method **main**
public static void main (String[] args)
- This declares an array
 - Formal parameter named **args**
 - Its base type is **String**
- Thus possible to pass to the run of a program multiple strings
 - These can then be used by the program

Array Assignment and Equality

- Arrays are objects
 - Assignment and equality operators behave (misbehave) as specified in previous chapter
- Variable for the array object contains memory address of the object
 - Assignment operator **=** copies this address
 - Equality operator **==** tests whether two arrays are stored in same place in memory

Gotcha – Don't Exceed Array Bounds

- The code below fails if the user enters a number like 4. Use input validation.

```
Scanner kbd = new Scanner(System.in);
int[] count = {0,0,0,0};

System.out.println("Enter ten numbers between 0 and 3.");
for (int i = 0; i < 10; i++)
{
    int num = kbd.nextInt();
    count[num]++;
}
for (int i = 0; i < count.length; i++)
    System.out.println("You entered " + count[i] + " " + i + "'s");
```


Gotcha – Creating an Array of Objects

- When you create an array of objects Java does not create instances of any of the objects! For example, consider the code:

```
SalesAssociate[] team = new SalesAssociate[10];
```

- We can't access team[0] yet; it is **null**. First we must create references to an object:

```
team[0] = new SalesAssociate("Jane Doe", 5000);  
team[1] = new SalesAssociate("John Doe", 5000);
```

- we can now access team[0].getName() or team[1].getSalary()

Methods that Return Arrays

- A Java method may return an array
- View [example program](#), listing 7.7
class ReturnArrayDemo
- Note definition of return type as an array
- To return the array value
 - Declare a local array
 - Use that identifier in the **return** statement

```

import java.util.Scanner;

public class ReturnArrayDemo {
    public static void main (String [] args) {
        Scanner keyboard = new Scanner (System.in);

        System.out.println ("Enter your score on exam 1:");

        int firstScore = keyboard.nextInt ();

        int [] nextScore = new int [3];
        for (int i = 0 ; i < nextScores.length ; i++)
            nextScore [i] = firstScore + 5 * i;

        double [] averageScore = getArrayOfAverages (firstScore, nextScores);
        for (int i = 0 ; i < nextScore.length ; i++)
        {
            System.out.println ("If your score on exam 2 is " + nextScore [i]);
            System.out.println ("your average will be " + averageScore [i]);
        }
    }

    public static double [] getArrayOfAverages (int firstScore, int [] nextScores)
    {
        double [] temp = new double [nextScores.length];
        for (int i = 0 ; i < temp.length ; i++)
            temp [i] = getAverage (firstScore, nextScores[i]);
        return temp;
    }

    public static double getAverage (int n1, int n2)
    {
        return (n1 + n2) / 2.0;
    }
}


```

Partially Filled Arrays

- Array size specified at definition
- Not all elements of the array might receive values
 - This is termed a *partially filled array*
- Programmer must keep track of how much of array is used

Partially Filled Arrays

- Figure 7.4 A partially filled array



Sorting, Searching Arrays: Outline


- Selection Sort
- Other Sorting Algorithms
- Searching an Array

Selection Sort

- Consider arranging all elements of an array so they are ascending order
- Algorithm is to step through the array
 - Place smallest element in index 0
 - Swap elements as needed to accomplish this
- Called an interchange sorting algorithm


Selection Sort

- Figure 7.5a



Selection Sort

- Figure 7.5b



Selection Sort

- Algorithm for selection sort of an array

```
for (index = 0; index < a.length - 1; index++)  
{// Place the correct value in a[index]:  
    indexOfNextSmallest = the index of the smallest value among  
                           a[index], a[index+1], ..., a[a.length - 1]  
    Interchange the values of a[index] and a[indexOfNextSmallest].  
    // Assertion: a[0] <= a[1] <= ... <= a[index] and these  
    // are the smallest of the original array elements.  
    // The remaining positions contain the rest of the  
    // original array elements.  
}
```

Selection Sort

- View [implementation](#) of selection sort, listing 7.10
class ArraySorter
- View [demo program](#), listing 7.11
class SelectionSortDemo

```
Array values before sorting:  
7 5 11 2 16 4 18 14 12 30  
Array values after sorting:  
2 4 5 7 11 12 14 16 18 30
```

Sample
screen
output

Other Sorting Algorithms

- Selection sort is simplest
 - But it is very inefficient for large arrays
- Java Class Library provides for efficient sorting
 - Has a class called Arrays
 - Class has multiple versions of a sort method

Searching an Array

- Method used in **OneWayNoRepeatsList** is sequential search
 - Looks in order from first to last
 - Good for unsorted arrays
- Search ends when
 - Item is found ... or ...
 - End of list is reached
- If list is sorted, use more efficient searches