

Array and Collection Classes

Array and Collections

Overview

- Arrays
 - Working with arrays
 - Java API support for arrays
- Collection classes
 - Types of collection
 - Working with Collections

Java Arrays – The Basics

- Declaring an array

```
int[] myArray;  
int[] myArray = new int[5];  
String[] stringArray = new String[10];  
String[] strings = new String[] {"one", "two"};
```

- Checking an arrays length

```
int arrayLength = myArray.length;
```

- Looping over an array

```
for(int I=0; I<myArray.length; i++)  
{  
    String s = myArray[i];  
}
```

Java Arrays – Bounds Checking

- Bounds checking

- Java does this automatically. Impossible to go beyond the end of an array (unlike C/C++)
- Automatically generates an `ArrayIndexOutOfBoundsException`

Java Arrays – Copying

- Don't copy arrays “by hand” by looping over the array
- The System class has an `arrayCopy` method to do this efficiently

```
int array1[] = new int[10];
int array2[] = new int[10];
//assume we add items to array1

//copy array1 into array2
System.arraycopy(array1, 0, array2, 0, 10);
//copy last 5 elements in array1 into first 5 of array2
System.arraycopy(array1, 5, array2, 0, 5);
```

Java Arrays – Sorting

- Again no need to do this “by hand”.
- The `java.util.Arrays` class has methods to sort different kinds of arrays

```
int myArray[] = new int[] {5, 4, 3, 2, 1};
java.util.Arrays.sort(myArray);
//myArray now holds 1, 2, 3, 4, 5
```

Multidimensional Array Declaration

```
int[][] x; //Valid  
int [][]x; //Valid  
int x[][]; //Valid  
int[] []x; //Valid  
int[] x[]; //Valid  
int[] []x[]; //Valid  
int[][] []x; //Valid  
int[][][] x[]; //Valid  
int[] []x[]; //Valid  
...  
...
```

```
int[] a,b; //a->1 b->1  
  
int[] a[],b; //a->2 b->1  
  
int[] a[],b[]; //a->b->2  
  
int[] []a,b; //a->b->2  
  
int[] []a,b[]; //a->2 b->3  
  
int[] []a,[]b; // Error  
  
int[] []a,[]b,[]c; // Error
```

Java Arrays

- Advantages
 - Very efficient, quick to access and add to
 - Type-safe, can only add items that match the declared type of the array
- Disadvantages
 - Fixed size, some overhead in copying/resizing
 - Can't tell how many items in the array, just how large it was declared to be
 - Limited functionality, need more general functionality

Java Collections

- The **Collection in Java** is a framework that provides an architecture to store and manipulate the group of objects.
- Java Collections can achieve all the operations that you perform on a data such as searching, sorting, insertion, manipulation, and deletion.
- Java Collection means a single unit of objects. Java Collection framework provides many interfaces (Set, List, Queue, Deque) and classes (ArrayList, Vector, LinkedList, PriorityQueue, LinkedHashSet, TreeSet).

Java Collections


- **What is a framework in Java**
- It provides readymade architecture.
- It represents a set of classes and interfaces.
- It is optional.

Java Collections


- **What is Collection framework**
- The Collection framework represents a unified architecture for storing and manipulating a group of objects. It has:
 1. Interfaces and its implementations, i.e., classes
 2. Algorithm

Java Collections

- **Hierarchy of Collection Framework**
- Let us see the hierarchy of Collection framework. The **java.util** package contains all the classes and interfaces for the Collection framework.



Interfaces in Collection Framework



Java Collections

- The Collection interface is the interface which is implemented by all the classes in the collection framework. It declares the methods that every collection will have. In other words, we can say that the Collection interface builds the foundation on which the collection framework depends.

• Methods of Collection interface

- There are many methods declared in the Collection interface. They are as follows:

No.	Method	Description
1	public boolean add(E e)	It is used to insert an element in this collection.
2	public boolean addAll(Collection<? extends E> c)	It is used to insert the specified collection elements in the invoking collection.
3	public boolean remove(Object element)	It is used to delete an element from the collection.
4	public boolean removeAll(Collection<?> c)	It is used to delete all the elements of the specified collection from the invoking collection.
5	default boolean removeIf(Predicate<? super E> filter)	It is used to delete all the elements of the collection that satisfy the specified predicate.
6	public boolean retainAll(Collection<?> c)	It is used to delete all the elements of invoking collection except the specified collection.

7	public int size()	It returns the total number of elements in the collection.
8	public void clear()	It removes the total number of elements from the collection.
9	public boolean contains(Object element)	It is used to search an element.
10	public boolean containsAll(Collection<?> c)	It is used to search the specified collection in the collection.
11	public Iterator iterator()	It returns an iterator.
12	public Object[] toArray()	It converts collection into array.
13	public <T> T[] toArray(T[] a)	It converts collection into array. Here, the runtime type of the returned array is that of the specified array.
14	public boolean isEmpty()	It checks if collection is empty.

15	default Stream<E> parallelStream()	It returns a possibly parallel Stream with the collection as its source.
16	default Stream<E> stream()	It returns a sequential Stream with the collection as its source.
17	default Spliterator<E> spliterator()	It generates a Spliterator over the specified elements in the collection.
18	public boolean equals(Object element)	It matches two collections.
19	public int hashCode()	It returns the hash code number of the collection.

Iterator interface

- Iterator interface provides the facility of iterating the elements in a forward direction only.

No.	Method	Description
1	public boolean hasNext()	It returns true if the iterator has more elements otherwise it returns false.
2	public Object next()	It returns the element and moves the cursor pointer to the next element.
3	public void remove()	It removes the last elements returned by the iterator. It is less used.

Iterable Interface

- The Iterable interface is the root interface for all the collection classes. The Collection interface extends the Iterable interface and therefore all the subclasses of Collection interface also implement the Iterable interface.
- It contains only one abstract method. i.e.,
- `Iterator<T> iterator()`
- It returns the iterator over the elements of type T.

Java List

- **List** in Java provides the facility to maintain the *ordered collection*. It contains the index-based methods to insert, update, delete and search the elements. It can have the duplicate elements also. We can also store the null elements in the list.
- The List interface is found in the `java.util` package and inherits the Collection interface.
- The implementation classes of List interface are ArrayList, LinkedList, Stack and Vector. The ArrayList and LinkedList are widely used in Java programming. The Vector class is deprecated since Java 5.

Java List

- **List** in Java provides the facility to maintain the *ordered collection*. It contains the index-based methods to insert, update, delete and search the elements. It can have the duplicate elements also. We can also store the null elements in the list.
- The List interface is found in the `java.util` package and inherits the Collection interface.
- It is a factory of ListIterator interface. Through the ListIterator, we can iterate the list in forward and backward directions.
- The implementation classes of List interface are ArrayList, LinkedList, Stack and Vector. The ArrayList and LinkedList are widely used in Java programming. The Vector class is deprecated since Java 5.

Java List Methods

void add(int index, E element)	It is used to insert the specified element at the specified position in a list.
boolean add(E e)	It is used to append the specified element at the end of a list.
boolean addAll(Collection<? extends E> c)	It is used to append all of the elements in the specified collection to the end of a list.
boolean addAll(int index, Collection<? extends E> c)	It is used to append all the elements in the specified collection, starting at the specified position of the list.
void clear()	It is used to remove all of the elements from this list.
boolean equals(Object o)	It is used to compare the specified object with the elements of a list.

int hashCode()	It is used to return the hash code value for a list.
E get(int index)	It is used to fetch the element from the particular position of the list.
boolean isEmpty()	It returns true if the list is empty, otherwise false.
int lastIndexOf(Object o)	It is used to return the index in this list of the last occurrence of the specified element, or -1 if the list does not contain this element.
Object[] toArray()	It is used to return an array containing all of the elements in this list in the correct order.
<T> T[] toArray(T[] a)	It is used to return an array containing all of the elements in this list in the correct order.

boolean contains(Object o)	It returns true if the list contains the specified element
boolean containsAll(Collection<?> c)	It returns true if the list contains all the specified element
int indexOf(Object o)	It is used to return the index in this list of the first occurrence of the specified element, or -1 if the List does not contain this element.
E remove(int index)	It is used to remove the element present at the specified position in the list.
boolean remove(Object o)	It is used to remove the first occurrence of the specified element.
boolean removeAll(Collection<?> c)	It is used to remove all the elements from the list.
void replaceAll(UnaryOperator<E> operator)	It is used to replace all the elements from the list with the specified element.
void retainAll(Collection<?> c)	It is used to retain all the elements in the list that are present in the specified collection.
E set(int index, E element)	It is used to replace the specified element in the list, present at the specified position.

Java List Methods

void sort(Comparator<? super E> c)	It is used to sort the elements of the list on the basis of specified comparator.
Splitterator<E> spliterator()	It is used to create spliterator over the elements in a list.
List<E> subList(int fromIndex, int toIndex)	It is used to fetch all the elements lies within the given range.
int size()	It is used to return the number of elements present in the list.

How to create List

The ArrayList and LinkedList classes provide the implementation of List interface.
Let's see the examples to create the List:

```
//Creating a List of type String using ArrayList  
List<String> list=new ArrayList<String>();
```

```
//Creating a List of type Integer using ArrayList  
List<Integer> list=new ArrayList<Integer>();
```

Java List Example

```
import java.util.*;  
public class ListExample1{  
public static void main(String args[]){  
    //Creating a List  
    List<String> list=new ArrayList<String>();  
    //Adding elements in the List  
    list.add("Mango");  
    list.add("Apple");  
    list.add("Banana");  
    list.add("Grapes");  
    //Iterating the List element using for-each loop  
    for(String fruit:list)  
        System.out.println(fruit);  
}
```

```
Mango  
Apple  
Banana  
Grapes  
Press any key to continue . . .
```

Get and Set Element in List

```
import java.util.*;
public class ListExample2{
    public static void main(String args[]){
        //Creating a List
        List<String> list=new ArrayList<String>();
        //Adding elements in the List
        list.add("Mango");
        list.add("Apple");
        list.add("Banana");
        list.add("Grapes");
        //accessing the element
        System.out.println("Returning element: "+list.get(1));
        //changing the element
        list.set(1,"Dates");
        //Iterating the List element using for-each loop
        for(String fruit:list)
            System.out.println(fruit);
    }
}
```

```
Returning element: Apple
Mango
Dates
Banana
Grapes
Press any key to continue . . .
```

```
import java.util.*;
class Book {
    int id;
    String name,author,publisher;
    int quantity;
    public Book(int id, String name, String author, String publisher, int quantity) {
        this.id = id;
        this.name = name;
        this.author = author;
        this.publisher = publisher;
        this.quantity = quantity;
    }
}
public class ListExample5 {
    public static void main(String[] args) {
        //Creating list of Books
        List<Book> list=new ArrayList<Book>();
        //Creating Books
        Book b1=new Book(101,"Let us C","Yashwant Kanetkar","BPB",8);
        Book b2=new Book(102,"Data Communications and Networking","Forouzan","Mc Graw Hill",4);
        Book b3=new Book(103,"Operating System","Galvin","Wiley",6);
        //Adding Books to list
        list.add(b1);
        list.add(b2);
        list.add(b3);
        //Traversing list
        for(Book b:list){
            System.out.println(b.id+" "+b.name+" "+b.author+" "+b.publisher+" "+b.quantity);
        }
    }
}
```

Java ArrayList

- Java ArrayList class uses a dynamic array for storing the elements. It is like an array, but there is no size limit. We can add or remove elements anytime. So, it is much more flexible than the traditional array. It is found in the `java.util` package.
- The ArrayList in Java can have the duplicate elements also. It implements the List interface so we can use all the methods of the List interface here.

Java ArrayList

- The important points about the Java ArrayList class are:
- Java ArrayList class can contain duplicate elements.
- Java ArrayList class maintains insertion order.
- Java ArrayList class is non synchronized.
- Java ArrayList allows random access because the array works on an index basis.
- In ArrayList, manipulation is a little bit slower than the LinkedList in Java because a lot of shifting needs to occur if any element is removed from the array list.
- We can not create an array list of the primitive types, such as int, float, char, etc. It is required to use the required wrapper class in such cases. For example:
- `ArrayList<int> al = ArrayList<int>(); // does not work`
- `ArrayList<Integer> al = new ArrayList<Integer>(); // works fine`

Methods of ArrayList

<code>void add(int index, E element)</code>	It is used to insert the specified element at the specified position in a list.
<code>boolean add(E e)</code>	It is used to append the specified element at the end of a list.
<code>boolean addAll(Collection<? extends E> c)</code>	It is used to append all of the elements in the specified collection to the end of this list, in the order that they are returned by the specified collection's iterator.
<code>boolean addAll(int index, Collection<? extends E> c)</code>	It is used to append all the elements in the specified collection, starting at the specified position of the list.
<code>void clear()</code>	It is used to remove all of the elements from this list.
<code>void ensureCapacity(int requiredCapacity)</code>	It is used to enhance the capacity of an ArrayList instance.
<code>E get(int index)</code>	It is used to fetch the element from the particular position of the list.
<code>boolean isEmpty()</code>	It returns true if the list is empty, otherwise false.

<code>int lastIndexOf(Object o)</code>	It is used to return the index in this list of the last occurrence of the specified element, or -1 if the list does not contain this element.
<code>Object[] toArray()</code>	It is used to return an array containing all of the elements in this list in the correct order.
<code><T> T[] toArray(T[] a)</code>	It is used to return an array containing all of the elements in this list in the correct order.
<code>Object clone()</code>	It is used to return a shallow copy of an ArrayList.
<code>boolean contains(Object o)</code>	It returns true if the list contains the specified element.
<code>int indexOf(Object o)</code>	It is used to return the index in this list of the first occurrence of the specified element, or -1 if the List does not contain this element.
<code>E remove(int index)</code>	It is used to remove the element present at the specified position in the list.
<code>boolean remove(Object o)</code>	It is used to remove the first occurrence of the specified element.
<code>boolean removeAll(Collection<?> c)</code>	It is used to remove all the elements from the list.

boolean removeIf(Predicate<? super E> filter)	It is used to remove all the elements from the list that satisfies the given predicate.
protected void removeRange(int fromIndex, int toIndex)	It is used to remove all the elements lies within the given range.
void replaceAll(UnaryOperator<E> operator)	It is used to replace all the elements from the list with the specified element.
void retainAll(Collection<?> c)	It is used to retain all the elements in the list that are present in the specified collection.
E set(int index, E element)	It is used to replace the specified element in the list, present at the specified position.
void sort(Comparator<? super E> c)	It is used to sort the elements of the list on the basis of the specified comparator.
Spliterator<E> spliterator()	It is used to create a spliterator over the elements in a list.
List<E> subList(int fromIndex, int toIndex)	It is used to fetch all the elements that lies within the given range.

Methods of ArrayList

int size()	It is used to return the number of elements present in the list.
void trimToSize()	It is used to trim the capacity of this ArrayList instance to be the list's current size.

Java ArrayList Example

```
import java.util.*;
public class ArrayListExample1{
public static void main(String args[]){
    ArrayList<String> list=new ArrayList<String>(); //Creating arraylist
    list.add("Mango"); //Adding object in arraylist
    list.add("Apple");
    list.add("Banana");
    list.add("Grapes");
    //Printing the arraylist object
    System.out.println(list);
}
}
```

Iterating ArrayList using Iterator

```
import java.util.*;
public class ArrayListExample2{
public static void main(String args[]){
    ArrayList<String> list=new ArrayList<String>(); //Creating arraylist
    list.add("Mango"); //Adding object in arraylist
    list.add("Apple");
    list.add("Banana");
    list.add("Grapes");
    //Traversing list through Iterator
    Iterator itr=list.iterator(); //getting the Iterator
    while(itr.hasNext()){//check if iterator has the elements
        System.out.println(itr.next()); //printing the element and move to next
    }
}
}
```

Java LinkedList class

- Java LinkedList class uses a doubly linked list to store the elements. It provides a linked-list data structure.
- **The important points about Java LinkedList are:**
 - Java LinkedList class can contain duplicate elements.
 - Java LinkedList class maintains insertion order.
 - In Java LinkedList class, manipulation is fast because no shifting needs to occur.
 - Java LinkedList class can be used as a list, stack or queue.

Methods of Java LinkedList

Method	Description
boolean add(E e)	It is used to append the specified element to the end of a list.
void add(int index, E element)	It is used to insert the specified element at the specified position index in a list.
boolean addAll(Collection<? extends E> c)	It is used to append all of the elements in the specified collection to the end of this list, in the order that they are returned by the specified collection's iterator.
boolean addAll(Collection<? extends E> c)	It is used to append all of the elements in the specified collection to the end of this list, in the order that they are returned by the specified collection's iterator.
boolean addAll(int index, Collection<? extends E> c)	It is used to append all the elements in the specified collection, starting at the specified position of the list.
void addFirst(E e)	It is used to insert the given element at the beginning of a list.
void addLast(E e)	It is used to append the given element to the end of a list.
void clear()	It is used to remove all the elements from a list.
Object clone()	It is used to return a shallow copy of an ArrayList.
boolean contains(Object o)	It is used to return true if a list contains a specified element.
Iterator<E> descendingIterator()	It is used to return an iterator over the elements in a deque in reverse sequential order.

E element()	It is used to retrieve the first element of a list.
E get(int index)	It is used to return the element at the specified position in a list.
E getFirst()	It is used to return the first element in a list.
E getLast()	It is used to return the last element in a list.
int indexOf(Object o)	It is used to return the index in a list of the first occurrence of the specified element, or -1 if the list does not contain any element.
int lastIndexOf(Object o)	It is used to return the index in a list of the last occurrence of the specified element, or -1 if the list does not contain any element.
ListIterator<E> listIterator(int index)	It is used to return a list-iterator of the elements in proper sequence, starting at the specified position in the list.
boolean offer(E e)	It adds the specified element as the last element of a list.
boolean offerFirst(E e)	It inserts the specified element at the front of a list.
boolean offerLast(E e)	It inserts the specified element at the end of a list.
E peek()	It retrieves the first element of a list

E peekFirst()	It retrieves the first element of a list or returns null if a list is empty.
E peekLast()	It retrieves the last element of a list or returns null if a list is empty.
E poll()	It retrieves and removes the first element of a list.
E pollFirst()	It retrieves and removes the first element of a list, or returns null if a list is empty.
E pollLast()	It retrieves and removes the last element of a list, or returns null if a list is empty.
E pop()	It pops an element from the stack represented by a list.
void push(E e)	It pushes an element onto the stack represented by a list.
E remove()	It is used to retrieve and removes the first element of a list.
E remove(int index)	It is used to remove the element at the specified position in a list.
boolean remove(Object o)	It is used to remove the first occurrence of the specified element in a list.
E removeFirst()	It removes and returns the first element from a list.
boolean removeFirstOccurrence(Object o)	It is used to remove the first occurrence of the specified element in a list (when traversing the list from head to tail).
E removeLast()	It removes and returns the last element from a list.

Methods of Java LinkedList

boolean removeLastOccurrence(Object o)	It removes the last occurrence of the specified element in a list (when traversing the list from head to tail).
E set(int index, E element)	It replaces the element at the specified position in a list with the specified element.
Object[] toArray()	It is used to return an array containing all the elements in a list in proper sequence (from first to the last element).
<T> T[] toArray(T[] a)	It returns an array containing all the elements in the proper sequence (from first to the last element); the runtime type of the returned array is that of the specified array.
int size()	It is used to return the number of elements in a list.

Java LinkedList Example

```
import java.util.*;
public class LinkedList1{
    public static void main(String args[]){
        LinkedList<String> al=new LinkedList<String>();
        al.add("Ravi");
        al.add("Vijay");
        al.add("Ravi");
        al.add("Ajay");

        Iterator<String> itr=al.iterator();
        while(itr.hasNext()){
            System.out.println(itr.next());
        }
    }
}
```

```
import java.util.*;
public class LinkedList2{
    public static void main(String args[]){
        LinkedList<String> ll=new LinkedList<String>();
        System.out.println("Initial list of elements: "+ll);
        ll.add("Ravi");
        ll.add("Vijay");
        ll.add("Ajay");
        System.out.println("After invoking add(E e) method: "+ll);
        //Adding an element at the specific position
        ll.add(1, "Gaurav");
        System.out.println("After invoking add(int index, E element) method: "+ll);
        LinkedList<String> ll2=new LinkedList<String>();
        ll2.add("Sonoo");
        ll2.add("Hanumat");
        //Adding second list elements to the first list
        ll.addAll(ll2);
        System.out.println("After invoking addAll(Collection<? extends E> c) method: "+ll);
        LinkedList<String> ll3=new LinkedList<String>();
        ll3.add("John");
        ll3.add("Rahul");
        //Adding second list elements to the first list at specific position
        ll.addAll(1, ll3);
        System.out.println("After invoking addAll(int index, Collection<? extends E> c) method: "+ll);
        //Adding an element at the first position
        ll.addFirst("Lokesh");
        System.out.println("After invoking addFirst(E e) method: "+ll);
        //Adding an element at the last position
        ll.addLast("Harsh");
        System.out.println("After invoking addLast(E e) method: "+ll);
    }
}
```

Java LinkedList Example

```
Initial list of elements: []
After invoking add(E e) method: [Ravi, Vijay, Ajay]
After invoking add(int index, E element) method: [Ravi, Gaurav, Vijay, Ajay]
After invoking addAll(Collection<? extends E> c) method: [Ravi, Gaurav, Vijay, Ajay, Sonoo, Hanumat]
After invoking addAll(int index, Collection<? extends E> c) method: [Ravi, John, Rahul, Gaurav, Vijay, Ajay, Sonoo, Hanumat]
After invoking addFirst(E e) method: [Lokesh, Ravi, John, Rahul, Gaurav, Vijay, Ajay, Sonoo, Hanumat]
After invoking addLast(E e) method: [Lokesh, Ravi, John, Rahul, Gaurav, Vijay, Ajay, Sonoo, Hanumat, Harsh]
Press any key to continue . . . ■
```

Java Deque interface

- Java Deque Interface is a linear collection that supports element insertion and removal at both ends. Deque is an acronym for "double ended queue".

Methods of Java Deque Interface

Method	Description
boolean add(object)	It is used to insert the specified element into this deque and return true upon success.
boolean offer(object)	It is used to insert the specified element into this deque.
Object remove()	It is used to retrieves and removes the head of this deque.
Object poll()	It is used to retrieves and removes the head of this deque, or returns null if this deque is empty.
Object element()	It is used to retrieves, but does not remove, the head of this deque.
Object peek()	It is used to retrieves, but does not remove, the head of this deque, or returns null if this deque is empty.

ArrayDeque class

- The ArrayDeque class provides the facility of using deque and resizable-array.
- The important points about ArrayDeque class are:
 - Unlike Queue, we can add or remove elements from both sides.
 - Null elements are not allowed in the ArrayDeque.
 - ArrayDeque has no capacity restrictions.
 - ArrayDeque is faster than LinkedList and Stack.

Java ArrayDeque Example

```
import java.util.*;
public class ArrayDequeExample {
    public static void main(String[] args) {
        //Creating Deque and adding elements
        Deque<String> deque = new ArrayDeque<String>();
        deque.add("Ravi");
        deque.add("Vijay");
        deque.add("Ajay");
        //Traversing elements
        for (String str : deque) {
            System.out.println(str);
        }
    }
}
```

Java ArrayDeque Example

```
import java.util.*;
public class DequeExample {
public static void main(String[] args) {
    Deque<String> deque=new ArrayDeque<String>();
    deque.offer("arvind");
    deque.offer("vimal");
    deque.add("mukul");
    deque.offerFirst("jai");
    System.out.println("After offerFirst Traversal..."); jai
    for(String s:deque) {
        System.out.println(s);
    }
    //deque.poll();
    //deque.pollFirst(); //it is same as poll()
    deque.pollLast();
    System.out.println("After pollLast() Traversal..."); jai
    for(String s:deque) {
        System.out.println(s);
    }
}
}
```

After offerFirst Traversal...
jai
arvind
vimal
mukul
After pollLast() Traversal...
jai
arvind
vimal

Java HashSet

- Java HashSet class is used to create a collection that uses a hash table for storage. It implements Set interface.
- The important points about Java HashSet class are:
 - HashSet stores the elements by using a mechanism called hashing.
 - HashSet contains unique elements only.
 - HashSet allows null value.
 - HashSet doesn't maintain the insertion order. Here, elements are inserted on the basis of their hashCode.
 - HashSet is the best approach for search operations.

Methods of Java HashSet class

SN	Modifier & Type	Method	Description
1)	boolean	<code>add(E e)</code>	It is used to add the specified element to this set if it is not already present.
2)	void	<code>clear()</code>	It is used to remove all of the elements from the set.
3)	object	<code>clone()</code>	It is used to return a shallow copy of this HashSet instance: the elements themselves are not cloned.
4)	boolean	<code>contains(Object o)</code>	It is used to return true if this set contains the specified element.
5)	boolean	<code>isEmpty()</code>	It is used to return true if this set contains no elements.
6)	Iterator<E>	<code>iterator()</code>	It is used to return an iterator over the elements in this set.
7)	boolean	<code>remove(Object o)</code>	It is used to remove the specified element from this set if it is present.
8)	int	<code>size()</code>	It is used to return the number of elements in the set.
9)	Spliterator<E>	<code>spliterator()</code>	It is used to create a late-binding and fail-fast Spliterator over the elements in the set.

Java HashSet Example

```
import java.util.*;
class HashSet1{
    public static void main(String args[]){
        //Creating HashSet and adding elements
        HashSet<String> set=new HashSet();
        set.add("One");
        set.add("Two");
        set.add("Three");
        set.add("Four");
        set.add("Five");
        Iterator<String> i=set.iterator();
        while(i.hasNext())
        {
            System.out.println(i.next());
        }
    }
}
```

Java HashSet Example

```
import java.util.*;
class HashSet3{
    public static void main(String args[]){
        HashSet<String> set=new HashSet<String>();
        set.add("Ravi");
        set.add("Vijay");
        set.add("Arun");
        set.add("Sumit");
        System.out.println("An initial list of elements: "+set);
        //Removing specific element from HashSet
        set.remove("Ravi");
        System.out.println("After invoking remove(object) method: "+set);

        set.removeIf(str->str.contains("Vijay"));
        System.out.println("After invoking removeIf() method: "+set);
        //Removing all the elements available in the set
        set.clear();
        System.out.println("After invoking clear() method: "+set);
    }
}
An initial list of elements: [Vijay, Ravi, Arun, Sumit]
After invoking remove(object) method: [Vijay, Arun, Sumit]
After invoking removeIf() method: [Arun, Sumit]
After invoking clear() method: []
Press any key to continue . . .
```

Java TreeSet class

- The important points about Java TreeSet class are:
- Java TreeSet class contains unique elements only like HashSet.
- Java TreeSet class access and retrieval times are quiet fast.
- Java TreeSet class doesn't allow null element.
- Java TreeSet class is non synchronized.
- Java TreeSet class maintains ascending order.

Methods of Java TreeSet class

Method	Description
boolean add(E e)	It is used to add the specified element to this set if it is not already present.
boolean addAll(Collection<? extends E> c)	It is used to add all of the elements in the specified collection to this set.
E ceiling(E e)	It returns the equal or closest greatest element of the specified element from the set, or null there is no such element.
Comparator<? super E> comparator()	It returns comparator that arranged elements in order.
Iterator descendingIterator()	It is used iterate the elements in descending order.
NavigableSet descendingSet()	It returns the elements in reverse order.
E floor(E e)	It returns the equal or closest least element of the specified element from the set, or null there is no such element.
SortedSet headSet(E toElement)	It returns the group of elements that are less than the specified element.

NavigableSet headSet(E toElement, boolean inclusive)	It returns the group of elements that are less than or equal to(if, inclusive is true) the specified element.
E higher(E e)	It returns the closest greatest element of the specified element from the set, or null there is no such element.
Iterator iterator()	It is used to iterate the elements in ascending order.
E lower(E e)	It returns the closest least element of the specified element from the set, or null there is no such element.
E pollFirst()	It is used to retrieve and remove the lowest(first) element.
E pollLast()	It is used to retrieve and remove the highest(last) element.
Spliterator spliterator()	It is used to create a late-binding and fail-fast spliterator over the elements.
NavigableSet subSet(E fromElement, boolean fromInclusive, E toElement, boolean toInclusive)	It returns a set of elements that lie between the given range.

SortedSet subSet(E fromElement, E toElement))	It returns a set of elements that lie between the given range which includes fromElement and excludes toElement.
SortedSet tailSet(E fromElement)	It returns a set of elements that are greater than or equal to the specified element.
NavigableSet tailSet(E fromElement, boolean inclusive)	It returns a set of elements that are greater than or equal to (if, inclusive is true) the specified element.
boolean contains(Object o)	It returns true if this set contains the specified element.
boolean isEmpty()	It returns true if this set contains no elements.
boolean remove(Object o)	It is used to remove the specified element from this set if it is present.
void clear()	It is used to remove all of the elements from this set.
Object clone()	It returns a shallow copy of this TreeSet instance.
E first()	It returns the first (lowest) element currently in this sorted set.
E last()	It returns the last (highest) element currently in this sorted set.
int size()	It returns the number of elements in this set.

Java TreeSet Examples

```

import java.util.*;
class TreeSet1{
    public static void main(String args[]){
        //Creating and adding elements
        TreeSet<String> al=new TreeSet<String>();
        al.add("Ravi");
        al.add("Vijay");
        al.add("Ravi");
        al.add("Ajay");
        //Traversing elements
        Iterator<String> itr=al.iterator();
        while(itr.hasNext()){
            System.out.println(itr.next());
        }
    }
}

```

Java TreeSet Examples

```
import java.util.*;
class TreeSet3{
    public static void main(String args[]){
        TreeSet<Integer> set=new TreeSet<Integer>();
        set.add(24);
        set.add(66);
        set.add(12);
        set.add(15);
        System.out.println("Highest Value: "+set.pollFirst());
        System.out.println("Lowest Value: "+set.pollLast());
    }
}
```

```
Highest Value: 12
Lowest Value: 66
```

```
import java.util.*;
class TreeSet4{
    public static void main(String args[]){
        TreeSet<String> set=new TreeSet<String>();
        set.add("A");
        set.add("B");
        set.add("C");
        set.add("D");
        set.add("E");
        System.out.println("Initial Set: "+set);

        System.out.println("Reverse Set: "+set.descendingSet());

        System.out.println("Head Set: "+set.headSet("C", true));

        System.out.println("SubSet: "+set.subSet("A", false, "E", true));

        System.out.println("TailSet: "+set.tailSet("C", false));
    }
}
```

```
Initial Set: [A, B, C, D, E]
Reverse Set: [E, D, C, B, A]
Head Set: [A, B, C]
SubSet: [B, C, D, E]
TailSet: [D, E]
```


Java Map Interface

A map contains values on the basis of key, i.e. key and value pair. Each key and value pair is known as an entry. A Map contains unique keys.

A Map is useful if you have to search, update or delete elements on the basis of a key.

A Map doesn't allow duplicate keys, but you can have duplicate values. HashMap and LinkedHashMap allow null keys and values, but TreeMap doesn't allow any null key or value.

Java Map Hierarchy



Methods of Map interface

Method	Description
V put(Object key, Object value)	It is used to insert an entry in the map.
void putAll(Map map)	It is used to insert the specified map in the map.
V putIfAbsent(K key, V value)	It inserts the specified value with the specified key in the map only if it is not already specified.
V remove(Object key)	It is used to delete an entry for the specified key.
boolean remove(Object key, Object value)	It removes the specified values with the associated specified keys from the map.
Set keySet()	It returns the Set view containing all the keys.
Set<Map.Entry<K,V>> entrySet()	It returns the Set view containing all the keys and values.
void clear()	It is used to reset the map.
V compute(K key, BiFunction<? super K,? super V,? extends V> remappingFunction)	It is used to compute a mapping for the specified key and its current mapped value (or null if there is no current mapping).

V computeIfPresent(K key, BiFunction<? super K,? super V,? extends V> remappingFunction)	It is used to compute a new mapping given the key and its current mapped value if the value for the specified key is present and non-null.
boolean containsValue(Object value)	This method returns true if some value equal to the value exists within the map, else return false.
boolean containsKey(Object key)	This method returns true if some key equal to the key exists within the map, else return false.
boolean equals(Object o)	It is used to compare the specified Object with the Map.
void forEach(BiConsumer<? super K,? super V> action)	It performs the given action for each entry in the map until all entries have been processed or the action throws an exception.
V get(Object key)	This method returns the object that contains the value associated with the key.
V getOrDefault(Object key, V defaultValue)	It returns the value to which the specified key is mapped, or defaultValue if the map contains no mapping for the key.
int hashCode()	It returns the hash code value for the Map
boolean isEmpty()	This method returns true if the map is empty; returns false if it contains at least one key.

Methods of Map interface

V merge(K key, V value, BiFunction<? super V,? super V,? extends V> remappingFunction)	If the specified key is not already associated with a value or is associated with null, associates it with the given non-null value.
V replace(K key, V value)	It replaces the specified value for a specified key.
boolean replace(K key, V oldValue, V newValue)	It replaces the old value with the new value for a specified key.
void replaceAll(BiFunction<? super K,? super V,? extends V> function)	It replaces each entry's value with the result of invoking the given function on that entry until all entries have been processed or the function throws an exception.
Collection values()	It returns a collection view of the values contained in the map.
int size()	This method returns the number of entries in the map.

Java Map Example

```
import java.util.*;
class MapExample2{
    public static void main(String args[]){
        Map<Integer, String> map=new HashMap<Integer, String>();
        map.put(100,"Amit");
        map.put(101,"Vijay");
        map.put(102,"Rahul");
        //Elements can traverse in any order
        for(Map.Entry m:map.entrySet()){
            System.out.println(m.getKey()+" "+m.getValue());
        }
    }
}
```

Java HashMap Class

- Java HashMap class implements the Map interface which allows us to store key and value pair, where keys should be unique. If you try to insert the duplicate key, it will replace the element of the corresponding key. It is easy to perform operations using the key index like updation, deletion, etc. HashMap class is found in the java.util package.
- It allows us to store the null elements as well, but there should be only one null key. Since Java 5, it is denoted as HashMap<K,V>, where K stands for key and V for value.

Java HashMap Class

- Points to remember
 - Java HashMap contains values based on the key.
 - Java HashMap contains only unique keys.
 - Java HashMap may have one null key and multiple null values.
 - Java HashMap maintains no order.

Methods of Java HashMap class

Method	Description
void clear()	It is used to remove all of the mappings from this map.
boolean isEmpty()	It is used to return true if this map contains no key-value mappings.
Object clone()	It is used to return a shallow copy of this HashMap instance: the keys and values themselves are not cloned.
Set entrySet()	It is used to return a collection view of the mappings contained in this map.
Set keySet()	It is used to return a set view of the keys contained in this map.
V put(Object key, Object value)	It is used to insert an entry in the map.
void putAll(Map map)	It is used to insert the specified map in the map.
V putIfAbsent(K key, V value)	It inserts the specified value with the specified key in the map only if it is not already specified.
V remove(Object key)	It is used to delete an entry for the specified key.

boolean remove(Object key, Object value)	It removes the specified values with the associated specified keys from the map.
V compute(K key, BiFunction<? super K,? super V,? extends V> remappingFunction)	It is used to compute a mapping for the specified key and its current mapped value (or null if there is no current mapping).
V computeIfAbsent(K key, Function<? super K,? extends V> mappingFunction)	It is used to compute its value using the given mapping function, if the specified key is not already associated with a value (or is mapped to null), and enters it into this map unless null.
V computeIfPresent(K key, BiFunction<? super K,? super V,? extends V> remappingFunction)	It is used to compute a new mapping given the key and its current mapped value if the value for the specified key is present and non-null.
boolean containsValue(Object value)	This method returns true if some value equal to the value exists within the map, else return false.
boolean containsKey(Object key)	This method returns true if some key equal to the key exists within the map, else return false.
boolean equals(Object o)	It is used to compare the specified Object with the Map.
void forEach(BiConsumer<? super K,? super V> action)	It performs the given action for each entry in the map until all entries have been processed or the action throws an exception.

V get(Object key)	This method returns the object that contains the value associated with the key.
V getOrDefault(Object key, V defaultValue)	It returns the value to which the specified key is mapped, or defaultValue if the map contains no mapping for the key.
boolean isEmpty()	This method returns true if the map is empty; returns false if it contains at least one key.
V merge(K key, V value, BiFunction<? super V,? super V,? extends V> remappingFunction)	If the specified key is not already associated with a value or is associated with null, associates it with the given non-null value.
V replace(K key, V value)	It replaces the specified value for a specified key.
boolean replace(K key, V oldValue, V newValue)	It replaces the old value with the new value for a specified key.
void replaceAll(BiFunction<? super K,? super V,? extends V> function)	It replaces each entry's value with the result of invoking the given function on that entry until all entries have been processed or the function throws an exception.
Collection<V> values()	It returns a collection view of the values contained in the map.
int size()	This method returns the number of entries in the map.

Java HashMap Example

```

import java.util.*;
public class HashMapExample1{
    public static void main(String args[]){
        HashMap<Integer, String> map=new HashMap<Integer, String>(); //Creating HashMap
        map.put(1,"Mango"); //Put elements in Map
        map.put(2,"Apple");
        map.put(3,"Banana");
        map.put(4,"Grapes");

        System.out.println("Iterating Hashmap...");
        for(Map.Entry m : map.entrySet()){
            System.out.println(m.getKey()+" "+m.getValue());
        }
    }
}

```

```

Iterating Hashmap...
1 Mango
2 Apple
3 Banana
4 Grapes

```

No Duplicate Key on HashMap

```
import java.util.*;
public class HashMapExample2{
    public static void main(String args[]){
        HashMap<Integer, String> map=new HashMap<Integer, String>(); //Creating HashMap
        map.put(1,"Mango"); //Put elements in Map
        map.put(2,"Apple");
        map.put(3,"Banana");
        map.put(1,"Grapes"); //trying duplicate key

        System.out.println("Iterating Hashmap...");
        for(Map.Entry m : map.entrySet()){
            System.out.println(m.getKey()+" "+m.getValue());
        }
    }
}
```

```
Iterating Hashmap...
1 Grapes
2 Apple
3 Banana
```

Java HashMap example to remove() elements

```
import java.util.*;
public class HashMap2 {
    public static void main(String args[]) {
        HashMap<Integer, String> map=new HashMap<Integer, String>();
        map.put(100,"Amit");
        map.put(101,"Vijay");
        map.put(102,"Rahul");
        map.put(103, "Gaurav");
        System.out.println("Initial list of elements: "+map);
        //key-based removal
        map.remove(100);
        System.out.println("Updated list of elements: "+map);
        //value-based removal
        map.remove(101);
        System.out.println("Updated list of elements: "+map);
        //key-value pair based removal
        map.remove(102, "Rahul");
        System.out.println("Updated list of elements: "+map);
    }
}
```

Java HashMap example to remove() elements

```
Initial list of elements: {100=Amit, 101=Vijay, 102=Rahul, 103=Gaurav}
Updated list of elements: {101=Vijay, 102=Rahul, 103=Gaurav}
Updated list of elements: {102=Rahul, 103=Gaurav}
Updated list of elements: {103=Gaurav}
```