



Install Astra Control Center

Astra Control Center

NetApp
August 16, 2022

This PDF was generated from https://docs.netapp.com/us-en/astra-control-center/get-started/acc_cluster_cr_options.html on August 16, 2022. Always check docs.netapp.com for the latest.

Table of Contents

- Install Astra Control Center using the standard process 1
 - Download and unpack the Astra Control Center bundle 2
 - Install the NetApp Astra kubectl plugin 2
 - Add the images to your local registry 3
 - Set up namespace and secret for registries with auth requirements 3
 - Install the Astra Control Center operator 5
 - Configure Astra Control Center 7
 - Complete Astra Control Center and operator installation 9
 - Verify system status 10
 - Set up ingress for load balancing 20
 - Log in to the Astra Control Center UI 25
 - Troubleshoot the installation 26
 - What's next 26
 - Understand Astra Control Center cluster CR options 26
 - Understand pod security policy restrictions 33
 - Configure an external cert-manager 37

Install Astra Control Center using the standard process

To install Astra Control Center, download the installation bundle from the NetApp Support Site and perform the following steps to install Astra Control Center Operator and Astra Control Center in your environment. You can use this procedure to install Astra Control Center in internet-connected or air-gapped environments.

For Red Hat OpenShift environments, you can use an [alternative procedure](#) to install Astra Control Center using OpenShift OperatorHub.

What you'll need

- [Before you begin installation, prepare your environment for Astra Control Center deployment.](#)
- If you have configured or want to configure pod security policies in your environment, familiarize yourself with pod security policies and how they affect Astra Control Center installation. See [Understand pod security policy restrictions](#).
- Ensure all cluster operators are in a healthy state and available.

```
kubectl get clusteroperators
```

- Ensure all API services are in a healthy state and available:

```
kubectl get apiservices
```

- Ensure the Astra FQDN you plan to use is routable to this cluster. This means that you either have a DNS entry in your internal DNS server or you are using a core URL route that is already registered.
- If a cert-manager already exists in the cluster, you need to perform some [prerequisite steps](#) so that Astra Control Center does not install its own cert-manager.

About this task

The Astra Control Center installation process does the following:

- Installs the Astra components into the `netapp-acc` (or custom-named) namespace.
- Creates a default account.
- Establishes a default administrative user email address and default one-time password. This user is assigned the Owner role in the system that is needed for first time login to the UI.
- Helps you determine that all Astra Control Center pods are running.
- Installs the Astra UI.



(Applies to the Astra Data Store Early Access Program (EAP) release only) If you intend to manage Astra Data Store using Astra Control Center and enable VMware workflows, deploy Astra Control Center only on the `pcloud` namespace and not on the `netapp-acc` namespace or a custom namespace described in the steps of this procedure.



Do not execute the following command during the entirety of the installation process to avoid deleting all Astra Control Center pods: `kubectl delete -f astra_control_center_operator_deploy.yaml`



If you are using Red Hat's Podman instead of Docker Engine, Podman commands can be used in place of Docker commands.

Steps

To install Astra Control Center, do the following steps:

- [Download and unpack the Astra Control Center bundle](#)
- [Install the NetApp Astra kubectl plugin](#)
- [Add the images to your local registry](#)
- [Set up namespace and secret for registries with auth requirements](#)
- [Install the Astra Control Center operator](#)
- [Configure Astra Control Center](#)
- [Complete Astra Control Center and operator installation](#)
- [Verify system status](#)
- [Set up ingress for load balancing](#)
- [Log in to the Astra Control Center UI](#)

Download and unpack the Astra Control Center bundle

1. Download the Astra Control Center bundle (`astra-control-center-[version].tar.gz`) from the [NetApp Support Site](#).
2. Download the zip of Astra Control Center certificates and keys from the [NetApp Support Site](#).
3. (Optional) Use the following command to verify the signature of the bundle:

```
openssl dgst -sha256 -verify AstraControlCenter-public.pub -signature  
astra-control-center-[version].tar.gz.sig astra-control-center-  
[version].tar.gz
```

4. Extract the images:

```
tar -vxzf astra-control-center-[version].tar.gz
```

Install the NetApp Astra kubectl plugin

The NetApp Astra `kubectl` command line plugin saves time when performing common tasks associated with deploying and upgrading Astra Control Center.

What you'll need

NetApp provides binaries for the plugin for different CPU architectures and operating systems. You need to know which CPU and operating system you have before you perform this task. On Linux and Mac operating systems, you can use the `uname -a` command to gather this information.

Steps

1. List the available NetApp Astra `kubectl` plugin binaries, and note the name of the file you need for your operating system and CPU architecture:

```
ls kubectl-astra/
```

2. Copy the file to the same location as the standard `kubectl` utility. In this example, the `kubectl` utility is located in the `/usr/local/bin` directory. Replace `<binary-name>` with the name of the file you need:

```
cp kubectl-astra/<binary-name> /usr/local/bin/kubectl-astra
```

Add the images to your local registry

1. Change to the Astra directory:

```
cd acc
```

2. Push the package images in the Astra Control Center image directory to your local registry. Make the following substitutions before running the command:
 - Replace `BUNDLE_FILE` with the name of the Astra Control bundle file (for example, `acc.manifest.bundle.yaml`).
 - Replace `MY_REGISTRY` with the URL of the Docker repository.
 - Replace `MY_REGISTRY_USER` and `MY_REGISTRY_PASSWORD` with the credentials for the repository.

```
kubectl astra packages push-images -m BUNDLE_FILE -r MY_REGISTRY -u MY_REGISTRY_USER -p MY_REGISTRY_PASSWORD
```

Set up namespace and secret for registries with auth requirements

1. If you use a registry that requires authentication, you need to do the following:
 - a. Create the `netapp-acc-operator` namespace:

```
kubectl create ns netapp-acc-operator
```

Response:

```
namespace/netapp-acc-operator created
```

- b. Create a secret for the `netapp-acc-operator` namespace. Add Docker information and run the following command:

```
kubectl create secret docker-registry astra-registry-cred -n netapp-acc-operator --docker-server=[your_registry_path] --docker-username=[username] --docker-password=[token]
```

Sample response:

```
secret/astra-registry-cred created
```

- c. Create the `netapp-acc` (or custom named) namespace.

```
kubectl create ns [netapp-acc or custom namespace]
```

Sample response:

```
namespace/netapp-acc created
```

- d. Create a secret for the `netapp-acc` (or custom named) namespace. Add Docker information and run the following command:

```
kubectl create secret docker-registry astra-registry-cred -n [netapp-acc or custom namespace] --docker-server=[your_registry_path] --docker-username=[username] --docker-password=[token]
```

Response

```
secret/astra-registry-cred created
```

- e. (Optional) If you want the cluster to be automatically managed by Astra Control Center after installation, make sure that you provide the kubeconfig as a secret within the Astra Control Center namespace you intend to deploy into using this command:

```
kubectl create secret generic [acc-kubeconfig-cred or custom secret name] --from-file=<path-to-your-kubeconfig> -n [netapp-acc or custom namespace]
```

Install the Astra Control Center operator

1. Edit the Astra Control Center operator deployment YAML (`astra_control_center_operator_deploy.yaml`) to refer to your local registry and secret.

```
vim astra_control_center_operator_deploy.yaml
```



An annotated sample YAML follows these steps.

- a. If you use a registry that requires authentication, replace the default line of `imagePullSecrets: []` with the following:

```
imagePullSecrets:  
- name: <name_of_secret_with_creds_to_local_registry>
```

- b. Change `[your_registry_path]` for the `kube-rbac-proxy` image to the registry path where you pushed the images in a [previous step](#).
- c. Change `[your_registry_path]` for the `acc-operator-controller-manager` image to the registry path where you pushed the images in a [previous step](#).
- d. (For installations using Astra Data Store preview) See this known issue regarding [storage class provisioners and additional changes you will need to make to the YAML](#).

```

apiVersion: apps/v1
kind: Deployment
metadata:
  labels:
    control-plane: controller-manager
  name: acc-operator-controller-manager
  namespace: netapp-acc-operator
spec:
  replicas: 1
  selector:
    matchLabels:
      control-plane: controller-manager
  template:
    metadata:
      labels:
        control-plane: controller-manager
    spec:
      containers:
        - args:
            - --secure-listen-address=0.0.0.0:8443
            - --upstream=http://127.0.0.1:8080/
            - --logtostderr=true
            - --v=10
            image: [your_registry_path]/kube-rbac-proxy:v4.8.0
          name: kube-rbac-proxy
          ports:
            - containerPort: 8443
              name: https
        - args:
            - --health-probe-bind-address=:8081
            - --metrics-bind-address=127.0.0.1:8080
            - --leader-elect
          command:
            - /manager
          env:
            - name: ACCOP_LOG_LEVEL
              value: "2"
            image: [your_registry_path]/acc-operator:[version x.y.z]
          imagePullPolicy: IfNotPresent
      imagePullSecrets: []

```

2. Install the Astra Control Center operator:

```
kubectl apply -f astra_control_center_operator_deploy.yaml
```


Sample response:

```
namespace/netapp-acc-operator created
customresourcedefinition.apiextensions.k8s.io/astracontrolcenters.astra.
netapp.io created
role.rbac.authorization.k8s.io/acc-operator-leader-election-role created
clusterrole.rbac.authorization.k8s.io/acc-operator-manager-role created
clusterrole.rbac.authorization.k8s.io/acc-operator-metrics-reader
created
clusterrole.rbac.authorization.k8s.io/acc-operator-proxy-role created
rolebinding.rbac.authorization.k8s.io/acc-operator-leader-election-
rolebinding created
clusterrolebinding.rbac.authorization.k8s.io/acc-operator-manager-
rolebinding created
clusterrolebinding.rbac.authorization.k8s.io/acc-operator-proxy-
rolebinding created
configmap/acc-operator-manager-config created
service/acc-operator-controller-manager-metrics-service created
deployment.apps/acc-operator-controller-manager created
```

Configure Astra Control Center

1. Edit the Astra Control Center custom resource (CR) file (`astra_control_center_min.yaml`) to make account, autoSupport, registry, and other necessary configurations:



`astra_control_center_min.yaml` is the default CR and is suitable for most installations. Familiarize yourself with all [CR options and their potential values](#) to ensure you deploy Astra Control Center correctly for your environment. If additional customizations are required for your environment, you can use `astra_control_center.yaml` as an alternative CR.

```
vim astra_control_center_min.yaml
```



If you are using a registry that does not require authorization, you must delete the `secret` line within `imageRegistry` or the installation will fail.

- a. Change `[your_registry_path]` to the registry path where you pushed the images in the previous step.
- b. Change the `accountName` string to the name you want to associate with the account.
- c. Change the `astraAddress` string to the FQDN you want to use in your browser to access Astra. Do not use `http://` or `https://` in the address. Copy this FQDN for use in a [later step](#).
- d. Change the `email` string to the default initial administrator address. Copy this email address for use in a [later step](#).

- e. Change `enrolled for AutoSupport` to `false` for sites without internet connectivity or retain `true` for connected sites.
- f. If you use an external cert-manager, add the following lines to `spec`:

```
spec:
  crds:
    externalCertManager: true
```

- g. (Optional) Add a first name `firstName` and last name `lastName` of the user associated with the account. You can perform this step now or later within the UI.
- h. (Optional) Change the `storageClass` value to another Trident `storageClass` resource if required by your installation.
- i. (Optional) If you want the cluster to be automatically managed by Astra Control Center after installation and you have already [created the secret containing the kubeconfig for this cluster](#), provide the name of the secret by adding a new field to this YAML file called `astraKubeConfigSecret`: `"acc-kubeconfig-cred` or `custom secret name"`
- j. Complete one of the following steps:

- **Other ingress controller (`ingressType:Generic`):** This is the default action with Astra Control Center. After Astra Control Center is deployed, you will need to configure the ingress controller to expose Astra Control Center with a URL.

The default Astra Control Center installation sets up its gateway (`service/traefik`) to be of the type `ClusterIP`. This default installation requires you to additionally set up a Kubernetes IngressController/Ingress to route traffic to it. If you want to use an ingress, see [Set up ingress for load balancing](#).

- **Service load balancer (`ingressType:AccTraefik`):** If you don't want to install an IngressController or create an Ingress resource, set `ingressType` to `AccTraefik`.

This deploys the Astra Control Center `traefik` gateway as a Kubernetes `LoadBalancer` type service.

Astra Control Center uses a service of the type "LoadBalancer" (`svc/traefik` in the Astra Control Center namespace), and requires that it be assigned an accessible external IP address. If load balancers are permitted in your environment and you don't already have one configured, you can use MetalLB or another external service load balancer to assign an external IP address to the service. In the internal DNS server configuration, you should point the chosen DNS name for Astra Control Center to the load-balanced IP address.



For details about the service type of "LoadBalancer" and ingress, see [Requirements](#).

```

apiVersion: astra.netapp.io/v1
kind: AstraControlCenter
metadata:
  name: astra
spec:
  accountName: "Example"
  astraVersion: "ASTRA_VERSION"
  astraAddress: "astra.example.com"
  astraKubeConfigSecret: "acc-kubeconfig-cred or custom secret name"
  ingressType: "Generic"
  autoSupport:
    enrolled: true
  email: "[admin@example.com]"
  firstName: "SRE"
  lastName: "Admin"
  imageRegistry:
    name: "[your_registry_path]"
    secret: "astra-registry-cred"
  storageClass: "ontap-gold"

```

Complete Astra Control Center and operator installation

1. If you didn't already do so in a previous step, create the `netapp-acc` (or custom) namespace:

```
kubectl create ns [netapp-acc or custom namespace]
```

Sample response:

```
namespace/netapp-acc created
```

2. Install Astra Control Center in the `netapp-acc` (or your custom) namespace:

```
kubectl apply -f astra_control_center_min.yaml -n [netapp-acc or custom namespace]
```

Sample response:

```
astracontrolcenter.astra.netapp.io/astra created
```

Verify system status



If you prefer to use OpenShift, you can use comparable `oc` commands for verification steps.

1. Verify that all system components installed successfully.

```
kubect1 get pods -n [netapp-acc or custom namespace]
```

Each pod should have a status of `Running`. It may take several minutes before the system pods are deployed.

Sample response

| NAME | READY | STATUS | |
|--|-------|---------|---|
| RESTARTS AGE | | | |
| acc-helm-repo-5f75c5f564-bzqmt 11m | 1/1 | Running | 0 |
| activity-6b8f7cccb9-mlrn4 9m2s | 1/1 | Running | 0 |
| api-token-authentication-6hznt 8m50s | 1/1 | Running | 0 |
| api-token-authentication-qpfqb 8m50s | 1/1 | Running | 0 |
| api-token-authentication-sqnb7 8m50s | 1/1 | Running | 0 |
| asup-5578bbdd57-dxkbp 9m3s | 1/1 | Running | 0 |
| authentication-56bff4f95d-mspmq 7m31s | 1/1 | Running | 0 |
| bucket-service-6f7968b95d-9rrrl 8m36s | 1/1 | Running | 0 |
| cert-manager-5f6cf4bc4b-82khn 6m19s | 1/1 | Running | 0 |
| cert-manager-cainjector-76cf976458-sdrbc 6m19s | 1/1 | Running | 0 |
| cert-manager-webhook-5b7896bfd8-2n45j 6m19s | 1/1 | Running | 0 |
| certificates-1a599d9f76-ab6sk 8m35s | 2/2 | Running | 0 |
| certificates-1a599d9f76-ab8fj 8m52s | 2/2 | Running | 0 |
| certificates-expiry-check-12331210--1-fc26j 8m19s | 1/1 | Running | 0 |
| cloud-extension-749d9f684c-8bdhq 9m6s | 1/1 | Running | 0 |
| cloud-insights-service-7d58687d9-h5tzw 8m56s | 1/1 | Running | 2 |
| composite-compute-968c79cb5-nv7l4 9m11s | 1/1 | Running | 0 |
| composite-volume-7687569985-jg9gg 8m33s | 1/1 | Running | 0 |
| credentials-5c9b75f4d6-nx9cz 8m42s | 1/1 | Running | 0 |
| entitlement-6c96fd8b78-zt7f8 8m28s | 1/1 | Running | 0 |
| features-5f7bfc9f68-gsjnl 8m57s | 1/1 | Running | 0 |

| | | | |
|--|-----|---------|---|
| fluent-bit-ds-h88p7 7m22s | 1/1 | Running | 0 |
| fluent-bit-ds-krhnj 7m23s | 1/1 | Running | 0 |
| fluent-bit-ds-l5bjj 7m22s | 1/1 | Running | 0 |
| fluent-bit-ds-lrclb 7m23s | 1/1 | Running | 0 |
| fluent-bit-ds-s5t4n 7m23s | 1/1 | Running | 0 |
| fluent-bit-ds-zpr6v 7m22s | 1/1 | Running | 0 |
| graphql-server-5f5976f4bd-vbb4z 7m13s | 1/1 | Running | 0 |
| identity-56f78b8f9f-8h9p9 8m29s | 1/1 | Running | 0 |
| influxdb2-0 11m | 1/1 | Running | 0 |
| keycloak-operator-5d47896894-74gq5 8m23s | 1/1 | Running | 0 |
| krakend-6f8d995b4d-5khkl 7m7s | 1/1 | Running | 0 |
| license-5b5db87c97-jmxzc 9m | 1/1 | Running | 0 |
| login-ui-57b57c74b8-6xtv7 7m10s | 1/1 | Running | 0 |
| loki-0 11m | 1/1 | Running | 0 |
| metrics-facade-db5c565d-5rncg 7m39s | 2/2 | Running | 0 |
| monitoring-operator-9dbc9c76d-8znck 7m33s | 2/2 | Running | 0 |
| nats-0 11m | 1/1 | Running | 0 |
| nats-1 10m | 1/1 | Running | 0 |
| nats-2 10m | 1/1 | Running | 0 |
| nautilus-6b9d88bc86-h8kfb 8m6s | 1/1 | Running | 0 |
| nautilus-6b9d88bc86-vn68r 8m35s | 1/1 | Running | 0 |
| openapi-b87d77dd8-5dz9h 9m7s | 1/1 | Running | 0 |
| packages-94b56b6b8-jb9rk 10m | 2/2 | Running | 0 |

| | | | |
|---|-----|---------|---|
| polaris-consul-consul-server-0 11m | 1/1 | Running | 0 |
| polaris-consul-consul-server-1 11m | 1/1 | Running | 0 |
| polaris-consul-consul-server-2 11m | 1/1 | Running | 0 |
| polaris-keycloak-0 7m22s | 1/1 | Running | 0 |
| polaris-keycloak-1 7m19s | 1/1 | Running | 0 |
| polaris-keycloak-2 7m17s | 1/1 | Running | 0 |
| polaris-keycloak-db-0 7m16s | 1/1 | Running | 0 |
| polaris-keycloak-db-1 7m13s | 1/1 | Running | 0 |
| polaris-keycloak-db-2 7m10s | 1/1 | Running | 0 |
| polaris-mongodb-0 11m | 2/2 | Running | 0 |
| polaris-mongodb-1 10m | 2/2 | Running | 0 |
| polaris-mongodb-2 10m | 2/2 | Running | 0 |
| polaris-ui-84dc87847f-zrg8w 7m12s | 1/1 | Running | 0 |
| polaris-vault-0 11m | 1/1 | Running | 0 |
| polaris-vault-1 11m | 1/1 | Running | 0 |
| polaris-vault-2 11m | 1/1 | Running | 0 |
| public-metrics-657698b66f-67pgt 8m47s | 1/1 | Running | 0 |
| storage-backend-metrics-6848b9fd87-w7x8r 8m39s | 1/1 | Running | 0 |
| storage-provider-5ff5868cd5-r9hj7 8m45s | 1/1 | Running | 0 |
| telegraf-ds-dw4hg 7m23s | 1/1 | Running | 0 |
| telegraf-ds-k92gn 7m23s | 1/1 | Running | 0 |
| telegraf-ds-mmxjl 7m23s | 1/1 | Running | 0 |
| telegraf-ds-nhs8s 7m23s | 1/1 | Running | 0 |

| | | | |
|------------------------------------|-----|---------|---|
| telegraf-ds-rj7lw | 1/1 | Running | 0 |
| 7m23s | | | |
| telegraf-ds-tqrkb | 1/1 | Running | 0 |
| 7m23s | | | |
| telegraf-rs-9mwgj | 1/1 | Running | 0 |
| 7m23s | | | |
| telemetry-service-56c49d689b-ffrzx | 1/1 | Running | 0 |
| 8m42s | | | |
| tenancy-767c77fb9d-g9ctv | 1/1 | Running | 0 |
| 8m52s | | | |
| traefik-5857d87f85-7pmx8 | 1/1 | Running | 0 |
| 6m49s | | | |
| traefik-5857d87f85-cpxgv | 1/1 | Running | 0 |
| 5m34s | | | |
| trident-svc-595f84dd78-zb8l6 | 1/1 | Running | 0 |
| 8m54s | | | |
| vault-controller-86c94fbf4f-krttq | 1/1 | Running | 0 |
| 9m24s | | | |

2. (Optional) To ensure the installation is completed, you can watch the `acc-operator` logs using the following command.

```
kubectl logs deploy/acc-operator-controller-manager -n netapp-acc-operator -c manager -f
```



`accHost` cluster registration is one of the last operations, and if it fails it will not cause deployment to fail. In the event of a cluster registration failure indicated in the logs, you can attempt registration again through the add cluster workflow [in the UI](#) or API.

3. When all the pods are running, verify installation success by retrieving the `AstraControlCenter` instance installed by the Astra Control Center Operator.

```
kubectl get acc -o yaml -n [netapp-acc or custom namespace]
```

4. In the YAML, check the `status.deploymentState` field in the response for the `Deployed` value. If deployment was unsuccessful, an error message appears instead.
5. To get the one-time password you will use when you log in to Astra Control Center, copy the `status.uuid` value. The password is `ACC-` followed by the UUID value (`ACC-[UUID]` or, in this example, `ACC-9aa5fdae-4214-4cb7-9976-5d8b4c0ce27f`).

Sample YAML Details

```
name: astra
namespace: netapp-acc
resourceVersion: "104424560"
uid: 9aa5fdae-4214-4cb7-9976-5d8b4c0ce27f
spec:
  accountName: Example
  additionalValues: {}
  astraAddress: astra.example.com
  astraKubeConfigSecret: ""
  astraResourcesScaler: "Off"
  astraVersion: 22.08.0-18
  autoSupport:
    enrolled: true
    url: https://support.netapp.com/asupprod/post/1.0/postAsup
  avpDeploy: false
  crds: {}
  email: admin@example.com
  firstName: SRE
  imageRegistry:
    name: registry_name/astra
  ingressType: AccTraefik
  lastName: Admin
  mtls:
    certDuration: 2140h0m0s
    enabled: true
status:
  accConditionHistory:
    items:
      - astraVersion: 22.08.0-18
        condition:
          lastTransitionTime: "2022-08-05T18:03:46Z"
          message: Deploying is currently in progress.
          reason: InProgress
          status: "False"
          type: Ready
        generation: 2
        observedSpec:
          accountName: Example
          additionalValues: {}
          astraAddress: astra.example.com
          astraKubeConfigSecret: ""
          astraResourcesScaler: "Off"
          astraVersion: 22.08.0-18
          autoSupport:
```

```

    enrolled: true
    url: https://support.netapp.com/asupprod/post/1.0/postAsup
    crds: {}
    email: admin@example.com
    firstName: SRE
    imageRegistry:
      name: registry_name/astra
    lastName: Admin
    mtls:
      certDuration: 2140h0m0s
      enabled: true
    timestamp: "2022-08-05T18:03:46Z"
- astraVersion: 22.08.0-18
  condition:
    lastTransitionTime: "2022-08-05T18:03:46Z"
    message: Deploying is currently in progress.
    reason: InProgress
    status: "True"
    type: Deploying
  generation: 2
  observedSpec:
    accountName: Example
    additionalValues: {}
    astraAddress: astra.example.com
    astraKubeConfigSecret: ""
    astraResourcesScaler: "Off"
    astraVersion: 22.08.0-18
    autoSupport:
      enrolled: true
      url: https://support.netapp.com/asupprod/post/1.0/postAsup
    avpDeploy: false
    crds: {}
    email: admin@example.com
    firstName: SRE
    imageRegistry:
      name: registry_name/astra
    lastName: Admin
    mtls:
      certDuration: 2140h0m0s
      enabled: true
    timestamp: "2022-08-05T18:03:46Z"
- astraVersion: 22.08.0-18
  condition:
    lastTransitionTime: "2022-08-05T18:16:50Z"
    message: Post Install was successful
    observedGeneration: 2

```

```

    reason: Complete
    status: "True"
    type: PostInstallComplete
generation: 2
observedSpec:
  accountName: Example
  additionalValues: {}
  astraAddress: astra.example.com
  astraKubeConfigSecret: ""
  astraResourcesScaler: "Off"
  astraVersion: 22.08.0-18
  autoSupport:
    enrolled: true
    url: https://support.netapp.com/asupprod/post/1.0/postAsup
  avpDeploy: false
  crds: {}
  email: admin@example.com
  firstName: SRE
  imageRegistry:
    name: registry_name/astra
  ingressType: AccTraefik
  lastName: Admin
  mtls:
    certDuration: 2140h0m0s
    enabled: true
timestamp: "2022-08-05T18:16:50Z"
- astraVersion: 22.08.0-18
condition:
  lastTransitionTime: "2022-08-05T18:03:46Z"
  message: Deploying succeeded.
  reason: Complete
  status: "False"
  type: Deploying
generation: 2
observedSpec:
  accountName: Example
  additionalValues: {}
  astraAddress: astra.example.com
  astraKubeConfigSecret: ""
  astraResourcesScaler: "Off"
  astraVersion: 22.08.0-18
  autoSupport:
    enrolled: true
    url: https://support.netapp.com/asupprod/post/1.0/postAsup
  avpDeploy: false
  crds: {}

```

```

    email: admin@example.com
    firstName: SRE
    imageRegistry:
      name: registry_name/astra
    ingressType: AccTraefik
    lastName: Admin
    mtls:
      certDuration: 2140h0m0s
      enabled: true
    timestamp: "2022-08-05T18:16:50Z"
- astraVersion: 22.08.0-18
  condition:
    lastTransitionTime: "2022-08-05T18:03:46Z"
    message: Astra is deployed
    reason: Complete
    status: "True"
    type: Deployed
  generation: 2
  observedSpec:
    accountName: Example
    additionalValues: {}
    astraAddress: astra.example.com
    astraKubeConfigSecret: ""
    astraResourcesScaler: "Off"
    astraVersion: 22.08.0-18
    autoSupport:
      enrolled: true
      url: https://support.netapp.com/asupprod/post/1.0/postAsup
    avpDeploy: false
    crds: {}
    email: admin@example.com
    firstName: SRE
    imageRegistry:
      name: registry_name/astra
    ingressType: AccTraefik
    lastName: Admin
    mtls:
      certDuration: 2140h0m0s
      enabled: true
    timestamp: "2022-08-05T18:16:50Z"
- astraVersion: 22.08.0-18
  condition:
    lastTransitionTime: "2022-08-05T18:16:50Z"
    message: Astra is deployed
    reason: Complete
    status: "True"

```

```

    type: Ready
generation: 2
observedSpec:
  accountName: Example
  additionalValues: {}
  astraAddress: astra.example.com
  astraKubeConfigSecret: ""
  astraResourcesScaler: "Off"
  astraVersion: 22.08.0-18
  autoSupport:
    enrolled: true
    url: https://support.netapp.com/asupprod/post/1.0/postAsup
  avpDeploy: false
  crds: {}
  email: admin@example.com
  firstName: SRE
  imageRegistry:
    name: registry_name/astra
  ingressType: AccTraefik
  lastName: Admin
  mtls:
    certDuration: 2140h0m0s
    enabled: true
  timestamp: "2022-08-05T18:16:50Z"
certManager: deploy
cluster:
  type: OCP
  vendorVersion: 4.9.29
  version: v1.22.5+a36406b
conditions:
- lastTransitionTime: "2022-08-05T18:23:41Z"
  message: Astra is deployed
  reason: Complete
  status: "True"
  type: Ready
- lastTransitionTime: "2022-08-05T18:23:41Z"
  message: Deploying succeeded.
  reason: Complete
  status: "False"
  type: Deploying
- lastTransitionTime: "2022-08-05T18:23:41Z"
  message: Post Install was successful
  observedGeneration: 2
  reason: Complete
  status: "True"
  type: PostInstallComplete

```

```

- lastTransitionTime: "2022-08-05T18:23:41Z"
  message: Astra is deployed
  reason: Complete
  status: "True"
  type: Deployed
deploymentState: Deployed
observedGeneration: 2
observedSpec:
  accountName: Example
  additionalValues: {}
  astraAddress: astra.example.com
  astraKubeConfigSecret: ""
  astraResourcesScaler: "Off"
  astraVersion: 22.08.0-18
  autoSupport:
    enrolled: true
    url: https://support.netapp.com/asupprod/post/1.0/postAsup
  avpDeploy: false
  crds: {}
  email: admin@example.com
  firstName: SRE
  imageRegistry:
    name: registry_name/astra
  ingressType: AccTraefik
  lastName: Admin
  mtls:
    certDuration: 2140h0m0s
    enabled: true
  observedVersion: 22.08.0-18
  postInstall: Complete
  serviceMesh:
    type: None
  uuid: 9aa5fdae-4214-4cb7-9976-5d8b4c0ce27f
kind: List
metadata:
  resourceVersion: ""
  selfLink: ""

```

Set up ingress for load balancing

You can set up a Kubernetes ingress controller that manages external access to services, such as load balancing in a cluster.

This procedure explains how to set up an ingress controller (`ingressType:Generic`). This is the default action with Astra Control Center. After Astra Control Center is deployed, you will need to configure the ingress

controller to expose Astra Control Center with a URL.



If you don't want to set up an ingress controller, you can set `ingressType:AccTraefik`). Astra Control Center uses a service of the type "LoadBalancer" (`svc/traefik` in the Astra Control Center namespace), and requires that it be assigned an accessible external IP address. If load balancers are permitted in your environment and you don't already have one configured, you can use MetalLB or another external service load balancer to assign an external IP address to the service. In the internal DNS server configuration, you should point the chosen DNS name for Astra Control Center to the load-balanced IP address. For details about the service type of "LoadBalancer" and ingress, see [Requirements](#).

The steps differ depending on the type of ingress controller you use:

- Istio ingress
- Nginx ingress controller
- OpenShift ingress controller

What you'll need

- The required [ingress controller](#) should already be deployed.
- The [ingress class](#) corresponding to the ingress controller should already be created.
- You are using Kubernetes versions between and including v1.19 and v1.22.

Steps for Istio ingress

1. Configure Istio ingress.



This procedure assumes that Istio is deployed using the "default" configuration profile.

2. Gather or create the desired certificate and private key file for the Ingress Gateway.

You can use a CA-signed or self-signed certificate. The common name must be the Astra address (FQDN).

Sample command:

```
openssl req -x509 -nodes -days 365 -newkey rsa:2048  
-keyout tls.key -out tls.crt
```

3. Create a secret `tls` secret name of type `kubernetes.io/tls` for a TLS private key and certificate in the `istio-system` namespace as described in [TLS secrets](#).

Sample command:

```
kubectl create secret tls [tls secret name]  
--key="tls.key"  
--cert="tls.crt" -n istio-system
```



The name of the secret should match the `spec.tls.secretName` provided in `istio-ingress.yaml` file.

4. Deploy an ingress resource in `netapp-acc` (or custom-named) namespace using either the `v1beta1` (deprecated in Kubernetes version less than or 1.22) or `v1` resource type for either a deprecated or a new schema:

Output:

```
apiVersion: networking.k8s.io/v1beta1
kind: IngressClass
metadata:
  name: istio
spec:
  controller: istio.io/ingress-controller
---
apiVersion: networking.k8s.io/v1beta1
kind: Ingress
metadata:
  name: ingress
  namespace: istio-system
spec:
  ingressClassName: istio
  tls:
  - hosts:
    - <ACC address>
    secretName: [tls secret name]
  rules:
  - host: [ACC address]
    http:
      paths:
      - path: /
        pathType: Prefix
        backend:
          serviceName: traefik
          servicePort: 80
```

For the `v1` new schema, follow this sample:

```
kubectl apply -f istio-Ingress.yaml
```

Output:


```

apiVersion: networking.k8s.io/v1
kind: IngressClass
metadata:
  name: istio
spec:
  controller: istio.io/ingress-controller
---
apiVersion: networking.k8s.io/v1
kind: Ingress
metadata:
  name: ingress
  namespace: istio-system
spec:
  ingressClassName: istio
  tls:
  - hosts:
    - <ACC address>
    secretName: [tls secret name]
  rules:
  - host: [ACC address]
    http:
      paths:
      - path: /
        pathType: Prefix
        backend:
          service:
            name: traefik
            port:
              number: 80

```

5. Deploy Astra Control Center as usual.

6. Check the status of the ingress:

```

kubectl get ingress -n netapp-acc

```

| NAME | CLASS | HOSTS | ADDRESS | PORTS | AGE |
|---------|-------|-------------------|----------------|---------|-----|
| ingress | istio | astra.example.com | 172.16.103.248 | 80, 443 | 1h |

Steps for Nginx ingress controller

1. Create a secret of type `kubernetes.io/tls` for a TLS private key and certificate in `netapp-acc` (or custom-named) namespace as described in [TLS secrets](#).
2. Deploy an ingress resource in `netapp-acc` (or custom-named) namespace using either the `v1beta1` (deprecated in Kubernetes version less than or 1.22) or `v1` resource type for either a deprecated or a new schema:

- a. For a `v1beta1` deprecated schema, follow this sample:

```
apiVersion: extensions/v1beta1
kind: Ingress
metadata:
  name: ingress-acc
  namespace: [netapp-acc or custom namespace]
  annotations:
    kubernetes.io/ingress.class: [class name for nginx controller]
spec:
  tls:
    - hosts:
        - <ACC address>
      secretName: [tls secret name]
  rules:
    - host: [ACC address]
      http:
        paths:
          - backend:
              serviceName: traefik
              servicePort: 80
            pathType: ImplementationSpecific
```

- b. For the `v1` new schema, follow this sample:

```

apiVersion: networking.k8s.io/v1
kind: Ingress
metadata:
  name: netapp-ingress
  namespace: [netapp-acc or custom namespace]
spec:
  ingressClassName: [class name for nginx controller]
  tls:
  - hosts:
    - <ACC address>
    secretName: [tls secret name]
  rules:
  - host: <ACC address>
    http:
      paths:
      - path:
        backend:
          service:
            name: traefik
            port:
              number: 80
          pathType: ImplementationSpecific

```

Steps for OpenShift ingress controller

1. Procure your certificate and get the key, certificate, and CA files ready for use by the OpenShift route.
2. Create the OpenShift route:

```

oc create route edge --service=traefik
--port=web -n [netapp-acc or custom namespace]
--insecure-policy=Redirect --hostname=<ACC address>
--cert=cert.pem --key=key.pem

```

Log in to the Astra Control Center UI

After installing Astra Control Center, you will change the password for the default administrator and log in to the Astra Control Center UI dashboard.

Steps

1. In a browser, enter the FQDN you used in the `astraAddress` in the `astra_control_center_min.yaml` CR when [you installed Astra Control Center](#).
2. Accept the self-signed certificates when prompted.



You can create a custom certificate after login.

3. At the Astra Control Center login page, enter the value you used for `email` in `astra_control_center_min.yaml` CR when [you installed Astra Control Center](#), followed by the one-time password (`ACC-[UUID]`).



If you enter an incorrect password three times, the admin account will be locked for 15 minutes.

4. Select **Login**.
5. Change the password when prompted.



If this is your first login and you forget the password and no other administrative user accounts have yet been created, contact NetApp Support for password recovery assistance.

6. (Optional) Remove the existing self-signed TLS certificate and replace it with a [custom TLS certificate signed by a Certificate Authority \(CA\)](#).

Troubleshoot the installation

If any of the services are in `Error` status, you can inspect the logs. Look for API response codes in the 400 to 500 range. Those indicate the place where a failure happened.

Steps

1. To inspect the Astra Control Center operator logs, enter the following:

```
kubectl logs --follow -n netapp-acc-operator $(kubectl get pods -n netapp-acc-operator -o name) -c manager
```

What's next

Complete the deployment by performing [setup tasks](#).

Understand Astra Control Center cluster CR options

You can use the following Astra Control Center cluster CR options to create custom configurations during deployment.

| Setting | Type | Use | Value Example | Description |
|---------------------------|--------|----------|---------------|---|
| <code>astraVersion</code> | string | Required | 1.5.2 | Version of AstraControlCenter to deploy. You are provided a Helm repository with a corresponding version. |

| Setting | Type | Use | Value Example | Description |
|----------------------|-----------|--------------------------------------|-----------------------------------|---|
| astraAddress | string | Required | astra.example.com | Defines how Astra will be found in the data center. This IP address and/or DNS A record must be created prior to provisioning Astra Control Center. |
| accountName | string | Required | Example | Astra Control Center account name. There can be only one. |
| email | string | Required | admin@example.com | The username of the administrator to be added as the first user of Astra. This email address will be notified by Astra Control as events warrant. |
| firstName | string | Required | SRE | The first name of the administrator supporting Astra. |
| lastName | string | Required | Admin | The last name of the administrator supporting Astra. |
| storageClass | string | Optional (this is the default value) | ontap-gold | The storage class to be used for PVCs. If not set, the default storage class will be used. |
| volumeReclaimPolicy | Undefined | Optional | Retain | Reclaim policy to be set for persistent volumes. |
| astraResourcesScaler | string | Required | Default | Scaling options for AstraControlCenter Resource limits. See setting complexities to understand how this settings affects others settings. |

| Setting | Type | Use | Value Example | Description |
|-----------------------|-----------|---|-------------------------------------|--|
| astraKubeConfigSecret | string | Required | acc-kubeconfig-cred | If this value is present and a secret exists, the operator will attempt to add that KubeConfig to become the first managed cluster. |
| ingressType | string | Optional | Generic (this is the default value) | The type of ingress Astra Control Center should be configured for. Valid values are <code>Generic</code> and <code>AccTraefik</code> . See setting complexities to understand how this settings affects others settings. |
| avpDeploy | Boolean | Optional | true (this is the default value) | Option that allows a user to disable deployment of Astra Plugin for VMware vSphere operator. |
| imageRegistry | Undefined | Optional | | The container image registry that is hosting the Astra application images, Astra Control Center Operator, and Astra Control Center Helm Repository. |
| imageRegistry.name | string | Required if you are using imageRegistry | example.registry.com/astra | The name of the image registry. Do not prefix with protocol. |
| imageRegistry.secret | string | Required if you are using imageRegistry | astra-registry-cred | The name of the Kubernetes secret used to authenticate with the image registry. |
| autoSupport | Undefined | Required | | Indicates participation status in NetApp's pro-active support application, NetApp Active IQ. An internet connection is required (port 442) and all support data is anonymized. |

| Setting | Type | Use | Value Example | Description |
|----------------------|-----------|--|---|--|
| autoSupport.enrolled | Boolean | Optional, but either <code>enrolled</code> or <code>url</code> fields must be selected | false (this value is the default) | Enrolled determines if you want to send anonymous data to NetApp for support purposes. The default election is <code>false</code> and indicates no support data will be sent to NetApp. |
| autoSupport.url | string | Optional, but either <code>enrolled</code> or <code>url</code> fields must be selected | https://support.netapp.com/asupprod/post/1.0/postAsup | URL determines where the anonymous data will be sent. |
| crds | Undefined | Undefined | | Options for how Astra Control Center should handle CRDs. |
| crds.externalTraefik | Boolean | Optional | True (this value is the default) | By default, Astra Control Center will install the required Traefik CRDs. CRDs are cluster-wide objects and installing them may have an impact on other parts of the cluster. You can use this flag to signal to Astra Control Center that these CRDs will be installed and managed by the cluster administrator outside of Astra Control Center. |

| Setting | Type | Use | Value Example | Description |
|--------------------------|---------|----------|----------------------------------|---|
| crds.externalCertManager | Boolean | Optional | True (this value is the default) | By default, Astra Control Center will install the required cert-manager CRDs. CRDs are cluster-wide objects and installing them may have an impact on other parts of the cluster. You can use this flag to signal to Astra Control Center that these CRDs will be installed and managed by the cluster administrator outside of Astra Control Center. |
| crds.shouldUpgrade | Boolean | Optional | Undefined | Determines if CRDs should be upgraded when Astra Control Center is upgraded. |
| mtls | | | | Options for how Astra Control Center should implement service to service mTLS in the cluster. See setting complexities to understand how this settings affects others settings |
| mtls.enabled | Boolean | Optional | true (this value is the default) | By default, Astra Control Center uses mTLS for service-to-service communication. This option should be disabled when using a service mesh to encrypt service-to-service communication instead. |

| Setting | Type | Use | Value Example | Description |
|--------------------------------|--------|----------|--|--|
| <code>mtls.certDuration</code> | string | Optional | 2140h (this value is the default duration) | The duration of time in hours to use as a certificate lifespan when issuing service TLS certificates. This setting only works when <code>mtls.enabled</code> is set to <code>true</code> . |

Configuration combinations and incompatibilities

Some Astra Control Center cluster CR configuration settings greatly affect the way Astra Control Center is installed and could conflict with other settings. The content that follows describes important configuration settings and how to avoid incompatible combinations.

`astraResourcesScaler`

By default, Astra Control Center deploys with resource requests set for most of the components within Astra. This configuration allows the Astra Control Center software stack to perform better in environments under increased application load and scale.

However, in scenarios using smaller development or test clusters, the CR field `AstraResourcesScaler` may be set to `Off`. This disables resource requests and allows for deployment on smaller clusters.

`ingressType`

There are two valid values for `ingressType`:

- Generic
- AccTraefik

Generic (default)

When `ingressType` is set to `Generic`, Astra Control does not install any ingress resources. The assumption is that the user has a common way of securing and routing traffic through their network to applications running on Kubernetes clusters and they want to use the same mechanisms here. When the user creates an ingress to route traffic to Astra Control, the ingress needs to point to the internal traefik service on port 80. Here is an example of an Nginx ingress resource that works with the `Generic` `ingressType` setting.

```

apiVersion: networking.k8s.io/v1
kind: Ingress
metadata:
  name: netapp-acc-ingress
  namespace: [netapp-acc or custom namespace]
spec:
  ingressClassName: [class name for nginx controller]
  tls:
  - hosts:
    - <ACC address>
    secretName: [tls secret name]
  rules:
  - host: <ACC address>
    http:
      paths:
      - path:
        backend:
          service:
            name: traefik
            port:
              number: 80
        pathType: ImplementationSpecific

```



When mTLS is disabled using the `mtls.enabled` setting in the CR, you must use `ingressType: Generic`.

AccTraefik

When `ingressType` is set to `AccTraefik`, Astra Control Center deploys its Traefik gateway as a Kubernetes LoadBalancer type service. Users need to provide an external Load Balancer (like MetalLB) for Astra Control Center to get an external IP.

mtls

The settings used in the CR determine how intra-application communication is secured. It is very important for the user to know ahead of time whether they will be using a service mesh or not.

- `enabled=true`: When this setting is enabled, Astra will deploy an internal service-to-service communication network that secures all traffic within the application.



Do not cover Astra Control Center in a service mesh while this setting is `true`.

- `enabled=false`: When this setting is disabled, Astra Control Center will not secure internal traffic and you must secure Astra namespaces independently with a service mesh.



When mTLS is disabled using the `mtls.enabled` setting in the CR, you must use `ingressType: Generic`.



If no service mesh is used and this setting is disabled, internal communication will be unsecure.

Understand pod security policy restrictions

Astra Control Center supports privilege limitation through pod security policies (PSPs). Pod security policies enable you to limit what users or groups are able to run containers and what privileges those containers can have.

Some Kubernetes distributions, such as RKE2, have a default pod security policy that is too restrictive, and causes problems when installing Astra Control Center.

You can use the information and examples included here to understand the pod security policies that Astra Control Center creates, and configure pod security policies that provide the protection you need without interfering with Astra Control Center functions.

PSPs installed by Astra Control Center

Astra Control Center creates several pod security policies during installation. Some of these are permanent, and some of them are created during certain operations and are removed once the operation is complete.

PSPs created during installation

During Astra Control Center installation, the Astra Control Center operator installs a custom pod security policy, a Role object, and a RoleBinding object to support the deployment of Astra Control Center services in the Astra Control Center namespace.

The new policy and objects have the following attributes:

```
$ kubectl get psp
NAME                                PRIV    CAPS                SELINUX    RUNASUSER
FSGROUP    SUPGROUP    READONLYROOTFS    VOLUMES
avp-psp                                false
RunAsAny    RunAsAny    false            *
netapp-astra-deployment-psp    false
RunAsAny    RunAsAny    false            *
```

```
$ kubectl get role
NAME                                CREATED AT
netapp-astra-deployment-role        2022-06-27T19:34:58Z
```

```
$ kubectl get rolebinding
NAME                                ROLE
AGE
netapp-astra-deployment-rb        Role/netapp-astra-deployment-role
32m
```

PSPs created during backup operations

During backup operations, Astra Control Center creates a dynamic pod security policy, a ClusterRole object, and a RoleBinding object. These support the backup process, which happens in a separate namespace.

The new policy and objects have the following attributes:

```
$ kubectl get psp
NAME                                PRIV    CAPS
SELINUX    RUNASUSER                FSGROUP    SUPGROUP    READONLYROOTFS
VOLUMES
netapp-astra-backup                false    DAC_READ_SEARCH
RunAsAny    RunAsAny                RunAsAny    RunAsAny    false      *
```

```
$ kubectl get role
NAME                                CREATED AT
netapp-astra-backup                2022-07-21T00:00:00Z
```

```
$ kubectl get rolebinding
NAME                                ROLE                                AGE
netapp-astra-backup                Role/netapp-astra-backup          62s
```

PSPs created during cluster management

When you manage a cluster, Astra Control Center installs the netapp-monitoring operator in the managed cluster. This operator creates a pod security policy, a ClusterRole object, and a RoleBinding object to deploy telemetry services in the Astra Control Center namespace.

The new policy and objects have the following attributes:

```
$ kubectl get psp
NAME                                PRIV    CAPS
SELINUX    RUNASUSER                FSGROUP    SUPGROUP    READONLYROOTFS
VOLUMES
netapp-monitoring-psp-nkmo        true     AUDIT_WRITE,NET_ADMIN,NET_RAW
RunAsAny    RunAsAny                RunAsAny    RunAsAny    false      *
```

```
$ kubectl get role
NAME                                CREATED AT
netapp-monitoring-role-privileged  2022-07-21T00:00:00Z
```

```
$ kubectl get rolebinding
NAME                                ROLE                                AGE
netapp-monitoring-role-binding-privileged  Role/netapp-monitoring-role-privileged  2m5s
```

Enable network communication between namespaces

Some environments use NetworkPolicy constructs to restrict traffic between namespaces. The Astra Control Center operator, Astra Control Center, and the Astra Plugin for VMware vSphere are all in different namespaces. The services in these different namespaces need to be able to communicate with one another. To enable this communication, follow these steps.

Steps

1. Delete any NetworkPolicy resources that exist in the Astra Control Center namespace:

```
$kubectl get networkpolicy -n netapp-acc
```

2. For each NetworkPolicy object that is returned by the preceding command, use the following command to delete it. Replace <OBJECT_NAME> with the name of the returned object:

```
$kubectl delete networkpolicy <OBJECT_NAME> -n netapp-acc
```

3. Apply the following resource file to configure the acc-avp-network-policy object to allow Astra Plugin for VMware vSphere services to make requests to Astra Control Center services. Replace the information in brackets <> with information from your environment:

```
apiVersion: networking.k8s.io/v1
kind: NetworkPolicy
metadata:
  name: acc-avp-network-policy
  namespace: <ACC_NAMESPACE_NAME> # REPLACE THIS WITH THE ASTRA CONTROL
CENTER NAMESPACE NAME
spec:
  podSelector: {}
  policyTypes:
    - Ingress
  ingress:
    - from:
      - namespaceSelector:
          matchLabels:
            kubernetes.io/metadata.name: <PLUGIN_NAMESPACE_NAME> #
REPLACE THIS WITH THE ASTRA PLUGIN FOR VMWARE VSPHERE NAMESPACE NAME
```

4. Apply the following resource file to configure the acc-operator-network-policy object to allow the Astra Control Center operator to communicate with Astra Control Center services. Replace the information in brackets <> with information from your environment:

```

apiVersion: networking.k8s.io/v1
kind: NetworkPolicy
metadata:
  name: acc-operator-network-policy
  namespace: <ACC_NAMESPACE_NAME> # REPLACE THIS WITH THE ASTRA CONTROL
CENTER NAMESPACE NAME
spec:
  podSelector: {}
  policyTypes:
    - Ingress
  ingress:
    - from:
      - namespaceSelector:
          matchLabels:
            kubernetes.io/metadata.name: <NETAPP-ACC-OPERATOR> #
REPLACE THIS WITH THE OPERATOR NAMESPACE NAME

```

Remove resource limitations

Some environments use the ResourceQuotas and LimitRanges objects to prevent the resources in a namespace from consuming all available CPU and memory on the cluster. Astra Control Center does not set maximum limits, so it will not be in compliance with those resources. You need to remove them from the namespaces where you plan to install Astra Control Center.

You can use the following steps to retrieve and remove these quotas and limits. In these examples, the command output is shown immediately after the command.

Steps

1. Get the resource quotas in the netapp-acc namespace:

```

$ kubectl get quota -n netapp-acc

```

| NAME | AGE | REQUEST | LIMIT |
|--|-----|--|-------|
| pods-high | 16s | requests.cpu: 0/20, requests.memory: 0/100Gi | |
| limits.cpu: 0/200, limits.memory: 0/1000Gi | | | |
| pods-low | 15s | requests.cpu: 0/1, requests.memory: 0/1Gi | |
| limits.cpu: 0/2, limits.memory: 0/2Gi | | | |
| pods-medium | 16s | requests.cpu: 0/10, requests.memory: 0/20Gi | |
| limits.cpu: 0/20, limits.memory: 0/200Gi | | | |

2. Delete all of the resource quotas by name:

```
$ kubectl delete resourcequota pods-high -n netapp-acc
resourcequota "pods-high" deleted

$ kubectl delete resourcequota pods-low -n netapp-acc
resourcequota "pods-low" deleted

$ kubectl delete resourcequota pods-medium -n netapp-acc
resourcequota "pods-medium" deleted
```

3. Get the limit ranges in the netapp-acc namespace:

```
$ kubectl get limits -n netapp-acc
```

| NAME | CREATED AT |
|-----------------|----------------------|
| cpu-limit-range | 2022-06-27T19:01:23Z |

4. Delete the limit ranges by name:

```
$ kubectl delete limitrange cpu-limit-range -n netapp-acc
```

Configure an external cert-manager

If a cert-manager already exists in your Kubernetes cluster, you need to perform some prerequisite steps so that Astra Control Center does not install its own cert-manager.

Steps

1. Confirm that you have a cert-manager installed:

```
kubectl get pods -A | grep 'cert-manager'
```

Sample response:

| | | |
|--------------|--|------|
| cert-manager | essential-cert-manager-84446f49d5-sf2zd | 1/1 |
| Running | 0 | 6d5h |
| cert-manager | essential-cert-manager-cainjector-66dc99cc56-9ldmt | 1/1 |
| Running | 0 | 6d5h |
| cert-manager | essential-cert-manager-webhook-56b76db9cc-fjqrq | 1/1 |
| Running | 0 | 6d5h |

2. Create a certificate/key pair for the astraAddress FQDN:

```
openssl req -x509 -nodes -days 365 -newkey rsa:2048 -keyout tls.key -out
tls.crt
```

Sample response:

```
Generating a 2048 bit RSA private key
.....+++
.....+++
writing new private key to 'tls.key'
```

3. Create a secret with previously generated files:

```
kubectl create secret tls selfsigned-tls --key tls.key --cert tls.crt -n
<cert-manager-namespace>
```

Sample response:

```
secret/selfsigned-tls created
```

4. Create a ClusterIssuer file that is **exactly** the following but includes the namespace location where your cert-manager pods are installed:

```
apiVersion: cert-manager.io/v1
kind: ClusterIssuer
metadata:
  name: astra-ca-clusterissuer
  namespace: <cert-manager-namespace>
spec:
  ca:
    secretName: selfsigned-tls
```

```
kubectl apply -f ClusterIssuer.yaml
```

Sample response:

```
clusterissuer.cert-manager.io/astra-ca-clusterissuer created
```

5. Verify that the ClusterIssuer has come up correctly. Ready must be True before you can proceed:


```
kubectl get ClusterIssuer
```

Sample response:

| NAME | READY | AGE |
|------------------------|-------|-----|
| astra-ca-clusterissuer | True | 9s |

6. Complete the [Astra Control Center installation process](#). There is a [required configuration step for the Astra Control Center cluster YAML](#) in which you change the CRD value to indicate that the cert-manager is externally installed. You must complete this step during installation so that Astra Control Center recognizes the external cert-manager.

Copyright Information

Copyright © 2022 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark Information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.