```python
def eliminate_digits_symbols(f):
    def process(string):
        new_str = ''
        for i in string:
            if i.isalpha():
                new_str = new_str + i
        else:
            f(new_str)
    return process
```

```python
@eliminate_digits_symbols
def showstring(s):
    print(s)
```

showstring ⇒ process

showstring( ) → ① process
↳ showstring

```python
def eliminate_digits_symbols(f):
    def process(string):
        new_str = ''
        for i in string:
            if i.isalpha():
                new_str = new_str + i
        else:
            f(new_str)
    return process
```

```python
@eliminate_digits_symbols
def showstring(s):
    print(s)
```

showstring → nested function

showstring() → nested function

↳ showstring

```python
def eliminate_digits_symbols(f):
    def process(string):
        new_str = ''
        for i in string:
            if i.isalpha():
                new_str = new_str + i
        else:
            f(new_str)
    return process
```

```python
@eliminate_digits_symbols
def showstring(s):
    print(s)
```



```
def filter_upper(f):
    def process(string):
        new_string = ''
        for i in string:
            if i.isupper():
                new_string+=i
        else:
            f(new_string)
    return process
```

```
@filter_upper
def showstring(s):
    print(s)

showstring('Good Afternoon')
```

```python
def filter_upper(f):
    def process(string):
        new_string = ''
        for i in string:
            if i.isupper():
                new_string+=i
        else:
            f(new_string)
    return process

@filter_upper
def showstring(s):
    print(s)

showstring('Good Afternoon')
```

filter_upper

```python
def process(string):
    new_string = ''
    for i in string:
        if i.isupper():
            new_string+=i
    else:
        f(new_string)
return process
```

```
def filter_upper(f):
    def process(string):
        new_string = ''
        for i in string:
            if i.isupper():
                new_string+=i
        else:
            f(new_string)
    return process

@filter_upper
def showstring(s):
    print(s)

showstring('Good Afternoon')
```

filter_upper

```
def process(string):
    new_string = ''
    for i in string:
        if i.isupper():
            new_string+=i
    else:
        f(new_string)
return process
```

showstring

```
print(s)
```

```
def filter_upper(f):
    def process(string):
        new_string = ''
        for i in string:
            if i.isupper():
                new_string+=i
        else:
            f(new_string)
    return process

@filter_upper
def showstring(s):
    print(s)

showstring('Good Afternoon')
```

filter_upper

```
def process(string):
    new_string = ''
    for i in string:
        if i.isupper():
            new_string+=i
    else:
        f(new_string)
return process
```

showstring

```
print(s)
```

f

showstring = filter_upper(showstring)

```python
def filter_upper(f):
    def process(string):
        new_string = ''
        for i in string:
            if i.isupper():
                new_string+=i
        else:
            f(new_string)
    return process

@filter_upper
def showstring(s):
    print(s)

showstring('Good Afternoon')
```

filter_upper

```python
def process(string):
    new_string = ''
    for i in string:
        if i.isupper():
            new_string+=i
    else:
        f(new_string)
return process
```

showstring

```python
print(s)
```

f

Process call

showstring = filter_upper(showstring)