

Level 1 — Easy Q56 — Number

```
<pre>
Debug the following code:
#include<stdio.h>
int main(){
    char c = 'A';
    switch(c){
        case 'A':
            printf("Letter A");
            break
    }
    return 0;
}
</pre>
```

Your Code

```
1 #include<stdio.h>
2 int main() {
3     char c = 'A';
4     switch(c) {
5         case 'A':
6             printf("Letter A");
7             break;
8     }
9     return 0;
10 }
```

Program Input (stdin)

Enter input if required...

Output

Letter A

Level 1 — Easy Q3 — Number

```
<pre>
#include <stdio.h>
int main() {
    if (5 > 2) {
        printf("Five is greater");
    }
}
</pre>
```

Your Code

```
1 #include <stdio.h>
2 int main() {
3     if (5 > 2) {
4         printf("Five is greater");
5     }
6     return 0;
7 }
```

Program Input (stdin)

Enter input if required...

Output

Five is greater

```
<pre>
Debug the following code:
#include<stdio.h>
int main(){
    int i;
    for(i=0; i<5; i++)
        printf("%d", i)
    return 0;
}
</pre>
```

Your Code

```
1 #include<stdio.h>
2 int main(){
3     int i;
4     for(i=0; i<5; i++)
5         printf("%d", i);
6     return 0;
7 }
```

Program Input (stdin)

Enter input if required...

Output

01234

```
<PRE>
#include<stdio.h>
int main(){
    int i;
    for(i = 1; i < 10; i++){
        printf("%d ", i);
    }
    printf("%d\n", 10);
}
</PRE>
```

Your Code

```
1 #include <stdio.h>
2
3 int main() {
4     for (int i = 1; i < 10; i++) {
5         printf("%d ", i);
6     }
7     printf("%d\n", 10);
8     return 0;
9 }
```

Program Input (stdin)

Enter input if required...

Output

1 2 3 4 5 6 7 8 9 10