

1.1.5. Multiplication Table 07:04

Write a Python program that takes an integer as input and prints the multiplication table for that integer from 1 to 10.

Input Format:

- The first line of input contains an integer that represents the number for which the multiplication table is to be printed.

Output Format:

- Print the multiplication table for the given number in the format:

<number> x <multiplier> = <result>

Note:

- The character "x" is used in the output to represent multiplication.
- Refer to the visible test-cases for more clarity.

Sample Test Cases +

multipl...

1 num=int(input())
2
3 for i in range(1,11):
4 print(f"{num} x {i} = {num*i}")
5
6
7

Average time
0.005 s
4.75 ms

Maximum time
0.008 s
8.00 ms

2 out of 2 shown test case(s) passed
2 out of 2 hidden test case(s) passed

Test case 1 5 ms Debug

Expected output	Actual output
8	8
8 x 1 = 8	8 x 1 = 8
8 x 2 = 16	8 x 2 = 16
8 x 3 = 24	8 x 3 = 24
8 x 4 = 32	8 x 4 = 32
8 x 5 = 40	8 x 5 = 40

Terminal Test cases

1.2.1. Pass or Fail

28:05

Write a Python program that accepts the number of courses and the marks of a student in those courses.

The grade is determined based on the aggregate percentage:

- If the aggregate percentage is greater than 75, the grade is Distinction.
- If the aggregate percentage is greater than or equal to 60 but less than 75, the grade is First Division.
- If the aggregate percentage is greater than or equal to 50 but less than 60, the grade is Second Division.
- If the aggregate percentage is greater than or equal to 40 but less than 50, the grade is Third Division.

Input Format:

- The first input will be an integer n , the number of courses.
- The second input will be n integers representing the marks of the student in each of the n courses, separated by a space.

Output Format:

If the student passes all courses:

- Print the aggregate percentage (formatted to two decimal places).
- Print the grade based on the aggregate percentage.

If the student fails any course (marks < 40 in any course), print:

- "Fail".

Note:

- Aggregate Percentage: Average performance across all courses, calculated by summing all marks and dividing by the number of courses

passorFa...

Submit

```
1 n=int(input())
2 marks=list(map(int,input().split()))
3
4 if any(mark<40 for mark in marks):
5     print("Fail")
6
7 else:
8     percentage=sum(marks)/n
9     print(f"Aggregate Percentage: {percentage:.2f}")
10
11 if percentage>75:
```

Average time

0.004 s

4.50 ms

Maximum time

0.008 s

8.00 ms

5 out of 5 shown test case(s) passed

5 out of 5 hidden test case(s) passed

Test case 1 8 ms Debug

Expected output

4

55 65 78 89

Aggregate Percentage: 71.75

Grade: First Division

Actual output

4

55 65 78 89

Aggregate Percentage: 71.75

Grade: First Division

Test case 2 4 ms

Terminal

Test cases

< Prev

Reset

Submit

Next >

1.2.2. Fibonacci Series 05:45

Write a Python program that uses recursion to print the first n terms of the Fibonacci series.

Input Format:

- A single integer n representing the number of terms to generate.

Output Format:

- A single line containing the first n terms of the Fibonacci sequence, separated by spaces.

Sample Test Cases +

fibonacci.... Submit

1 def fibonacci(n):
2
3 # write the code..
4 if n==1:
5 return 0
6 elif n==2:
7 return 1
8 else:
9 return fibonacci(n-1)+fibonacci(n-2)
10
11

Average time
0.013 s
13.50 ms

Maximum time
0.026 s
26.00 ms

2 out of 2 shown test case(s) passed
2 out of 2 hidden test case(s) passed

Test case 1 0 ms Debug

Expected output
5
0 1 1 2 3

Actual output
5
0 1 1 2 3

Test case 2 5 ms

Terminal Test cases

1.2.3. Pattern - 1

Write a Python program to print a pattern of asterisks in the form of a right-angled triangle.

Input Format:

- The input is an integer, representing the number of rows in the pattern.

Output Format:

- The output should display the pattern of asterisks (*), with each row containing an increasing number of asterisks.

Note: Refer to the displayed test cases for the sample pattern.

Sample Test Cases

rightangl...

```
1 n=int(input())
2
3 for i in range(1,n+1):
4     for j in range(i):
5         print("*",end=" ")
6     print()
```

Average time
0.004 s
4.17 ms

Maximum time
0.006 s
6.00 ms

2 out of 2 shown test case(s) passed
4 out of 4 hidden test case(s) passed

Test case 1 5 ms Debug

Expected output

5
*
* *
* * *
* * * *
* * * * *

Actual output

5
*
* *
* * *
* * * *
* * * * *

Terminal Test cases

1.2.4. Pattern - 2 06:44

Write a Python program to print a right-angled triangle pattern of numbers.

Input Format:

- The input is an integer, representing the number of rows in the pattern.

Output Format:

- The output should display the pattern of numbers separated by space, with each row containing increasing numbers starting from 1 up to the row number.

Note:

- Refer to the displayed test cases for the sample pattern.

Sample Test Cases +

numberP... Submit

Explorer

1 n=int(input())
2
3 for i in range(1,n+1):
4 for j in range(1,i+1):
5 print(j,end=" ")
6 print()
7

Debugger

Average time
0.003 s
3.00 ms

Maximum time
0.004 s
4.00 ms

2 out of 2 shown test case(s) passed
2 out of 2 hidden test case(s) passed

Test case 1 3 ms Debug

Expected output	Actual output
5	5
1	1
1 2	1 2
1 2 3	1 2 3
1 2 3 4	1 2 3 4
1 2 3 4 5	1 2 3 4 5

Terminal

Test cases

1.1.1. Calculate Momentum 06:29

Write a program that accepts the mass of an object (in kilograms) and its velocity (in meters per second), then calculates and displays the momentum of the object. The momentum p is calculated using the formula:

$$p = m \times v$$

where:

- m is the mass of the object (in kilograms).
- v is the velocity of the object (in meters per second).

- Input Format:**
- A single floating-point number representing the mass of the object in kilograms.
 - A single floating-point number representing the velocity of the object in meters per second.

- Output Format:**
- The output will display calculated momentum with appropriate units (kgm/s) (rounded up to 2 decimal places).

Sample Test Cases +

calculate... Submit

Explorer

1 mass=float(input())
2
3 velocity=float(input())
4
5 mom=mass*velocity
6
7 print(f"mom: .2f)kgm/s")

Debugger

Average time 0.006 s 6.50 ms
Maximum time 0.008 s 8.00 ms

2 out of 2 shown test case(s) passed
2 out of 2 hidden test case(s) passed

Test case 1 8 ms Debug

Expected output
5.0
10.0
50.00kgm/s

Actual output
5.0
10.0
50.00kgm/s

Test case 2 6 ms

Terminal Test cases

1.1.2. Conditional Calculation Based on the Number of Digits 08:43

Write a Python program that accepts an integer n as input. Depending on the number of digits in n .

Constraints:
 $1 \leq n \leq 999$

Input Format:
• The input consists of a single integer n .

Output Format:

- If n is a single-digit number, print its square.
- If n is a two-digit number, print its square root (rounded to two decimal places).
- If n is a three-digit number, print its cube root (rounded to two decimal places).
- Else print "Invalid".

Sample Test Cases +

condition... Submit

1 import math
2 n=int(input())
3
4 if n>=1 and n<=9:
5 print(n*n)
6
7 elif n>=10 and n<=99:
8 print(f"{math.sqrt(n):.2f}")
9
10 elif n>=100 and n<=999:
11 print(f"{math.cbrt(n):.2f}")
12
13 else:
14 print("Invalid")

Average time
0.005 s
4.57 ms

Maximum time
0.007 s
7.00 ms

4 out of 4 shown test case(s) passed
3 out of 3 hidden test case(s) passed

Test case 1 7 ms Debug

Expected output

Actual output

99
8181

Terminal Test cases

< Prev Reset Submit Next >

1.1.3. Days between Two Dates 09:19

Write a Python program to calculate number of days between two dates.

- Input Format:**
- The first line contains the first date in the format `YYYY - MM - DD`.
 - The second line contains the second date in the format `YYYY - MM - DD`.

- Output Format:**
- An integer representing the number of days between the given dates.

- Note:**
- The first date should always be considered earlier than the second date.

Sample Test Cases +

noOfDay... Submit

1 from datetime import datetime
2
3 date1=input()
4 date2=input()
5
6 d1=datetime.strptime(date1,"%Y-%m-%d")
7 d2=datetime.strptime(date2,"%Y-%m-%d")
8
9 diff=(d2-d1).days
10
11 print(diff)

Average time
0.011 s
11.60 ms

Maximum time
0.025 s
25.00 ms

2 out of 2 shown test case(s) passed
2 out of 2 hidden test case(s) passed

Test case 1 25 ms Debug

Expected output	Actual output
2014-07-02	2014-07-02
2014-11-02	2014-11-02
123	123

Test case 2 8 ms

Terminal Test cases

1.1.4. Reverse a Number

Write a Python program to reverse the digits of the number and print the reversed number.

Input Format:

- The input is a single integer.

Output Format:

- The output prints a single integer, which is the reversed number.

Sample Test Cases

reverseN... Submit

1 n=int(input())
2
3 rev=int(str(n)[::-1])
4
5 print(rev)

Average time
0.003 s
2.60 ms

Maximum time
0.004 s
4.00 ms

2 out of 2 shown test case(s) passed
3 out of 3 hidden test case(s) passed

Test case 1 3 ms Debug

Expected output
5367
7635

Actual output
5367
7635

Test case 2 2 ms

Terminal Test cases