

Learning-Guided Simulated Annealing for the Capacitated Vehicle Routing Problem

Anonymous submission

Abstract

Introduction

Background and Related Work

Problem Definition

The *Capacitated Vehicle Routing Problem (CVRP)* is defined on a complete undirected graph $G = (V, E)$, where $V = \{0\} \cup \mathcal{C}$ and $E = V \times V$ denote the sets of nodes and edges, respectively. Node 0 corresponds to the central depot, and $\mathcal{C} = \{1, \dots, N\}$ represents the set of N customers.

Each edge $(i, j) \in E$ is associated with a travel cost $c_{ij} = \|\mathbf{p}_i - \mathbf{p}_j\|_2$, the Euclidean distance between the 2D coordinates $\mathbf{p}_i, \mathbf{p}_j \in [0, 1]^2$, satisfying $c_{ij} = c_{ji}$. Each customer $i \in \mathcal{C}$ has a non-negative demand q_i , while the depot has zero demand ($q_0 = 0$). An unlimited fleet of identical vehicles, each with uniform capacity Q , is stationed at the depot; the number of routes m is therefore a decision variable unconstrained from above.

A route $R_k = (0, v_1, v_2, \dots, v_p, 0)$ is a simple cycle starting and ending at the depot, where $\{v_1, \dots, v_p\} \subseteq \mathcal{C}$ denotes the subset of customers served by vehicle k . A *solution* $s = \{R_1, \dots, R_m\}$ consists of a set of m routes. A solution s is *feasible* if and only if it satisfies the following conditions:

1. Each customer is visited exactly once by a single vehicle,

$$\sum_{k=1}^m \mathbf{1}_{\{i \in R_k\}} = 1, \quad \forall i \in \mathcal{C}.$$

2. For every route R_k , the total demand of its customers does not exceed the vehicle capacity Q , i.e.,

$$\sum_{i \in R_k \setminus \{0\}} q_i \leq Q, \quad \forall k = 1, \dots, m.$$

The set of *feasible solutions* is denoted by $\mathcal{F}$.

Let $x_{ij}(s)$ be a binary indicator variable with $x_{ij}(s) = 1$ if edge (i, j) is traversed in any route R_k of s , and $x_{ij}(s) = 0$

otherwise. The objective of the CVRP is to find a feasible solution $s^* \in \mathcal{F}$ that minimizes the total travel cost $C(s)$:

$$s^* = \arg \min_{s \in \mathcal{F}} \left\{ C(s) = \sum_{i \in V} \sum_{j \in V, i < j} c_{ij} x_{ij}(s) \right\}.$$

Proposed Method

Overview

We propose *Learning-Guided Simulated Annealing (LG-SA)*, a hybrid method that combines *Simulated Annealing (SA)* with a lightweight neural policy trained by *Reinforcement Learning (RL)*. Following the Neural Simulated Annealing framework (Correia, Worrall, and Bondesan 2023), the SA component orchestrates the global exploration of the solution space through its acceptance criterion and cooling schedule, while the neural network replaces the single blind component of SA — the uniform move proposal — with a learned, state-dependent proposal distribution. This design contrasts with “heavyweight” improvement architectures such as the Dual-Aspect Collaborative Transformer (Ma et al. 2021), which replace the heuristic logic entirely with a deep encoder: our policy remains deliberately small, so that the guided search retains a per-step cost close to that of classical SA and can be batched over thousands of instances on a single GPU.

Simulated Annealing (Kirkpatrick, Gelatt, and Vecchi 1983) iteratively explores the neighborhood of a current solution. Given a solution s , SA samples a neighboring solution $s' \in \mathcal{N}(s)$ and accepts it according to the *Metropolis criterion*: improving moves are always accepted, while worsening moves are accepted with probability $\exp(-\Delta C/T)$, where $\Delta C = C(s') - C(s)$ is the cost difference and T the current temperature. The temperature decays from an initial value T_0 to a final value T_{final} over the search horizon according to a monotone cooling schedule, which regulates the transition from exploration to exploitation.

Neighboring solutions are produced by a *neighborhood operator* $H : \mathcal{S} \times \mathcal{A} \rightarrow \mathcal{S}$ that maps a solution s and an action $a \in \mathcal{A}(s)$ to the neighbor $s' = H(s, a)$, so that

$$\mathcal{N}(s) = \{H(s, a) : a \in \mathcal{A}(s)\}.$$

In our setting, an action designates a pair of nodes $a = (i, j)$, and H applies a standard pairwise local search move to them (e.g., relocating node i next to node j). The operator is a

This is an anonymized submission for review purposes only. Distribution, citation, or public sharing of this manuscript is strictly prohibited. Copyright and publication details will appear in the final version if accepted.

Algorithm 1 Learning-Guided Simulated Annealing

Input: instance, initial solution s , policy π_θ , operator H **Output:** best solution found s^*

```
1: Initialize  $s^* \leftarrow s$  and temperature  $T \leftarrow T_0$ 
2: while termination criterion not met do
3:   Encode  $s$  into per-node feature vectors
4:   Sample action  $a \sim \pi_\theta(\cdot | s)$  (guided proposal)
5:   Generate candidate  $s' \leftarrow H(s, a)$ 
6:    $s \leftarrow s'$  with probability  $\min(1, e^{-\Delta C/T})$  (Metropolis)
7:   Update  $s^*$  if  $C(s) < C(s^*)$ ; cool  $T$ 
8: end while
9: return  $s^*$ 
```

modular component of the framework; the candidate operators and their comparison are presented in the experimental section.

Whereas classical SA draws a uniformly over $\mathcal{A}(s)$, LG-SA samples it from a policy π_θ conditioned on the current solution:

$$a \sim \pi_\theta(\cdot | s) \quad \text{and} \quad s' = H(s, a) \in \mathcal{N}(s).$$

Everything else — the operator, the Metropolis acceptance, the cooling schedule — is kept from classical SA. The overall procedure is summarized in Algorithm 1 and illustrated in Figure 1.

The Guided Search as a Markov Decision Process

To learn the proposal distribution with RL, we frame the SA loop as a Markov Decision Process. At step t , the *state* s_t is the current feasible solution together with the search meta-information (current temperature and remaining budget), encoded as a set of per-node feature vectors described below. The *action* $a_t = (i, j)$ is the node pair handed to the operator H . The *transition* is the composition of the operator and the stochastic Metropolis acceptance: the next state is $H(s_t, a_t)$ if the move is accepted and s_t otherwise, so the environment dynamics include the acceptance randomness of SA.

The *reward* is derived from the evolution of the solution cost along the search: a move that is accepted and improves the solution receives a positive reward proportional to the (normalized) cost reduction, a rejected move yields no improvement signal, and proposals leading to infeasible neighbors can be penalized. Reward variants that instead emphasize improvements of the best solution found so far, or the final solution quality at the end of the horizon, fit the same framework; the precise shaping is a design choice studied experimentally. The agent thus maximizes the expected cumulative discounted reward over the SA horizon, which aligns the learned proposal with the overall goal of driving the annealing process toward low-cost solutions rather than with any single greedy step.

Node-Centric State Representation

To be applicable to any problem size N and to remain *scale-invariant*, the state is encoded in a *node-centric* fashion:

each node i carries its own local feature vector $\mathbf{x}_i$, and no fixed-size global descriptor is used. The features fall into four groups:

- *Static instance features*: node coordinates, polar coordinates relative to the depot, a depot indicator, and the normalized demand q_i/Q ;
- *Solution topology and local geometry*: the coordinates of the node’s current predecessor and successor in its route, together with local quality signals such as the detour cost incurred by the node at its current position, its distance to the route centroid, and local density statistics of the instance;
- *Capacity status*: the load ratio and remaining slack of the node’s current route, and the node’s own contribution to that load;
- *Search meta-features*: the current (normalized) SA temperature and the fraction of the search budget remaining, which let the policy adapt its behavior to the phase of the annealing schedule.

All features are local to a node and standardized, so the same trained model can be deployed on instances of arbitrary size without retraining. The complete list of features, with their formal definitions, is given in the appendix; their individual contribution is analyzed in the experimental section.

Two-Stage Conditional Policy

The policy must define a distribution over the $\mathcal{O}(N^2)$ node pairs while remaining cheap enough to be evaluated at every SA step. We therefore factorize the joint selection as

$$P(i, j | s) = P(i | s) \cdot P(j | i, s),$$

and implement it with a lightweight two-stage architecture, illustrated in Figure 2. In the first stage, a small network f_θ maps each feature vector to a scalar score $z_i = f_\theta(\mathbf{x}_i)$, and the first node is sampled from the softmax distribution over these scores:

$$i \sim P(\cdot | s) = \text{softmax}(\{z_i : i \in \mathcal{C}\}).$$

In the second stage, the representation of the selected node i is combined with that of every other node j , and a second network g_θ assigns a conditional score $z_{ij} = g_\theta(\mathbf{x}_i, \mathbf{x}_j)$ from which the partner is sampled:

$$j \sim P(\cdot | i, s) = \text{softmax}(\{z_{ij} : j \in \mathcal{C}\}).$$

Both stages are built from small multilayer perceptrons applied identically to every node, which makes the policy permutation-equivariant. The second stage can additionally be conditioned on cheap pairwise descriptors of the candidate move (e.g., the exact cost of the move joining i and j), computed only for the selected i .

This factorization also provides a natural hook for the capacity constraints: once i is selected, the partners j for which $H(s, (i, j))$ would be infeasible are masked out of the second-stage distribution, so every proposed neighbor is feasible at the price of $\mathcal{O}(N)$ feasibility checks per step. Alternative constraint-handling strategies are discussed and compared in the experimental section.




Figure 1: The LG-SA loop. Classical SA components (gray) are kept unchanged: the operator H , the Metropolis acceptance, and the cooling schedule. The only modified block is the move proposal (orange): the current solution is encoded into per-node feature vectors and a learned policy samples the node pair $a_t = (i, j)$, replacing the uniform sampling of classical SA.




Figure 2: Two-stage conditional sampling of the node pair (i, j) , shown on a toy route of three customers. Stage 1: every node’s feature vector is scored independently by a shared network f_θ and the first node i is sampled from the softmax over the scores. Stage 2: the representation of the selected node i is combined with that of every candidate partner j and scored by a second network g_θ ; infeasible partners are masked out before the softmax, and j is sampled from the conditional distribution. The factorization $P(i, j) = P(i) \cdot P(j | i)$ makes each proposal $\mathcal{O}(N)$.

Since the conditional network is evaluated only for the single selected first node, each proposal costs $\mathcal{O}(N)$ — as opposed to the $\mathcal{O}(N^2)$ cost of scoring all pairs jointly — and the whole step is expressed as batched tensor operations, allowing thousands of instances to be advanced in parallel on one GPU.

Training with PPO

The policy is trained with *Proximal Policy Optimization* (PPO) (Schulman et al. 2017), the standard on-policy actor-critic algorithm. Training alternates between a *collection* phase, in which the current policy runs the full LG-SA loop of Algorithm 1 on a large batch of freshly generated instances in parallel and stores every transition (s_t, a_t, r_t) , and an *update* phase, in which the stored episodes are replayed for several optimization epochs. Advantages are estimated with Generalized Advantage Estimation, and the actor maximizes the usual clipped surrogate objective with an entropy bonus; we refer to Schulman et al. (2017) for the standard formulation and only detail our departures from it.

The critic V_ϕ is a separate permutation-invariant network: it encodes each node feature vector independently, pools the embeddings across nodes into a fixed-size summary, and maps this summary to a scalar value estimate. Keeping the

actor and critic distinct prevents interference between the policy and value representations.

Our implementation departs from standard PPO in three ways, all aimed at stabilizing training on the long and noisy SA horizon:

- *Hybrid clipping–KL objective.* Rather than choosing between the clipped surrogate and the KL-penalized objective, we use both: an adaptive Kullback–Leibler penalty $\beta_{\text{KL}} D_{\text{KL}}(\pi_{\theta_{\text{old}}} || \pi_\theta)$ is added to the clipped loss, and its coefficient is doubled or halved after each update epoch depending on whether the measured divergence leaves a band around a target value. This soft trust region allows many optimization epochs on each collected batch without catastrophic policy drift.
- *KL-coupled learning rate.* The same divergence signal modulates the actor’s learning rate within fixed bounds — gently decreased when the policy moves too fast, increased when it stalls — so the effective step size tracks the trust region automatically.
- *Regularized critic.* The value loss is clipped, mirroring the actor’s trust region, and augmented with a gradient penalty that encourages a smooth (near-Lipschitz) value landscape; we found this useful given that consecutive

states differ by a single local move whose acceptance is itself stochastic.

Experimental Results

Experimental Setup

Benchmark. All experiments reported in this section use the uniform benchmark distribution of Nazari et al. (2018): depot and customer coordinates drawn uniformly in $[0, 1]^2$, demands drawn uniformly in $\{1, \dots, 9\}$, and a size-dependent vehicle capacity ($Q = 20, 30, 40, 50$ for $N = 10, 20, 50, 100$). For each size we pre-generate a fixed test set of 10,000 instances that is reused by every configuration, so that all comparisons are paired at the instance level. Unless stated otherwise, results are reported at $N = 100$.

Evaluation protocol. A trained model is evaluated by running the LG-SA loop over the full test set in parallel on a single GPU, starting from random feasible solutions and running 10,000 SA steps per instance with half-precision inference. We report the mean final routing cost over the 10,000 instances and the wall-clock time of the whole batch. Classical (blind) SA — uniform proposals with the same operator, step budget, and cooling schedule — is evaluated under the identical protocol, as is an OR-Tools baseline with a fixed per-instance time limit (Furnon and Perron 2024).

Statistical protocol. Every configuration is trained under 3 random seeds (5 for confirmation and headline runs), and we report means over seeds. Comparisons are *seed-paired*: competing configurations share their training seeds, and we examine the mean and the sign consistency of the per-seed differences. Significance is judged against a per-batch *noise floor* — the pooled seed-to-seed standard deviation of the stable arms of the batch at hand — rather than against a single global threshold, because the seed variance is itself configuration-dependent: unstable arms (e.g., sparse rewards or structured initializations) inflate the pooled spread and would mask real effects measured elsewhere. Each comparison below states the floor it is judged against; a difference under its floor is treated as a tie.

Sequential validation protocol. The design space of LG-SA — operator, feasibility strategy, features, architecture, reward, annealing parameters, initialization, optimization budget, curriculum — is far too large for a full factorial study. We therefore validate it by coordinate descent: the axes are swept one at a time in order of expected leverage, and the winner of each sweep is frozen into the configuration before the next axis is examined, so later sweeps inherit all earlier decisions. Targeted follow-up batches probe the interactions we consider most at risk (e.g., the construction of the minimal feature set and the curriculum mechanism ablation), and the complete winning configuration is re-trained from scratch with 5 seeds as a final confirmation.

Local Search Operators and Feasibility Strategies

The first axis fixes the foundational search mechanics: the operator H and the way capacity constraints are enforced.

Operators. We consider three standard pairwise operators, illustrated in Figure 5 (appendix):

- *Swap*: exchanges the positions of nodes i and j , within a route or across routes;
- *Insertion (relocation)*: removes node i from its current position and reinserts it immediately after node j ;
- *2-opt / 2-opt**: for intra-route pairs, reverses the path segment between i and j ; for inter-route pairs, exchanges the route suffixes following i and j (tail swap).

The operator is fixed for a given model: the policy is trained to propose moves for one operator, and learns a distribution tailored to it.

Feasibility strategies. Under capacity constraints, many actions produce an infeasible neighbor $H(s, a) \notin \mathcal{F}$ — the central obstacle in extending neural SA from unconstrained problems to the CVRP. We compare three ways of keeping the search inside $\mathcal{F}$:

- *Proactive filtering (action masking)*. The policy is restricted to the feasible subset $\mathcal{A}_f(s) = \{a : H(s, a) \in \mathcal{F}\}$ by masking infeasible actions before sampling. The conditional factorization makes this cheap: the first node i is selected freely, and only then are the feasible partners $\{j : H(s, (i, j)) \in \mathcal{F}\}$ computed and used to mask the second stage — $\mathcal{O}(N)$ checks per step instead of $\mathcal{O}(N^2)$. Every proposal is feasible by construction; since the fleet is unlimited, a node can always open a new route, so the feasible set is never empty.
- *Reactive rejection*. The policy samples any action from its learned distribution and the resulting neighbor is checked afterwards: if $s' \notin \mathcal{F}$, the move is rejected and the current solution retained. This avoids the filtering overhead but can waste both compute and learning signal when many sampled moves are infeasible.
- *Indirect representation*. Feasibility is delegated to the representation: the solution is encoded as an unconstrained permutation of the customers, the policy modifies the permutation, and a deterministic *greedy split* heuristic packs it back into capacity-feasible routes (Vidal 2016). Every state is feasible by construction and the policy never handles constraints, but the reconstruction runs at every step and its cost grows with the problem size.

We train one policy for each of the nine operator–strategy combinations under the common protocol (3 seeds per cell, 27 runs); the winning pairing is carried unchanged through all subsequent experiments. Table 1 reports the full grid; the complete set of diagnostic plots (heatmap, cost–compute trade-off, per-seed spread) is given in the appendix.

Results. Insertion with proactive masking is the best cell (16.68) and *dominates*: it attains the lowest cost, the lowest seed variance (std 0.03, against up to 3.0 for the swap cells), and is among the cheapest in compute (173 s for the full 10,000-instance evaluation). The two factors do not interact perversely — the best operator and the best strategy also combine into the best cell. Averaged over feasibility strategies, insertion (20.00) beats 2-opt (22.02) and swap (26.03): relocating a single node is the move that best matches a

Operator	Masking	Indirect	Rejection
Insertion	16.68 ± 0.03	16.97 ± 0.04	26.36 ± 0.71
Swap	19.50 ± 1.54	22.82 ± 1.36	35.75 ± 3.04
2-opt(*)	18.93 ± 0.09	21.29 ± 0.39	25.84 ± 0.42

Table 1: Operator $\times$ feasibility study: mean final cost $\pm$ seed std at $N = 100$ (10^4 SA steps, 10,000 instances, 3 seeds; all runs start from mean cost 57.87). Insertion with proactive masking wins and is also the most stable cell.

learned pointer to a promising node pair, whereas the value of a swap or a segment reversal depends more delicately on both endpoints simultaneously, making the credit assignment noisier — visible in the swap column’s large seed variance. Averaged over operators, masking (18.37) edges out the indirect representation (20.36), while reactive rejection is far behind (29.31) and is uniformly the worst choice for every operator: discarding infeasible proposals wastes both search budget and learning signal, and the policy must spend capacity learning the feasibility boundary instead of move quality. The indirect (greedy-split) representation is competitive in cost for insertion but pays the reconstruction at every step; 2-opt under masking is the slowest cell (301 s, about $1.7\times$ the rest) because suffix exchanges require more expensive feasibility checks, yet still loses to insertion on quality — its extra compute buys nothing.

Adopted configuration. All subsequent experiments use the *insertion* operator with *proactive masking*. The decision is robust: the runner-up (insertion with the indirect representation, 16.97) points to the same operator, so even if the two feasibility strategies were statistically tied the operator choice would stand.

State Feature Ablation

The node representation is validated with three complementary protocols, all trained on the winning operator–feasibility pairing and all operating on the feature groups defined in the appendix. *Leave-one-out* removes a single group from the full set and measures the degradation; *thematic* ablations remove a whole correlated cluster at once (e.g., all three density scales, or all capacity signals), exposing groups whose members are individually redundant but collectively useful; *isolation* adds a single group to a minimal base containing only the static and meta features, measuring its standalone value. From these measurements we construct candidate minimal feature sets — keeping groups whose removal hurts, dropping those that fail both the leave-one-out and the isolation test, and keeping one representative per correlated cluster — and confirm the candidates seed-paired against the full set. Finally, the conditional pair descriptors of the second stage (edge distance-ranks and exact insertion cost, defined in the appendix) are evaluated on top of the chosen set, individually and combined.

Reference points. The full 13-group representation reaches a mean final cost of 16.678 ± 0.026 , against 20.084 ± 0.049 for the static+meta base: the solution-dependent fea-

Group	Δ_{LOO}	Δ_{iso}
Static	+3.84 ± 0.85	(in base)
Detour Δ_i	+0.60 ± 0.08	+2.60 ± 0.07
Topology	+0.46 ± 0.08	+2.19 ± 0.15
Meta	+0.31 ± 0.08	(in base)
Slack $S_{r(i)}$	+0.12 ± 0.04	−0.42 ± 0.31
Centroid $d_{i,\text{cent}}$	+0.10 ± 0.08	+0.48 ± 0.06
Density $\mu_{N/3}$	+0.09 ± 0.12	−0.08 ± 0.06
Neighbor ranks	+0.03 ± 0.05	+1.26 ± 0.09
Relative demand	+0.03 ± 0.09	−0.01 ± 0.02
Density μ_5	+0.01 ± 0.01	−0.02 ± 0.09
Load share η_i	+0.01 ± 0.04	−0.42 ± 0.10
Density $\mu_{N/10}$	−0.03 ± 0.07	−0.09 ± 0.09
Load ratio $L_{r(i)}$	−0.06 ± 0.08	−0.44 ± 0.36

Table 2: Single-group signals, sorted by marginal value. Δ_{LOO} : cost increase when the group is removed from the full set (positive = useful at the margin). Δ_{iso} : cost reduction when the group alone is added to the static+meta base (positive = useful standalone). Bold: exceeds the noise floor. Static and meta belong to the isolation base and have no standalone entry.

tures cut cost by 3.41 routing units ($\approx 17\%$). All configurations are trained with 3 seeds and evaluated seed-paired on the common test set; the pooled within-configuration seed std, $\sigma \approx 0.18$, serves as the significance floor for this sweep (it is inflated by the single high-variance no-static configuration; the typical seed std is ≈ 0.05).

Single-group signals. Table 2 summarizes the leave-one-out and isolation measurements (full plots in the appendix). Four groups clear the noise floor at the margin: static (whose removal is catastrophic, +3.84), detour, topology, and meta. In isolation, the geometric and relational signals carry almost all the standalone value — detour (+2.60), topology (+2.19), neighbor ranks (+1.26), centroid (+0.48) — while the three capacity signals *hurt* when added alone to the base, and no density scale helps on its own. Thematic removals confirm the cluster picture (appendix table): the relational and geometry themes each cost ≈ 0.6 when removed, capacity +0.34, density only +0.15. Applied mechanically, the single-feature pruning rule would therefore retain only six groups (static, meta, topology, neighbor ranks, detour, centroid) and drop the density, capacity, and relative-demand groups.

Joint validation overturns single-group pruning. Because the leave-one-out and isolation protocols measure *single-group* signals, they are blind to collective value. The candidate sets were therefore re-trained head-to-head at 5 seeds (Table 3), on a batch whose noise floor is clean ($\sigma \approx 0.057$). The verdict reverses the pruning rule: every down-pruned set is significantly worse than the full set, and cost degrades monotonically as groups are removed (core5 $\rightarrow$ set7 $\rightarrow$ full). The smallest penalty (set7, +0.337) is already $6\times$ the noise floor — the density and capacity groups that looked redundant one at a time contribute real joint value. The reversal is not about feature *count*: dropping the load ratio $L_{r(i)}$ alone is a statistical tie with the full set (-0.035 ± 0.106 at 5 seeds,

Set	Groups	Cost	Time (s)	Δ vs. full
no load ratio	12	16.648	173	-0.035 ± 0.106
full set	13	16.683	173	ref
set7	7	17.020	129	$+0.337 \pm 0.091$
nodepct6	6	17.088	121	$+0.405 \pm 0.077$
centroid6	6	17.100	122	$+0.417 \pm 0.049$
core5	5	17.162	115	$+0.479 \pm 0.075$

Table 3: Best-set validation at 5 seeds, seed-paired against the full set (noise floor $\sigma \approx 0.057$; per-set seed std between 0.04 and 0.07). *core5* = static, meta, topology, neighbor ranks, detour; *set7* adds centroid and load share. Every coarsely pruned set is significantly worse; the only quality-neutral trim is dropping the load ratio alone.

independently reproduced at 3 seeds with -0.059 ± 0.076), whereas additionally dropping the neighbor ranks costs an incremental $+0.200 \pm 0.066$ — several times the floor. Pruning buys only compute: *set7* trades 2% solution quality for a 25% speedup, an option under a tight inference budget but not the quality-optimal choice.

Conditional pair descriptors. On top of the retained set, the two second-stage conditioning signals were swept standalone and as a 2×2 cross-product (3 seeds, noise floor $\sigma \approx 0.071$). Both *hurt*: enabling the distance-rank descriptor costs $+0.14 \pm 0.11$ and the insertion-cost descriptor $+0.18 \pm 0.07$, each adding ≈ 20 s of wall-clock; the 2×2 main effects match the standalone deltas ($+0.13$ and $+0.17$) and the interaction is negligible (-0.02 , within the floor), so the effects are additive and the both-on cell is the worst. The extra signal apparently distracts more than it informs: the per-node features already encode the local geometry the descriptors summarize.

Adopted configuration. We retain the full 13-group feature set (the load ratio may be dropped at no quality cost, but it brings no compute benefit either) and keep both conditional pair descriptors disabled.

Policy and Critic Architecture

The value proposition of the policy is to stay light, so this axis asks whether any cheap capacity or structure upgrade pays for itself; it is swept in four steps, each inheriting the previous winner.

Critic. The baseline critic scores each node with a small MLP and averages the scalar outputs into the value estimate, which makes V_ϕ a linear functional of the mean node representation. The alternative is the multi-statistic variant of the training section: nodes are encoded into embeddings, pooled with mean, max, and standard deviation, and mapped to the value by a nonlinear head — so dispersion information (clustered against scattered instances) survives the pooling.

Capacity. The embedding width and the number of hidden layers of the scoring networks are swept jointly, trading representational capacity against per-step inference cost.

Variant	Cost	Time (s)
<i>Critic (training-only — deployment unaffected)</i>		
mean-pooled MLP (ref)	16.693	—
multi-statistic	16.635	—
<i>Actor capacity</i>		
32×1 (ref)	16.637	173
64×2 (largest cell)	16.589	238
<i>Actor structure</i>		
independent scorers (ref)	16.633	180
+ pooled global context	17.143	255
shared encoder (best cell)	19.830	196
<i>Distribution shaping</i>		
both off (ref)	16.630	175
logit clipping $C = 10$	16.457	177
learnable temperature	16.580	176
clipping + temperature	16.481	179

Table 4: Architecture study: mean final cost over 3 seeds per cell, with the evaluation wall-clock where the variant affects deployment; each block is read against its own reference row (bold = adopted changes). Full grids, seed-paired deltas, and noise floors are given in the appendix.

Structure. The incumbent actor applies two independent MLPs directly to the raw feature vectors (Figure 2). We compare it with a *shared-encoder* variant (Figure 20, appendix): each node is encoded once into an embedding $\mathbf{h}_i$, and both stages are lightweight heads over the shared embeddings, the conditional score being computed either by a concatenation head over $[\mathbf{h}_j \parallel \mathbf{h}_i]$ or as a bilinear compatibility $\mathbf{q}^\top \mathbf{k} / \sqrt{d}$ between a query built from the selected node and a key per candidate. Orthogonally, a *global context* option pools the node representations into a summary g (mean, max, and standard deviation) appended to the input of both stages — the cheapest way to give the per-node scores access to instance-level information, at one pooling operation per step.

Distribution shaping. Finally, two flags tame the proposal distribution without adding capacity: *logit clipping*, which bounds the logits to $C \tanh(z)$ before the softmax so the distribution cannot collapse to a near-deterministic choice (Kool, van Hoof, and Welling 2019), and a *learnable softmax temperature* per stage.

Results. Table 4 summarizes the four axes; each comparison is judged against its own batch’s pooled-seed-std noise floor, with the seed-paired deltas reported in the appendix. Two changes help, and neither adds capacity to the actor. The multi-statistic critic lowers cost by 0.058 routing units (floor 0.027) and is free at deployment, since the critic is discarded after training. Logit clipping is the only actor-side win: bounding the logits to $10 \tanh(z)$ improves all three seeds, a seed-paired -0.173 ± 0.059 against a floor of 0.072, at unchanged compute. Everything that enlarges or rewires the actor is at best neutral. The capacity grid is a plateau: the full spread from the smallest to the largest network is 0.079, no cell clears the floor (0.053) against the 32×1 incumbent, and wall-clock rises by up to 38%; the faint monotone trend

favors width over depth (main-effect spans 0.069 against 0.019). The pooled global context worsens *every* seed (paired $+0.508 \pm 0.496$, one seed degrading by $+1.08$) while adding 48% wall-clock — the instance-level summary distracts the per-node scores rather than informing them. The shared encoder is not a plateau but a cliff: all four cells of its grid land $+3.20$ to $+3.53$ above the reference, a 19% quality loss and more than $18\times$ that batch’s noise floor (0.176), so forcing both selection stages through one trunk destroys the pair-scoring ability at this problem size; within the shared family the bilinear head beats concatenation (-0.31) and the context toggle is neutral, but the best shared cell remains $+3.20$ away. Finally, the learnable temperature is within noise on its own (-0.050 ± 0.069) and slightly degrades the clipped configuration when stacked (16.481 against 16.457, with doubled seed variance) — one more trainable knob for PPO to destabilize.

Adopted configuration. The retained policy keeps the incumbent actor on every structural axis — two independent per-stage scoring MLPs, 32-dimensional embeddings with a single hidden layer, no pooled context — and changes exactly two things: the multi-statistic critic and logit clipping at $C = 10$ with a fixed temperature. The pattern is consistent: at $N = 100$ the actor’s capacity and wiring are not the bottleneck; the leverage lies in the quality of the value estimate and in keeping the proposal distribution from collapsing — exactly the failure mode a near-deterministic policy induces inside a Metropolis loop, which needs proposal diversity to explore.

Reward Shaping

Motivation. The reward decides which behavior PPO reinforces: per-step improvement, new records, or only the final outcome. Because the SA loop already owns part of the exploration — worsening moves are accepted by the Metropolis criterion, not chosen by the policy — it is not obvious how much of the trajectory should be credited to the actor.

Candidates. Let Δ_t denote the cost improvement realized by the executed transition (zero when the move is rejected) and B_t the best cost found so far. The compared variants are: *immediate*, $r_t = \Delta_t$ with a fixed penalty for infeasible proposals; *acceptance-aligned*, which rewards accepted improving moves by Δ_t but deliberately assigns zero to accepted worsening moves (exploration is SA’s responsibility, not the policy’s fault) and a small constant penalty to rejected proposals; *best-so-far*, $r_t = \max(0, B_{t-1} - B_t)$, which only rewards new records; *terminal*, a single end-of-episode reward equal to the relative improvement over the initial cost; *mixtures*, either a fixed convex combination of the immediate and best-so-far signals or a scheduled interpolation that starts from the dense acceptance-aligned signal early in training and shifts toward the sparser best-so-far or terminal signals; and *step-penalty*, a negative per-step reward proportional to the current best cost, pressuring fast descent.

Results. Table 5 splits the nine candidates into two regimes (noise floor 0.042, the pooled seed std of the stable cluster). Every reward built on dense per-step improvement lands in a

Reward	Cost
immediate (incumbent)	16.459
fixed mixture	16.460
sched. $\rightarrow$ best-so-far	16.503
best-so-far	16.510
acceptance-aligned	16.516
sched. $\rightarrow$ terminal	16.531
step-penalty (const.)	17.198
step-penalty (init)	17.549
terminal	19.411

Table 5: Reward ablation: mean final cost over 3 seeds, sorted; the rule separates the dense stable cluster from the sparse and penalty-based rewards. Wall-clock is flat across arms (173–177 s). Per-seed diagnostics in the appendix.

Schedule	Cost
geometric (incumbent)	16.460
step decay	16.473

Table 6: Cooling-schedule comparison: mean final cost over 3 seeds.

band only 0.07 wide: the incumbent immediate reward is best at 16.459, the fixed mixture is a statistical tie (seed-paired $+0.001 \pm 0.042$), and the acceptance-aligned, best-so-far, and scheduled variants trail by at most 0.07 — the actor is largely insensitive to the exact shaping as long as the signal is dense. Removing the per-step credit is catastrophic: the terminal reward loses 2.95 routing units with seed swings of almost a full unit, and the step-penalty schemes lose 0.7 to 1.1 with similarly unstable training — the penalty fights the improvement signal instead of complementing it (Figures 23 and 24, appendix).

Conclusion. The immediate reward is retained. What matters is not the exact shaping but density: every variant that keeps per-step credit ties the incumbent within a few hundredths, and every variant that removes it fails to train a useful actor.

Annealing Schedule

Motivation. The cooling schedule controls how quickly the acceptance criterion hardens from tolerant exploration to strict descent; a learned proposal could in principle prefer a different cooling profile than blind SA.

Candidates. Both arms share the same temperature range (T_0, T_{final}) and differ only in the shape of the decay: *geometric*, $T_{k+1} = \alpha T_k$, against a piecewise-constant *step* schedule that drops the temperature at one half, two thirds, and three quarters of the horizon.

Results and conclusion. The comparison is a statistical tie (Table 6): the seed-paired gap is -0.013 ± 0.034 against a noise floor of 0.044, with the per-seed sign split and identical wall-clock (Figure 25, appendix). Once its endpoints

Train \ Test	Metropolis	Accept-all
Metropolis (incumbent)	16.459	16.578
Accept-all	16.432	16.526

Table 7: Metropolis 2×2 cross: mean final cost over 3 seeds; rows = training setting, columns = deployment setting. Per-seed effects in the appendix (Figure 26).

are fixed, the loop is insensitive to the shape of the cooling curve; the geometric schedule is kept.

Metropolis Acceptance

Motivation. Once the proposal is learned, does the stochastic acceptance still earn its keep — and should the policy be trained with it in the loop? A 2×2 ablation enables or disables the Metropolis criterion independently at training and at test time (the “off” arm accepts every proposed move), quantifying whether the learned proposal replaces the stochastic acceptance or complements it.

Results. The cross (Table 7) gives the sharpest verdict of this section: the criterion earns its keep at deployment, not at training. Removing the acceptance at test time costs $+0.119 \pm 0.025$ over the incumbent-trained actor and $+0.094 \pm 0.009$ over the greedy-trained one — several times the 0.034 floor and unanimous across seeds — whereas the training-time flag is within noise at the standard test-on deployment ($+0.027 \pm 0.045$, sign split). Only when deploying greedily does greedy training pay ($+0.052 \pm 0.050$), a mild train/test-consistency effect outside the regime we deploy in.

Proposal mode at inference. In standard RL applications, trained policies are often exploited greedily by selecting the most probable action. Our framework deviates from this practice: since the policy acts as the proposal distribution of an SA step, we retain stochastic sampling, $a_t \sim \pi_\theta(\cdot | s_t)$, at inference as well. A greedy policy would repeatedly propose the same “best” move, collapsing the diversity that the Metropolis criterion needs to balance exploration and exploitation.

Conclusion. The solver always runs with the Metropolis criterion on: the learned proposal complements the stochastic acceptance rather than replacing it, and a greedy descent over the learned moves gets stuck in worse local optima whatever trajectories the actor was trained on. The training-time flag is a wash and stays on.

Solution Initialization

Motivation. Every episode starts from a constructive solution, both during training and at deployment, and the two roles need not agree: at training time the construction fixes the state distribution the policy learns from, while at deployment it is a free knob of the solver.

Candidates. Training starts from a single constructive heuristic — random assignment, nearest neighbor, sweep, or single-customer routes — or from a progressively introduced mixture of all four, which exposes the policy to qualitatively

Training construction	Cost
random (incumbent)	16.460
mixed	16.682
sweep	17.548
single-customer	17.736
nearest neighbor	19.228

Table 8: Training-construction effect: mean final cost over 3 seeds at the standard random-start deployment. The full train $\times$ test cross is given in the appendix (Table 18).

different regions of the solution space. Every trained policy is additionally cross-tested from all five test-time constructions (the four above plus Clarke–Wright savings), measuring how much the final quality depends on the starting point.

Results. The cross reverses the usual intuition that the starting solution is a deployment knob. At deployment the construction barely matters: the incumbent actor lands in a band only 0.160 wide across all five test constructions, although their construction costs span 16.4 to 104.0 — ten thousand annealing steps wash the starting point out almost entirely, the one real edge being a start from the Clarke–Wright savings solution, which already sits at the fixed point of the search (-0.153 ± 0.021 against the 0.063 stable floor). At training time the construction is instead decisive (Table 8): actors trained from the structured heuristics lose 1.1 to 2.8 routing units at the standard deployment, unanimously and far past even the global 0.395 floor, and the matched train/test diagonal is worse than the random-trained actor everywhere — so the failure is not a train/test mismatch (Figure 28, appendix). Random construction wins by coverage: starting from the worst solutions forces the policy to learn moves over the widest state distribution, which then transfer to every start. Mixing all four constructions into training only dilutes that coverage, a small but unanimous regression ($+0.222 \pm 0.084$ against the 0.063 floor).

Conclusion. Training keeps purely random constructions; the deployment start is a free choice, with a small extra margin available from a Clarke–Wright start.

Optimization Hyperparameters

The optimization knobs — actor and critic learning rates, entropy coefficient, and the rollout length (the number of SA steps collected per PPO update, which sets the horizon over which advantages are estimated) — are swept on the frozen configuration. The number of PPO epochs per collected batch is examined last and re-visited jointly with the curriculum in the final model, since the two interact.

Curriculum Learning

Training episodes are much shorter than the search budgets used at deployment, so a policy trained only from raw constructive solutions rarely visits the fine-grained regime near local optima that dominates the end of a long search. The curriculum closes this gap by moving the *starting point*: before each collection phase, the batch of instances is first warmed




Figure 3: Curriculum ramp: the warm-up depth t_{init} grows from 0 to the warm-up strength ξ_{CL} over E training epochs, following a linear or sigmoid schedule, and stays saturated afterwards.

up by the current policy for t_{init} steps, and t_{init} grows over training from 0 to a maximum warm-up strength ξ_{CL} over E epochs, following a linear or sigmoid ramp (Figure 3). Early in training the policy thus learns to repair poor solutions; later it increasingly learns to improve already-refined ones. A further variant draws a per-instance depth $d_i \sim \mathcal{U}\{0, \dots, t_{\text{init}}\}$ instead of warming every instance to the same depth, so that a single batch covers the entire spectrum from raw initializations to deeply improved solutions.

The curriculum is validated with its own sequential protocol: (0) a multi-seed no-curriculum baseline, which also provides the noise floor used throughout this section; (1) a go/no-go comparison of a neutral mid-range curriculum against that baseline; (2) schedule shape (sigmoid against linear); (3) warm-up strength ξ_{CL} ; (4) ramp duration E ; (5) sigmoid steepness; (6) a mechanism ablation opposing the ramped warm-up to a constant warm-up of equal budget, separating the contribution of the progression itself; and (7) the per-instance random depth, hypothesized to pay off in robustness and out-of-distribution behavior more than in the in-distribution headline. The winning curriculum is confirmed against the baseline with 5 seeds.

Final Model and Comparison with Baselines

All component winners, the best curriculum, and the tuned PPO budget are combined into the final model, trained with 5 seeds; the best checkpoint provides the headline numbers. We compare it against blind SA under matched conditions (same operator, budget, and schedule) and against the OR-Tools baseline, and we report the mean cost as a function of the SA step budget from 10^2 to 10^6 steps to characterize the anytime behavior of the guided search.

Generalization and Scalability

Finally, we probe how far the node-centric representation carries across problem scales: models trained at each size are cross-tested at every other size, and the final model is evaluated on instances well beyond its training size with the same checkpoint, reporting both solution quality and runtime scaling.

Conclusion

References

- Correia, A. H. C.; Worrall, D. E.; and Bondesan, R. 2023. Neural Simulated Annealing. In *Proceedings of The 26th International Conference on Artificial Intelligence and Statistics*, 4946–4962. PMLR. ISSN: 2640-3498.
- Furnon, V.; and Perron, L. 2024. OR-Tools Routing Library.
- Kirkpatrick, S.; Gelatt, C. D.; and Vecchi, M. P. 1983. Optimization by Simulated Annealing. 220.
- Kool, W.; van Hoof, H.; and Welling, M. 2019. Attention, Learn to Solve Routing Problems! In *International Conference on Learning Representations*.
- Ma, Y.; Li, J.; Cao, Z.; Song, W.; Zhang, L.; Chen, Z.; and Tang, J. 2021. Learning to Iteratively Solve Routing Problems with Dual-Aspect Collaborative Transformer. In *Advances in Neural Information Processing Systems*, volume 34, 11096–11107. Curran Associates, Inc.
- Nazari, M.; Oroojlooy, A.; Snyder, L.; and Takac, M. 2018. Reinforcement Learning for Solving the Vehicle Routing Problem. In *Advances in Neural Information Processing Systems*, volume 31. Curran Associates, Inc.
- Schulman, J.; Wolski, F.; Dhariwal, P.; Radford, A.; and Klimov, O. 2017. Proximal Policy Optimization Algorithms. ArXiv:1707.06347 [cs].
- Vidal, T. 2016. Technical note: Split algorithm in $O(n)$ for the capacitated vehicle routing problem. *Computers & Operations Research*, 69: 40–47.

Appendix Overview

The appendices mirror the order of the experimental section. *State Feature Definitions* gives the formal definition of every component of the node feature vector. The four *Full Results* appendices then collect, for each validation axis of the main text — operators and feasibility, features, architecture, and the search-loop components (reward, annealing, acceptance, initialization) — the complete grids, secondary tables, and per-seed diagnostic plots behind the summary tables. Two conventions are shared throughout: every comparison is seed-paired (both arms are trained on the same seeds), and every delta plot shows the per-seed differences against a shaded band marking that batch’s noise floor — an effect is trusted only if it clears the band with a consistent sign across seeds. Each full-results appendix opens with the mapping from the internal configuration names appearing in the plot legends to the paper terminology.

Appendix: State Feature Definitions

This appendix defines every component of the node feature vector $\mathbf{x}_i$ used by the policy and the critic. Throughout, $\text{prev}(i)$ and $\text{succ}(i)$ denote the nodes immediately before and after i in the current visiting order, $r(i)$ the route currently serving i , $Q_{r(i)}$ the total load of that route, and $d(\cdot, \cdot)$ the Euclidean distance. Figure 4 illustrates the geometric quantities, and Table 9 summarizes the groups and their dimensions. All features are normalized to comparable ranges,




Figure 4: Geometric features attached to a node i (orange) within its current route. The detour Δ_i measures the extra length caused by visiting i between its neighbors; (θ_i, d_{i0}) locate i in polar coordinates around the depot; $d_{i,\text{cent}}$ measures how far i lies from the center of gravity of its own route.

and each is computed locally at node i : the encoding contains no fixed-size global descriptor, which is what makes the representation applicable to any instance size.

Static instance features (6). The 2D coordinates $\mathbf{p}_i = (p_i^x, p_i^y) \in [0, 1]^2$; a depot indicator $\mathbf{1}_{\{i=0\}}$; the polar angle θ_i of the node around the depot; the distance to the depot d_{i0} , min-max normalized per instance; and the demand normalized by the vehicle capacity, q_i/Q . These features depend only on the instance, not on the current solution.

Route topology (4). The coordinates $\mathbf{p}_{\text{prev}(i)}$ and $\mathbf{p}_{\text{succ}(i)}$ of the node’s current neighbors in the visiting order. They give the policy direct access to the local shape of the route around each node.

Neighbor distance-ranks (2). For each of $\text{prev}(i)$ and $\text{succ}(i)$, the rank of that neighbor in the list of all nodes sorted by distance from i , normalized to $[0, 1]$ (the nearest node has rank ≈ 0). A well-placed node is linked to low-rank neighbors; a high rank signals a locally poor connection, independently of the absolute scale of the instance.

Relative demand (1). The demand normalized by the largest demand in the instance, $q_i / \max_{j \in C} q_j$, complementing q_i/Q with a signal that is invariant to the capacity level.

Spatial density (3). The mean distance from i to its k nearest neighbors, evaluated at three scales: $k = 5$, $k = \lceil N/10 \rceil$, and $k = \lceil N/3 \rceil$. These static statistics distinguish nodes in dense clusters from isolated ones.

Local solution quality (2). The *detour cost*

$$\Delta_i = d(\text{prev}(i), i) + d(i, \text{succ}(i)) - d(\text{prev}(i), \text{succ}(i)),$$

i.e., the extra length the tour pays for visiting i at its current position (equivalently, the saving obtained by removing it); and the distance $d_{i,\text{cent}}$ from i to the centroid of the nodes of its route, which flags spatial outliers assigned to the wrong route.

Capacity status (3). The load ratio of the node’s route, $L_{r(i)} = Q_{r(i)}/Q$; the remaining slack, $S_{r(i)} = (Q - Q_{r(i)})/Q$; and the node’s share of its route load, $\eta_i = q_i/Q_{r(i)}$. These dynamic signals indicate whether a route

Group	Features	Dim
Static	$\mathbf{p}_i, \mathbf{1}_{\{i=0\}}, \theta_i, d_{i0}, q_i/Q$	6
Topology	$\mathbf{p}_{\text{prev}(i)}, \mathbf{p}_{\text{succ}(i)}$	4
Neighbor ranks	rank of $\text{prev}(i), \text{succ}(i)$	2
Relative demand	$q_i / \max_j q_j$	1
Spatial density	$\mu_5, \mu_{N/10}, \mu_{N/3}$	3
Local quality	$\Delta_i, d_{i,\text{cent}}$	2
Capacity status	$L_{r(i)}, S_{r(i)}, \eta_i$	3
Meta	temperature, remaining budget	2
Total		23

Table 9: Summary of the node feature vector $\mathbf{x}_i$.

is nearly saturated and how much a given node contributes to that saturation.

Search meta-features (2). The current SA temperature, normalized to $[0, 1]$ over the schedule range, and the fraction of the search budget remaining. They are identical across nodes of the same state and let the policy modulate its behavior along the annealing schedule (e.g., bolder restructuring at high temperature, fine repairs near the end).

Conditional pair features (stage 2, optional). In addition to the per-node vectors above, the second stage of the policy can receive descriptors of the candidate move itself, computed only for the selected first node u and every candidate partner v : the exact insertion cost $d(v, u) + d(u, \text{succ}(v)) - d(v, \text{succ}(v))$ together with the net cost change of the full move (insertion cost minus the removal saving of u), and the normalized distance-ranks of the edges the move would create. Because they are evaluated for a single u , these descriptors preserve the $\mathcal{O}(N)$ per-step complexity.

Appendix: Operator–Feasibility Study, Full Results

This appendix collects the complete diagnostics of the operator $\times$ feasibility sweep summarized in Table 1. In the plot legends, the internal configuration names map to the paper terminology as `valid` = proactive masking, `free` = indirect representation (greedy split), `rm_depot` = reactive rejection.

Operator definitions. Figure 5 illustrates the three pairwise operators on two route fragments. The same action $a = (i, j)$ triggers a qualitatively different transformation under each operator, which is why a policy is trained for one fixed operator and learns a proposal distribution tailored to it.

Main effects. Table 10 averages each factor level over the other factor. Insertion and masking win marginally as well as jointly, so the winning cell of Table 1 is not an interaction artefact: the best operator and the best feasibility strategy are individually best as well.

Compute. Table 11 reports the evaluation wall-clock of every cell. Quality and compute are essentially uncorrelated over the grid — the cheapest column (rejection) is the worst




Figure 5: The three pairwise operators on two route fragments (top: before, bottom: after). *Swap* exchanges i (orange) and j (green). *Insertion* removes i and reinserts it immediately after j . *2-opt** exchanges the route suffixes following i and j ; when i and j belong to the same route, the operator instead reverses the path segment between them (standard 2-opt).

Operator	Cost	Feasibility	Cost
Insertion	20.00	Masking	18.37
2-opt(*)	22.02	Indirect	20.36
Swap	26.03	Rejection	29.31

Table 10: Main effects: mean final cost of each factor level averaged over the other factor. Insertion and masking win marginally as well as jointly.

Operator	Masking	Indirect	Rejection
Insertion	173	172	152
Swap	170	167	148
2-opt(*)	301	177	157

Table 11: Mean wall-clock time (s) to evaluate the full 10,000-instance test set for 10^4 SA steps. Rejection is cheapest because infeasible proposals are simply discarded; 2-opt(*) under masking pays $1.7\times$ the compute of every other cell for its suffix-exchange feasibility checks.

on quality, and the most expensive cell (2-opt(*) under masking) still loses to insertion — so the quality ranking of the main text is not a compute artefact.

Per-cell diagnostics. Figures 6–8 give three complementary views of the grid: the cost heatmap, the cost–compute trade-off, and the per-seed spread of the four best cells. Seed variance grows quickly as cell quality degrades, so the winning cell is also the most reproducible one.

Appendix: Feature Ablation, Full Results

This appendix collects the complete plots and secondary tables of the feature-ablation study summarized in Tables 2 and 3, in the order of the main-text narrative: single-group diagnostics, thematic (cluster) removals, the head-to-head validation of the candidate best sets, the targeted single-group refinements, and the conditional pair descriptors. In the plot labels, the internal group names map to the paper terminology of Table 9 as $\text{neighbor_rank} = \text{neighbor distance-ranks}$, $\text{demand_max} = \text{relative demand}$, $\text{density}_{5/10\%/33\%} = \mu_5/\mu_{N/10}/\mu_{N/3}$, $\text{route_pct} = \text{load ratio } L_{r(i)}$, slack




Figure 6: Mean final cost over the operator $\times$ feasibility grid (green = better). The insertion/masking corner is the optimum; the rejection column is uniformly poor across all operators.

= slack $S_{r(i)}$, and $\text{node_pct} = \text{load share } \eta_i$.

Single-group diagnostics. Figures 9 and 10 visualize the two columns of Table 2: the leave-one-out deltas (marginal value with everything else present) and the isolation deltas (standalone value over the static+meta base). Figure 11 ranks all 30 ablation configurations and makes the two-cluster structure visible: leave-one-out runs stay near the full-set reference while isolation runs stay near the base, i.e., no single group is responsible for the 17% gap between the two. Figure 12 shows the per-seed spread of the reference configurations and explains why the pooled 3-seed floor ($\sigma \approx 0.18$) is inflated by the single high-variance no-static run.

Thematic ablation. Table 12 and Figure 13 report the removal of whole correlated clusters. This is the protocol that exposes collective value invisible to leave-one-out: no single capacity feature clears the floor on its own, but removing all three costs $+0.343$.




Figure 7: Cost against evaluation time for the nine cells. Insertion/masking sits at the bottom left (best on both axes); 2-opt(*)/masking spends $1.7\times$ the compute and remains worse.




Figure 8: Per-seed final cost for the four best cells. The winning cell is tightly clustered; seed variance grows quickly as quality drops.

Best-set validation. Figure 14 complements Table 3 with the per-seed view of the 5-seed confirmation: the left panel shows that the 12-group and full-set clusters overlap and sit cleanly below every pruned candidate, and the right panel shows the seed-paired deltas against the noise floor — the evidence behind the reversal of the single-group pruning rule.

Targeted refinements. Table 13 and Figure 15 isolate the two borderline groups. Dropping the load ratio alone is a tie with the full set (reproduced independently at 3 and 5 seeds); additionally dropping the neighbor ranks costs an incremental $+0.200 \pm 0.066$, several times the floor — the neighbor ranks, not the load ratio, are the group that must stay.

Conditional pair descriptors. Figure 16 reports the 2×2 sweep of the two second-stage conditioning signals on top of the retained set: both hurt individually, their effects are additive, and the both-on cell is the worst — the basis for disabling them.




Figure 9: Leave-one-out ablation: cost increase when a single group is removed from the full set. Static dominates; detour, topology and meta are the next clearly useful groups. The shaded band is the noise floor.




Figure 10: Isolation ablation: gain from adding a single group to the static+meta base. Detour, topology and the neighbor ranks carry most of the standalone signal; the capacity trio harms the policy when added in isolation.

Appendix: Architecture Study, Full Results

This appendix collects the complete grids and per-seed diagnostics of the architecture study summarized in Table 4, one paragraph per axis in the order they were swept (critic, capacity, global context, shared encoder, distribution shaping). In the plot labels, the internal names map to the paper terminology as *deepsets* = multi-statistic critic, *ff* = mean-pooled feed-forward critic, *seq* = the incumbent actor with independent per-stage scorers, *shared* = the shared-encoder variant, *gc* = pooled global context, *bil* = bilinear second-stage head (0 = concatenation), and networks are written width/depth, e.g. $64/2L$.

Critic. Table 14 compares the two critic architectures. The critic only shapes the advantage estimates during training and is discarded afterwards, so the comparison is on solution quality alone.

Actor capacity. Table 15 gives the full width $\times$ depth grid. Figure 17 adds the seed-paired deltas against the noise

Theme removed	Cost	Δ vs. full
Relational (topology + nbr. ranks)	17.277	+0.599 $\pm$ 0.016
Geometry (detour + centroid)	17.274	+0.596 $\pm$ 0.033
Capacity (L, S, η)	17.021	+0.343 $\pm$ 0.059
Density ($\mu_5, \mu_{N/10}, \mu_{N/3}$)	16.822	+0.145 $\pm$ 0.033

Table 12: Thematic ablation (3 seeds, seed-paired vs. the full set; positive Δ = the theme helps). The relational and geometry clusters are the two most valuable; capacity clears the typical seed noise while density does not.

Set	Groups	Cost	Time (s)	Δ vs. full
full set	13	16.678	179	ref
– load ratio	12	16.619	166	–0.059 $\pm$ 0.076
– load ratio, – ranks	11	16.819	154	+0.141 $\pm$ 0.022

Table 13: Targeted single-group refinements (3 seeds, seed-paired; mini-batch noise floor $\approx$ 0.035; per-set seed std between 0.02 and 0.05). Dropping the load ratio alone is a statistical tie with the full set; additionally dropping the neighbor ranks costs an incremental +0.200 $\pm$ 0.066. The apparent 7% speedup of the 12-group set did not replicate at 5 seeds (Table 3) and is machine-load noise.

band — every cell falls inside it — and Figure 18 shows the cost–compute view: quality improves only marginally along a steeply rising compute axis, the signature of a capacity plateau.

Global context. Figure 19 shows the per-seed effect of appending the pooled instance summary to both scoring stages: every seed degrades, one dramatically, so the regression is not a variance artefact.

Shared encoder. Figure 20 illustrates the variant: one encoder produces node embeddings $\mathbf{h}_i$, and two lightweight heads score the two selection stages over them. Table 16 and Figure 21 report its 2×2 grid (head type $\times$ context) against the incumbent: every cell sits $\approx$ 3 routing units above the reference, so the failure is structural rather than a bad corner of the grid.

Distribution shaping. Table 17 and Figure 22 report the logit-clipping $\times$ learnable-temperature grid: only clipping clears the floor, and stacking the temperature on top of it adds nothing but variance.

Appendix: Search-Loop Components, Full Results

This appendix collects the full rankings and per-seed diagnostics behind the reward, annealing, acceptance, and initialization studies of the main text, one paragraph per axis. All four batches follow the standard protocol (3 seeds, 10,000 SA steps at half precision on the Nazari $N = 100$ test set); the incumbent configuration reproduces at 16.459–16.460 across the four batches, matching the adopted cell of the architecture study (Table 17).

Critic	Cost
multi-statistic	16.635 $\pm$ 0.038
feed-forward	16.693 $\pm$ 0.006

Table 14: Critic comparison (3 runs per arm; noise floor $\approx$ 0.027). The multi-statistic critic improves the mean final cost by 0.058, about twice the floor. The critic is used only during training, so deployment cost is unchanged.

Net	Cost	Time (s)	Δ vs. 32×1
64×2	16.589 $\pm$ 0.004	238	–0.049 $\pm$ 0.039
64×1	16.591 $\pm$ 0.084	207	–0.047 $\pm$ 0.060
32×2	16.601 $\pm$ 0.008	187	–0.037 $\pm$ 0.030
32×1	16.637 $\pm$ 0.036	173	ref
16×2	16.649 $\pm$ 0.083	165	+0.011 $\pm$ 0.093
16×1	16.668 $\pm$ 0.042	160	+0.031 $\pm$ 0.063

Table 15: Actor capacity grid (embedding width $\times$ hidden layers), sorted by mean cost; Δ is seed-paired against the 32×1 incumbent. No cell clears the noise floor ($\approx$ 0.053); the width main effect spans 0.069 against 0.019 for depth.

Reward. In the plot labels, the internal reward names map to the paper terminology as `immediate` = immediate, `sa_aligned` = acceptance-aligned, `global_best` = best-so-far, `hybrid` = the fixed mixture ($\alpha = 0.5$) of the immediate and best-so-far signals, `curriculum` and `curriculum_terminal` = the scheduled interpolations from acceptance-aligned toward best-so-far and terminal respectively, and `step_penalty_init` and `step_penalty_16` = the per-step penalty normalized by the initial cost and by a fixed constant close to the typical final cost. Figure 23 shows the full ranking with seed stds; Figure 24 zooms on the stable cluster and shows the seed-paired deltas against the noise band.

Cooling schedule. Figure 25 shows the per-seed costs and paired deltas of the two schedules: every delta lies inside the noise band and the sign is not consistent across seeds — the signature of a tie rather than an effect.

Metropolis acceptance. Figure 26 decomposes the 2×2 cross of Table 7 into its two effects: the test-time effect (removing the acceptance at deployment) is well past the noise band at both training settings, while the training-flag effect at the standard deployment sits inside it. The greedy-trained arms also show markedly lower seed variance (0.010/0.020 against 0.040/0.050).

Initialization. The constructive heuristics appear under their code names `random` (random assignment), `sweep`, `nearest_neighbor`, `Clark_and_Wright` (Clarke–Wright savings), and `isolate` (single-customer routes); their construction costs on the test set are 57.9, 30.5, 19.0, 16.4, and 104.0 respectively. Table 18 gives the full train $\times$ test cross behind Table 8; Figure 27 shows it as a heatmap, and Figure 28 shows the two slices that support the main-text reading: training construction matters, deployment construc-

Stage-2 head	Context	Cost	Time (s)	Δ vs. ref
bilinear	on	19.830	196	$+3.196 \pm 0.103$
bilinear	off	19.860	168	$+3.226 \pm 0.163$
concat	off	20.154	192	$+3.520 \pm 0.251$
concat	on	20.160	236	$+3.526 \pm 0.099$

Table 16: Shared-encoder grid, sorted by mean cost; Δ is seed-paired against the incumbent actor re-run with context off (16.633 ± 0.036 , 180 s). Per-cell seed std between 0.06 and 0.26; noise floor ≈ 0.176 . Within the shared family the bilinear head beats concatenation (main effect -0.31) and the context toggle is neutral (-0.01), but every cell is ≈ 3 units worse than the reference.

Clipping	Temp.	Cost	Time (s)	Δ vs. ref
$C = 10$	fixed	16.457	177	-0.173 ± 0.059
$C = 10$	learned	16.481	179	-0.149 ± 0.085
off	learned	16.580	176	-0.050 ± 0.069
off	fixed	16.630	175	ref

Table 17: Distribution-shaping grid, sorted by mean cost; Δ is seed-paired against the both-off incumbent. Per-cell seed std between 0.04 and 0.11; noise floor ≈ 0.072 . Only logit clipping clears the floor; the learnable temperature does not help it (clipping main effect -0.136 , temperature -0.014).

tion barely does, and the matched train/test diagonal rules out a mismatch explanation.

Train \ Test	Rand.	Sweep	NN	C-W	Isol.
random (incumbent)	16.460	16.467	16.467	16.307	16.444
sweep	17.548	16.950	16.854	16.271	17.148
nearest neighbor	19.228	17.729	17.401	16.381	18.837
single-customer	17.736	17.725	17.753	16.442	17.706
mixed	16.682	16.663	16.700	16.357	16.673

Table 18: Initialization cross: mean final cost over 3 seeds, rows = training construction, columns = test-time construction (NN = nearest neighbor, C-W = Clarke-Wright savings, Isol. = single-customer routes). The random-trained row is uniformly the best, and its spread across test constructions is only 0.160 although the construction costs span 16.4 (C-W) to 104.0 (single-customer). The structured-training rows recover only in the C-W column, where the construction itself already sits at the fixed point of the search — that column measures the deployment, not the actor. Worst case over deployments: 16.467 (random), 16.700 (mixed), 17.5–19.2 (structured).




Figure 11: All 30 ablation configurations ranked by mean final cost. Leave-one-out configurations (dark blue) cluster tightly near the full-set reference (red dashed); isolation configurations (light blue) sit near the static+meta base (dotted).




Figure 12: Per-seed final cost for the key reference configurations (red bars = means). Seed variance is tiny except for the no-static configuration, which inflates the pooled noise floor of the 3-seed sweep.




Figure 13: Thematic ablation (Table 12): removing the relational or geometry cluster costs ≈ 0.6 routing units each.




Figure 14: Best-set validation, per-seed view. Left: per-seed final cost — the 12-group and full-set clusters overlap and sit cleanly below every pruned set. Right: seed-paired Δ vs. the full set — the pruned sets (red) clear the noise floor by a wide margin; the 12-group set (green) sits below zero.




Figure 15: Targeted refinements (Table 13). Left: per-seed final cost — dropping the load ratio overlaps the full set, while additionally dropping the neighbor ranks lifts the whole cluster. Right: seed-paired Δ vs. the full set — the load-ratio removal (green) sits inside the noise floor, the neighbor-rank removal (red) clears it decisively.




Figure 16: Conditional pair descriptors. Left: 2×2 grid of mean final cost — the both-off cell (plain retained set) is best, both-on is worst. Right: standalone deltas and 2×2 main effects — both descriptors sit clearly beyond the noise floor on the harmful side; the interaction is within it.




Figure 17: Actor capacity grid (Table 15). Left: mean final cost and wall-clock per cell (green = better). Right: seed-paired Δ against the 32×1 incumbent — every cell falls inside the shaded noise band, so no capacity change is a significant win.




Figure 18: Cost against compute across the six capacity cells, colored by embedding width. Quality improves only marginally along a steeply rising compute axis — the hallmark of a capacity plateau.




Figure 19: Global-context toggle. Left: per-seed final cost (black bars = means); the context-on arm is both worse and far more variable. Right: per-seed Δ from enabling context — every seed is positive (worse), one dramatically so, so the degradation is not a variance artefact.




Figure 20: Shared-encoder actor variant. Each node is encoded once into an embedding h_i ; two lightweight heads then score the two stages over the shared embeddings, either by concatenation or as a bilinear compatibility between the selected node and each candidate. An optional pooled summary g of all node embeddings (dashed) is appended to both heads' inputs, giving every score access to instance-level context.




Figure 21: Shared encoder against independent scorers (Table 16). Left: per-seed final cost, incumbent reference (green) against the four shared cells (red); the dashed line marks the reference mean, and every shared seed sits far above it. Right: the shared 2×2 grid — the bilinear head beats concatenation and context is roughly neutral, but all four cells are ≈ 3 units worse than the reference.




Figure 22: Distribution shaping (Table 17). Left: 2×2 grid of mean final cost and time (green = better); the clipping-on, fixed-temperature cell is the best. Right: seed-paired Δ against the both-off incumbent — only logit clipping escapes the noise band, and stacking the learnable temperature on top of it does not help.




Figure 23: Full reward ranking (Table 5; mean $\pm$ seed std, best at top). Gold = incumbent, green = the stable cluster within 0.15 of it, red = degraded. The three red bars (terminal and the two step-penalty schemes) are a different regime entirely: they fail to train a useful actor and carry runaway seed variance.




Figure 24: Zoom on the stable reward cluster. Left: per-seed final cost (black bars = means); the arms overlap heavily. Right: seed-paired Δ against the incumbent immediate reward — the fixed mixture sits inside the noise band (a tie), the remaining dense variants are marginally but consistently above zero.




Figure 25: Cooling-schedule comparison (Table 6). Left: per-seed final cost for the two schedules (black bars = means); the clusters overlap heavily. Right: per-seed paired Δ (geometric - step) — every bar lies inside the noise band and the sign is not consistent, the signature of a tie rather than an effect.




Figure 26: Metropolis train $\times$ test cross (Table 7). Left: 2×2 heatmap of mean final cost (greener = better). Center: cost of removing test-time Metropolis (off - on) at each training setting — both bars are well past the noise band, the dominant effect. Right: training-flag effect (on - off) at each deployment — the test-on bar sits inside the band (a tie), test-off just clears it.




Figure 27: Initialization cross (Table 18): rows = training construction, columns = test-time construction, greener = lower final cost. The random-trained and mixed-trained rows are uniformly good; the three structured-training rows are poor and only recover in the Clarke–Wright column, where the construction itself already did the work.




Figure 28: Left: final cost by training construction at the standard random-start deployment — random (gold) is far below the rest, with mixed (gray) a close second. Right: final cost of selected actors across the five test constructions: the random-trained actor (gold) is nearly flat and mostly inside the stable-floor band, the mixed actor (purple) sits uniformly a touch above it, and the matched train/test diagonal (green diamonds) climbs away — ruling out a train/test-matching explanation for the training-construction effect.