

# Outline

- ① Introduction
- ② Clustering
  - Definition
  - Taxonomy
  - The  $k$ -means clustering method
  - Cluster determination techniques
- ③ Dimensionality reduction
  - Definition
  - Statistical approaches
  - Neural approaches
- ④ Other tasks

# Definition

**Curse of dimensionality:** Large feature dimensionalities  $\mathbb{R}^d \nRightarrow$  beneficial

# Definition

**Curse of dimensionality:** Large feature dimensionalities  $\mathbb{R}^d \nRightarrow$  beneficial

- Data sparsity
- Correlations in the feature space

# Definition

**Curse of dimensionality:** Large feature dimensionalities  $\mathbb{R}^d \nRightarrow$  beneficial

- Data sparsity
- Correlations in the feature space

**Dimensionality reduction:** Decrease the number  $d$  of features

# Definition

**Curse of dimensionality:** Large feature dimensionalities  $\mathbb{R}^d \nRightarrow$  beneficial

- Data sparsity
- Correlations in the feature space

**Dimensionality reduction:** Decrease the number  $d$  of features

- $\mathcal{R} : \mathbb{R}^d \rightarrow \mathbb{R}^{d'}$  with  $d' \leq d$
- Does not reduce the number of elements in the  $\mathcal{D}$
- Unsupervised strategies

# Definition

**Curse of dimensionality:** Large feature dimensionalities  $\mathbb{R}^d \nRightarrow$  beneficial

- Data sparsity
- Correlations in the feature space

**Dimensionality reduction:** Decrease the number  $d$  of features

- $\mathcal{R} : \mathbb{R}^d \rightarrow \mathbb{R}^{d'}$  with  $d' \leq d$
- Does not reduce the number of elements in the  $\mathcal{D}$
- Unsupervised strategies

**Common** paradigms:

- Statistical frameworks: PCA, t-SNE
- Neural-based approaches: Autoencoder

# Principal Components Analysis

- Linear projection from  $\mathbb{R}^d$  to  $\mathbb{R}^{d'}$ :

# Principal Components Analysis

- Linear projection from  $\mathbb{R}^d$  to  $\mathbb{R}^{d'}$ :
  - Datum  $\mathbf{x} \in \mathbb{R}^d$  **projected** onto  $\mathbb{R}^{d'}$  as:  $(\mathbf{x}^T \mathbf{v}_1, \dots, \mathbf{x}^T \mathbf{v}_{d'})$  with  $\mathbf{v} \in \mathbb{R}^d$



# Principal Components Analysis


- Linear projection from  $\mathbb{R}^d$  to  $\mathbb{R}^{d'}$ :
  - Datum  $\mathbf{x} \in \mathbb{R}^d$  **projected** onto  $\mathbb{R}^{d'}$  as:  $(\mathbf{x}^T \mathbf{v}_1, \dots, \mathbf{x}^T \mathbf{v}_{d'})$  with  $\mathbf{v} \in \mathbb{R}^d$
  - ⇒  $\mathbf{x}_{\text{proj}} = \mathbf{x} \mathcal{V}$  with  $\mathcal{V} \in \mathbb{R}^{d \times d'}$

# Principal Components Analysis

- Linear projection from  $\mathbb{R}^d$  to  $\mathbb{R}^{d'}$ :
  - Datum  $\mathbf{x} \in \mathbb{R}^d$  **projected** onto  $\mathbb{R}^{d'}$  as:  $(\mathbf{x}^T \mathbf{v}_1, \dots, \mathbf{x}^T \mathbf{v}_{d'})$  with  $\mathbf{v} \in \mathbb{R}^d$ 
    - ⇒  $\mathbf{x}_{\text{proj}} = \mathbf{x} \mathcal{V}$  with  $\mathcal{V} \in \mathbb{R}^{d \times d'}$
  - If  $d' < d \Rightarrow$  **Dimensionality reduction**



# Principal Components Analysis

- **Linear** projection from  $\mathbb{R}^d$  to  $\mathbb{R}^{d'}$ :
  - Datum  $\mathbf{x} \in \mathbb{R}^d$  **projected** onto  $\mathbb{R}^{d'}$  as:  $(\mathbf{x}^T \mathbf{v}_1, \dots, \mathbf{x}^T \mathbf{v}_{d'})$  with  $\mathbf{v} \in \mathbb{R}^d$ 
    - ⇒  $\mathbf{x}_{\text{proj}} = \mathbf{x} \mathcal{V}$  with  $\mathcal{V} \in \mathbb{R}^{d \times d'}$
  - If  $d' < d \Rightarrow$  **Dimensionality reduction**
- **Goal:** Find *directions* that capture the **most variance** in the data





# Principal Components Analysis

- **Linear** projection from  $\mathbb{R}^d$  to  $\mathbb{R}^{d'}$ :
  - Datum  $\mathbf{x} \in \mathbb{R}^d$  **projected** onto  $\mathbb{R}^{d'}$  as:  $(\mathbf{x}^T \mathbf{v}_1, \dots, \mathbf{x}^T \mathbf{v}_{d'})$  with  $\mathbf{v} \in \mathbb{R}^d$ 
    - ⇒  $\mathbf{x}_{\text{proj}} = \mathbf{x} \mathcal{V}$  with  $\mathcal{V} \in \mathbb{R}^{d \times d'}$
  - If  $d' < d \Rightarrow$  **Dimensionality reduction**
- **Goal:** Find **directions** that capture the **most variance** in the data
  - These **directions** constitute the **coordinates** of the **new space**





# Principal Components Analysis

- **Linear** projection from  $\mathbb{R}^d$  to  $\mathbb{R}^{d'}$ :
  - Datum  $\mathbf{x} \in \mathbb{R}^d$  **projected** onto  $\mathbb{R}^{d'}$  as:  $(\mathbf{x}^T \mathbf{v}_1, \dots, \mathbf{x}^T \mathbf{v}_{d'})$  with  $\mathbf{v} \in \mathbb{R}^d$ 
    - ⇒  $\mathbf{x}_{\text{proj}} = \mathbf{x} \mathcal{V}$  with  $\mathcal{V} \in \mathbb{R}^{d \times d'}$
  - If  $d' < d \Rightarrow$  **Dimensionality reduction**
- **Goal:** Find **directions** that capture the **most variance** in the data
  - These **directions** constitute the **coordinates** of the **new space**
  - Correspond to the **eigenvectors** of the data



# Principal Components Analysis

- **Linear** projection from  $\mathbb{R}^d$  to  $\mathbb{R}^{d'}$ :
  - Datum  $\mathbf{x} \in \mathbb{R}^d$  **projected** onto  $\mathbb{R}^{d'}$  as:  $(\mathbf{x}^T \mathbf{v}_1, \dots, \mathbf{x}^T \mathbf{v}_{d'})$  with  $\mathbf{v} \in \mathbb{R}^d$ 
    - ⇒  $\mathbf{x}_{\text{proj}} = \mathbf{x} \mathcal{V}$  with  $\mathcal{V} \in \mathbb{R}^{d \times d'}$
  - If  $d' < d \Rightarrow$  **Dimensionality reduction**
- **Goal:** Find **directions** that capture the **most variance** in the data
  - These **directions** constitute the **coordinates** of the **new space**
  - Correspond to the **eigenvectors** of the data
  - Known as **Principal Components**



# Mathematical formulation

- Initial assortment  $\mathcal{D} = \{\mathbf{x}_i\}_{i=1}^{|\mathcal{D}|}$  with  $\mathbf{x}_i \in \mathbb{R}^d$

# Mathematical formulation

- Initial assortment  $\mathcal{D} = \{\mathbf{x}_i\}_{i=1}^{|\mathcal{D}|}$  with  $\mathbf{x}_i \in \mathbb{R}^d \Rightarrow \mathbf{D} \in \mathbb{R}^{|\mathcal{D}| \times d}$



# Mathematical formulation

- Initial **assortment**  $\mathcal{D} = \{\mathbf{x}_i\}_{i=1}^{|\mathcal{D}|}$  with  $\mathbf{x}_i \in \mathbb{R}^d \Rightarrow \mathbf{D} \in \mathbb{R}^{|\mathcal{D}| \times d}$ 
  - **Column-wise mean zero**  $\Rightarrow \sum_{i=1}^{|\mathcal{D}|} x_{ij} = 0$  with  $1 \leq j \leq d$

# Mathematical formulation

- Initial **assortment**  $\mathcal{D} = \{\mathbf{x}_i\}_{i=1}^{|\mathcal{D}|}$  with  $\mathbf{x}_i \in \mathbb{R}^d \Rightarrow \mathbf{D} \in \mathbb{R}^{|\mathcal{D}| \times d}$   
→ **Column-wise mean zero**  $\Rightarrow \sum_{i=1}^{|\mathcal{D}|} x_{ij} = 0$  with  $1 \leq j \leq d$
- **Covariance** matrix ( $\Sigma$ ): pairwise **relationships** between **features**

$$\Sigma = \frac{1}{|\mathcal{D}| - 1} \mathbf{D}^T \mathbf{D} \quad \left( \in \mathbb{R}^{d \times d} \right)$$

# Mathematical formulation

- Initial **assortment**  $\mathcal{D} = \{\mathbf{x}_i\}_{i=1}^{|\mathcal{D}|}$  with  $\mathbf{x}_i \in \mathbb{R}^d \Rightarrow \mathbf{D} \in \mathbb{R}^{|\mathcal{D}| \times d}$   
→ **Column-wise mean zero**  $\Rightarrow \sum_{i=1}^{|\mathcal{D}|} x_{ij} = 0$  with  $1 \leq j \leq d$
- **Covariance** matrix ( $\Sigma$ ): pairwise **relationships** between **features**

$$\Sigma = \frac{1}{|\mathcal{D}| - 1} \mathbf{D}^T \mathbf{D} \quad \left( \in \mathbb{R}^{d \times d} \right)$$

- **Variance** on the projected space:  $\text{Var}(\mathbf{D}\mathbf{v}) = \mathbf{v}^T \Sigma \mathbf{v}$

# Mathematical formulation

- Initial **assortment**  $\mathcal{D} = \{\mathbf{x}_i\}_{i=1}^{|\mathcal{D}|}$  with  $\mathbf{x}_i \in \mathbb{R}^d \Rightarrow \mathbf{D} \in \mathbb{R}^{|\mathcal{D}| \times d}$   
 → **Column-wise mean zero**  $\Rightarrow \sum_{i=1}^{|\mathcal{D}|} x_{ij} = 0$  with  $1 \leq j \leq d$
- **Covariance** matrix ( $\Sigma$ ): pairwise **relationships** between **features**

$$\Sigma = \frac{1}{|\mathcal{D}| - 1} \mathbf{D}^T \mathbf{D} \quad \left( \in \mathbb{R}^{d \times d} \right)$$

- **Variance** on the projected space:  $\text{Var}(\mathbf{D}\mathbf{v}) = \mathbf{v}^T \Sigma \mathbf{v}$   
 → **Key** condition: **eigenvector** must **maximize**  $\text{Var}(\mathbf{D}\mathbf{v})$

# Mathematical formulation

- First *eigenvector*: variance condition

# Mathematical formulation

- First *eigenvector*: variance condition

$$\mathbf{v}_1 = \arg \max_{\|\mathbf{v}\|=1} \mathbf{v}^T \Sigma \mathbf{v}$$

# Mathematical formulation

- First *eigenvector*: variance condition

$$\mathbf{v}_1 = \arg \max_{\|\mathbf{v}\|=1} \mathbf{v}^T \Sigma \mathbf{v}$$

- Second *eigenvector*: variance condition + orthogonal to  $\mathbf{v}_1$

# Mathematical formulation

- First *eigenvector*: variance condition

$$\mathbf{v}_1 = \arg \max_{\|\mathbf{v}\|=1} \mathbf{v}^T \Sigma \mathbf{v}$$

- Second *eigenvector*: variance condition + orthogonal to  $\mathbf{v}_1$

$$\mathbf{v}_2 = \arg \max_{\|\mathbf{v}\|=1, \mathbf{v} \perp \mathbf{v}_1} \mathbf{v}^T \Sigma \mathbf{v}$$



# Mathematical formulation

- First *eigenvector*: variance condition

$$\mathbf{v}_1 = \arg \max_{\|\mathbf{v}\|=1} \mathbf{v}^T \Sigma \mathbf{v}$$

- Second *eigenvector*: variance condition + orthogonal to  $\mathbf{v}_1$

$$\mathbf{v}_2 = \arg \max_{\|\mathbf{v}\|=1, \mathbf{v} \perp \mathbf{v}_1} \mathbf{v}^T \Sigma \mathbf{v}$$

- Third *eigenvector*: variance condition + orthogonal to  $\mathbf{v}_1, \mathbf{v}_2$

$$\mathbf{v}_3 = \arg \max_{\|\mathbf{v}\|=1, \mathbf{v} \perp \{\mathbf{v}_1, \mathbf{v}_2\}} \mathbf{v}^T \Sigma \mathbf{v}$$

# Mathematical formulation

- First *eigenvector*: variance condition

$$\mathbf{v}_1 = \arg \max_{\|\mathbf{v}\|=1} \mathbf{v}^T \Sigma \mathbf{v}$$

- Second *eigenvector*: variance condition + orthogonal to  $\mathbf{v}_1$

$$\mathbf{v}_2 = \arg \max_{\|\mathbf{v}\|=1, \mathbf{v} \perp \mathbf{v}_1} \mathbf{v}^T \Sigma \mathbf{v}$$

- Third *eigenvector*: variance condition + orthogonal to  $\mathbf{v}_1, \mathbf{v}_2$

$$\mathbf{v}_3 = \arg \max_{\|\mathbf{v}\|=1, \mathbf{v} \perp \{\mathbf{v}_1, \mathbf{v}_2\}} \mathbf{v}^T \Sigma \mathbf{v}$$

- $d'$ -th *eigenvector*: variance condition + orthogonal to  $\{\mathbf{v}_i\}_{i=1}^{d'-1}$

$$\mathbf{v}_{d'} = \arg \max_{\|\mathbf{v}\|=1, \mathbf{v} \perp \{\mathbf{v}_i\}_{i=1}^{d'-1}} \mathbf{v}^T \Sigma \mathbf{v}$$

# Mathematical formulation

- Vector  $\mathcal{V} = \{\mathbf{v}_i\}_{i=1}^{d'} \Rightarrow$  *eigenvectors* sorted by the **encoded variance**

# Mathematical formulation

- Vector  $\mathcal{V} = \{\mathbf{v}_i\}_{i=1}^{d'} \Rightarrow$  *eigenvectors* sorted by the **encoded variance**
  - **Relates** to the **compression degree** of the **Dimensionality Reduction**

# Mathematical formulation

- Vector  $\mathcal{V} = \{\mathbf{v}_i\}_{i=1}^{d'} \Rightarrow$  *eigenvectors* sorted by the **encoded variance**  
→ **Relates** to the **compression degree** of the **Dimensionality Reduction**
- How much **information** are we **keeping**? → **Cumulative Variance**

# Mathematical formulation

- Vector  $\mathcal{V} = \{\mathbf{v}_i\}_{i=1}^{d'} \Rightarrow$  *eigenvectors* sorted by the **encoded variance**  
→ **Relates** to the **compression degree** of the **Dimensionality Reduction**
- How much **information** are we **keeping**? → **Cumulative Variance**

$$\text{CumVar}(d') = \frac{\sum_{i=1}^{d'} \lambda_i}{\sum_{j=1}^d \lambda_j} \quad \text{where } \lambda_j = \mathbf{v}_j^T \Sigma \mathbf{v}_j$$

# Example - Single component

# Example - Two components



# t-Stochastic Nearest Embedding

- Non-linear projection from  $\mathbb{R}^d$  to  $\mathbb{R}^{d'}$ :

# t-Stochastic Nearest Embedding


- Non-linear projection from  $\mathbb{R}^d$  to  $\mathbb{R}^{d'}$ :
  - Typically,  $d' = \{2, 3\}$
  - Most commonly used for visualization purposes

# t-Stochastic Nearest Embedding

- **Non-linear** projection from  $\mathbb{R}^d$  to  $\mathbb{R}^{d'}$ :
  - Typically,  $d' = \{2, 3\}$
  - Most commonly used for **visualization purposes**
- **Key premise:** **preserving** local **neighborhoods**
  - Points **close in  $\mathbb{R}^d$**  remain **close in  $\mathbb{R}^{d'}$**

# t-Stochastic Nearest Embedding

- **Non-linear** projection from  $\mathbb{R}^d$  to  $\mathbb{R}^{d'}$ :
  - Typically,  $d' = \{2, 3\}$
  - Most commonly used for **visualization** purposes
- **Key premise:** **preserving** local **neighborhoods**
  - Points **close** in  $\mathbb{R}^d$  remain **close** in  $\mathbb{R}^{d'}$



# Mathematical formulation

Models the problem from a probabilistic perspective:

# Mathematical formulation

Models the problem from a probabilistic perspective:

1. Distribution  $P \Rightarrow$  similarities in high-dimensional space
2. Distribution  $Q \Rightarrow$  similarities in low-dimensional space

# Mathematical formulation

Models the problem from a probabilistic perspective:

1. Distribution  $P \Rightarrow$  similarities in high-dimensional space
2. Distribution  $Q \Rightarrow$  similarities in low-dimensional space

**Task:** allocate elements in  $Q$  to resemble distribution in  $P$

# Mathematical formulation

Models the problem from a **probabilistic perspective**:

1. Distribution  $P \Rightarrow$  similarities in **high-dimensional** space
2. Distribution  $Q \Rightarrow$  similarities in **low-dimensional** space

**Task:** **allocate** elements in  $Q$  to **resemble** distribution in  $P$

- $Q$  is considerably **less dimensional** than  $P$



# Mathematical formulation

Models the problem from a **probabilistic perspective**:

1. Distribution  $P \Rightarrow$  similarities in **high-dimensional** space
2. Distribution  $Q \Rightarrow$  similarities in **low-dimensional** space

**Task:** **allocate** elements in  $Q$  to **resemble** distribution in  $P$

- $Q$  is considerably **less dimensional** than  $P$
- **Optimization** goal:

$$\min \sum_{\mathbf{x} \in \mathcal{D}} P(\mathbf{x}) \log \frac{P(\mathbf{x})}{Q(\mathbf{x})}$$

# Mathematical formulation

Models the problem from a **probabilistic perspective**:

1. Distribution  $P \Rightarrow$  similarities in **high-dimensional** space
2. Distribution  $Q \Rightarrow$  similarities in **low-dimensional** space

**Task:** **allocate** elements in  $Q$  to **resemble** distribution in  $P$

- $Q$  is considerably **less dimensional** than  $P$
- **Optimization** goal:

$$\min \sum_{\mathbf{x} \in \mathcal{D}} P(\mathbf{x}) \log \frac{P(\mathbf{x})}{Q(\mathbf{x})} = \min D_{KL}(P||Q)$$

$D_{KL} \rightarrow$  Kullback-Leibler Divergence

# Autoencoders

- Neural *disposition* devised for learning efficient representations

# Autoencoders

- Neural *disposition* devised for learning efficient representations
  - Typically known as latent representation / embedding

# Autoencoders

- Neural *disposition* devised for learning efficient representations
  - Typically known as latent representation / embedding
  - Unsupervised ⇒ Which is the target for training the model?

# Autoencoders


- Neural *disposition* devised for learning efficient representations
  - Typically known as latent representation / embedding
  - Unsupervised  $\Rightarrow$  Which is the target for training the model?
  - *Shallow* and *deep* models

# Autoencoders

- Neural *disposition* devised for learning efficient representations
  - Typically known as latent representation / embedding
  - Unsupervised  $\Rightarrow$  Which is the target for training the model?
  - *Shallow* and *deep* models
- Exhibits two parts:

# Autoencoders


- Neural *disposition* devised for learning **efficient representations**
  - Typically known as **latent representation** / **embedding**
  - **Unsupervised** ⇒ Which is the **target** for **training the model**?
  - *Shallow* and *deep* models
- Exhibits **two parts**:
  1. **Encoder**: **Reduces** the **dimensionality** of the data
  2. **Decoder**: **Recovers** the **original dimensionality** of the data





# Autoencoders

- Neural *disposition* devised for learning **efficient representations**
  - Typically known as **latent representation** / **embedding**
  - **Unsupervised** ⇒ Which is the **target** for **training the model**?
  - *Shallow* and *deep* models
- Exhibits **two parts**:
  1. **Encoder**: **Reduces** the **dimensionality** of the data
  2. **Decoder**: **Recovers** the **original dimensionality** of the data



- Once trained, we are only **interested in the Encoder**
  - **Decoder** in this case is used for **training purposes**

# Mathematical formulation

**Goal:** Learn two **mapping** functions:

# Mathematical formulation

**Goal:** Learn two **mapping** functions:

- **Encoder:**  $E_{\phi_E} : \mathbb{R}^d \rightarrow \mathbb{R}^{d'}$

# Mathematical formulation

**Goal:** Learn two **mapping** functions:

- Encoder:  $E_{\phi_E} : \mathbb{R}^d \rightarrow \mathbb{R}^{d'}$
- Decoder:  $D_{\phi_D} : \mathbb{R}^{d'} \rightarrow \mathbb{R}^d$

# Mathematical formulation

**Goal:** Learn two **mapping** functions:

- **Encoder:**  $E_{\phi_E} : \mathbb{R}^d \rightarrow \mathbb{R}^{d'}$
- **Decoder:**  $D_{\phi_D} : \mathbb{R}^{d'} \rightarrow \mathbb{R}^d$

Given an **input** datum **x**:

- **Embedded** representation:  $\mathbf{x}^e = E_{\phi_E}(\mathbf{x})$
- **Reconstructed** datum:  $\tilde{\mathbf{x}} = D_{\phi_D}(\mathbf{x}^e) = D_{\phi_D}(E_{\phi_E}(\mathbf{x}))$

# Mathematical formulation

**Goal:** Learn two **mapping** functions:

- **Encoder:**  $E_{\phi_E} : \mathbb{R}^d \rightarrow \mathbb{R}^{d'}$
- **Decoder:**  $D_{\phi_D} : \mathbb{R}^{d'} \rightarrow \mathbb{R}^d$

Given an **input** datum **x**:

- **Embedded** representation:  $\mathbf{x}^e = E_{\phi_E}(\mathbf{x})$
- **Reconstructed** datum:  $\tilde{\mathbf{x}} = D_{\phi_D}(\mathbf{x}^e) = D_{\phi_D}(E_{\phi_E}(\mathbf{x}))$

**Optimization:** **minimize** the **difference** between **input** and **reconstruction**

$$\arg \min_{\phi_E, \phi_D} \mathcal{L}(\mathbf{x}, \tilde{\mathbf{x}}) = \arg \min_{\phi_E, \phi_D} \mathcal{L}(\mathbf{x}, D_{\phi_D}(E_{\phi_E}(\mathbf{x})))$$

# Final considerations

- Typically **symmetrical** but **not** a **necessary** condition
  - **Decoder**  $D_{\phi_D}(\cdot)$  **undoes** the **mapping** by the **encoder**  $E_{\phi_E}(\cdot)$

# Final considerations

- Typically **symmetrical** but **not** a **necessary** condition
  - **Decoder**  $D_{\phi_D}(\cdot)$  **undoes** the **mapping** by the **encoder**  $E_{\phi_E}(\cdot)$
- There exist **other versions** of these structures:
  - **Variational** AE: Assumes data follows a particular **statistical distribution**
  - **Denoising** AE: Trained to **remove noise** from input data



# Final considerations

- Typically **symmetrical** but **not** a **necessary** condition
  - **Decoder**  $D_{\phi_D}(\cdot)$  **undoes** the **mapping** by the **encoder**  $E_{\phi_E}(\cdot)$
- There exist **other versions** of these structures:
  - **Variational** AE: Assumes data follows a particular **statistical distribution**
  - **Denoising** AE: Trained to **remove noise** from input data
- Related to **PCA**:
  - **Single hidden** layer with **linear activation**  $\Rightarrow$  **Equivalent** approaches

# Outline

- ① Introduction
- ② Clustering
  - Definition
  - Taxonomy
  - The  $k$ -means clustering method
  - Cluster determination techniques
- ③ Dimensionality reduction
  - Definition
  - Statistical approaches
  - Neural approaches
- ④ Other tasks

# Other unsupervised learning tasks

## 1. Outlier detection

- Detect elements whose features remarkably differ from the rest
- **Strategies:** PCA error, Autoencoder, Isolation Forest

# Other unsupervised learning tasks

## 1. Outlier detection

- **Detect elements** whose **features** remarkably **differ** from the rest
- **Strategies**: PCA error, Autoencoder, Isolation Forest

## 2. Generative modeling

- **Generate** new samples similar to the existing ones
- **Strategies**: Variational AE (decoder  $D_{\phi_D}(\cdot)$ )

# Other unsupervised learning tasks

## 1. Outlier detection

- **Detect elements** whose **features** remarkably **differ** from the rest
- **Strategies**: PCA error, Autoencoder, Isolation Forest

## 2. Generative modeling

- **Generate** new samples similar to the existing ones
- **Strategies**: Variational AE (decoder  $D_{\phi_D}(\cdot)$ )

## 3. Motif discovery

- **Mining** patterns in time-series data collections

# T6: Unsupervised learning

Fundamentos del Aprendizaje Automático

Curso 2025/2026