HAP-2850

BUYBACK GAS PREHEATER
DUTY: 1.25 MMBTU/HR
PRESSURE (DES/OP/MIN): 3000 / 2120 / psig
TEMPERATURE (DES/OP/MIN): 250 / 41 / °F
POWER: 370 KW

ME-7650

FUEL GAS PACKAGE

CONTINUED ON DWG. D-CAB-BEB-DPP-10-188-01

DPP-10-188-01 — 10"-FL-A9A-9210 — FROM FUEL GAS EXCHANGER AND HP FUEL GAS K.O. DRUM

CONTINUED ON DWG. D-CAB-BEB-DPP-10-189

10"-FL-A9A-9210 — DPP-10-189 — TO HP FLARE HEADER

DPP-10-188-01 — 6"-FG-E3-5258 — TO HP FUEL GAS K.O. DRUM MBF-8250

CONTINUED ON DWG. D-CAB-BEB-DPP-10-188-01

220 — DPP-10-181-02 — 4"-FG-E3-5257 — FROM GAS METERING SKID

DPP-10-915 — 4"-P-E3-1386 — FROM GAS LIFT FLOWLINES

TP5

4" VB-86N — NOTE 4

3/4" VB-36N

N1

2"H

N2

HAP-2850

SKIN RTD — TE 2850C (F)

XS 2850A — I — S — PNL-2850

HS 2850A — ON/OFF

XA 2850A — COMMON TROUBLE

XA 2850B — SYSTEM SHUTDOWN

UC — 2" VB-86N

TAHH 2850B1 — TI 2850B — NOTE 2 — TSHH 2850B — S — I

TIT 2850B — TE 2850B — TW 2850B — 1.1/2" — 2500#

TI 2850A — TW 2850A — 1.1/2" — 2500#

2"-FG-E3-9300

H

1D2 SET AT 3000 PSIG FIRE — PSV 2850A — A9A — E3 — 300# — 3"x2"

3/4" VB-34N

VB-64N — 3" CSO FB

2"x1"

3/4" VB-36N

VB-86N — CSO FB

TI 2850F — L — TIT 2850F — TE 2850F — NOTE 6

T 188-02 03 — U02

3"-FL-A9A-9213

2" VGL-52N — A9A — E3

VB-86N

4"-FG-E3-9301-1"H

4" VB-86N — NOTE 4 — 4" — NOTE 1,5

4" VB-86N — 3/4" VB-36N — PV 2850A — 4"x2" — FC — NOTE 5 — 6"x2" — 3/4" VB-36N

H — N — 6" VB-88N — 1" VGL-52N

4" — NOTE 1,5

ME-7650

SET AT NOTE 3 — PIC 2850A — H — L

PY 2850A — DVC

PIT 2850A — 3/4" VB-18N

SET AT 50 °F — TIC 2850D — L

TY 2850A

TIT 2850D — TE 2850D — TW 2850D — 1.1/2" — 2500#

TSLL 2850E1 — TALL 2850E1 — NOTE 2 — 1oo2 — S — 0

TI 2850E1 — S — I

TIT 2850E1 — TE 2850E1 — TW 2850E1 — 1.1/2" — 2500#

TI 2850E2 — S — I

TIT 2850E2 — TE 2850E2 — TW 2850E2 — 1.1/2" — 2500#

FSV 2850A — 6" VC-93N — 3/4" VB-36N — 6" VB-88N