


# DSP56304

## Advance Information 24-BIT DIGITAL SIGNAL PROCESSOR

Motorola designed the ROM-based DSP56304 to support multifunction wireless and embedded DSP applications. In addition to the large on-chip ROM spaces, the DSP56304 also has a ROM patch feature that facilitates updates to the mask-program ROM-based on-chip software. The DSP56304 includes a triple timer module, Host Interface (HI08), an Enhanced Synchronous Serial Interface (ESSI), and a Serial Communications Interface (SCI). The DSP56300 core family includes a Phase Lock Loop (PLL), External Memory Interface (EMI), Data Arithmetic Logic Unit (Data ALU), 24-bit addressing, instruction cache, and DMA. The DSP56304 offers 66/80 MIPS using an internal 66/80 MHz clock at 3.0–3.6 volts.



**Figure 1** DSP56304 Block Diagram

This document contains information on a new product. Specifications and information herein are subject to change without notice.

## DSP56304 FEATURES

- High performance DSP56300 core
  - 66/80 Million Instructions Per Second (MIPS) with a 66/80 MHz clock
  - Object code compatible with the DSP56000 core
  - Highly parallel instruction set
  - Fully pipelined  $24 \times 24$ -bit parallel Multiplier-Accumulator (MAC)
  - 56-bit parallel barrel shifter
  - 24-bit or 16-bit arithmetic support under software control
  - Position independent code support
  - Addressing modes optimized for DSP applications
  - On-chip instruction cache controller
  - On-chip memory-expandable hardware stack
  - Nested hardware DO loops
  - Fast auto-return interrupts
  - On-chip concurrent six-channel DMA controller
  - On-chip Phase Lock Loop (PLL) and clock generator
  - On-Chip Emulation (OnCE™) module
  - JTAG Test Access Port (TAP)
  - Address Tracing mode reflects internal accesses at the external port
- On-chip memories
  - Program RAM, Instruction Cache, X data RAM, and Y data RAM size is programmable:

Instruction Cache	Switch Mode	Program RAM Size	Instruction Cache Size	X Data RAM Size	Y Data Ram Size
disabled	disabled	$1024 \times 24$ -bit	0	$3328 \times 24$ -bit	$1792 \times 24$ -bit
enabled	disabled	0	$1024 \times 24$ -bit	$3328 \times 24$ -bit	$1792 \times 24$ -bit
disabled	enabled	$3584 \times 24$ -bit	0	$2048 \times 24$ -bit	$512 \times 24$ -bit
enabled	enabled	$2560 \times 24$ -bit	$1024 \times 24$ -bit	$2048 \times 24$ -bit	$512 \times 24$ -bit

- $33,792 \times 24$ -bit Program ROM with Patch mode update capability using instruction cache memory space
- $9,216 \times 24$ -bit X data ROM and  $9,216 \times 24$ -bit Y data ROM
- $192 \times 24$ -bit bootstrap ROM

- Off-chip memory expansion
  - Data memory expansion to two 256 K × 24-bit word memory spaces
  - Program memory expansion to one 256 K × 24-bit word memory space
  - External memory expansion port
  - Chip select logic requires no additional circuitry to interface to SRAMs and SSRAMs
  - On-chip DRAM controller requires no additional circuitry to interface to DRAMs
- On-chip peripherals
  - 8-bit parallel Host Interface (HI08), ISA-compatible bus interface, providing a cost-effective solution for applications not requiring the PCI bus
  - Two Enhanced Synchronous Serial Interfaces (ESSI0 and ESSI1)
  - Serial Communications Interface (SCI) with baud rate generator
  - Triple timer module
  - Up to thirty-four programmable General Purpose I/O pins (GPIO), depending on which peripherals are enabled
- Reduced power dissipation
  - Very low power CMOS design
  - Wait and Stop low power standby modes
  - Fully-static logic, operation frequency down to DC
  - Optimized power management circuitry

## TARGET APPLICATIONS

The DSP56304 is intended for use in embedded multifunction DSP applications requiring large on-board ROM spaces, such as wireless products that combine standard cellular phone operation with options such as two-way digital paging and fax capability in one unit.

# PRODUCT DOCUMENTATION


The three manuals listed in **Table 1** are required for a complete description of the DSP56304 and are necessary to design with the part properly. Documentation is available from a local Motorola distributor, a Motorola semiconductor sales office, a Motorola Literature Distribution Center, or the World Wide Web.

**Table 1** DSP56304 Documentation

Document Name	Description of Contents	Order Number
DSP56300 Family Manual	Detailed description of the DSP56300 family architecture and the 24-bit core processor and instruction set	DSP56300FM/AD
DSP56304 User's Manual	Detailed description of DSP56304 memory, peripherals, and interfaces	DSP56304UM/AD
DSP56304 Technical Data	DSP56304 pin and package descriptions, and electrical and timing specifications	DSP56304/D

Mfax and OnCE are trademarks of Motorola, Inc.



Motorola reserves the right to make changes without further notice to any products herein. Motorola makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Motorola assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "typical" parameters which may be provided in Motorola data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. Motorola does not convey any license under its patent rights nor the rights of others. Motorola products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support life, or for any other application in which the failure of the Motorola product could create a situation where personal injury or death may occur. Should Buyer purchase or use Motorola products for any such unintended or unauthorized application, Buyer shall indemnify and hold Motorola and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Motorola was negligent regarding the design or manufacture of the part. Motorola and  are registered trademarks of Motorola, Inc. Motorola, Inc. is an Equal Opportunity/Affirmative Action Employer.

How to reach us:

**USA/Europe/Locations Not Listed:**

Motorola Literature Distribution  
P.O. Box 20912  
Phoenix, Arizona 85036  
1 (800) 441-2447 or  
1 (602) 303-5454

**Mfax™:**

RMFAX0@email.sps.mot.com  
TOUCHTONE (602) 244-6609

**Asia/Pacific:**

Motorola Semiconductors H.K. Ltd.  
8B Tai Ping Industrial Park  
51 Ting Kok Road  
Tai Po, N.T., Hong Kong  
852-2662928

**Technical Resource Center:**

1 (800) 521-6274

**DSP Helpline**

dsphelp@dsp.sps.mot.com

**Japan:**

Nippon Motorola Ltd.  
Tatsumi-SPD-JLDC  
6F Seibu-Butsuryu-Center  
3-14-2 Tatsumi Koto-Ku  
Tokyo 135, Japan  
03-3521-8315

**Internet:**

<http://www.motorola-dsp.com>



**MOTOROLA**