

CSCI 200: Foundational Programming Concepts & Design

Lecture 38



Searching Algorithms

Previously in CSCI 200




- Merge Sort
 - split()
 - merge()
- Recursion
 - Defined in terms of self
 - Solve smaller version of same problem
 - Divide-and-Conquer
 - Decrease-and-Conquer

Sorting Complexities



Algorithm	Worst Case	Best Case	Average Case
Selection Sort	$O(n^2)$	$O(n^2)$	$O(n^2)$
Insertion Sort	$O(n^2)$	$O(n)$	$O(n^2)$
Bubble Sort	$O(n^2)$	$O(n)$	$O(n^2)$
Merge Sort	$O(n \log n)$	$O(n \log n)$	$O(n \log n)$

Questions?



??

Learning Outcomes For Today



- Explain how sorting a list affects the performance of searching for a value in a list.
- Implement linear and binary search.

On Tap For Today



- Searching
 - Linear Search
 - Binary Search
- Practice

On Tap For Today



- Searching
 - Linear Search
 - Binary Search
- Practice

Searching



- Different Types of Searches



Linear (unordered list)



Binary (ordered list)

On Tap For Today



- Searching
 - Linear Search
 - Binary Search
- Practice

Linear Search



- No knowledge of list contents
 - No requirement of list ordering
 - List is unsorted (or sorted)

Algorithm Complexities



Algorithm	Worst Case	Best Case	Average Case
Selection Sort	$O(n^2)$	$O(n^2)$	$O(n^2)$
Insertion Sort	$O(n^2)$	$O(n)$	$O(n^2)$
Bubble Sort	$O(n^2)$	$O(n)$	$O(n^2)$
Merge Sort	$O(n \log n)$	$O(n \log n)$	$O(n \log n)$
Algorithm	Worst Case	Best Case	Average Case
Linear Search			

Algorithm Complexities



Algorithm	Worst Case	Best Case	Average Case
Selection Sort	$O(n^2)$	$O(n^2)$	$O(n^2)$
Insertion Sort	$O(n^2)$	$O(n)$	$O(n^2)$
Bubble Sort	$O(n^2)$	$O(n)$	$O(n^2)$
Merge Sort	$O(n \log n)$	$O(n \log n)$	$O(n \log n)$
Algorithm	Worst Case	Best Case	Average Case
Linear Search	$O(n)$	$O(1)$	$O(n)$

On Tap For Today




- Searching
 - Linear Search
 - Binary Search
- Practice

Binary Search



- List must be sorted

Binary Search



Binary Search



- Values to keep track of
 - The list to search
 - Target value
 - Index to start search
 - Index to end search

Binary Search Pseudocode



- Examine middle element
 - If equals target
 - item found, return location
 - If greater than target
 - Ignore top half of list, continue search on bottom half
 - If less than target
 - Ignore bottom half of list, continue search on top half
- Repeat until
 - Target is found
 - start and end cross (not found)

Binary Search Pseudocode



- Examine middle element
 - If equals target
 - item found, return location
 - If greater than target
 - Ignore top half of list, **continue search on bottom half**
 - If less than target
 - Ignore bottom half of list, **continue search on top half**
- Repeat until
 - Target is found
 - start and end cross (not found)

Sounds Recursive!




- $T(n) = T(n/2) + 1$
- $T(1) = 1$
 - Follows the form of the “Master Theorem”

T

Sounds Recursive!



- $T(n) = T(n/2) + 1$
- $T(1) = 1$
 - Follows the form of the “Master Theorem”



Sounds Recursive!




- $T(n) = T(n/2) + 1$
- $T(1) = 1$
 - Follows the form of the “Master Theorem”



Sounds Recursive!




- $T(n) = T(n/2) + 1$
- $T(1) = 1$
 - Follows the form of the “Master Theorem”



Sounds Recursive!




- $T(n) = T(n/2) + 1$
- $T(1) = 1$
 - Follows the form of the “Master Theorem”



Sounds Recursive!




- $T(n) = T(n/2) + 1$
- $T(1) = 1$
 - Follows the form of the “Master Theorem”



Sounds Recursive!




- $T(n) = T(n/2) + 1$
- $T(1) = 1$
 - Follows the form of the “Master Theorem”



Sounds Recursive!



- $T(n) = T(n/2) + 1$
- $T(1) = 1$
 - Follows the form of the “Master Theorem”



- $O(\log n)$

Algorithm Complexities



Algorithm	Worst Case	Best Case	Average Case
Selection Sort	$O(n^2)$	$O(n^2)$	$O(n^2)$
Insertion Sort	$O(n^2)$	$O(n)$	$O(n^2)$
Bubble Sort	$O(n^2)$	$O(n)$	$O(n^2)$
Merge Sort	$O(n \log n)$	$O(n \log n)$	$O(n \log n)$
Algorithm	Worst Case	Best Case	Average Case
Linear Search	$O(n)$	$O(1)$	$O(n)$
Binary Search			

Algorithm Complexities



Algorithm	Worst Case	Best Case	Average Case
Selection Sort	$O(n^2)$	$O(n^2)$	$O(n^2)$
Insertion Sort	$O(n^2)$	$O(n)$	$O(n^2)$
Bubble Sort	$O(n^2)$	$O(n)$	$O(n^2)$
Merge Sort	$O(n \log n)$	$O(n \log n)$	$O(n \log n)$
Algorithm	Worst Case	Best Case	Average Case
Linear Search	$O(n)$	$O(1)$	$O(n)$
Binary Search	$O(\log n)$	$O(1)$	$O(\log n)$

Algorithm Complexities



Algorithm	Worst Case	Best Case	Average Case
Selection Sort	$O(n^2)$	$O(n^2)$	$O(n^2)$
Insertion Sort	$O(n^2)$	$O(n)$	$O(n^2)$
Bubble Sort	$O(n^2)$	$O(n)$	$O(n^2)$
Algorithm	Worst Case	Best Case	Average Case
Linear Search	$O(n)$	$O(1)$	$O(n)$
Binary Search	$O(\log n)$	$O(1)$	$O(\log n)$

- Other search algorithms exist (just as other sort algorithms exist too)

Binary Search



- Values to keep track of
 - The array to search, Target value, Index to start search, Index to end search
- Examine middle element
 - If equals target
 - item found, return location
 - If $\text{end} < \text{start}$
 - Item not found
 - If greater than target
 - Ignore top half of list, continue search on bottom half
 - If less than target
 - Ignore bottom half of list, continue search on top half

Binary Search



- Values to keep track of
 - The array to search, Target value, Index to start search, Index to end search
- Examine middle element
 - If equals target
 - item found, return location
 - If $\text{end} < \text{start}$
 - Item not found
 - If greater than target
 - Ignore top half of list, continue search on bottom half
 - If less than target
 - Ignore bottom half of list, continue search on top half

Binary Search



- Values to keep track of
 - The array to search, Target value, Index to start search, Index to end search
- Examine middle element
 - If equals target
 - item found, return location
 - If $\text{end} < \text{start}$
 - Item not found
 - If greater than target
 - Ignore top half of list, continue search on bottom half
 - If less than target
 - Ignore bottom half of list, continue search on top half
- Decrease-and-Conquer

Binary Search



- Values to keep track of
 - The array to search, Target value, Index to start search, Index to end search
- Examine middle element
 - If equals target
 - item found, return location
 - If $\text{end} < \text{start}$
 - Item not found
 - If greater than target
 - Ignore top half of list, continue search on bottom half
 - If less than target
 - Ignore bottom half of list, continue search on top half
- Decrease-and-Conquer
- So tempting to make recursive function...

Recursive Binary Search



```
template<typename T>
int binary_search(const List<T>& LIST, const T TARGET,
                 const int START_POS, const int END_POS) {
    const int MIDDLE_POS = (END_POS - START_POS) / 2 + START_POS;
    if (END_POS < START_POS)
        return -1;
    if (LIST[MIDDLE_POS] == TARGET)
        return MIDDLE_POS;
    if (LIST[MIDDLE_POS] > TARGET)
        return binary_search(LIST, TARGET, START_POS, MIDDLE_POS - 1);
    if (LIST[MIDDLE_POS] < TARGET)
        return binary_search(LIST, TARGET, MIDDLE_POS + 1, END_POS);
}

int targetPos = binary_search(myList, target, 0, myList.size() - 1);
```

Recursive Binary Search



```
template<typename T>
int binary_search(const List<T>& LIST, const T TARGET,
                 const int START_POS, const int END_POS) {
    const int MIDDLE_POS = (END_POS - START_POS) / 2 + START_POS;
    if (END_POS < START_POS)
        return -1;
    if (LIST[MIDDLE_POS] == TARGET)
        return MIDDLE_POS;
    if (LIST[MIDDLE_POS] > TARGET)
        return binary_search(LIST, TARGET, START_POS, MIDDLE_POS - 1);
    if (LIST[MIDDLE_POS] < TARGET)
        return binary_search(LIST, TARGET, MIDDLE_POS + 1, END_POS);
}

int targetPos = binary_search(myList, target, 0, myList.size() - 1);
```

- Concern/danger of recursion?

The Call Stack



```
void print_space(const int N) {
    for(int i = 0; i < N; i++) cout << " ";
}

void recurse( const int N ) {
    if(N <= 1) {
        print_space(N);  cout << "Done!" << endl;
    } else {
        print_space(N);  cout << "Start " << N << endl;
        recurse(N-1);
        print_space(N);  cout << "End " << N << endl;
    }
}

int main() {
    recurse(6);
    return 0;
}
```

The Call Stack



```
void print_space(const int N) {  
    for(int i = 0; i < N; i++) cout << " ";  
}  
void recurse( const int N ) {  
    if(N <= 1) {  
        print_space(N);  cout << "Done!" << endl;  
    } else {  
        print_space(N);  cout << "Start " << N << endl;  
        recurse(N-1);  
        print_space(N);  cout << "End " << N << endl;  
    }  
}  
int main() {  
    recurse(6);  
    return 0;  
}
```


./recurse
Start 6
Start 5
Start 4
Start 3
Start 2
Done!
End 2
End 3
End 4
End 5
End 6

The Call Stack



```
void print_space(const int N) {
    for(int i = 0; i < N; i++) cout << " ";
}
void recurse( const int N ) {
    if(N <= 1) {
        print_space(N);  cout << "Done!" << endl;
    } else {
        print_space(N);  cout << "Start " << N << endl;
        recurse(N-1);
        print_space(N);  cout << "End " << N << endl;
    }
}
int main() {
    recurse(6);
    return 0;
}
```

./recurse



The Call Stack



```
01 void print_space(const int N) {
02     for(int i = 0; i < N; i++) cout << " ";
03 }
04 void recurse( const int N ) {
05     if(N <= 1) {
06         print_space(N);  cout << "Done!" << endl;
07     } else {
08         print_space(N);  cout << "Start " << N << endl;
09         recurse(N-1);
10         print_space(N);  cout << "End " << N << endl;
11     }
12 }
13 int main() {
14     recurse(6);
15     return 0;
16 }
```

The Call Stack



```
01 void print_space(const int N) {
02     for(int i = 0; i < N; i++) cout << " ";
03 }
04 void recurse( const int N ) {
05     if(N <= 1) {
06         print_space(N);  cout << "Done!" << endl;
07     } else {
08         print_space(N);  cout << "Start " << N << endl;
09         recurse(N-1);
10         print_space(N);  cout << "End " << N << endl;
11     }
12 }
13 int main() {
14     recurse(6);
15     return 0;
16 }
```

main(): 14

The Call Stack



```
01 void print_space(const int N) {
02     for(int i = 0; i < N; i++) cout << " ";
03 }
04 void recurse( const int N ) {
05     if(N <= 1) {
06         print_space(N);  cout << "Done!" << endl;
07     } else {
08         print_space(N);  cout << "Start " << N << endl;
09         recurse(N-1);
10         print_space(N);  cout << "End " << N << endl;
11     }
12 }
13 int main() {
14     recurse(6);
15     return 0;
16 }
```

recurse(6): 04

main(): 14

The Call Stack



```
01 void print_space(const int N) {
02     for(int i = 0; i < N; i++) cout << " ";
03 }
04 void recurse( const int N ) {
05     if(N <= 1) {
06         print_space(N);  cout << "Done!" << endl;
07     } else {
08         print_space(N);  cout << "Start " << N << endl;
09         recurse(N-1);
10         print_space(N);  cout << "End " << N << endl;
11     }
12 }
13 int main() {
14     recurse(6);
15     return 0;
16 }
```

recurse(6): 05

main(): 14

The Call Stack



```
01 void print_space(const int N) {
02     for(int i = 0; i < N; i++) cout << " ";
03 }
04 void recurse( const int N ) {
05     if(N <= 1) {
06         print_space(N);  cout << "Done!" << endl;
07     } else {
08         print_space(N);  cout << "Start " << N << endl;
09         recurse(N-1);
10         print_space(N);  cout << "End " << N << endl;
11     }
12 }
13 int main() {
14     recurse(6);
15     return 0;
16 }
```

recurse(6): 08

main(): 14

The Call Stack



```
01 void print_space(const int N) {
02     for(int i = 0; i < N; i++) cout << " ";
03 }
04 void recurse( const int N ) {
05     if(N <= 1) {
06         print_space(N);  cout << "Done!" << endl;
07     } else {
08         print_space(N);  cout << "Start " << N << endl;
09         recurse(N-1);
10         print_space(N);  cout << "End " << N << endl;
11     }
12 }
13 int main() {
14     recurse(6);
15     return 0;
16 }
// output
    Start 6
```

recurse(6): 09

main(): 14

The Call Stack



```
01 void print_space(const int N) {
02     for(int i = 0; i < N; i++) cout << " ";
03 }
04 void recurse( const int N ) {
05     if(N <= 1) {
06         print_space(N);  cout << "Done!" << endl;
07     } else {
08         print_space(N);  cout << "Start " << N << endl;
09         recurse(N-1);
10         print_space(N);  cout << "End " << N << endl;
11     }
12 }
13 int main() {
14     recurse(6);
15     return 0;
16 }
// output
    Start 6
```

recurse(5): 04

recurse(6): 09

main(): 14

The Call Stack



```
01 void print_space(const int N) {
02     for(int i = 0; i < N; i++) cout << " ";
03 }
04 void recurse( const int N ) {
05     if(N <= 1) {
06         print_space(N);  cout << "Done!" << endl;
07     } else {
08         print_space(N);  cout << "Start " << N << endl;
09         recurse(N-1);
10         print_space(N);  cout << "End " << N << endl;
11     }
12 }
13 int main() {
14     recurse(6);
15     return 0;
16 }
// output
    Start 6
```

recurse(5): 05

recurse(6): 09

main(): 14

The Call Stack



```
01 void print_space(const int N) {
02     for(int i = 0; i < N; i++) cout << " ";
03 }
04 void recurse( const int N ) {
05     if(N <= 1) {
06         print_space(N);  cout << "Done!" << endl;
07     } else {
08         print_space(N);  cout << "Start " << N << endl;
09         recurse(N-1);
10         print_space(N);  cout << "End " << N << endl;
11     }
12 }
13 int main() {
14     recurse(6);
15     return 0;
16 }
// output
    Start 6
```

recurse(5): 08

recurse(6): 09

main(): 14

The Call Stack



```
01 void print_space(const int N) {
02     for(int i = 0; i < N; i++) cout << " ";
03 }
04 void recurse( const int N ) {
05     if(N <= 1) {
06         print_space(N);  cout << "Done!" << endl;
07     } else {
08         print_space(N);  cout << "Start " << N << endl;
09         recurse(N-1);
10         print_space(N);  cout << "End " << N << endl;
11     }
12 }
13 int main() {
14     recurse(6);
15     return 0;
16 }
// output
    Start 6
    Start 5
```

recurse(5): 09

recurse(6): 09

main(): 14

The Call Stack



```
01 void print_space(const int N) {
02     for(int i = 0; i < N; i++) cout << " ";
03 }
04 void recurse( const int N ) {
05     if(N <= 1) {
06         print_space(N);  cout << "Done!" << endl;
07     } else {
08         print_space(N);  cout << "Start " << N << endl;
09         recurse(N-1);
10         print_space(N);  cout << "End " << N << endl;
11     }
12 }
13 int main() {
14     recurse(6);
15     return 0;
16 }
// output
    Start 6
    Start 5
    Start 4
    Start 3
    Start 2
    Start 1
```

recurse(1): 05

recurse(2): 09

recurse(3): 09

recurse(4): 09

recurse(5): 09

recurse(6): 09

main(): 14

The Call Stack



```
01 void print_space(const int N) {
02     for(int i = 0; i < N; i++) cout << " ";
03 }
04 void recurse( const int N ) {
05     if(N <= 1) {
06         print_space(N);  cout << "Done!" << endl;
07     } else {
08         print_space(N);  cout << "Start " << N << endl;
09         recurse(N-1);
10         print_space(N);  cout << "End " << N << endl;
11     }
12 }
13 int main() {
14     recurse(6);
15     return 0;
16 }
// output
    Start 6
    Start 5
    Start 4
    Start 3
    Start 2
    Start 1
```

recurse(1): 06

recurse(2): 09

recurse(3): 09

recurse(4): 09

recurse(5): 09

recurse(6): 09

main(): 14

The Call Stack



```
01 void print_space(const int N) {
02     for(int i = 0; i < N; i++) cout << " ";
03 }
04 void recurse( const int N ) {
05     if(N <= 1) {
06         print_space(N);  cout << "Done!" << endl;
07     } else {
08         print_space(N);  cout << "Start " << N << endl;
09         recurse(N-1);
10         print_space(N);  cout << "End " << N << endl;
11     }
12 }
13 int main() {
14     recurse(6);
15     return 0;
16 }
// output
    Start 6
    Start 5
    Start 4
    Start 3
    Start 2
    Start 1
Done!
```

recurse(2): 09

recurse(3): 09

recurse(4): 09

recurse(5): 09

recurse(6): 09

main(): 14

The Call Stack



```
01 void print_space(const int N) {
02     for(int i = 0; i < N; i++) cout << " ";
03 }
04 void recurse( const int N ) {
05     if(N <= 1) {
06         print_space(N);  cout << "Done!" << endl;
07     } else {
08         print_space(N);  cout << "Start " << N << endl;
09         recurse(N-1);
10         print_space(N);  cout << "End " << N << endl;
11     }
12 }
13 int main() {
14     recurse(6);
15     return 0;
16 }
// output
    Start 6
    Start 5
    Start 4
    Start 3
    Start 2
    Start 1
Done!
```

recurse(2): 10
recurse(3): 09
recurse(4): 09
recurse(5): 09
recurse(6): 09
main(): 14

The Call Stack



```
01 void print_space(const int N) {
02     for(int i = 0; i < N; i++) cout << " ";
03 }
04 void recurse( const int N ) {
05     if(N <= 1) {
06         print_space(N);  cout << "Done!" << endl;
07     } else {
08         print_space(N);  cout << "Start " << N << endl;
09         recurse(N-1);
10         print_space(N);  cout << "End " << N << endl;
11     }
12 }
13 int main() {
14     recurse(6);
15     return 0;
16 }
```

```
// output
    Start 6
    Start 5
    Start 4
    Start 3
    Start 2
    Start 1
```

Done!

End 1

recurse(3): 09

recurse(4): 09

recurse(5): 09

recurse(6): 09

main(): 14

The Call Stack



```
01 void print_space(const int N) {
02     for(int i = 0; i < N; i++) cout << " ";
03 }
04 void recurse( const int N ) {
05     if(N <= 1) {
06         print_space(N);  cout << "Done!" << endl;
07     } else {
08         print_space(N);  cout << "Start " << N << endl;
09         recurse(N-1);
10         print_space(N);  cout << "End " << N << endl;
11     }
12 }
13 int main() {
14     recurse(6);
15     return 0;
16 }
```

```
// output
    Start 6
    Start 5
    Start 4
    Start 3
    Start 2
    Start 1
```

Done!

End 1

recurse(3): 10

recurse(4): 09

recurse(5): 09

recurse(6): 09

main(): 14

The Call Stack



```
01 void print_space(const int N) {
02     for(int i = 0; i < N; i++) cout << " ";
03 }
04 void recurse( const int N ) {
05     if(N <= 1) {
06         print_space(N);  cout << "Done!" << endl;
07     } else {
08         print_space(N);  cout << "Start " << N << endl;
09         recurse(N-1);
10         print_space(N);  cout << "End " << N << endl;
11     }
12 }
13 int main() {
14     recurse(6);
15     return 0;
16 }
```

```
// output
    Start 6
    Start 5
    Start 4
    Start 3
    Start 2
    Start 1
```

Done!

End 1

recurse(6): 10

main(): 14

The Call Stack



```
01 void print_space(const int N) {
02     for(int i = 0; i < N; i++) cout << " ";
03 }
04 void recurse( const int N ) {
05     if(N <= 1) {
06         print_space(N);  cout << "Done!" << endl;
07     } else {
08         print_space(N);  cout << "Start " << N << endl;
09         recurse(N-1);
10         print_space(N);  cout << "End " << N << endl;
11     }
12 }
13 int main() {
14     recurse(6);
15     return 0;
16 }
```

```
// output
    Start 6
    Start 5
    Start 4
    Start 3
    Start 2
    Start 1
```

Done!

End 1

main(): 15

The Call Stack



```
01 void print_space(const int N) {
02     for(int i = 0; i < N; i++) cout << " ";
03 }
04 void recurse( const int N ) {
05     if(N <= 1) {
06         print_space(N);  cout << "Done!" << endl;
07     } else {
08         print_space(N);  cout << "Start " << N << endl;
09         recurse(N-1);
10         print_space(N);  cout << "End " << N << endl;
11     }
12 }
13 int main() {
14     recurse(6);
15     return 0;
16 }

// output
    Start 6
    Start 5
    Start 4
    Start 3
    Start 2
    Start 1
Done!
    End 1
```

Recursive Binary Search



```
template<typename T>
int binary_search(const List<T>& LIST, const T TARGET,
                 const int START_POS, const int END_POS) {
    ...
    return binary_search(LIST, TARGET, START_POS, MIDDLE_POS - 1);
}
```

- What is the run time?

Recursive Binary Search



```
template<typename T>
int binary_search(const List<T>& LIST, const T TARGET,
                 const int START_POS, const int END_POS) {
    ...
    return binary_search(LIST, TARGET, START_POS, MIDDLE_POS - 1);
}
```

- What is the run time? $O(\log n)$

Recursive Binary Search



```
template<typename T>
int binary_search(const List<T>& LIST, const T TARGET,
                 const int START_POS, const int END_POS) {
    ...
    return binary_search(LIST, TARGET, START_POS, MIDDLE_POS - 1);
}
```

- What is the run time? $O(\log n)$
- What is the extra memory usage?

Recursive Binary Search



```
template<typename T>
int binary_search(const List<T>& LIST, const T TARGET,
                 const int START_POS, const int END_POS) {
    ...
    return binary_search(LIST, TARGET, START_POS, MIDDLE_POS - 1);
}
```

- What is the run time? $O(\log n)$
- What is the extra memory usage? $O(\log n)$

Recursive Binary Search



```
template<typename T>
int binary_search(const List<T>& LIST, const T TARGET,
                 const int START_POS, const int END_POS) {
    ...
    return binary_search(LIST, TARGET, START_POS, MIDDLE_POS - 1);
}
```

- What is the run time? $O(\log n)$
- What is the extra memory usage? $O(\log n)$
- Is recursion necessary?

Recursive Binary Search



```
template<typename T>
int binary_search(const List<T>& LIST, const T TARGET,
                 const int START_POS, const int END_POS) {
    ...
    return binary_search(LIST, TARGET, START_POS, MIDDLE_POS - 1);
}
```

- What is the run time? $O(\log n)$
- What is the extra memory usage? $O(\log n)$
- Is recursion necessary?
 - Is there any backtracking going on?

Recursive Binary Search



```
template<typename T>
int binary_search(const List<T>& LIST, const T TARGET,
                 const int START_POS, const int END_POS) {
    ...
    return binary_search(LIST, TARGET, START_POS, MIDDLE_POS - 1);
}
```

- What is the run time? $O(\log n)$
- What is the extra memory usage? $O(\log n)$
- Is recursion necessary?
 - Is there any backtracking going on?
 - Any post-recursive work?

Recursive Binary Search



```
template<typename T>
int binary_search(const List<T>& LIST, const T TARGET,
                  const int START_POS, const int END_POS) {
    ...
    return binary_search(LIST, TARGET, START_POS, MIDDLE_POS - 1);
}
```

- What is the run time? $O(\log n)$
- What is the extra memory usage? $O(\log n)$
- Is recursion necessary? **No**
 - Is there any backtracking going on? **No**
 - Any post-recursive work? **No**

Iteration v Recursion



- If **Task ()** definition is of form
 A ()
 Task ()
 B ()
 use recursion
- If **Task ()** definition is of form
 A ()
 Task ()
 use iteration in place of tail recursion

Iteration v Recursion



- If **Task ()** definition is of form
 A ()
 Task ()
 B ()
use recursion
- If **Task ()** definition is of form
 A ()
 Task ()
use iteration in place of tail recursion
- *(NOTE: general rule of thumb...iteration can always replace recursion...)*

Iterative Binary Search



- Run Time is still $O(\log n)$
- Extra memory usage is now $O(1)$

```
template<typename T>
int binary_search(const List<T>& LIST, const T TARGET) {
    int startPos = 0, endPos = myList.size() - 1;
    int targetPos = -1;
    while( true ) {
        // perform search...
    }
    return targetPos;
}
```

Algorithm Complexities



- Scenario A
 - Unsorted list of n elements
 - Need to check if m values exist
 - Total Cost?
- Scenario B
 - Sort list of n elements
 - Need to check if m values exist
 - Total Cost?

Algorithm Complexities



- Scenario A
 - Unsorted list of n elements $O(1)$
 - Need to check if m values exist $m \cdot O(n) \rightarrow O(mn)$
 - Total Cost? $O(mn) \rightarrow O(n^2)$
- Scenario B
 - Sort list of n elements $O(n \log n)$
 - Need to check if m values exist $m \cdot O(\log n) \rightarrow O(m \log n)$
 - Total Cost? $O(\max(m, n) \log n) \rightarrow O(n \log n)$

On Tap For Today



- Searching
 - Linear Search
 - Binary Search
- Practice

To Do For Next Time



- Rest of semester
 - W 12/03: 2D Lists + BFS/DFS
 - F 12/05: Stack & Queue
 - M 12/08: Trees & Graphs, L6B due, Quiz 6
 - W 12/10: Exam Review, L6C due, Exam XC due
 - R 12/11: A6, AXC, Final Project due
 - M 12/15 8am - 10am: Final Exam