

Kantech

Data Sheet

KT-2 Two-Door Controller



Key Features

- Configurable in two different modes: Provides advanced access control features when used with EntraPass Security Management Software (using an Ethernet, RS-485, or WiFi connection) or basic door security in Standalone Mode*
- The built-in Wi-Fi antenna helps reduce installation costs when used with EntraPass
- Included 12Vdc 4A power Supply in metal cabinet. (KT-2-EU-MET)
- Flexible power input – Power over Ethernet (PoE), PoE+ or 12 VDC
- End-to-end encryption using Kantech's ioSmart reader & smart card
- Compatible with EntraPass Security Management Software v8.40 or higher

Kantech KT-2 two-door controller supports four** readers and can be configured in two user friendly operational modes. The KT-2 Standalone Mode offers basic two-door security using a simple web browser without the need to connect to a host system. Alternatively KT-2 can be used with the powerful EntraPass Security Management Software to provide more advanced and fully integrated access control features such as Wi-Fi connection. Utilizing the built-in Wi-Fi antenna reduces installation time and costs while providing an ideal solution for projects with challenging infrastructure designs that would require extensive cabling.



* WiFi communication is not available in stand-alone mode.

** With EntraPass version 8.50 onwards

The power behind **your mission**

KT-2 Standalone Mode

Simple and User-Friendly Access Control

Ideal for sites that only need basic door security, the KT-2 two-door controller features an embedded web server which enables it to operate in Standalone Mode – meaning no server based EntraPass software is required.

One Combined Hardware and Web-based Software Solution

With no extra security software to purchase and install, and using an intuitive web browser for quick set up, KT-2 Standalone provides a cost-effective, yet feature rich alternative for two-door security.

Responsive Web-based Software

Intuitive and responsive web-based software enables you to simply manage and configure your two-door security from anywhere, using a desktop or mobile device.

Standalone Set-Up Wizard

KT-2 Standalone offers the ultimate simplicity in access control installation. Simply power up KT-2; connect to a web browser; follow the quick set-up configuration wizard and your two-door security is up and running in minutes.

Standalone Mode Parameters

Function	Limit
Cardholders	2,000 (1,000 with image/ 1,000 without image)
Door Access	Per door, per user
Card Families or Site Codes	Unlimited
Events	60,000 (Offline Mode)
Operators	2 (Installer, Operator)
Schedules	20 (5 intervals)
Holidays	25
Action Scheduler	100
Monitored Points (Inputs)	4
Auxiliary Outputs	4
Browsers	Safari, Google Chrome, Mozilla Firefox, Internet Explorer, Microsoft Edge
Mobile Operating Software	iOS, Android (No native app)
Integrations	Basic intrusion via relays
Upgrade Path	EntraPass/ hattrix
Languages	English, French, Spanish, Italian
Firmware version	KT-2 Standalone version 3.03 & higher. (Subject to firmware upgrade fees)



KT-2 Using EntraPass

Advanced and Fully Integrated Access Control

Using EntraPass software a single KT-2 Controller can control two doors or can act as a 'head IP controller', linking together 31 additional controllers under one IP connection in EntraPass. This significantly reduces the amount of IP connections required to EntraPass and reduces programming time in the software, thus creating installation cost benefits and a highly scalable solution.

One Touch for Quick Connection to EntraPass

The KT-2 controller features a capacitive touch-sensitive button for plug and play installation. Simply provide an IP connection, push a single button and you're done. There is no need to manually enter MAC/Serial numbers. With its innovative single button programming, the KT-2 is automatically detected and enrolled onto the EntraPass security management software (v8.40 and higher). Quickly connect using Universal Plug and Play (UPnP) protocol allowing the controller to be network discoverable without requiring the IP address*.

With its Ethernet port for direct network connection, its Power over Ethernet capabilities, the WiFi and its unique single button programming, the KT-2 controller is up and running in just a few simple steps.



EntraPass Web & Go

Combine the KT-2 controller with EntraPass security management software and the EntraPass web and go mobile applications to create an innovative solution that installs quickly, can be managed remotely and provides a superior user experience. Admin users can connect via a web browser or a dedicated app on their smart phone/tablet and manage common security tasks wherever they are.

Alarm Panel Integration

DSC MAXSYS, PowerSeries, PowerSeries Neo and PowerSeries Pro alarm panel data integration can be accomplished by connecting it to the KT-2 controller. Using this controller; EntraPass Special, Corporate or Global Editions are able to receive intrusion events, view the status of zones and partitions, and program users' code. In addition the system can be armed/disarmed (single or multiple partitions) via the reader or manual operation from the workstation.

Encrypted and Efficient Network Communication

The KT-2 controller uses 128-bit AES encryption to protect communication. It also acts as a polling device to ensure the controllers communicate with EntraPass only as required, thus reducing network traffic. Flexible options allow KT-2 to connect to EntraPass via:

- On-board IP (Ethernet) port
- RS-485 (COM1) port for communication between the EntraPass Gateway/ Kantech Network Communication Controller (KT-NCC) and KT-1/KT-300/KT-400 door controllers.

*Universal Plug and Play (UPnP) feature available when KT-2 is in factory mode or in Standalone Mode.
UPnP is turned off when the first connection is established to EntraPass Security Management Software

Specifications

Power Requirements	12 VDC / PoE / PoE+, 1.5 A
Operating temperatures	For European compliant installations: -10°C to 55°C (14°F to 131°F) Environmental Class II
Humidity level	85% relative humidity non-condensing
Cabinet dimensions	Metal Enclosure 380 mm x 334 mm x 95 mm (W x H x D)
Weight of the controller	2.16 kg (4.75 lb)
Reader types	Wiegand, proximity, ABA Clock and Data, bar code, magnetic, integrated keypad, smartcard and others
Reader power output	Maximum 0.5 A @ 12 VDC, typical 250mA per reader, protected and supervised
Monitored points (zone inputs)	8 monitored points (Z1 to Z8), NO/NC without EOL (DRY), single EOL, double EOL and 1 fixed-function tamper input
Points maximum wiring	AWG #22-600 m (2000 ft) For the relevant reader's maximum wiring specifications, refer to the reader's installation manual
Door strike power supervised	750 mA for one output or 1.0 A total (in PoE 13 W, 375 mA each or 750 mA total). Lock outputs are supervised for open circuit or short to ground fault detection
Auxiliary reader outputs	LEDs and buzzer (BUZ), 25 mA maximum each, open collector outputs
Relay controlled outputs	2 onboard Form C relays, 30 VDC, 3 Amps each, 0.6 power factor
Communication ports	1 x RS-232 with RJ-12, 2 x RS-485, 1 x Ethernet 10/100 Base-T with RJ-45, WiFi Note: Use the RS-232 for integrations, with a maximum cable length of 3 m (10 ft).
Wi-Fi specifications	Station mode wireless 802.11 b/g/n (2.4 GHz only) Access point wireless 802.11 n (2.4 GHz only)
Auxiliary power	1.0 A maximum. This is shared with door strike power
Communication speed	1200 to 115200 Bauds (automatic detection) over RS-485 10/100 Mb/s BaseT over Ethernet 1 Mb/s over Wi-Fi
Flash memory	256 MB NAND flash for application, storage and standalone event buffer holding 60,000 events
Network type	IEEE 802.00 b/g/n (Wireless LAN)
Frequency	2412-2471 MHz
RAM memory	128 MB DDR2 for application loading and running
Network autonomy	Distributed data and processing
Certifications/ Listing	EU: CE Radio Equipment Directive
AES Encryption	NIST CAVP validation number AES 3092, key length 128

Note: The KT-2 restarts automatically after total power loss and keeps its programming after an unlimited time of power interruption. The design uses flash memory to save access rules. For PoE-powered KT-2 and Class B installations, use a ferrite on the Ethernet cable.

Note: The KT-2 Wi-Fi performance level depends on the type of router that you use and on the installation environment. The KT-2 Wi-Fi access point mode is used for configuration: it requires a mobile, tablet, or laptop that has Wi-Fi capability and a web browser.

Ordering Information

KT-2 Order Information

Model Number	Description
KT-2-EU-MET	KT-2 2 Door Four** reader controller, Kit part contains a KT-2-PCB + KT-2-CAB-PSU
KT-2-CAB-PSU	KT-2 Metal Cabinet including Battery backed power supply 100-240VAC providing 13.VDC/ 5A to power the readers and locks (4x1.25A fused)
KT-2-PCB-EU	Replacement Part: KT-2 two Door reader Controller and backplane, no cabinet

** With EntraPass version 8.50 onwards

About Johnson Controls

Johnson Controls is a global diversified technology and multi-industrial leader serving a wide range of customers in more than 150 countries. Our 120,000 employees create intelligent buildings, efficient energy solutions, integrated infrastructure and next generation transportation systems that work seamlessly together to deliver on the promise of smart cities and communities. Our commitment to sustainability dates back to our roots in 1885, with the invention of the first electric room thermostat.

For additional information, please visit www.kantech.com or follow Kantech on LinkedIn, Twitter and Facebook.

© 2021 Johnson Controls. All rights reserved. Product offerings and specifications are subject to change without notice.

Actual products may vary from photos. Not all products include all features. Availability varies by region; contact your sales representative.

KT1332-DS-202108-R01-HS-EN-EMEA

The power behind **your mission**

