

Features



Best-in-class Performance

- Latest Suprema algorithm
- 1.2GHz quad-core CPU



Improved Accuracy & Security

- New advanced Live Finger Detection(LFD) technique
- High-precision OP5 optical sensor



Expanded Capacity

- Max. 500k users/1 million text logs
- Large memory: 2GB Flash + 256 MB RAM



Rugged Structure

- IK09 impact protection
- IP67 ingress protection
- Ideal for outdoor installation



Multi RFID Card Reading

- LF(125kHz), HF(13.56MHz) dual-band
- Reads all card types that HID multiCLASS supports (EM/HID Prox/MIFARE/iCLASS/DESFire/FeliCa/NFC)

Specifications

Model Name	BEW2-OHPB	BEW2-ODPB	BEW2-OAPB
RF Option	125KHz EM, HID Prox & 13.56MHz MIFARE, MIFARE Plus, DESFire, DESFire EV2/EV2/EV3 ^(*) , FeliCa	125KHz EM & 13.56MHz MIFARE, MIFARE Plus, DESFire, DESFire EV2/EV2/EV3 ^(*) , FeliCa	125KHz EM, HID Prox & 13.56MHz MIFARE, MIFARE Plus, DESFire, DESFire EV2/EV2/EV3 ^(*) , FeliCa, iCLASS SE/SR/Seos
Mobile Card	NFC, BLE		
Biometric	Fingerprint		
Sensor Type	Optical Sensor (OP5)		
Template	SUPREMA / ISO 19794-2 / ANSI 378		
Extractor / Matcher	MINEX certified and compliant		
LFD	Supported		
CPU	1.2 GHz Quad Core		
Memory	2GB Flash + 256 MB RAM		
Max. User	500,000 ^(*)		
Max. Credential (1:N)	Fingerprint: 100,000		
Max. Credential (1:1)	Fingerprint: 500,000 / Card: 500,000		
Max. Text Log	1,000,000		
Max. Image Log	Not supported		
LED	Multi-Color		
Sound	Multi-tone Buzzer		
Ethernet	Supported (10/100 Mbps, auto MDI/MDI-X)		
RS-485	1ch Master / Slave (Selectable)		
RS-485 Communication Protocol	OSDP V2 Compliant		
Wiegand	1ch Input / Output (Selectable)		
TTL Input	2ch Input		
Relay	1 Relay		
PoE	IEEE 802.3af compliant		
Ingress Protection	IP67		
Impact Protection	IK09		
Tamper	Supported		
Power	DC 12V 0.5A		
Operating Temperature	-20°C ~ 50°C (-4°F ~ 122°F)		
Operating Humidity	0% ~ 80%, non-condensing		
Dimensions (WxHxD, mm)	50 x 172 x 43.4 (Bottom) / 38.2 (Top)		
Certificates	CE, UKCA, KC, FCC, IC, RCM, BIS, ANATEL, SIG, RoHS, REACH, WEEE, ETL Listed to UL 294 * UL 294 is applied to only BEW2-OAPB model.		

^(*)DESFire EV2/EV3 cards are supported by having backward compatibility of DESFire EV3 cards. CSN and smart card functions are compatible with BioEntry W2.
^(**)The number of users registered without any credential data.