

Specifications

Model Name		BS3-DB	BS3-APWB
Biometrics		Face	
Credential	RF Option	125kHz EM & 13.56MHz MIFARE, MIFARE Plus, DESFire, DESFire EV1/EV2/EV3, FeliCa	125kHz EM, HID Prox & 13.56MHz MIFARE, MIFARE Plus, DESFire, DESFire EV1/EV2/EV3, FeliCa, iCLASS SE/SR/Seos
	RF Read Range ¹⁾	EM/HID Prox/MIFARE/DESFire/HID iCLASS: 30 mm, FeliCa: 15 mm	
	Mobile	NFC, BLE	
	Scramble Keypad (PIN)	Supported	
	QR/Barcode ²⁾	Supported ³⁾	
General	CPU	1.5 GHz Quad Core	
	Memory	32 GB Flash + 4 GB RAM	
	Crypto Chip	Supported	
	Display	5.5" IPS color LCD	
	Display Resolution	720 x 1280 pixels	
	Sound	16 bit	
	Operating Temperature	-20 °C ~ 50 °C (-4 °F ~ 122 °F)	
	Operating Humidity	0 % ~ 80 %, non-condensing	
	Camera	IR: 2M pixels / Visual: 2M pixels	
	Dimension (W x H x D)	82.5 x 171 x 23.4 (mm)	
	Weight	Device: 370 g	Device: 380 g
		Bracket: 90 g (Including washers and bolts)	
	IP Rating	IP65	
	IK Rating	IK06	
	Certifications	CE, UKCA, KC, FCC, IC, RCM, BIS, SIG, RoHS, REACH, WEEE, MIC, TELEC	CE, UKCA, KC, FCC, IC, RCM, BIS, SIG, RoHS, REACH, WEEE, MIC, TELEC, ETL Listed to UL294
Face	Authentication Distance ⁴⁾	0.3 ~ 1.0 m (11.8"~39")	
	Authentication Height	1.4 ~ 1.9 m (55.1"~74.8")	
	Matching Speed	Within 0.2 seconds	
	Live Face Detection (Anti-Spoofing)	Supported	
Capacity	Max. User	100,000 ⁵⁾	
	Max. Credential (1:N)	Face: 50,000	
	Max. Credential (1:1)	Face: 100,000 / Card: 100,000 / PIN: 100,000	
	Max. Text Log	5,000,000	
	Max. Image Log	50,000	
Interface	Ethernet	Supported (10/100/1000 Mbps, auto MDI/MDI-X)	
	Wi-Fi	Not supported	Supported (802.11 b/g/n 2.4 GHz)
	Network Protocol	TCP, UDP	
	RS-485	1 ch Master / Slave (Selectable)	
	RS-485 Communication Protocol	OSDP V2 compliant	
	Wiegand	1 ch Input, 1 ch Output	
	Input	3 ch Inputs	
	Relay	1 Relay	
	PoE+	Not supported	Supported (IEEE 802.3at compliant)
	Intercom	Supported	
	RTSP (Real Time Streaming Protocol)	Supported	
	USB	USB 2.0 (Host)	
	USB expansion port	Supported	
	Tamper	Supported	
Power		Voltage: 12 Vdc / Current: Max. 1 A Voltage: 24 Vdc / Current: Max. 0.7 A	

1) RF read range will vary depending on installation environment.

2) Supports QR/Barcodes composed of up to 32 ASCII code strings.

3) Requires a separate license.

4) The minimum facial authentication distance shown is the default setting for the product, and the recommended facial authentication distance is 0.6 to 1.0 m.

5) The number of users registered without having any credential data.

· If BioStation 3 is a master device and a device with a fingerprint sensor is connected as a slave, the slave device can be used for fingerprint authentication.

– Max. Fingerprint Credentials (1:N): 100,000 / Max. Fingerprint Credentials (1:1): 100,000