Report on indirect reciprocity, strategies for agents and the development of a concrete model to implement

JAMES KING Supervisor: Kostas Stathis

October 2018

Abstract

Indirect reciprocity is a mechanism that uses reciprocation theory to aid in the evolution of cooperation. Cooperation being an action taken by an individual that benefits another individual but at a cost to itself. Indirect reciprocity is a promising motivator for cooperation in societies with agents of higher intelligence levels and of greater sizes, such as human societies or even multi-agent systems. I plan to implement the mechanism programmatically, but there are many models and many possible additions to these models. In this report I will explore past approaches to indirect reciprocity, comparing and contrasting the variations proposed. The outcome of this exploration of approaches will be a concrete model to implement in this project.

I. Introduction

The evolution and preservation of cooperation has been a puzzle for evolutionary theorists for a long time. Many different approaches have been taken to give an explanation to cooperative phenomena, especially from the field of game-theory. Often these approaches have come from the idea of reciprocity, where agents can grow mutually beneficial relationships by repeated interactions. The most popular mechanism of this being direct reciprocity where interactions are repeated between the same two individuals, and thus they may reciprocate directly with each other.

There is another game-theoretic mechanism known as indirect reciprocity, which works on the idea that nice agents will help those who help each other. This means learning information about another player does not require direct interaction. A number of models have been proposed to run indirect reciprocity. It is these models I shall be describing and review-

ing, before using them to formulate my own to implement in my project.

II. REVIEW OF PAST WORK

i. Nowak, Sigmund and Image Scoring

Nowak and Sigmund's model [3] chooses a set of pairs of players at random each generation. A pair is made up of a donor and recipient. The donor can choose to cooperate - at a cost c, the recipient receives b points (b>c) - or defect - both receive 0 points, there is no cost to the donor though.

The model utilizes the idea of image scoring. In the first formulation of this all scores are public, but later on it is suggested that this model is unlikely to hold true in real life. As an alternative the idea of onlookers is suggested, where a set of onlookers are chosen for each interaction. In both models image scores are increased by one for a cooperation as a donor or decreased by one for a defection as a donor, though in the second model only the onlookers and recipient can add this to their perception of the donor. The use of onlookers does make cooperation harder to establish, as it is dependent on whether a player knows an accurate image score of the recipient.

The points accrued through interactions gives the fitness score of each player. The amount a player reproduces into the next generation is dependent of the fitness score. Mutation is also an option in this model, this phenomena is when a player reproduces at random their offspring can be a different strategy. Mutation can lead to loops where defectors are invaded by discriminators and then discriminators are undermined by cooperators - allowing defectors to take hold again.

The two simplest strategies are pure defection and pure cooperation. A key strategy to the evolution of cooperation is the discriminator strategy. In fact there is a baseline number of discriminators required for cooperation to evolve. This strategy is given a number k, if the image score of a player is greater than or equal to k a discriminator will cooperate with them. More interesting strategies take into account their own image score or theirs and the recipients image score, these can aid in the evolution of cooperation too. In the absence of information on other players these strategies can believe other players to have an image score of k with a certain probability.

The model is known to be dependent on the probability of knowing the image of another player. Cooperation can only be stable if q > c/b, q being the probability of knowing the image, c being the cost and b being the benefit.

Leimar and Hammerstein recognised the problems of genetic drift in this model [1]. Adopting an island population model to restrict this. Rather than one single population group, the group is divided up into g amount of groups each with population n. This model also uses a different reproductive strategy where relative reproductive success locally is calculated as a normalisation of the sum of the fitness of all strategies within the same group. For global expected reproductive success sum each strategy and normalize over the whole population. A new individual is then locally derived with probability p or globally derived with probability 1-p. The strategy for the individual produced is randomly generated with a distribution corresponding to the local or global reproductive success.

ii. Standing Strategy

The standing strategy was suggested by both Leimar and Hammerstein [1] and Roberts [5] to be superior to image scoring. Their models used the island population structure given above. Leimar and Hammerstein replaced image scoring with the standing strategy whereas Roberts mixed direct and indirect reciprocity (with both image scoring and the standing strategy).

The standing strategy as described by Milinski *et al.* [2] is that players should not just aim for a good fitness, but also good standing. Everyone starts on a good standing, but if a player is a donor to a good standing recipient and does not cooperate with them the donor loses their good standing.

This is seen as a benefit as with image scoring it is not always in a players interest to punish those with a low image score, as they lose reputation themselves and in turn reduces the likelihood of them being the recipient of a cooperation. Whereas reputation is only lost in the standing strategy if the recipient is not of a good standing.

iii. Mixed Reciprocity Models

Gilbert Roberts puts forward mixed direct and indirect reciprocity models [5] using image scoring in one model similar to Nowak and Sigmund [3] and standing strategy. Both models use the island and reproductive systems Leimar and Hammerstein [1] utilized. Roberts put forward this notion due to his perception that indirect reciprocity alone is not a generalisable concept due to the close knit nature of many societies.

Decisions can be made by agents in Roberts' model on the basis of either a reputation or an experience score. Reputation scores use image scoring in one model, differing from Nowak and Sigmund's as the score is within the range -1 to 1, initially at 0, decreasing by one for a defection and increasing by 1 for a cooperation. The standing strategy version assigns a -1 to a player when they defect against an individual or 1 to a player for anything else.

Experience scores are analoguous to direct reciprocity for Roberts. When using image scoring, the experience scores between 2 players are initially 0 and go to -1 if they have defected or 1 if the have cooperated in the previous interaction. For standing strategy -1 is assigned only if the players has defected with a partner of experience score 0 or 1 with them.

As you can see experience scores only reflect the previous interaction between the two individuals. This is a clear limitation as the model is seeking to describe a society made up of agents that have a higher intelligence.

Interestingly Roberts also considers the case where an agent has no resources to cooperate and thus must defect.

Steve Phelps [4] also recognises the same issue with indirect reciprocity as Gilbert Roberts - namely that remeeting in groups is likely, especially in smaller groups according to Phelps. Due to this Phelps suggests a mixed framework, to test how group sizes affect the use of direct or indirect reciprocity by agents.

iv. Gossip and Onlookers

It is recognised by Nowak and Sigmund [3] that it is unrealistic to expect all players to have directly observed a given interation. Yet their answer - onlookers - hampers the evolution of cooperation, which relies on the probability that a player knows the image score of another player.

Sommerfeld *et al.* highlighted the importance of communication to the management of reputations. Gossip is a type of communication that is key part of societal mechanics. The findings of their experiment were that gossip needs to

accurately reflect the interaction and the recipient of the gossip needs to correctly acted upon for gossip to be a adequate replacement for direct observation.

v. Comparison of Models

The aim of Roberts [5] is to compare the effectiveness of indirect reciprocity models and direct reciprocity. Roberts' results support Nowak and Sigmund's 1998 result that image scoring can support cooperation is robust even when criticisms relating to genetic drift and errors are taken into consideration.

However, it is highlighted that image scoring does not take into account who the donor is defecting against, whereas standing strategy does. Due to this image scoring suffers from an inability to distinguish between pure defectors and those who would cooperate with a cooperator. Standing strategy gives information both about how agents have interacted and the context of this action, an advantage over image scoring.

Counter to standing strategies percieved benefits it is seen that players are more susceptible to errors in perception, as standing falls faster than image score. Roberts also criticizes the standing strategy as not being a representation of the evolution of cooperation, as good standing can't have been established before the game had begun.

Roberts also points out that cooperation is only worth it when that cooperation is improving your chance of being cooperated with. This could be a counter point to the effectiveness of gossip as an alternative to direct observation. In gossip there is a possibility of interactions being distorted by incorrect gossip. It could be interesting to see how the spread of misinformation could permeate society.

III. A CONCRETE MODEL

Specification of the Model

Both image scoring and standing strategy are good models for indirect reciprocity. They allow an agent to interpret a reputation and act as they see fit. However, the reputation of each player being universally viewable is unrealistic. The idea of onlookers seems closer to real life but is restrictive to the evolution of cooperation. The addition of gossip from these onlookers could be a sufficient alternative to direct observation, but gossip can be distorted by players wishing to influence proceedings against cooperation.

Gossip complicates a model because there is a need to interpret the information gossiped by another player. This also highlights an issue with the models that use purely standing strategy or image scoring: reputation is not a centralised system with everyone interpretting events the same way. Reputation has a very subjective nature, especially when gossip is introduced. Due to the subjectivity of perception about an agents reputation I do not believe that one specific model for all agents can be considered appropriate. How a player views another players reputation must be up to their inside workings.

This requires an agent to have a view of past events and also a way to interpret these events in order to make decisions about another player. A model that uses this decentralised judgement on past events easily becomes a hybrid indirect and direct reciprocity game, as agents can have their own way to interpret interactions.

For an agent to interpret gossip, the gossip must be comprehensible by them, and thus should have a given structure. In our model, gossip shall be split into two categories: positive and negative. Gossip will also involve 3 agents, the agent gossiping, the recipient of the gossip, and the gossip that the agent is about (who shall not be able to view that the gossip has taken place).

The structure of the game will be as follows. There is one singular population (this is to not overly complicate the model, though the addition of island population groups could be an extension), a population is replaced by their offspring after the conclusion of a generation. A generation is made up of a number of distinct time points (the number of time points per gen-

eration will be a variable) in which interactions occur simultaneously and are then gossiped about in that same time point. Each interaction shall be made up of a donor-recipient pair, chosen at random from the population. The number of interactions per time point is another variable. For each interaction a subset of the population should be chosen as direct observers. After the interaction has taken place the observers, recipient and donor will then have the chance to gossip (this shall take place at the same time point for simplicity). The opportunity to gossip shall be limited by the number of people they are able to gossip to, this number of people is a variable.

Finally reproduction occurs at the end of every generation and will be relative to each players fitness. Fitness is altered in each interaction, if the donor cooperates they lose a fitness point but the recipient gains two, if the donor defects they both gain nothing and lose nothing. The group size remains the same over generations, so in a new generation individuals are generated and assigned strategies. The chance an individual will be a certain strategy is worked out by summing the fitness of all individuals of that strategy and dividing it by the fitness of the overall group. There will be optional mutation, if chosen there will be a 1% chance that a new individuals strategy will be chosen completely at random.

ii. Specification of Agent Strategies

In our model an agent is required to have three strategies: one strategy on spreading information, one to interpret the information it is presented from direct observation, gossip and interaction and the other as a way to act on the interpretation of events. An agent will also have to have their own way of being a donor with no information available to the recipient. First I will look at agents interpretation of events. Of course some players will not bother to interpret events, but simply act as according to a given plan e.g. pure defection, cooperation or an alternation of both.

There will be two classes of strategy: trusting

and distrusting. Both can use any of the strategies, but distrusting strategies will not take into account gossip.

There should be a strategy for a player to form an image score of another player based on events related to this other player, this allows discriminator strategies and strategies that base their decision on their own image score and the recipients to be present. The image score will increase when viewing a cooperation, hearing positive gossip about them, or being the recipient of cooperation and vice versa.

Another strategy is similar to the standing strategy where a player considers everyone in neutral standing (similar to Roberts' version) until a negative event about them, a negative event specifically being a defection against another agent with what the agent considers to be neutral/good standing (including themselves) or negative gossip about the agent.

Spreading of gossip also requires a strategy, following are a few possible strategies: always gossip accurate information to random players, always gossip innaccurate information to random people, always gossip negative or positive information to random players, randomly gossip positively or negatively. The last two having a close connection to pure defectors and pure cooperators respectively.

An extension of the project could be to look at other strategies for spreading and interpretting gossip.

Of course how an agent acts is dependent upon their interpretation mechanism. Pure defectors and cooperators do not rely on one, but discriminators could use either their inner image scoring mechanism and agents using a standing strategy may cooperate with another agent with neutral/good standing. Other strategies include the use of image scores of both their own and the recipients and random cooperation/defection. An extension of this could be a strategy that uses some sort of machine learning algorithm.

IV. Discussion and Conclusion

Consider how it applies to multi-agent systems.

REFERENCES

- [1] Olof Leimar and Peter Hammerstein. Evolution of cooperation through indirect reciprocity. *Proceedings of The Royal Society*, 268:745–753, May 2001.
- [2] Theo C. M. Bakker Manfred Milinski, Dirk Semmann and Hans-Jürgen Krambeck. Cooperation through indirect reciprocity: image scoring or standing strategy? *Proceedings of The Royal Society*, 268:2495–2501, May 2001.
- [3] Martin A. Nowak and Karl Sigmund. Evolution of indirect reciprocity by image scoring. *Nature*, 393:573–577, 1998.
- [4] Steve Phelps. An empirical game-theoretic analysis of the dynamics of cooperation in small groups. *Journal of Artificial Societies and Social Simulation*, 2016.
- [5] Gilbert Roberts. Evolution of direct and indirect reciprocity. *Proceedings of The Royal Society*, 275:173–179, September 2008.
- [6] Ralf D. Sommerfeld, Hans-Jürgen Krambeck, Dirk Semmann, and Manfred Milinski. Gossip as an alternative for direct observation in games of indirect reciprocity. Proceedings of the National Academy of Sciences of the United States of America, 104:17435–17440, 2007.