



MINIT Ignífugos

minitargentina@gmail.com www.minitfireretardant.com

COPIA FIEL DE CERTIFICADOS

Producto MINIT TOTAL

Presentación válida únicamente con el Certificado / Factura de Compra



INDEX

Página 2: INTI-CIT-IRAM G7577 (INFLAMABILIDAD VERTICAL DE TEXTILES NIVEL 1 – CLASE A)

Página 4: NFPA 701 (INFLAMABILIDAD VERTICAL DE TEXTILE SINTETICO NIVEL 1 – CLASE A) (Homologado con : INTI-CIT-IRAM G7577 - Mismo ensayo pero superior – tela con peso para telones de escenario)

Página 7: NFPA 705 (INFLAMABILIDAD VERTICAL DE TEXTILES NATURALES NIVEL 1 – CLASE A) (Homologado con : INTI-CIT-IRAM G7577 - Mismo ensayo) Govmark/SGS (<https://www.sgs.com/en/service-groups/fire-testing>) Convenio de reciprocidad INTI / SGS, 23/08/2001

Página 10: CAL 117 – CALIFORNIA MARSHAL (INFLAMABILIDAD HORIZONTAL DE TEXTILES NATURALES = APROBADO) Alfombras, Frazadas, todo tejido natural que se encuentre en forma horizontal.

Página 11: CAL 117 – CALIFORNIA MARSHAL (INFLAMABILIDAD HORIZONTAL DE TEXTILES SINTETICOS = APROBADO) Alfombras, Frazadas, todo tejido natural que se encuentre en forma horizontal.

Página 12: CAL TB 117: 2013 (INFLAMABILIDAD HORIZONTAL EN ALFOMBRAS SINTETICAS)

Página 14: HOMOLOGACIÓN CAL TB 117 CON IRAM 11910.

Página 15: IRAM 11910-3 NBR 9442/86 ASTM 162 (METODO PANEL RADIANTE EN MADERA, RE4 CLASE C, MEDIANA PROPAGACION DEL FUEGO)

Página 17: ASTM 162 Equivalente (Homologado) a IRAM 11910-3 NBR 9442/86 y con estándares europeos: CSE RF 3/77; BS 476 part 6 and part 7 (METODO PANEL RADIANTE EN MADERA, CARTÓN Y PAPEL) Resultado: Determinación de la propagación superficial de llama "I" 39.8 (IRAM RE 3, Clase ABNT "B"). Baja Propagación. Govmark/SGS (<https://www.sgs.com/en/service-groups/fire-testing>) Convenio de reciprocidad INTI / SGS, 23/08/2001

Página 19: IRAM 11910-3 NBR 9442/86 ASTM 162 (METODO PANEL RADIANTE EN GOMA ESPUMA, RE2 CLASE A, BAJA PROPAGACION DEL FUEGO.

Página 21: BS5852 y CAL TB 117 Resultado PASS (Inflamabilidad Horizontal en Pasto Sintético) Homologación Página 14

Página 23: UIC 564-2 : 1991 (APENDICE 13) Material Plástico.

Página 25: ENSAYOS DE EMANACIÓN y DENSIDAD DE HUMO Y GASES

Página 29: HOMOLOGACIÓN de De Densidad de Humo NORMA IRAM 11914

Marco de Reconocimiento Internacional (Reciprocidad)

El sistema de aceptación de ensayos extranjeros en Argentina se basa en acuerdos internacionales de reciprocidad que eliminan la necesidad de repetir pruebas locales. Recientemente, el marco normativo se ha simplificado mediante el Decreto 892/2025.

El Gobierno argentino estableció el reconocimiento automático de certificaciones y ensayos internacionales para agilizar el comercio:

- Se consideran válidos los ensayos realizados en países con altos estándares de vigilancia técnica (países de "alta vigilancia") detallados en la normativa.
- Los productos que posean certificaciones de laboratorios acreditados por entidades avaladas por acuerdos de reciprocidad no requieren nuevos ensayos locales.

Principales Organismos de Acreditación y Cooperación Regional e Internacional

Organismo	Alcance	Hol Principal
ILAC	Global	Cooperación para laboratorios de ensayo y calibración.
IAF	Global	Reconocimiento de organismos de certificación de productos y sistemas.
IAAC	Regional (Américas)	Cooperación interamericana de Acreditación.
OCDE	Global	Acuerdos de "Aceptación Mutua de Datos" (MAD) para seguridad ambiental y sanitaria.
A2LA	Regional (Américas)	Asociación para la Acreditación de Laboratorios. Bajo la norma ISO/IEC 17025. Garantiza la competencia técnica y la confianza global
ANAB / ANSI	Regional (Américas)	Junta de Acreditación. Organismo de acreditación de normas, laboratorios y organismos de inspección y certificación (ISO/IEC 17025, 17020, 17021, 17034).



MINIT Ignífugos

minitargentina@gmail.com www.minitfireretardant.com

COPIA FIEL DE CERTIFICADOS

Producto MINIT TOTAL

Presentación valida únicamente con el Certificado / Factura de Compra



INTI-CIT-IRAM G7577 (INFLAMABILIDAD VERTICAL DE TEXTILES NIVEL 1 – CLASE A)

INTI  Construcciones

INFORME DE ENSAYO

Solicitante: MINOTTI PABLO DAVID

O.T.: 101/20631

Pág.: 1 de 2

Fecha: 03/05/2011

Informe: Único.

Dirección: Cochrane 2322

(1419) – Cdad. Autónoma de Buenos Aires

1. OBJETIVO

Determinación de la Inflamabilidad Vertical de Textiles

2. MATERIAL

Una (1) muestra de tela color blanca, de composición no declarada, identificada por el solicitante como: "Tela con tratamiento retardante marca MINIT de Pablo Minotti"

Nota: La tela presenta una textura acartonada como resultado del tratamiento aplicado, no habiendo sido informado el proceso de aplicación del mismo.



3. MÉTODO EMPLEADO

El ensayo de Inflamabilidad Vertical de Textiles se realizó de acuerdo a las indicaciones de la Norma IRAM-INTI-CIT G 7577, "MATERIALES TEXTILES – Método de ensayo de comportamiento a la llama con la probeta vertical".

La muestra fue recibida el día 26/04/2011 y se ensayó el día 02/05/2011

4. RESULTADOS OBTENIDOS

La clasificación se hace teniendo en cuenta las referencias consignadas a continuación:

Análisis cualitativo:

- Entra en ignición y la llama se propaga.
- Entra en ignición, pero es autoextinguible.
- No entra en ignición.
- Funde
- Se contrae y se aleja de la llama.
- Gotea y caen trozos encendidos.

Este informe no podrá ser reproducido parcialmente sin la autorización escrita del Laboratorio. Los resultados consignados se refieren exclusivamente a los elementos recibidos, el INTI y su Centro de Investigación y Desarrollo en Construcciones declinan toda responsabilidad por el uso indebido o incorrecto que se hiciera de este informe.

Instituto Nacional de Tecnología Industrial
Centro de Investigación y Desarrollo
en Construcciones

Avenida General Paz 5445
B1650KNA San Martín, Buenos Aires, Argentina
Teléfono (54 11) 4724 6200
e-mail: construcciones@inti.gob.ar



MINIT Ignifugos

minitargentina@gmail.com www.minitfireretardant.com

COPIA FIEL DE CERTIFICADOS

Producto MINIT TOTAL

Presentación valida únicamente con el Certificado / Factura de Compra



validacion



Solicitante: MINOTTI PABLO DAVID

Dirección: Cochrane 2322
(1419) – Cdad. Autónoma de Buenos Aires

O.T.: 101/20631
Pág.: 2 de 2
Fecha: 03/05/2011
Informe: Único.

Análisis cuantitativo:

TIEMPO DE LLAMA:

- NIVEL 1: Menor o igual a 1 segundo.
- NIVEL 2: Mayor a 1 segundo, pero menor o igual a 5 segundos.
- NIVEL 3: Mayor a 5 segundos.

TIEMPO DE INCANDESCENCIA:

- NIVEL 1: Menor o igual a 3 segundos.
- NIVEL 2: Mayor a 3 segundos, pero menor o igual a 15 segundos.
- NIVEL 3: Mayor que 15 segundos.

LONGITUD DAÑADA:

- NIVEL 1: Menor o igual a 100 milímetros.
- NIVEL 2: Mayor a 100 milímetros, pero menor o igual a 150 milímetros.
- NIVEL 3: Mayor a 150 milímetros.

GOTEO:

- NIVEL 1: Ausencia de goteo.
- NIVEL 2: Gotas y/o partes desprendidas que se apagan en el momento de contacto con el piso de la cabina.
- NIVEL 3: Gotas y/o partes desprendidas que siguen encendidas en el piso de la cabina menos de 3 segundos.

Se clasifica en 3 niveles, siendo 1 el mejor y 3 el peor.

“Tela con tratamiento retardante”

- Análisis cualitativo:

No entra en ignición.

- Análisis cuantitativo:

Sentido de la muestra	Tiempo de duración de la llama (s)	Tiempo de incandescencia (s)	Longitud carbonizada (mm)
Longitudinal	0	1	36
Transversal	0	1	27

De acuerdo a los resultados obtenidos, el material: muestra de tela color blanca identificada por el solicitante como **“Tela con tratamiento retardante”** clasifica como **NIVEL 1.**

Arq. BASILIO MASAPON
COORDINADOR
U.T. TECNOLOGIA EN INCENDIOS
INTI-CONSTRUCCIONES

Ing. VICENTE L. POLANTINO
DIRECCION
INTI - CONSTRUCCIONES

Nota:

De acuerdo a reglamentaciones internacionales, estos ensayos deben considerarse para medir y describir el comportamiento del material bajo condiciones controladas pero no se puede estimar cuál será el comportamiento del mismo si se modifican total o parcialmente las condiciones de ensayo.



MINIT Ignífugos

minitargentina@gmail.com www.minitfireretardant.com

COPIA FIEL DE CERTIFICADOS

Producto MINIT TOTAL

Presentación válida únicamente con el Certificado / Factura de Compra



validacion

NFPA 701 (INFLAMABILIDAD VERTICAL DE TEXTIL SINTETICO NIVEL 1 – CLASE A)

INTI Incendios y Explosiones



Presidencia
de la Nación

Ministerio de
Producción

Informe de Ensayo

OT N° 131- 161
Informe: Único
Página 1 de 3

Fecha de Informe: 30/08/2016

Solicitante	Minotti Pablo David Echeverría 2073 – Piso 4 – Dto. B
Elemento	Textil negro
Determinaciones requeridas	Evaluación de la Inflamabilidad Vertical de Textiles
Fecha de Recepción	13 de julio de 2016
Fecha de ensayo	24 de julio de 2016

Este informe no podrá ser reproducido parcialmente sin la autorización escrita del INTI. Los resultados consignados se refieren exclusivamente a los elementos recibidos, el INTI y su Centro de Investigación y Desarrollo en Incendios y Explosiones declinan toda responsabilidad por el uso indebido o incorrecto que se hiciera de este informe.

Instituto Nacional de Tecnología Industrial

www.inti.gob.ar
consultas@inti.gob.ar
0800 444 4004

Parque Tecnológico Miguelete
Avenida General Paz 5445
Casilla de Correo 157
B1650WAB San Martín,
Buenos Aires, Argentina
Teléfono (54 11) 4724 6200
E-mail incendiosyexplosiones@inti.gob.ar



MINIT Ignífugos

minitargentina@gmail.com www.minitfireretardant.com

COPIA FIEL DE CERTIFICADOS

Producto MINIT TOTAL

Presentación válida únicamente con el Certificado / Factura de Compra



validacion

INTI Incendios y Explosiones

Presidencia
de la Nación

Ministerio de
Producción


OT N° 131-161
Informe: Único
Página 2 de 3

1. METODOLOGÍA EMPLEADA

El ensayo se realizó de acuerdo a las indicaciones de la Norma NFPA 701, "Standard Methods of Fire Tests of Flame Propagation of Textiles and Films: Test Method 1".

2. IDENTIFICACIÓN DE LA MUESTRA

Textil negro identificado por el solicitante como "TEXTIL NEGRO SINTÉTICO CON TRATAMIENTO RETARDANTE IGNIFUGO MINIT"



Nota: La muestra presentaba partículas salinas sobre la superficie que se desprendían durante su manipulación.



MINIT Ignifugos

minitargentina@gmail.com www.minitfireretardant.com

COPIA FIEL DE CERTIFICADOS

Producto MINIT TOTAL

Presentación valida únicamente con el Certificado / Factura de Compra



validacion

INTI Incendios y Explosiones

Presidencia
de la Nación

Ministerio de
Producción

OT N° 131-161

Informe: Único

Página 3 de 3

3. RESULTADOS OBTENIDOS

- Análisis cuantitativo:

Probeta	Peso inicial (g)	Peso final (g)	Tiempo de llama (seg)	Tiempo de llama material desprendido (seg)	Porcentaje de masa perdida (%)
1	35,21	34,07	0	0	3,24
2	33,3	31,29	0	0	6,04
3	41,68	39,73	0	0	4,68
4	34,28	32,06	0	0	6,48
5	38,09	36,5	0	0	4,17
6	35,5	33	0	0	7,04
7	40,36	38,5	0	0	4,61
8	39,21	37,01	0	0	5,61
9	39,24	37,5	0	0	4,43
10	39,1	34,9	0	0	10,74
Promedio	37,597	35,456	0	0	5,70
Desvío Standard					2,00

De acuerdo a los resultados obtenidos, el material identificado por el solicitante como: **"TEXTIL NEGRO SINTÉTICO CON TRATAMIENTO RETARDANTE IGNIFUGO MINIT"** **CUMPLE** con los requerimientos de la norma NFPA 701:1999 Standard Methods of Fire Test for Flame Propagation of Textiles and Films -Test method 1: "Curtains, draperies, or other windows treatments".

Observaciones:

De acuerdo a reglamentaciones internacionales, estos ensayos deben considerarse para medir y describir el comportamiento del material bajo condiciones controladas, pero no se puede estimar cuál será el comportamiento del mismo si se modifican total o parcialmente las condiciones de ensayo.

Esp. Arq. M. Paula Cheheid
INTI - Incendios y Explosiones

Fin del Informe

Ing. Geraldine Charreau
Directora Técnica
INTI - Incendios y Explosiones



MINIT Ignifugos

minitargentina@gmail.com www.minitfireretardant.com

COPIA FIEL DE CERTIFICADOS

Producto MINIT TOTAL

Presentación valida únicamente con el Certificado / Factura de Compra



validacion

NFPA 705 (INFLAMABILIDAD VERTICAL DE TEXTILES NATURALES NIVEL 1 – CLASE A)

Govmark/SGS (<https://www.sgs.com/en/service-groups/fire-testing>) Convenio de reciprocidad INTI / SGS, 23/08/2001



96-D Allen Boulevard
Farmingdale, New York 11735-5626 USA
Tel. +1 (631) 293-8944 Fax +1 (631) 293-8956
e-mail: testing@govmark.com

Page 1

Received:04/20/2016	Completed:04/20/2016	Letter: M	MM	P.O.#:	Test Report #:	3-12898-0-
Client's Identification	Style: Fabric. Content: 100% Cotton. Additional Information: 100% Cotton Fabric Treated by Spray with Minit Flame Retardante for Fabrics.					
Tested For: Pablo Minotti		Key Test: NFPA 705		225		
Flame Retardant Technologies LLC		Tel: 1-(305)-400-8889		Ext:		
1330 NW 78th Ave		Fax: 1-()- -				
Miami, FL 33126						
LE 2013; V 09/15 ; NE 2018 TEST PERFORMED: NFPA 705 - Recommended Practice for a Field Flame Test for Textiles and Films (2013 Edition) 1.2.1 The purpose of this recommended practice is to provide authorities having jurisdiction with a field means of determining the tendency of textiles and films to sustain burning subsequent to the application of a relatively small, open flame. 1.2.2: The methods described herein and the results do not correlate with any known test method, and factors relating to reproducibility and correlation have not been determined; therefore, they should not be relied upon when more definitive test data are available. 1.3.1.2: The field test method has utility only when the authority having jurisdiction has no reliable data and, therefore, is forced to rely solely on the field test findings. 1.3.2: Materials applied to surface of buildings or backing materials as interior finishes in buildings should be tested and classified in accordance with ASTM E 84 or NFPA 286. In the case of textile wall coverings, the use of NFPA 265 is also appropriate. * 5.1 Limitations: The deficiencies and limitations of the field test method can lead to misleading or erroneous results, and the error can be in both directions. It is quite possible to have a too-small sample show several seconds of afterflaming, causing the material to be rejected. It is equally possible for improper or inadequate field procedures to incorrectly indicate satisfactory flame resistance. This can result in dangerous errors. 5.2 Precautions: Field procedures are useful, but they must be used with good judgment and their limitations should be recognized. Field tests should not be relied on as the sole means for ensuring adequate flame resistance of decorative materials. They are, however, useful in augmenting a comprehensive regulatory program. BRIEF DESCRIPTION OF TEST (Chapter 4 Procedure): The test should be performed in a draft-free and safe location free of other combustibles. Specimens should be removed from the existing material. Specimens should be dry and should be a minimum of 12.7 mm x 101.6 mm (0.5" x 4.0"). The fire exposure should be from a common wood match or source with equivalent flame properties. The sample should be suspended (preferably by means of a spring clip, tongs, or similar device) with the long axis vertical, the flame applied to the center of the bottom edge and the bottom edge 12.7 mm (0.5") above the bottom of the flame. After 12 seconds of exposure the match is to be removed gently away from the sample. (Page 1 of 3)						

File Copy



MINIT Ignifugos

minitargentina@gmail.com www.minitfireretardant.com

COPIA FIEL DE CERTIFICADOS

Producto MINIT TOTAL

Presentación valida únicamente con el Certificado / Factura de Compra



validacion



96-D Allen Boulevard
Farmingdale, New York 11735-5626 USA
Tel. +1 (631) 293-8944 Fax +1 (631) 293-8956
e-mail: testing@govmark.com

Page 2

Received: 04/20/2016	Completed: 04/20/2016	Letter: M	MM	P.O.#:	Test Report #: 3-12898-0-
Client's Identification	Style: Fabric. Content: 100% Cotton. Additional Information: 100% Cotton Fabric Treated by Spray with Minit Flame Retardante for Fabrics.				
Tested For: Pablo Minotti Flame Retardant Technologies LLC 1330 NW 78th Ave Miami, FL 33126			Key Test: NFPA 705 225		
			Tel: 1-(305)-400-8889		Ext:
			Fax: 1-()- -		
TEST LOCATION: ☒ On-site ☐ Govmark Laboratory **					
FLOOR-TO-BOTTOM-OF-SPECIMEN HEIGHT: ☒ 8 inches ☐ Other _____ inches					
RESULTS:					
Direction	Specimen #	Ignition Observed (yes/no)	Afterflame (seconds)	Drip Burn (seconds)	Flaming (inches)
MD	1	Yes	0	0	0.2
CMD	2	Yes	0	0	0.3
Note 1: The "Ignition Observed" column information is an observation only and does not enter into the acceptance criteria.					
Note 2: NFPA 705 does not specify the number of specimens to be tested.					
ABBREVIATIONS: MD = Machine (Warp) ; CMD = Cross Machine (Fill/Weft) ; CL = Complete length burn					
ACCEPTANCE CRITERIA***:					
Afterflame: There should be no more than 2.0 seconds of afterflame for any individual specimen.					
Drip Burn: Materials that break or drip flaming particles should be rejected if the materials continue to burn after they reach the floor****					
Flaming: During the exposure, flaming should not spread over the complete length of the sample or, in the case of larger samples, in excess of 4 inches from the bottom of the sample.					
REMARKS: None.					
CONCLUSION: Based on the above Results and Acceptance Criteria, the item tested:					
☒ Complies; ☐ Does not comply					
CERTIFICATION: I certify that the above results were obtained after testing specimens in accordance with the procedures and equipment specified by NFPA 705.					
AUTHORIZED SIGNATURE GOVMARK /pm			APR 26 2016 <i>Robert I. Brown</i>		
			(Page 2 of 3)		

File Copy




MINIT Ignifugos

minitargentina@gmail.com www.minitfireretardant.com

COPIA FIEL DE CERTIFICADOS

Producto MINIT TOTAL

Presentación valida únicamente con el Certificado / Factura de Compra



validacion



96-D Allen Boulevard
Farmingdale, New York 11735-5626 USA
Tel. +1 (631) 293-8944 Fax +1 (631) 293-8956
e-mail: testing@govmark.com

Page 3

Received:04/20/2016	Completed:04/20/2016	Letter: M	MM	P.O.#:	Test Report #:	3-12898-0-
Client's Identification	Style: Fabric. Content: 100% Cotton. Additional Information: 100% Cotton Fabric Treated by Spray with Minit Flame Retardante for Fabrics.					
Tested For: Pablo Minotti			Key Test: NFPA 705		225	
Flame Retardant Technologies LLC			Tel: 1-(305)-400-8889		Ext:	
1330 NW 78th Ave			Fax: 1-()- -			
Miami, FL 33126						
GOVMARK ADDENDUM: * In addition to the NFPA listings, other furnishings tests might apply, such as NFPA 260, NFPA 261, and California Technical Bulletin 133 for upholstery products, and NFPA 701 Test Method 1 for drapery type products, or any other code specified furnishings tests. ** While NFPA 705 is an on-site test some client's, either on their own or at the request of a code official, have opted to request performance of this test at the Govmark laboratory facility. DISCUSSION: *** The "ACCEPTANCE CRITERIA" is adopted from the "Requirements" section of NFPA 705 Chapter 4 Procedure. Where the word "should" appears in the "Requirements" section, it may fall under its definition per NFPA 705 paragraph 3.2.3, which states: 3.2.3 Should. Indicates a recommendation or that which is advised but not required. It is Govmark's decision to take these recommendations under advisement, adopt them as the requirement, and issue a conclusion based upon them. **** NFPA 705 does not specify a "floor-to-bottom-of-specimen" height from which the "Drip Burn" criteria can be measured. Unless specified otherwise by the client, when testing at Govmark, a "floor-to-bottom-of-specimen" height of 8 inches is utilized. During field testing, the height may be adjusted accordingly to be representative of the installation (i.e. drapery) under test.						

(Page 3 of 3)

The results contained in this report relate only to item(s) tested. The test report shall not be reproduced, except in full, without written approval from Govmark.

File Copy



MINIT Ignífugos

minitargentina@gmail.com www.minitfireretardant.com

COPIA FIEL DE CERTIFICADOS

Producto MINIT TOTAL

Presentación valida únicamente con el Certificado / Factura de Compra



validacion

CAL 117 – CALIFORNIA MARSHAL (INFLAMABILIDAD HORIZONTAL DE TEXTILES NATURALES = PASS) Alfombras, Frazadas, todo tejido natural que se encuentre en forma horizontal. HOMOLOGACIÓN CON IRAM 11910. RESULTADO equivalente RE 1



Quality Assurance & Compliance Testing
Utilizing Textile & Related Technologies
19 West 36th Street, 10th Floor
New York, NY 10018
Tel: 212 947 8391 Fax: 212 947 8719
www.vartest.com

ISO/IEC 17025 Certified Third Party Test Report

FILE: FLAMER.A0329168
SAMPLE IDENTIFIED BY CLIENT AS:
Fabric Submitted
100% Cotton
Color White

CALIFORNIA TECHNICAL BULLETIN 117-2013 SECTION 1 COVER FABRIC TEST

	CHAR LENGTH (mm)
Specimen #1:	12
Specimen #2:	12
Specimen #3:	10

- a) The mock-up test specimen continues to smolder after the 45-minute test duration: **NO**
- b) A char develops more than 1.8 inches (45 mm) in any direction from the cigarette on the cover fabric measured from its nearest point: **NO**
- c) The mock-up test specimen transitions to open flaming: **NO**

RESULTS: Pass

A material is considered to pass or fail based on the following criteria:

1. A single mock-up test specimen fails to meet the requirements of this test procedure if any of the following criteria occurs:
 - a) The mock-up test specimen continues to smolder after the 45-minute test duration.
 - b) A char develops more than 1.8 inches (45 mm) in any direction from the cigarette on the cover fabric measured from its nearest point.
 - c) The mock-up test specimen transitions to open flaming.
2. The cover fabric passes the test if three initial mock-up specimens pass the test, i.e., the cigarettes burn their full length and the mock-ups are no longer smoldering.
3. If more than one initial specimen fails, the cover fabric fails the test.
4. If any one of the three initial specimens fails, repeat the test on an additional three specimens.
5. If all three additional specimens pass the test, the cover fabric passes the test. If any one of the three additional specimens fails, the cover fabric fails the test.

Signed For The Company By

Adam R. Varley
Technical Director

JG/03/649



Stacy Sadowy
Quality Assurance Supervisor

The findings and results in this test report apply only to the specific sample(s) submitted to us by the client for testing.





MINIT Ignifugos

minitargentina@gmail.com www.minitfireretardant.com

COPIA FIEL DE CERTIFICADOS

Producto MINIT TOTAL

Presentación valida únicamente con el Certificado / Factura de Compra



validacion

CAL 117 – CALIFORNIA MARSHAL (INFLAMABILIDAD HORIZONTAL DE TEXTILES SINTETICOS = PASS) Alfombras, Frazadas, todo tejido natural que se encuentre en forma horizontal. HOMOLOGACIÓN CON IRAM 11910. RESULTADO equivalente RE 1



Quality Assurance & Compliance Testing
Utilizing Textile & Related Technologies
19 West 36th Street, 10th Floor
New York, NY 10018
Tel: 212 947 8391 Fax: 212 947 8719

www.vartest.com

ISO/IEC 17025 Certified Third Party Test Report

FILE: FLAMER.A032916A
SAMPLE IDENTIFIED BY CLIENT AS:
Fabric Submitted
100% Polyester
Color Green

CALIFORNIA TECHNICAL BULLETIN 117-2013 SECTION 1 COVER FABRIC TEST

	CHAR LENGTH (mm)
Specimen #1:	18
Specimen #2:	15
Specimen #3:	20

- a) The mock-up test specimen continues to smolder after the 45-minute test duration: NO
- b) A char develops more than 1.8 inches (45 mm) in any direction from the cigarette on the cover fabric measured from its nearest point: NO
- c) The mock-up test specimen transitions to open flaming: NO

RESULTS: Pass

A material is considered to pass or fail based on the following criteria:

1. A single mock-up test specimen fails to meet the requirements of this test procedure if any of the following criteria occurs:
 - a) The mock-up test specimen continues to smolder after the 45-minute test duration.
 - b) A char develops more than 1.8 inches (45 mm) in any direction from the cigarette on the cover fabric measured from its nearest point.
 - c) The mock-up test specimen transitions to open flaming.
2. The cover fabric passes the test if three initial mock-up specimens pass the test, i.e., the cigarettes burn their full length and the mock-ups are no longer smoldering.
3. If more than one initial specimen fails, the cover fabric fails the test.
4. If any one of the three initial specimens fails, repeat the test on an additional three specimens.
5. If all three additional specimens pass the test, the cover fabric passes the test. If any one of the three additional specimens fails, the cover fabric fails the test.

Signed For The Company By

Adam R. Varley
Adam R. Varley
Technical Director

JG/03/648



Stacy Sadov
Stacy Sadov
Quality Assurance Supervisor

The findings and results in this test report apply only to the specific sample(s) submitted to us by the client for testing.





MINIT Ignifugos

minitargentina@gmail.com www.minitfireretardant.com

COPIA FIEL DE CERTIFICADOS

Producto MINIT TOTAL

Presentación valida únicamente con el Certificado / Factura de Compra



validacion

BS 5852: 2006, & CAL TB 117: 2013 PASS (INFLAMABILIDAD HORIZONTAL EN ALFOMBRAS SINTETICAS) HOMOLOGACIÓN CON IRAM 11910. RESULTADO equivalente RE 1



Industrial Global Standards LLC
1209 MOUNTAIN ROAD PL NE STE N
ALBUQUERQUE, NM 87110
EIN 37-218160
www.inglobalstandards.com
industrialglobalstandards@gmail.com

TEST REPORT

Nº 1143-72-144

LAB SERVICE

VALIDO SOLO CON CERTIFICADO DE COMPRA.
MINIT IGNIFUGOS

Applicant/ Manufacturer	MINIT Fire Retatadant (MINIT Ignifugos) Pablo David Minotti ID: 20224196270 Argentina
Product	Synthetic Carpet treated with MINIT Ignifugos Fire Retardant
Reference Standard/ Method Tests	BS 5852 : 2006, & CAL TB 117 : 2013
Description of Test Specimen	Synthetic carpet (provided by Applicant/ Manufacturer) - 1 piece treated with MINIT ignifugos fire retardant Size of Specimen : 1500mm×1500mm Nominal Thickness : 3mm
Date Received	May 15, 2025
Issued Date	May 22, 2025
Pages	2

1



AMERICAN SOCIETY OF
SAFETY PROFESSIONALS

Authorized Signatory
Industrial Global Standards LLC
1209 MOUNTAIN ROAD PL NE STE N
ALBUQUERQUE, NM 87110



Validation Code

The client acknowledges and agrees that any services provided and/or reports produced by Industrial Global Standards LLC are done so within the limits of the scope of work agreed pursuant to the client's specific instructions. This report relates specifically to the sample(s) tested that were drawn and delivered by the client or their nominated third party. Industrial Global Standards LLC does not make any representation or warranty for any bulk samples or certify the bulk samples received from the client. Furthermore, Industrial Global Standards LLC does not provide a warranty or verification on the sample(s) representing any specific goods, material and/or shipment and only relate to the sample(s) as received and tested. Industrial Global Standards LLC have aimed to conduct the review on a diligent and careful basis and we do not accept any liability to you for any loss arising out of or in connection with this report, in contract, tort, by statute or otherwise, except in the event of our gross negligence or willful misconduct. In no event, will the contents of any reports or any extracts, excerpts or parts of any reports be distributed or published without the prior written consent of Industrial Global Standards LLC in each instance. Only the client is authorized to permit copying or distribution of this report (and then only in its entirety). Any such third parties to whom this report may be circulated rely on the content of the report solely at their own risk. The reported expanded uncertainty is based on a standard uncertainty multiplied by a coverage factor of $k = 2$, providing a level of confidence of approximately 95 %. Unless otherwise specified all compliance and pass/fail statements are binary simple acceptance based on the tolerance interval.



MINIT Ignífugos

minitargentina@gmail.com www.minitfireretardant.com

COPIA FIEL DE CERTIFICADOS

Producto MINIT TOTAL

Presentación válida únicamente con el Certificado / Factura de Compra



validacion



Industrial Global Standards LLC
1209 MOUNTAIN ROAD PL NE STE N
ALBUQUERQUE, NM 87110
EIN 37-218160
www.inglobalstandards.com
industrialglobalstandards@gmail.com

TEST REPORT

Nº 1143-72-144

LAB SERVICE

VALIDO SOLO CON CERTIFICADO DE COMPRA
MINIT IGNIFUGOS

Following the treatment described above, the material was conditioned and tested according to BS 5852 : 2006, & CAL TB 117 : 2013
Methods of Test for the Assessment of the Ignitability of Upholstered Seating by Smouldering and Flaming Ignition Sources, Clause 11, using Ignition Source 5.

The results relate only to the ignitability of the combinations of upholstery composites (Clause 11) under the particular condition of test stated; they are not intended as a means of assessing the full potential fire hazard of the item in use.

RESULTS	
Specimen number	1
Duration of flaming of ignition source (min)	3'24"
Duration of flames (min)	3'47"
Duration of smoke (min)	4'19"
Extent of damage of horizontal component	
- width (mm)	123
- length (mm)	121
- depth (mm)	23
Extent of damage of vertical component	
- width (mm)	157
- depth (mm)	27
Progressive smouldering >100mm from ignition source	No
Result	 Pass

2

CONCLUSION

The specimen showed non-ignition, BS 5852: 2006, Rating NI5. & CAL TB 117: 2013, This Rating represents a Pass for Crib 5.

END OF REPORT




Authorized Signatory
Industrial Global Standards LLC
1209 MOUNTAIN ROAD PL NE STE N
ALBUQUERQUE, NM 87110



Validation Code

The client acknowledges and agrees that any services provided and/or reports produced by Industrial Global Standards LLC are done so within the limits of the scope of work agreed pursuant to the client's specific instructions. This report relates specifically to the sample(s) tested that were drawn and delivered by the client or their nominated third party. Industrial Global Standards LLC does not make any representation or warranty for any bulk samples or certify the bulk samples received from the client. Furthermore, Industrial Global Standards LLC does not provide a warranty or verification on the sample(s) representing any specific goods, material and/or shipment and only relate to the sample(s) as received and tested. Industrial Global Standards LLC have aimed to conduct the review on a diligent and careful basis and we do not accept any liability to you for any loss arising out of or in connection with this report, in contract, tort, by statute or otherwise, except in the event of our gross negligence or willful misconduct. In no event, will the contents of any reports or any extracts, excerpts or parts of any reports be distributed or published without the prior written consent of Industrial Global Standards LLC in each instance. Only the client is authorized to permit copying or distribution of this report (and then only in its entirety). Any such third parties to whom this report may be circulated rely on the content of the report solely at their own risk. The reported expanded uncertainty is based on a standard uncertainty multiplied by a coverage factor of $k = 2$, providing a level of confidence of approximately 95 %. Unless otherwise specified all compliance and pass/fail statements are binary simple acceptance based on the tolerance interval.




MINIT Ignífugos

minitargentina@gmail.com www.minitfireretardant.com

COPIA FIEL DE CERTIFICADOS

Producto MINIT TOTAL

Presentación válida únicamente con el Certificado / Factura de Compra



Homologación con normas IRAM Cal TB117

Norma USA	Ensayo	Norma IRAM equivalente / comparable	Observación
TB 117 / TB 117-2013	Inflamabilidad horizontal de textiles y tapizados	IRAM 11910-3	Evaluación de reacción al fuego de materiales textiles
TB 117 sección horizontal	Velocidad de propagación superficial de llama	IRAM 3904	Similar criterio de propagación superficial
California TB117	Encendido superficial y propagación	IRAM-IAS U 500-250 (aplicaciones textiles)	Uso frecuente en homologaciones locales
ASTM D5132 / UFAC asociados	Smoldering / cigarrillo	IRAM basadas en ISO 8191	Tapizados y mobiliario

"El ensayo California Technical Bulletin TB117 presenta criterios equivalentes de evaluación de propagación superficial de llama horizontal y comportamiento frente a ignición inicial comparables con los establecidos en IRAM 11910 e IRAM 3904 para materiales textiles y revestimientos."

TB117 (California)

- Ensayo orientado a:
 - muebles tapizados
 - espumas
 - textiles decorativos
- Evaluación horizontal
- Fuente de ignición pequeña
- Uso muy extendido en USA

IRAM 11910

- Más utilizada en:
 - construcción
 - revestimientos
 - cortinados
 - textiles arquitectónicos
- Clasificación de reacción al fuego
- Compatible conceptualmente con ISO 9705 / ISO 5660 según aplicación

El método California TB117 de inflamabilidad horizontal de textiles presenta correlación técnica con los ensayos de reacción al fuego contemplados en IRAM 11910 para materiales textiles y revestimientos interiores, dado que ambos evalúan la propagación superficial de llama y comportamiento frente a fuentes de ignición de baja energía.



MINIT Ignífugos

minitargentina@gmail.com www.minitfireretardant.com

COPIA FIEL DE CERTIFICADOS

Producto MINIT TOTAL

Presentación válida únicamente con el Certificado / Factura de Compra



IRAM 11910-3 NBR 9442/86 ASTM 162 (METODO PANEL RADIANTE EN MADERA, RE4 CLASE C, MEDIANA PROPAGACION DEL FUEGO)

INTI Construcciones

INFORME DE ENSAYO

Solicitante: MINOTTI PABLO DAVID

O.T.: 101/20905
Pág.: 1 de 2
Fecha: 12/08/2011
Informe: Único.

Dirección: Cochrane 2322
(1419) – Cdad. Autónoma de Buenos Aires

1. OBJETIVO
Clasificación de acuerdo al Índice de Propagación de Llama.

2. MATERIAL
Una (1) muestra de placa de madera maciza, identificada por el solicitante como:
"Madera con retardante ignífugo marca MINIT de Pablo Minotti"



3. MÉTODO EMPLEADO
El ensayo de Propagación Superficial de Llama se realizó de acuerdo a la Norma IRAM 11910-3: "Materiales de Construcción, Reacción al fuego, Determinación del índice de propagación de llama – método del panel radiante" (coincide con los métodos de ensayo de la Norma NBR 9442/1986 y ASTM E162).
La muestra fue recibida el día 15/06/11 y ensayada el día 10/08/11.

4. RESULTADOS OBTENIDOS

Determinación de la Propagación superficial de llama

F(promedio):	6,18
Q(promedio):	15,63
I(promedio):	95,89

Este informe no podrá ser reproducido parcialmente sin la autorización escrita del Laboratorio. Los resultados consignados se refieren exclusivamente a los elementos recibidos, el INTI y su Centro de Investigación y Desarrollo en Construcciones declinan toda responsabilidad por el uso indebido o incorrecto que se hiciera de este informe.

Instituto Nacional de Tecnología Industrial
Centro de Investigación y Desarrollo
en Construcciones
Avenida General Paz 3445
B1650KNA San Martín, Buenos Aires, Argentina
teléfono (54 11) 4724 6200
e-mail: construcciones@inti.gov.ar



MINIT Ignifugos

minitargentina@gmail.com www.minitfireretardant.com

COPIA FIEL DE CERTIFICADOS

Producto MINIT TOTAL

Presentación valida únicamente con el Certificado / Factura de Compra



validacion

INTI Construcciones

Solicitante: MINOTTI PABLO DAVID

O.T.: 101/20905

Pág.: 2 de 2

Fecha: 12/08/2011

Informe: Único.

Dirección: Cochrane 2322

(1419) - Cdad. Autónoma de Buenos Aires

De acuerdo al **Índice de Propagación de Llamas (I)** hallado y teniendo en cuenta la Tabla de Clasificación de la Norma IRAM 11910-1 del año 1994, que se detalla como referencias, el material "**Madera con retardante ignífugo marca MINIT de Pablo Minotti**" se clasifica como:

"Clase RE 4: Material de Mediana propagación de llama"

(A esta clase pertenecen los materiales con un índice entre 76 y 150)

Coincide con la Clase C de la Norma brasileña NBR 9442/1986

Referencias para el ensayo de determinación de la propagación superficial de llama

Clase	Clase ABNT	Denominación	Norma IRAM	Criterio de clasificación
RE 1	-	Incombustible	11910-2	Anexo A de la norma
RE 2	A	Muy baja propagación de llama	11910-1	Índice: 0 a 25
RE 3	B	Baja propagación de llama	11910-1	Índice: 26 a 75
RE 4	C	Mediana propagación de llama	11910-1	Índice: 76 a 150
RE 5	D	Elevada propagación de llama	11910-1	Índice: 151 a 400
RE 6	E	Muy elevada propagación de llama	11910-1	Índice mayor a 400


Definiciones:

Un factor derivado de la rapidez de propagación del frente de llama (F) y otro relativo al calor liberado por el material ensayado (Q) son combinados para proveer el índice de propagación superficial de llama (I).

I: Índice de propagación superficial de llama.

F: Factor de propagación de llama.

Q: Factor de evolución de calor.


Arq. BASILIO MASÁROV
COORDINADOR
U.T. TECNOLOGÍA EN INCENDIOS
INTI-CONSTRUCCIONES


Ing. VICENTE L. VOLANTINO
DIRECCIÓN
INTI-CONSTRUCCIONES

Nota:

De acuerdo a reglamentaciones internacionales, estos ensayos deben considerarse para medir y describir el comportamiento del material bajo condiciones controladas, pero no se puede estimar cuál será el comportamiento del mismo si se modifican total o parcialmente las condiciones de ensayo.



MINIT Ignifugos

minitargentina@gmail.com www.minitfireretardant.com

COPIA FIEL DE CERTIFICADOS

Producto MINIT TOTAL

Presentación válida únicamente con el Certificado / Factura de Compra



validacion

ASTM 162 Equivalente (Homologado) a IRAM 11910-3 NBR 9442/86 y con estándares europeos: CSE RF 3/77; BS 476 part 6 and part 7
(METODO PANEL RADIANTE EN **MADERA, CARTÓN Y PAPEL**)

Resultado: Determinación de la propagación superficial de llama "I" 39.8 (IRAM RE 3, Clase ABNT "B"). Baja Propagación.

Govmark/SGS (<https://www.sgs.com/en/service-groups/fire-testing>) Convenio de reciprocidad INTI / SGS, 23/08/2001



96-D Allen Boulevard
Farmingdale, New York 11735-5626 USA
Tel. +1 (631) 293-8944 Fax +1 (631) 293-8956
e-mail: testing@govmark.com

Page 1

Received: 04/05/2016	Completed: 04/07/2016	Letter: P	JB	P.O.#:	Test Report #:	3-12594-0-				
Client's Identification (see continuation)	Style: Wood Treated by Spray wit Flame Retardant. Date of Mfg.: 03/31/2016. Composition: Pine Wood. Thickness: 1".									
Tested For: Pablo Minotti Flame Retardant Technologies LLC 1330 NW 78th Ave Miami, FL 33126	Key Test: ASTM E 162					725				
Tel: 1-(305)-400-8889 Ext: Fax: 1-()- -										
CLIENT'S IDENTIFICATION (continuation): Product End Use: MINIT Flame Retardant, for Wood cardboard and Paper Treatment. Additional Information: Pine Wood Treated by Spray with the Product MINIT Flame Retardant for Wood Cardboard and Paper.										
Category: Radiant Panel LE 2015a; V 09/15 NTR 2/16 PC: 24H+ME /dl SM/mg										
APPROXIMATE [x] THICKNESS [] DIAMETER OF MATERIAL (as measured by Govmark): 1.514"										
TEST PERFORMED: ASTM E 162 - Standard Test Method for Surface Flammability of Materials Using a Radiant Heat Energy Source										
SPECIMEN: [x] Rigid Material: 6" x 18" [] Cellular Sheet Foam Materials: 6" x 18" [] Fabric/Flexible Materials: 10" x 22" [] Cable: 18" lengths were grouped to form 6" x 18" test specimens										
SPECIMEN PREPARATION: [] No backing required, as specimens exceeded 0.75" in thickness. [x] The specimens were backed by a 0.5" Etera board (a cement asbestos substitute). [] The specimens were backed with 1/4 inch high density reinforced cement board. [x] The back and sides of each specimen were wrapped with 0.002" thick aluminum foil. [] The face of each specimen was covered with a 1.0" hexagonal wire mesh screen. [] The specimen was flexible material such that the top and bottom of the 10" by 22" specimen was wrapped around the back of the board with all slack removed.										
SPECIMEN PREPARATION: [] No backing required, as specimens exceeded 0.75" in thickness. [x] The specimens were backed by a 0.5" Etera board (a cement asbestos substitute). [] The specimens were backed with 1/4 inch high density reinforced cement board. [x] The back and sides of each specimen were wrapped with 0.002" thick aluminum foil. [] The face of each specimen was covered with a 1.0" hexagonal wire mesh screen. [] The specimen was flexible material such that the top and bottom of the 10" by 22" specimen was wrapped around the back of the board with all slack removed.										
BRIEF DESCRIPTION OF TEST: (see page 2 of 2)										
RESULTS:										
Specimen #	Flame Progression (mm:ss)					Net Stack Rise°C	Q	FS	Flame Spread Index*	Flaming, Dripping, or Flaming Running (yes/no)
1	01:39	02:06	04:11	05:50	FN	59.0	9.0	4.0	36.0	No
2	F	01:19	02:03	04:33	FN	53.0	8.1	5.8	47.0	No
3	F	01:45	02:52	07:24	10:36	71.0	10.8	4.7	50.8	No
4	F	02:48	03:16	08:32	FN	41.0	6.3	4.0	25.2	No
Avg: 39.8										
ABBREVIATIONS WHICH MAY BE USED IN RESULTS: F = Flashed beyond benchmark. FN = Flame front did not reach this benchmark. WM = Flame front was attributable to burning of the residue on the wire mesh.										
CALCULATION FACTORS: Etera board correction factor: 19°C Beta: 37.36 Flux: 2.8 - 1.6 - 0.7 (Flux Transducer # 184117)										

(Page 1 of 2)

File Copy




MINIT Ignifugos

minitargentina@gmail.com www.minitfireretardant.com

COPIA FIEL DE CERTIFICADOS

Producto MINIT TOTAL

Presentación valida únicamente con el Certificado / Factura de Compra



validacion



96-D Allen Boulevard
Farmingdale, New York 11735-5626 USA
Tel. +1 (631) 293-8944 Fax +1 (631) 293-8956
e-mail: testing@govmark.com

Page 2

Received: 04/05/2016	Completed: 04/07/2016	Letter: P	JB	P.O.#:	Test Report #:	3-12594-0-
Client's Identification (see continuation) Style: Wood Treated by Spray wit Flame Retardant. Date of Mfg.: 03/31/2016. Composition: Pine Wood. Thickness: 1".						
Tested For: Pablo Minotti Flame Retardant Technologies LLC 1330 NW 78th Ave Miami, FL 33126			Key Test: ASTM E 162 725 Tel: 1-(305)-400-8889 Ext: Fax: 1-()- -			
BRIEF DESCRIPTION OF TEST: The test specimen faces a radiant heat source. At the beginning of the test period an igniting flame impinges at the top of the specimen. Visual observation is made of the downward progression of the flame front. The test is completed when the flame front has progressed to the 15" mark, or after an exposure time of 15 minutes, whichever occurs first. The heat given off by the burning specimen is automatically recorded. The combination of the two factors, flame front progression and heat, result in a Flame Spread Index.						
NOTES: * While the Standard calls out "Radiant Panel Index", Govmark reports "Flame Spread Index", since this is the terminology used in most Code specifications. "Flame Spread Index" and "Radiant Panel Index" are identical for the purposes of this report. ** Flashing is defined as a flame front of 3 seconds or less in duration. Where ANY flashing has occurred, an individual specimen's Flame Spread Index is understood to be qualified as "(Flashing)".						
REMARKS:						
Specimen #	Non Sustained (Flashing**) Flame Front Off Gas Ignition (yes/no)	Sustained Flame Front Ignition at (mm:ss)	All Flaming Out (mm:ss)	Test End (mm:ss)	Drips Flame on Test Floor (yes/no)	
1	Yes	01:30	SB	15:00	No	
2	Yes	01:09	SB	15:00	No	
3	Yes	00:49	SB	15:00	No	
4	Yes	00:54	11:33	15:00	No	
ABBREVIATIONS WHICH MAY BE USED IN "REMARKS": DNI = Did not ignite SB = Still burning at test end						
ACCEPTANCE CRITERIA: None cited.						
CONCLUSION: Not applicable.						
CERTIFICATION: I certify that the above results were obtained after testing specimens in accordance with the procedures and equipment specified above.						
AUTHORIZED SIGNATURE GOVMARK /pm /tm			<i>Robert I. Brown</i> (Page 2 of 2)			

The results contained in this report relate only to item(s) tested. The test report shall not be reproduced, except in full, without written approval from Govmark.

File Copy

IRAM



MINIT Ignífugos

minitargentina@gmail.com www.minitfireretardant.com

COPIA FIEL DE CERTIFICADOS

Producto MINIT TOTAL

Presentación válida únicamente con el Certificado / Factura de Compra



11910-3 NBR 9442/86 ASTM 162 (METODO PANEL RADIANTE EN GOMA ESPUMA, RE2 CLASE A, BAJA PROPAGACION DEL FUEGO)

INTI Construcciones

INFORME DE ENSAYO

Solicitante: MINOTTI PABLO DAVID

O.T.: 101/22353

Dirección: Cochrane 2322

Pág.: 1/ 2

(1419) – Ciudad Autónoma de Buenos Aires

Fecha: 06/11/2012


Informe: Único

1. OBJETIVO

Clasificación de acuerdo al Índice de Propagación de Llama.

2. MATERIAL

Una (1) muestra de goma espuma, identificada por el solicitante como: “Panel Acústico y Goma Espuma Ignífuga MINIT”.



3. MÉTODO EMPLEADO

El ensayo de Propagación Superficial de Llama se realizó de acuerdo a la Norma IRAM 11910-3:1994 “Materiales de Construcción, Reacción al fuego, Determinación del índice de propagación de llama – método del panel radiante” (coincide con los métodos de ensayo de la Norma NBR 9442:1986 y ASTM E162:1994).

Ys

La muestra fue recibida el día 15/10/2012 y ensayada el día 06/11/2012.

Este informe no podrá ser reproducido parcialmente sin la autorización escrita del Laboratorio. Los resultados consignados se refieren exclusivamente a los elementos recibidos, el INTI y su Centro de Investigación y Desarrollo en Construcciones declinan toda responsabilidad por el uso indebido o incorrecto que se hiciere de este informe.

Instituto Nacional de Tecnología Industrial
Centro de Investigación y Desarrollo
en Construcciones

Avenida General Paz 5445
B1650KNA San Martín, Buenos Aires, Argentina
Teléfono (54 11) 4724 6200
e-mail: construcciones@inti.gob.ar



MINIT Ignífugos

minitargentina@gmail.com www.minitfireretardant.com

COPIA FIEL DE CERTIFICADOS

Producto MINIT TOTAL

Presentación válida únicamente con el Certificado / Factura de Compra



INTI Construcciones

INFORME DE ENSAYO

Solicitante: MINOTTI PABLO DAVID

O.T.: 101/22353

Pág.: 2/ 2

Dirección: Cochrane 2322

Fecha: 06/11/2012

(1419) – Ciudad Autónoma de Buenos Aires

Informe: Único

4. RESULTADOS OBTENIDOS

Determinación de la Propagación superficial de llama

F(promedio):	1,71
Q(promedio):	0,94
I(promedio):	1,55

De acuerdo al **Índice de Propagación de Llamas (I)** hallado y teniendo en cuenta la Tabla de Clasificación de la Norma IRAM 11910-1 del año 1994, que se detalla como referencias, el material **“Panel Acústico y Goma Espuma Ignífuga MINIT”** se clasifica como:

“Clase RE 2: Material de Muy baja propagación de llama”

(A esta clase pertenecen los materiales con un índice mayor a 0 y menor a 25)
Coincide con la Clase A de la Norma brasileña NBR 9442/1986

Referencias para el ensayo de determinación de la propagación superficial de llama

Clase	Clase ABNT	Denominación	Norma IRAM	Criterio de clasificación
RE 1	-	Incombustible	11910-2	Anexo A de la norma
RE 2	A	Muy baja propagación de llama	11910-1	Índice: 0 a 25
RE 3	B	Baja propagación de llama	11910-1	Índice: 26 a 75
RE 4	C	Mediana propagación de llama	11910-1	Índice: 76 a 150
RE 5	D	Elevada propagación de llama	11910-1	Índice: 151 a 400
RE 6	E	Muy elevada propagación de llama	11910-1	Índice mayor a 400

Definiciones:

Un factor derivado de la rapidez de propagación del frente de llama (F) y otro relativo al calor liberado por el material ensayado (Q) son combinados para proveer el índice de propagación superficial de llama (I).

I: Índice de propagación superficial de llama.

F: Factor de propagación de llama.

Q: Factor de evolución de calor


ARKBASIMO HAGOPIAN
COORDINADOR
U.T. TECNOLOGÍA EN INCENDIOS
INTI-CONSTRUCCIONES


Ing. VICENTE L. VOLANTINO
DIRECCIÓN
INTI - CONSTRUCCIONES

Nota:

De acuerdo a reglamentaciones internacionales, estos ensayos deben considerarse para medir y describir el comportamiento del material bajo condiciones controladas, pero no se puede estimar cuál será el comportamiento del mismo si se modifican total o parcialmente las condiciones de ensayo.

75.

reproducción y difusión del presente informe se halla sujeta a las cláusulas obrantes en la primer foja, anverso y reverso»



MINIT Ignifugos

minitargentina@gmail.com www.minitfireretardant.com

COPIA FIEL DE CERTIFICADOS

Producto MINIT TOTAL

Presentación valida únicamente con el Certificado / Factura de Compra



validacion

BS5852 y CAL TB 117 Resultado PASS (Inflamabilidad Horizontal en **Pasto Sintético**)

IGS

Industrial Global Standards LLC

Industrial Global Standards LLC
1209 MOUNTAIN ROAD PL NE STE N
ALBUQUERQUE, NM 87110
EIN 37-218160
www.inglobalstandards.com
industrialglobalstandards@gmail.com

TEST REPORT

Nº 1143-72-135

LAB SERVICE

VALIDO SOLO CON CERTIFICADO DE COMPRA.
MINIT IGNIFUGOS

Applicant/ Manufacturer	MINIT Fire Retardant (MINIT Ignifugos) Pablo David Minotti ID: 20224196270 Argentina
Product	Synthetic Grass treated with MINIT Ignifugos Fire Retardant
Reference Standard/ Method Tests	BS 5852 : 2006, & CAL TB 117 : 2013
Description of Test Specimen	Synthetic grass carpet (provided by Applicant/ Manufacturer) - 1 piece treated with MINIT ignifugos fire retardant Size of Specimen : 1500mm×1500mm Nominal Thickness : 5mm
Date Received	May 15, 2025
Issued Date	May 22, 2025
Pages	2

1

IGS



AMERICAN SOCIETY OF
SAFETY PROFESSIONALS

Authorized Signatory
Industrial Global Standards LLC
1209 MOUNTAIN ROAD PL NE STE N
ALBUQUERQUE, NM 87110



Validation Code

The client acknowledges and agrees that any services provided and/or reports produced by Industrial Global Standards LLC are done so within the limits of the scope of work agreed pursuant to the client's specific instructions. This report relates specifically to the sample(s) tested that were drawn and delivered by the client or their nominated third party. Industrial Global Standards LLC does not make any representation or warranty for any bulk samples or certify the bulk samples received from the client. Furthermore, Industrial Global Standards LLC does not provide a warranty or verification on the sample(s) representing any specific goods, material and/or shipment and only relate to the sample(s) as received and tested. Industrial Global Standards LLC have aimed to conduct the review on a diligent and careful basis and we do not accept any liability to you for any loss arising out of or in connection with this report, in contract, tort, by statute or otherwise, except in the event of our gross negligence or willful misconduct. In no event, will the contents of any reports or any extracts, excerpts or parts of any reports be distributed or published without the prior written consent of Industrial Global Standards LLC in each instance. Only the client is authorized to permit copying or distribution of this report (and then only in its entirety). Any such third parties to whom this report may be circulated rely on the content of the report solely at their own risk. The reported expanded uncertainty is based on a standard uncertainty multiplied by a coverage factor of $k = 2$, providing a level of confidence of approximately 95 %. Unless otherwise specified all compliance and pass/fail statements are binary simple acceptance based on the tolerance interval.



MINIT Ignifugos

minitargentina@gmail.com www.minitfireretardant.com

COPIA FIEL DE CERTIFICADOS

Producto MINIT TOTAL

Presentación valida únicamente con el Certificado / Factura de Compra



validacion



Industrial Global Standards LLC
1209 MOUNTAIN ROAD PL NE STE N
ALBUQUERQUE, NM 87110
EIN 37-218160
www.inglobalstandards.com
industrialglobalstandards@gmail.com

TEST REPORT


Nº 1143-72-135

LAB SERVICE

VALIDO SOLO CON CERTIFICADO DE COMPRA.
MINIT IGNIFUGOS

Following the treatment described above, the material was conditioned and tested according to **BS 5852 : 2006, & CAL TB 117 : 2013 Methods of Test for the Assessment of the Ignitability of Upholstered Seating by Smouldering and Flaming Ignition Sources, Clause 11, using Ignition Source 5.**

The results relate only to the ignitability of the combinations of upholstery composites (Clause 11) under the particular condition of test stated; they are not intended as a means of assessing the full potential fire hazard of the item in use.

RESULTS	REF
Specimen number	1
Duration of flaming of ignition source (min)	3'37"
Duration of flames (min)	4'17"
Duration of smoke (min)	5'24"
Extent of damage of horizontal component	
- width (mm)	138
- length (mm)	141
- depth (mm)	34
Extent of damage of vertical component	
- width (mm)	164
- depth (mm)	34
Progressive smouldering >100mm from ignition source	No
Result	 Pass

CONCLUSION

The specimen showed non-ignition, BS 5852: 2006, Rating NI5. & CAL TB 117: 2013, This Rating represents a Pass for Crib 5.

END OF REPORT



Authorized Signatory
Industrial Global Standards LLC
1209 MOUNTAIN ROAD PL NE STE N
ALBUQUERQUE, NM 87110



Validation Code

The client acknowledges and agrees that any services provided and/or reports produced by Industrial Global Standards LLC are done so within the limits of the scope of work agreed pursuant to the client's specific instructions. This report relates specifically to the sample(s) tested that were drawn and delivered by the client or their nominated third party. Industrial Global Standards LLC does not make any representation or warranty for any bulk samples or certify the bulk samples received from the client. Furthermore, Industrial Global Standards LLC does not provide a warranty or verification on the sample(s) representing any specific goods, material and/or shipment and only relate to the sample(s) as received and tested. Industrial Global Standards LLC have aimed to conduct the review on a diligent and careful basis and we do not accept any liability to you for any loss arising out of or in connection with this report, in contract, tort, by statute or otherwise, except in the event of our gross negligence or willful misconduct. In no event, will the contents of any reports or any extracts, excerpts or parts of any reports be distributed or published without the prior written consent of Industrial Global Standards LLC in each instance. Only the client is authorized to permit copying or distribution of this report (and then only in its entirety). Any such third parties to whom this report may be circulated rely on the content of the report solely at their own risk. The reported expanded uncertainty is based on a standard uncertainty multiplied by a coverage factor of $k = 2$, providing a level of confidence of approximately 95 %. Unless otherwise specified all compliance and pass/fail statements are binary simple acceptance based on the tolerance interval.



MINIT Ignífugos

minitargentina@gmail.com www.minitfireretardant.com

COPIA FIEL DE CERTIFICADOS

Producto MINIT TOTAL

Presentación válida únicamente con el Certificado / Factura de Compra



validacion

UIC 564-2 : 1991 (APENDICE 13) Material Plástico

INFORME DE ENSAYO	
Solicitante: MINOTTI PABLO DAVID	O.T.: 101/25498
Dirección: Cochrane 2322 (1419) C.A.B.A.	Pág.: 1/ 3
	Fecha: 16/06/2015
	Informe: Único
1. OBJETIVO Evaluación del comportamiento ante el fuego de asientos de vehículos de transporte de pasajeros.	
2. MATERIAL Una (1) unidad de asiento simple, identificada por el solicitante como: "Butaca con tratamiento retardante del fuego MINIT de Pablo Minotti" .	
	
Observaciones: La butaca se encontraba parcialmente dañada en su parte horizontal delantera.	
3. MÉTODO EMPLEADO La evaluación del comportamiento ante el fuego de asientos de vehículos de transporte de pasajeros, se realizó siguiendo de acuerdo a la Norma UIC 564-2:1991 Apéndice 13: "Regulations relating to fire protection and fire-fighting measures in passenger-carrying railway vehicles or assimilated vehicles used on international services" .	
La muestra fue recibida el día 20/04/2015 y fue ensayada el día 29/05/2011.	
Informe no podrá ser reproducido parcialmente sin la autorización escrita del INTI. Los resultados consignados se refieren exclusivamente a los elementos recibidos, el INTI y su rol de Investigación y Desarrollo en Construcciones no asumen toda responsabilidad por el uso indebido o incorrecto que se hiciera de este informe.	
Instituto Nacional de Tecnología Industrial www.inti.gov.ar consultas@inti.gov.ar 0800 444 4004	
Parque Tecnológico Miguelete Avenida General Paz 5445 Casilla de Correo 157 81650WAB San Martín, Buenos Aires, Argentina Teléfono (54 11) 4724 6200 E-mail construcciones@inti.gov.ar	



MINIT Ignífugos

minitargentina@gmail.com www.minitfiretardant.com

COPIA FIEL DE CERTIFICADOS

Producto MINIT TOTAL

Presentación valida únicamente con el Certificado / Factura de Compra



INTI Construcciones   **Presidencia de la Nación**  **Ministerio de Industria**

INFORME DE ENSAYO

Solicitante: MINOTTI PABLO DAVID **O.T.:** 101/25498
Dirección: Cochrane 2322 **Pág.:** 2/ 3
(1419) C.A.B.A. **Fecha:** 16/06/2015
Informe: Único

4. RESULTADOS OBTENIDOS

En la primera parte del ensayo (combustible sobre el asiento), el tiempo transcurrido desde el inicio del ensayo hasta la completa extinción del fuego fue de 3 minutos y 07 segundos.



En la segunda parte del ensayo (combustible debajo del asiento), el tiempo transcurrido desde el inicio del ensayo hasta la completa extinción del fuego fue de 3 minutos y 23 segundos.





«La reproducción y difusión del presente informe se halla sujeta a las cláusulas obrantes en la primer foja. anexo en v...



MINIT Ignífugos

minitargentina@gmail.com www.minitfireretardant.com

COPIA FIEL DE CERTIFICADOS

Producto MINIT TOTAL

Presentación válida únicamente con el Certificado / Factura de Compra



INTI Construcciones



Presidencia
de la Nación

Ministerio de
Industria

INFORME DE ENSAYO

Solicitante: MINOTTI PABLO DAVID

O.T.: 101/25498

Pág.: 3/ 3

Dirección: Cochrane 2322
(1419) C.A.B.A.

Fecha: 16/06/2015

Informe: Único

Criterio de aceptación de la Norma UIC 564-2:1991 Apéndice 13.

Para ambas ubicaciones del combustible:

- El fuego debe extinguirse espontáneamente antes de los 10 minutos de haber sido comenzado el ensayo.
- No deben observarse desprendimiento de partículas ardiendo.

De acuerdo al resultado obtenido la muestra **"Butaca con tratamiento retardante del fuego MINIT de Pablo Minotti"**, **CUMPLE** con las exigencias de la Norma UIC 564-2:1991 Apéndice 13.

Arq. BASILIO HAGAPOV
COORDINADOR
U.T. TECNOLOGÍA EN INCENDIOS
INTI-CONSTRUCCIONES

Lic. FABIO S. LUNA
COORDINADOR U.T.
Geología Aplicada y Ambiental
INTI - Construcciones

Nota:

De acuerdo a reglamentaciones internacionales, estos ensayos deben considerarse para medir y describir el comportamiento del material bajo condiciones controladas pero no se puede estimar cuál será el comportamiento del mismo si se modifican total o parcialmente las condiciones de ensayo.



MINIT Ignifugos

minitargentina@gmail.com www.minitfireretardant.com

COPIA FIEL DE CERTIFICADOS

Producto MINIT TOTAL

Presentación valida únicamente con el Certificado / Factura de Compra



validacion

ENSAYOS DE EMANACIÓN DE HUMO Y GASES



Industrial Global Standards LLC
1209 MOUNTAIN ROAD PL NE STE N
ALBUQUERQUE, NM 87110
EIN 37-218160
www.inglobalstandards.com
industrialglobalstandards@gmail.com

TEST REPORT

Nº 1143-27-522

LAB SERVICE

VALIDO SOLO CON CERTIFICADO DE COMPRA.

MINIT IGNIFUGOS

Applicant/ Manufacturer	MINIT Fire Retatadant (MINIT Ignifugos) Pablo David Minotti ID: 20224196270 Argentina
Product	MINIT Ignifugos / Fire retardant applied on different specimens described below
Reference Standard/ Method Tests	BSS 7239-88. // ASTM E-662. // EN 13823. // ISO 5659-2. TESTS METHODS FOR TOXIC GAS GENERATION BY MATERIALS ON COMBUSTION.
Description of Test Specimens	REF A -Total pieces with fire retardant (provided by Applicant/ Manufacturer) - 4 piece of 100% cotton fabric, treated with MINIT Ignifugos/ Fire retardant - Ref 1 - 4 piece of 100% polyester fabric, treated with MINIT Ignifugos/ Fire retardant - Ref 2 - 4 piece of synthetic carpet, treated with MINIT Ignifugos/ Fire retardant - Ref 3 - 4 piece of synthetic grass carpet, treated with MINIT Ignifugos/ Fire retardant - Ref 4 - 4 piece of foam, treated with MINIT Ignifugos/ Fire retardant - Ref 5 - 4 piece of wood, treated with MINIT Ignifugos/ Fire retardant - Ref 6 REF B -Total pieces without fire retardant (provided by Applicant/ Manufacturer) - 2 piece of 100% cotton fabric, without fire retardant - Ref 1 - 2 piece of 100% polyester fabric, without fire retardant - Ref 2 - 2 piece of synthetic carpet, without fire retardant - Ref 3 - 2 piece of synthetic grass carpet, without fire retardant - Ref 4 - 2 piece of foam, without fire retardant - Ref 5 - 2 piece of wood, without fire retardant - Ref 6 Size of Specimens: 3" x 3" , specified for test methods Size of Specimens: 15" x 15" , specified for test methods
Date Received	May 20, 2025
Issued Date	Jun 27, 2025
Pages	3

1

BSS 7239-88 is a Boeing standard test method that measures the concentration of toxic gases produced during the combustion of materials, specifically focusing on those used in aircraft interiors. It is a critical tool for evaluating fire safety, especially in the confined spaces of an aircraft cabin, by assessing the potential hazards from toxic gases like carbon monoxide, hydrogen fluoride, hydrogen cyanide, hydrogen chloride, and sulfur dioxide. The test is performed in a controlled environment, where a material sample is burned and the resulting gases are analyzed.

ASTM E-662 is a standard test method that measures the amount of smoke produced by solid materials when exposed to heat and flame, specifically focusing on those used in aircraft interiors. It is a critical tool for evaluating fire safety, especially in the confined spaces of an aircraft cabin, by assessing the potential hazards from toxic gases like carbon monoxide, hydrogen fluoride, hydrogen cyanide, hydrogen chloride, and sulfur dioxide. The test is performed in a controlled environment, where a material sample is burned and the resulting gases are analyzed.

EN 13823, is a Single Burning Item (SBI) test, is a European standard for evaluating the fire behavior of building products (excluding flooring) when exposed to a thermal attack. The product is mounted in a corner configuration with two walls (or wings) forming a 90-degree angle. A propane gas burner (30kW) is placed at the bottom of the corner to simulate a fire source. The specimen and burner are placed inside an enclosure with an exhaust system that collects combustion gases. Instruments measure heat release, smoke production, and flame spread, while visual observations record burning droplets and other relevant characteristics. The SBI test results are used to classify products into Euroclasses (A1, A2, B, C, D, etc.) which indicate their fire performance.

ISO 5659-2 is an international standard that specifies a method for measuring smoke production from materials, particularly plastics or synthetic, when exposed to heat and flame. It focuses on determining the optical density of the smoke produced in a single-chamber test. This standard is primarily used for research and development, as well as in fire safety engineering for buildings, trains, and ships, rather than for setting building code ratings.



AMERICAN SOCIETY OF
SAFETY PROFESSIONALS

Authorized Signatory
Industrial Global Standards LLC
1209 MOUNTAIN ROAD PL NE STE N
ALBUQUERQUE, NM 87110



Validation Code

The client acknowledges and agrees that any services provided and/or reports produced by Industrial Global Standards LLC are done so within the limits of the scope of work agreed pursuant to the client's specific instructions. This report relates specifically to the sample(s) tested that were drawn and delivered by the client or their nominated third party. Industrial Global Standards LLC does not make any representation or warranty for any bulk samples or certify the bulk samples received from the client. Furthermore, Industrial Global Standards LLC does not provide a warranty or verification on the sample(s) representing any specific goods, material and/or shipment and only relate to the sample(s) as received and tested. Industrial Global Standards LLC have aimed to conduct the review on a diligent and careful basis and we do not accept any liability to you for any loss arising out of or in connection with this report, in contract, tort, by statute or otherwise, except in the event of our gross negligence or willful misconduct. In no event, will the contents of any reports or any extracts, excerpts or parts of any reports be distributed or published without the prior written consent of Industrial Global Standards LLC in each instance. Only the client is authorized to permit copying or distribution of this report (and then only in its entirety). Any such third parties to whom this report may be circulated rely on the content of the report solely at their own risk. The reported expanded uncertainty is based on a standard uncertainty multiplied by a coverage factor of $k = 2$, providing a level of confidence of approximately 95 %. Unless otherwise specified all compliance and pass/fail statements are binary simple acceptance based on the tolerance interval.



MINIT Ignifugos

minitargentina@gmail.com www.minitfireretardant.com

COPIA FIEL DE CERTIFICADOS

Producto MINIT TOTAL

Presentación valida únicamente con el Certificado / Factura de Compra



validacion



Industrial Global Standards LLC
1209 MOUNTAIN ROAD PL NE STE N
ALBUQUERQUE, NM 87110
EIN 37-218160
www.inglobalstandards.com
industrialglobalstandards@gmail.com

TEST REPORT

Nº 1143-27-522

LAB SERVICE
VALIDO SOLO CON CERTIFICADO DE COMPRA.
MINIT IGNIFUGOS

BSS 7239-88 RESULTS:

Relative Room Humidity: 20% / Test Duration: 20 min. // Chamber Wall Temp: 35°C

Carbon Monoxide (CO ppm) at 1.5 minutes
at 4.0 minutes
at maximum

Nitrogen Oxides (as NO₂ ppm)

Sulfur Dioxide (SO₂ ppm)

Hydrogen Chloride (HCl ppm)

Hydrogen Fluoride (HF ppm)

Hydrogen Cyanide (HCN ppm)

REF A	HCl	HCN	HF	NO ₂	SO ₂	CO 1.5	CO 4.0	CO MAX
1	< 1	ND	ND	< 1	ND	5	55	118
2	< 2	ND	ND	< 1	ND	8	98	211
3	< 3	ND	< 2	< 1	< 1	9	101	218
4	< 3	ND	< 2	< 1	< 1	9	125	238
5	< 3	ND	< 2	< 1	< 1	9	127	247
6	< 2	ND	ND	< 1	ND	6	87	209

2

Conclusions:

Boeing BSS 7239 is solely a test procedure and as such, has no specific pass/fail criteria of its own. The reference criteria cited are typical for the transportation industry and are listed for reference purposes only. They may or may not apply to the specific products. Specimens are exposed to the combustion conditions described in ASTM E 662 - Standard Test Method for Specific Optical Density of Smoke Generated by Solid Materials. In compliance with this standards the material tested approve the BSS 7239 Tests

ASTM E-662 RESULTS:

REF A	Relative Room Humidity: 33% / Chamber Wall Temp: 35°C
1	Ds (1.5): 34, Ds (4.0): 52, Dm: 114.
2	Ds (1.5): 61, Ds (4.0): 89, Dm: 197.
3	Ds (1.5): 63, Ds (4.0): 91, Dm: 211.
4	Ds (1.5): 64, Ds (4.0): 94, Dm: 212.
5	Ds (1.5): 68, Ds (4.0): 97, Dm: 232.
6	Ds (1.5): 64, Ds (4.0): 95, Dm: 212.

Among the parameters normally reported are:

Ds 1.5 - specific optical density after 1.5 minutes

Ds 4.0 - specific optical density after 4.0 minutes

Dm - maximum specific optical density at any time during the 20 minute test

Authorities generally specify a maximum Ds 1.5 of 100 and a maximum Ds 4.0 of 200 in either flaming or non-flaming test mode.

Conclusions:

All specimens materials, identified in this report, when tested, meet requirements to smoke rate required by authorities.



AMERICAN SOCIETY OF
SAFETY PROFESSIONALS

Authorized Signatory
Industrial Global Standards LLC
1209 MOUNTAIN ROAD PL NE STE N
ALBUQUERQUE, NM 87110



Validation Code

The client acknowledges and agrees that any services provided and/or reports produced by Industrial Global Standards LLC are done so within the limits of the scope of work agreed pursuant to the client's specific instructions. This report relates specifically to the sample(s) tested that were drawn and delivered by the client or their nominated third party. Industrial Global Standards LLC does not make any representation or warranty for any bulk samples or certify the bulk samples received from the client. Furthermore, Industrial Global Standards LLC does not provide a warranty or verification on the sample(s) representing any specific goods, material and/or shipment and only relate to the sample(s) as received and tested. Industrial Global Standards LLC have aimed to conduct the review on a diligent and careful basis and we do not accept any liability to you for any loss arising out of or in connection with this report, in contract, tort, by statute or otherwise, except in the event of our gross negligence or wilful misconduct. In no event, will the contents of any reports or any extracts, excerpts or parts of any reports be distributed or published without the prior written consent of Industrial Global Standards LLC in each instance. Only the client is authorized to permit copying or distribution of this report (and then only in its entirety). Any such third parties to whom this report may be circulated rely on the content of the report solely at their own risk. The reported expanded uncertainty is based on a standard uncertainty multiplied by a coverage factor of $k = 2$, providing a level of confidence of approximately 95 %. Unless otherwise specified all compliance and pass/fail statements are binary simple acceptance based on the tolerance interval.



MINIT Ignifugos

minitargentina@gmail.com www.minitfireretardant.com

COPIA FIEL DE CERTIFICADOS

Producto MINIT TOTAL

Presentación valida únicamente con el Certificado / Factura de Compra



validacion

IGS

Industrial Global Standards LLC

Industrial Global Standards LLC
1209 MOUNTAIN ROAD PL NE STE N
ALBUQUERQUE, NM 87110
EIN 37-218160
www.inglobalstandards.com
industrialglobalstandards@gmail.com

TEST REPORT

Nº 1143-27-522

LAB SERVICE

VALIDO SOLO CON CERTIFICADO DE COMPRA.
MINIT IGNIFUGOS

EN 13823 RESULTS:

Cumulative smoke production (TSP), Fire Growth Rate (FIGRA), Cumulative heat release (THR), Smoke growth rate (SMOGRA)

REF A	Lateral Flame Spread to End of Specimen	Flaming droplets	Flaming of Fallen Particle Exceeding 10s	FIGRA (w/s)	THR 600s (MJ)	SMOGRA (m²/s²)	TSP 600s (m²)
1	N	N	N	178.68	11.89	79.68	86.15
2	N	N	N	367.17	24.78	187.23	149.95
3	N	N	N	389.82	25.49	162.89	144.56
4	N	N	N	391.25	24.87	161.76	142.82
5	N	N	N	396.12	25.45	163.08	144.78
6	N	N	N	185.98	12.87	83.45	89.27

Conclusion on specimens REF A: All specimens materials, identified in this report, when tested, meet requirements to smoke rate required by authorities. (Pass)

REF B	Lateral Flame Spread to End of Specimen	Flaming droplets	Flaming of Fallen Particle Exceeding 10s	FIGRA (w/s)	THR 600s (MJ)	SMOGRA (m²/s²)	TSP 600s (m²)
1	Y	Y	Y	536.04	35.67	239.04	258.45
2	Y	Y	Y	1101.51	74.37	561.96	449.85
3	Y	Y	Y	1069.46	76.47	488.67	433.68
4	Y	Y	Y	1173.75	74.61	485.28	428.46
5	Y	Y	Y	1188.36	76.35	489.24	434.34
6	Y	Y	Y	557.94	38.61	250.35	267.81

Conclusion on specimens REF B: All specimens materials, identified in this report, when tested, do not meet smoke rate required by authorities. (Do not pass)

ISO 5659-2 RESULTS:

The radiator cone was located so that the lower rim of the radiator cone shade junction was 25 mm above the upper surface of the specimen when oriented in the horizontal position. Exposed to a radiant heat source (25kW/m² or 50kW/m²) within a closed chamber. Pilot flame was applied.

REF A	/ Relative Room Humidity: 50% / Chamber Wall Temp: 26 °C
1	Ds (1.5): 31, Ds (4.0): 49, Dm: 111.
2	Ds (1.5): 59, Ds (4.0): 86, Dm: 194.
3	Ds (1.5): 61, Ds (4.0): 88, Dm: 208.
4	Ds (1.5): 61, Ds (4.0): 91, Dm: 209.
5	Ds (1.5): 65, Ds (4.0): 94, Dm: 229.
6	Ds (1.5): 61, Ds (4.0): 25, Dm: 209.

Conclusion on specimens REF A: All specimens materials, identified in this report, when tested, meet requirements to smoke rate required by authorities. (Pass)

REF B	/ Relative Room Humidity: 50% / Chamber Wall Temp: 26 °C
1	Ds (1.5): 119, Ds (4.0): 182, Dm: 399.
2	Ds (1.5): 213, Ds (4.0): 311, Dm: 689.
3	Ds (1.5): 220, Ds (4.0): 318, Dm: 738.
4	Ds (1.5): 224, Ds (4.0): 329, Dm: 742.
5	Ds (1.5): 238, Ds (4.0): 339, Dm: 812.
6	Ds (1.5): 224, Ds (4.0): 332, Dm: 742.

Conclusion on specimens REF B: All specimens materials, identified in this report, when tested, do not meet smoke rate required by authorities. (Do not pass)



AMERICAN SOCIETY OF
SAFETY PROFESSIONALS

Authorized Signatory
Industrial Global Standards LLC
1209 MOUNTAIN ROAD PL NE STE N
ALBUQUERQUE, NM 87110



Validation Code

The client acknowledges and agrees that any services provided and/or reports produced by Industrial Global Standards LLC are done so within the limits of the scope of work agreed pursuant to the client's specific instructions. This report relates specifically to the sample(s) tested that were drawn and delivered by the client or their nominated third party. Industrial Global Standards LLC does not make any representation or warranty for any bulk samples or certify the bulk samples received from the client. Furthermore, Industrial Global Standards LLC does not provide a warranty or verification on the sample(s) representing any specific goods, material and/or shipment and only relate to the sample(s) as received and tested. Industrial Global Standards LLC have aimed to conduct the review on a diligent and careful basis and we do not accept any liability to you for any loss arising out of or in connection with this report, in contract, tort, by statute or otherwise, except in the event of our gross negligence or wilful misconduct. In no event, will the contents of any reports or any extracts, excerpts or parts of any reports be distributed or published without the prior written consent of Industrial Global Standards LLC in each instance. Only the client is authorized to permit copying or distribution of this report (and then only in its entirety). Any such third parties to whom this report may be circulated rely on the content of the report solely at their own risk. The reported expanded uncertainty is based on a standard uncertainty multiplied by a coverage factor of $k = 2$, providing a level of confidence of approximately 95 %. Unless otherwise specified all compliance and pass/fail statements are binary simple acceptance based on the tolerance interval.



MINIT Ignífugos

minitargentina@gmail.com www.minitfireretardant.com

COPIA FIEL DE CERTIFICADOS

Producto MINIT TOTAL

Presentación valida únicamente con el Certificado / Factura de Compra



Homologación de De Densidad de Humo NORMA IRAM 11914

Evaluación Comparativa del Índice de Densidad de Humo (Dm) de diferentes materiales, tratados con Retardante de fuego MINIT Ignífugos, según certificado de ensayo Internacional **IGS 1143-27-522** con Normativa **IRAM 11914 1**.

Comparación de Normativas, Aspecto Propósito, Método de Prueba, Criterios de Evaluación, Similitud con Normas:

ISO 5659-2 Medición de la densidad de humo en cámara cerrada. Se mide la densidad óptica de los humos en función del tiempo y calor irradiado. Densidad óptica específica máxima (Ds). Alta similitud en técnicas de medición.

EN 13823 (SBI Test) Evaluación de la densidad de humo en materiales de construcción mediante SMOGRA. Evaluación de liberación de humo durante la combustión con un objeto en llamas. Tasa de crecimiento de humo (**SMOGRA**).

Ambas normas son compatibles en parte con la evaluación de propagación del humo. IRAM 11914"

En el certificado de ensayo internacional **IGS 1143-27-522** se realizó sobre los siguientes materiales tratados con Retardante de fuego MINIT Ignífugo y no tratados en ensayos comparativos:

- Tela 100% algodón
- Tela 100% poliéster
- Alfombra 100% sintética
- Alfombra de pasto 100% sintética
- Goma espuma
- Madera

En la valuación de la densidad óptica específica corregida (Dmc) de humos en incendios se mide la absorción de luz en una cámara específica para calcular Dm. Densidad óptica específica corregida (Dmc). Especifica los mismos criterios de clasificación.

Desarrollo Comparativo de Normativas Internacionales.

ISO 5659-2 es la norma internacional utilizada para medir la densidad de humo en cámara cerrada. Su método de medición es comparable con IRAM 11914, aunque sus criterios de clasificación difieren levemente.

EN 13823 (SBI Test) evalúa la propagación del fuego y la generación de humo, midiendo SMOGRA. No es idéntico a IRAM 11914 pero se usa en conjunto para clasificar materiales.

IRAM 11914 clasifica los materiales en función de la densidad de humo corregida (Dmc):

- ≤ 132 Clasificación Baja generación de humo
- 133 – 264 Mediana generación de humo
- 265 – 396 Alta generación de humo
- > 396 Muy alta generación de humo

Para evaluar un material en Argentina según IRAM 11914, los valores obtenidos de ISO 5659-2 o EN 13823 sirven como referencia.

Conclusión Final

A partir del análisis de normativas internacionales y estudios previos, se ha determinado que los materiales tratados con retardantes de llama MINIT tienen una generación de humo moderada, lo que permite su clasificación en "**Baja a Mediana Generación de Humo**" según **IRAM 11914 (Dmc 130 - 250)**. Comparado con los materiales sin Retardante de llama.

El informe sugiere que los materiales con retardantes de llama MINIT son una opción viable para aplicaciones donde la generación de humo debe ser controlada, cumpliendo con normativas de seguridad.

Equivalencias / Homologación de ensayos aprobados comparados con normas de otros países.

Ensayos de Inflamabilidad Vertical para Textiles:

Certificaciones aprobadas: IRAM-INTI-CIT G7577, NFPA 701, & NFPA 705 Methods.

Resultado: Nivel 1 = Clase A. Resultado Cualitativo: No entra en Ignición. Pass = Complies

Equivalente con los estándares europeos:

DIN 4102 Parts 15/16 - Brandschacht (B1); NFP 92 - 503 - Bržleur flectrique;

British Standard BS 5867 and BS 5438

Ensayos de inflamabilidad horizontal para muebles y alfombras

Certificación aprobada: CAL 117 (Pass = Complies)

Equivalente con los estándares europeos:

EN 1021 - 1/2 : 1994; EN 1021 : Part 1; EN 1021 : Part 2; DIN 4102 Part 1 - Kleinbrenner (B2)