


Role Based Access Control




RBAC

- ✦ Many organizations base access control decisions on “**the roles** that individual users take on as part of the organization”.
- ✦ They prefer to centrally control and maintain access rights that reflect the organization’s protection guidelines.
- ✦ With RBAC, role-permission relationships can be predefined, which makes it simple to assign users to the predefined roles.
- ✦ The combination of users and permissions tend to change over time, the permissions associated with a role are more stable.
- ✦ RBAC concept supports three well-known security principles:
 - Least privilege
 - Separation of duties
 - Data abstraction

Role Based Access Control (RBAC)

- ✦ Access control in organizations is based on “roles that individual users take on as part of the organization”
- ✦ A role is “is a collection of permissions”



RBAC




✦ Access depends on role/function, not identity

- Example: Allison is **bookkeeper** for Math Dept. She has access to financial records. If she leaves and Betty is hired as the new **bookkeeper**, Betty now has access to those records. The role of “bookkeeper” dictates access, not the identity of the individual.

Advantages of RBAC

- ✦ Allows Efficient Security Management
 - Administrative roles, Role hierarchy
- ✦ Principle of least privilege allows minimizing damage
- ✦ **Separation of Duties** constraints to prevent fraud
- ✦ Allows grouping of objects
- ✦ Policy-neutral - Provides generality


RBAC



Core RBAC (relations)

- ✦ $\text{Permissions} = 2^{\text{Operations} \times \text{Objects}}$
- ✦ $\text{UA} \subseteq \text{Users} \times \text{Roles}$
- ✦ $\text{PA} \subseteq \text{Permissions} \times \text{Roles}$
- ✦ $\text{assigned_users}: \text{Roles} \rightarrow 2^{\text{Users}}$
- ✦ $\text{assigned_permissions}: \text{Roles} \rightarrow 2^{\text{Permissions}}$
- ✦ $\text{Op}(p)$: set of operations associated with permission p
- ✦ $\text{Ob}(p)$: set of objects associated with permission p
- ✦ $\text{user_sessions}: \text{Users} \rightarrow 2^{\text{Sessions}}$
- ✦ $\text{session_user}: \text{Sessions} \rightarrow \text{Users}$
- ✦ $\text{session_roles}: \text{Sessions} \rightarrow 2^{\text{Roles}}$
 - $\text{session_roles}(s) = \{r \mid (\text{session_user}(s), r) \in \text{UA}\}$
- ✦ $\text{avail_session_perms}: \text{Sessions} \rightarrow 2^{\text{Permissions}}$

RBAC (NIST Standard)



Separation of Duties

- No user should be given enough privileges to misuse the system on their own.
- Statically: defining the conflicting roles
- Dynamically: Enforcing the control at access time

