

Musky Setup - Google SSO Integration Guide

This document outlines the required steps to configure Google SSO integration for the Musky system. This includes steps for setting up a service account, enabling APIs, managing group-based tool access, and storing credentials.

1. Enable Admin SDK API

- Visit <https://console.developers.google.com/> - Select your project (or create a new one). - Navigate to "Library". - Search for and enable: Admin SDK API.

2. Create a Google Service Account

- Go to "IAM & Admin" > "Service Accounts". - Click "Create Service Account". - Give it a name and description (e.g., musky-ss0). - Click "Create and Continue", then skip roles and finish. - After creation, click on the service account and go to the "Keys" tab. - Add a new JSON key and download it. - Store this file at: `/usr/local/Smillieware-CommonConfigz/musky/GoogleCreds/musky-service.json`

3. Delegate Domain-Wide Authority

- Still in the Service Account page, click "Show Domain-Wide Delegation". - Enable it and set a product name. - Go to: <https://admin.google.com/ac/owl/domainwidedelegation> - Add a new API client: - Client ID: Use the numeric client ID from your service account - OAuth Scopes: <https://www.googleapis.com/auth/admin.directory.user.readonly>, <https://www.googleapis.com/auth/admin.directory.group.readonly>

4. Required File Structure

You must have the following directory and credential file: Path: `/usr/local/Smillieware-CommonConfigz/musky/GoogleCreds/musky-service.json` This file must be readable by the web service running Musky.

5. Google Group to Tool Access Mapping

Inside the Musky database, the 'musky_group_access' table maps group email addresses to allowed tools. Example row: group_email: `hdk@gatewayk12.org` allowed_tools: `DEVICE_MANAGER,ADMIN_PANEL`

6. Optional Debug Files and Logs

When enabled, the system may generate: - `/tmp/google_directory_user_dump.json` - `/tmp/google_user_groups.json` Additionally, if `GOOGLE_DEBUG_LOG_DIR` is configured, per-user dumps are written to: `/var/log/musky/GoogleAuths/`

7. Session Variables

After login, these session values are populated: - \$_SESSION['sso_user'] -
\$_SESSION['google_directory_user'] - \$_SESSION['google_groups'] - \$_SESSION['musky_user']