

# Report Project Part 1

Jacob Chedore

(6347506)

420-635-AB-Network Installation and Administration

Prof. Antoine Tohme

April 21<sup>st</sup>, 2025

# Table of Contents

1-Creating a Website .....	3
2-Authentication .....	6
3-Accessibility .....	19
4-Authorization .....	28

# 1-Creating a Website

## -On the AlmaLinux machine

Install the httpd service

```
[root@server10 ~]# dnf install httpd
```

Creating a backup copy of the original configuration file

```
[root@server10 conf]# cp httpd.conf httpd.conf.original
[root@server10 conf]# ls -la
total 40
drwxr-xr-x. 2 root root   64 Apr 15 15:24 .
drwxr-xr-x. 5 root root  105 Apr 15 15:09 ..
-rw-r--r--. 1 root root 12005 Jan 21 16:19 httpd.conf
-rw-r--r--. 1 root root 12005 Apr 15 15:24 httpd.conf.original
-rw-r--r--. 1 root root 13430 Jan 21 16:24 magic
```

Creating the html\_project1 directory in the www folder and giving it proper permissions

```
[root@server10 ~]# mkdir /var/www/html_project1
[root@server10 ~]# ls /var/www
cgi-bin  html  html_project1
```

```
[root@server10 ~]# chmod -R 755 /var/www/html_project1
```

Changing the configuration file for Apache to read from the new directory

```
DocumentRoot "/var/www/html_project1"

<Directory "/var/www">
    AllowOverride None
    # Allow open access:
    Require all granted
</Directory>

<Directory "/var/www/html_project1">
    Options Indexes FollowSymLinks
    AllowOverride None
    Require all granted
</Directory>
```

Allowing the server to be accessible from an ip address

```
[root@server10 ~]# vim /etc/httpd/conf/httpd.conf
```

```
<Directory "/var/www/html_project1">
    Options Indexes FollowSymLinks
    AllowOverride None
    Require all granted
    Require ip 192.168.50.10
```

Ensuring the httpd service is running and enabled

```
[root@server10 ~]# systemctl start httpd
[root@server10 ~]# systemctl enable httpd
Created symlink /etc/systemd/system/multi-user.target.wants/httpd.service → /usr/lib/systemd/system/httpd.service.
[root@server10 ~]# systemctl status httpd
● httpd.service - The Apache HTTP Server
   Loaded: loaded (/usr/lib/systemd/system/httpd.service; enabled; preset:
   Active: active (running) since Tue 2025-04-15 17:36:14 EDT; 13s ago
```

Creating the index.html

```
[root@server10 ~]# vim /var/www/html_project1/index.html
```

Setting the document type and the head of the html page

```
<!doctype html>
<html>
  <head>
    <title>Project Part 1 - Homepage</title>
  </head>
```

Adding the body and a hyperlink to each web page following the example

```
<body>
  <p><b><h2>Project Part 1</b></p></h2>
  <hr>
<p><b><u>Task 2 - Secure directories:</b></u></p>
  <ul>
    <p><b><u><a href=http://192.168.50.10/secure1>secure1 (user01 - accessible)</a></b></u></p>
    <p><b><u><a href=http://192.168.50.10/secure2>secure2 (user01 and 192.168.50.0/24 - accessible)</a></b></u></p>
    <p><b><u><a href=http://10.35.16.1/secure2>secure2 (user01 and 10.35.16.1/24 - not accessible)</a></b></u></p>
    <p><b><u><a href=http://192.168.50.10/secure3>secure3 (user01 or 192.168.50.0/24 - accessible)</a></b></u></p>
    <p><b><u><a href=http://10.35.16.1/secure3>secure3 (user01 or 192.168.50.0/24 - accessible)</a></b></u></p>
    <p><b><u><a href=http://192.168.50.10/secure4>secure4 (user02 - accessible)</a></b></u></p>
    <p><b><u><a href=http://192.168.50.10/secure5>secure5 (user01 with .htaccess - accessible)</a></b></u></p>
    <p><b><u><a href=http://192.168.50.10/secure6>secure6 (user01 and 192.168.50 with .htaccess - Accessible)</a></b></u></p>
    <p><b><u><a href=http://10.35.16.1/secure6>secure6 (user01 and 10.35.16.1/24 with .htaccess - Not accessible)</a></b></u></p>
  </ul>
```

```
<hr>
<p><b><u>Task 3 - Project 1</b></u></p>
  <ul>
    <p><b><u><a href=http://192.168.50.10/Project1>Project1 (192.168.50.10 - All is accessible)</a></b></u></p>
    <p><b><u><a href=http://10.35.16.1/Project1>Project1 (10.35.16.1 accessible except files secret.* and *.txt)</a></b></u></p>
    <p><b><u><a href=http://10.35.17.1/Project1>Project1 (10.35.17.1 accessible except files secret.* and *.txt)</a></b></u></p>
  </ul>
  <hr>
<p><b><u>Task 3 - Project 2</b></u></p>
  <ul>
    <p><b><u><a href=http://192.168.50.10/Project2>Project2 (192.168.50.10 - All is accessible)</a></b></u></p>
    <p><b><u><a href=http://10.35.16.1/Project2>Project2 (10.35.16.1 Not accessible)</a></b></u></p>
    <p><b><u><a href=http://10.35.17.1/Project2>Project2 (10.35.17.1 accessible except files *.txt)</a></b></u></p>
    <p><b><u><a href=http://192.168.100.1/Project2>Project2 (192.168.100.1 accessible except files *.txt)</a></b></u></p>
  </ul>
```

```

<hr>
<p><b><u>Task 3 - Project 3:</b></u></p>
<ul>
<p><b><u><a href=http://192.168.50.10/Project3>Project3 (192.168.50.10 - All is accessible)</a></b></u></p>
<p><b><u><a href=http://10.35.16.1/Project3>Project3 (10.35.16.1 Not accessible)</a></b></u></p>
<p><b><u><a href=http://10.35.17.1/Project3>Project3 (10.35.17.1 Not accessible)</a></b></u></p>
<p><b><u><a href=http://192.168.100.1/Project3>Project3 (192.168.100.1 accessible except files *.gif and *.txt)</a></b></u></p>
</ul>
<hr>
<p><b><u>Task 3 - Project 4:</b></u></p>
<ul>
<p><b><u><a href=http://192.168.50.10/Project4>Project4 (192.168.50.10 - All is accessible)</a></b></u></p>
<p><b><u><a href=http://10.35.16.1/Project4>Project4 (10.35.16.1 accessible except files test.html)</a></b></u></p>
<p><b><u><a href=http://10.35.17.1/Project4>Project4 (10.35.17.1 Not accessible)</a></b></u></p>
<p><b><u><a href=http://192.168.100.1/Project4>Project4 (192.168.100.1 accessible except files test.html)</a></b></u></p>
</ul>

```

```

<hr>
<p><b><u>Task 4 - Vendors website:</b></u></p>
<ul>
<p><b><u><a href=http://10.50.1.1/vendors>Accessible to Vendors (10.50.1.0/24)</a></b></u></p>
<p><b><u><a href=http://10.51.1.1/vendors>Not accessible to Accountants (10.51.1.0/24)</a></b></u></p>
<p><b><u><a href=http://10.52.1.1/vendors>Accessible to Administrators (10.52.1.0/24)</a></b></u></p>
<p><b><u><a href=http://10.53.1.1/vendors>Accessible to Programmers (10.53.1.0/24) but not *.gif and *.jpg files</a></b></u></p>
</ul>
<hr>
<p><b><u>Task 4 - Accountants website:</b></u></p>
<ul>
<p><b><u><a href=http://10.50.1.1/accountants>Not accessible to Vendors (10.50.1.0/24) but not *.html files</a></b></u></p>
<p><b><u><a href=http://10.51.1.1/accountants>Accessible to Accountants (10.51.1.0/24)</a></b></u></p>
<p><b><u><a href=http://10.52.1.1/accountants>Accessible to Administrators (10.52.1.0/24)</a></b></u></p>
<p><b><u><a href=http://10.53.1.1/accountants>Accessible to Programmers (10.53.1.0/24) but not *.gif and *.jpg files</a></b></u></p>
</ul>

```

```

<hr>
<p><b><u>Task 4 - Programmers website:</b></u></p>
<ul>
<p><b><u><a href=http://10.50.1.1/programmers>Not accessible to Vendors (10.50.1.0/24)</a></b></u></p>
<p><b><u><a href=http://10.51.1.1/programmers>Not accessible to Accountants (10.51.1.0/24)</a></b></u></p>
<p><b><u><a href=http://10.52.1.1/programmers>Accessible to Administrators (10.52.1.0/24)</a></b></u></p>
<p><b><u><a href=http://10.53.1.1/programmers>Accessible to Programmers (10.53.1.0/24)</a></b></u></p>
</ul>
<hr>
<p><b><u>Task 4 - Administrators website:</b></u></p>
<ul>
<p><b><u><a href=http://10.50.1.1/administrators>Not accessible to Vendors (10.50.1.0/24) but not *.html files</a></b></u></p>
<p><b><u><a href=http://10.51.1.1/administrators>Not accessible to Accountants (10.51.1.0/24)</a></b></u></p>
<p><b><u><a href=http://10.52.1.1/administrators>Accessible to Administrators (10.52.1.0/24)</a></b></u></p>
<p><b><u><a href=http://10.53.1.1/administrators>Accessible to Programmers (10.53.1.0/24) but not *.gif and *.jpg files</a></b></u></p>
</ul>
</body>
</html>

```

Restarting the httpd service

```
[root@server10 html_project1]# systemctl restart httpd
```

Change firewall permissions to add the httpd port

```

[root@server10 html_project1]# firewall-cmd --permanent --add-port=80/tcp --zone=nm-shared
success
[root@server10 html_project1]# firewall-cmd --reload
success

```

-On the Ubuntu machine

Open a browser and type in the provided IP address to access the newly created website



Project Part 1 - Homepa x +

← → ↻ ⚠ Not secure 192.168.50.10 ☆ ⓘ ⋮

## Project Part 1

---

**Task 2 - Secure directories:**

- [secure1 \(user01 - accessible\)](#)
- [secure2 \(user01 and 192.168.50.0/24 - accessible\)](#)
- [secure2 \(user01 and 10.35.16.1/24 - not accessible\)](#)
- [secure3 \(user01 or 192.168.50.0/24 - accessible\)](#)
- [secure3 \(user01 or 192.168.50.0/24 - accessible\)](#)
- [secure4 \(user02 - accessible\)](#)
- [secure5 \(user01 with .htaccess - accessible\)](#)
- [secure6 \(user01 and 192.168.50 with .htaccess - Accessible\)](#)
- [secure6 \(user01 and 10.35.16.1/24 with .htaccess - Not accessible\)](#)
- [secure7 \(user01 or 192.168.50 with .htaccess - Accessible\)](#)

---

**Task 3 - Project 1:**

- [Project1 \(192.168.50.10 - All is accessible\)](#)
- [Project1 \(10.35.16.1 accessible except files secret.\\* and \\*.txt\)](#)
- [Project1 \(10.35.17.1 accessible except files secret.\\* and \\*.txt\)](#)
- [Project1 \(192.168.100.1 Not accessible\)](#)

---

**Task 3 - Project 2:**

## 2-Authentication

### -On the AlmaLinux machine

Creating user01 and user02 with htpasswd

```
[root@server10 www]# htpasswd -bc /var/www/.htpasswd user01 secret
Adding password for user user01
```

```
[root@server10 www]# htpasswd -b /var/www/.htpasswd user02 secret
Adding password for user user02
```

```
[root@server10 www]# cat .htpasswd
user01:$apr1$U1T7E055$R8unUD/4Q8ksr7FLCE4nE0
user02:$apr1$d6ZsBC1d$WlMwJvC9.TGXYX3IJo48c0
```

Adding the necessary IP address to the LAN1 connection

```
[root@server10 ~]# nmcli con mod LAN1 +ipv4.addresses 10.35.16.1/24 +ipv4.addresses 10.35.17.1/24 +ipv4.addresses 192.168.100.1/24 +ipv4.addresses 10.50.1.1/24 +ipv4.addresses 10.51.1.1/24 +ipv4.addresses 10.52.1.1/24 +ipv4.addresses 10.53.1.1/24
[root@server10 ~]# nmcli con d LAN1 ; nmcli con u LAN1
Connection 'LAN1' successfully deactivated (D-Bus active path: /org/freedesktop/NetworkManager/ActiveConnection/3)
Connection successfully activated (D-Bus active path: /org/freedesktop/NetworkManager/ActiveConnection/4)
```

### -On the Ubuntu machine

Adding the necessary IP address to the LAN1 connection

```
jchedore@client10:~$ nmcli con mod LAN1 +ipv4.addresses 10.35.16.2/24 +ipv4.addresses 10.35.17.2/24 +ipv4.addresses 192.168.100.2/24 +ipv4.addresses 10.50.1.2/24 +ipv4.addresses 10.51.1.2/24 +ipv4.addresses 10.52.1.2/24 +ipv4.addresses 10.53.1.2/24
jchedore@client10:~$ nmcli con d LAN1 ; nmcli con u LAN1
Connection 'LAN1' successfully deactivated (D-Bus active path: /org/freedesktop/NetworkManager/ActiveConnection/2)
Connection successfully activated (D-Bus active path: /org/freedesktop/NetworkManager/ActiveConnection/3)
```

### -On the AlmaLinux machine

Creating the seven secure directories in the html\_project1 directory

```
[root@server10 ~]# cd /var/www/html_project1
```

```
[root@server10 html_project1]# mkdir secure1
[root@server10 html_project1]# mkdir secure2
[root@server10 html_project1]# mkdir secure3
[root@server10 html_project1]# mkdir secure4
```

```
[root@server10 html_project1]# mkdir secure5
[root@server10 html_project1]# mkdir secure6
[root@server10 html_project1]# mkdir secure7
[root@server10 html_project1]# ls
index.html  secure1  secure2  secure3  secure4  secure5  secure6  secure7
```

Creating the html files for the secure folders

```
[root@server10 secure1]# vim index.html
```

```
<!doctype html>
<html>
  <head>
    <title>Project Part 1-Jacob Chedore</title>
  </head>
  <body>
    <p><b><u>Secure1</b></u></p>
  </body>
</html>
```

```
[root@server10 html_project1]# cd secure2
[root@server10 secure2]# vim index.html
```

```
<!doctype html>
<html>
  <head>
    <title>Project Part 1-Jacob Chedore</title>
  </head>
  <body>
    <p><b><u>Secure2</b></u></p>
  </body>
</html>
```

```
[root@server10 html_project1]# cd secure3
[root@server10 secure3]# vim index.html
```

```
<!doctype html>
<html>
  <head>
    <title>Project Part 1-Jacob Chedore</title>
  </head>
  <body>
    <p><b><u>Secure3</b></u></p>
  </body>
</html>
```

```
[root@server10 html_project1]# cd secure4
[root@server10 secure4]# vim index.html
```

```
<!doctype html>
<html>
  <head>
    <title>Project Part 1-Jacob Chedore</title>
  </head>
  <body>
    <p><b><u>Secure4</b></u></p>
  </body>
</html>
```

```
[root@server10 html_project1]# cd secure5
[root@server10 secure5]# vim index.html
```

```
<!doctype html>
<html>
  <head>
    <title>Project Part 1-Jacob Chedore</title>
  </head>
  <body>
    <p><b><u>Secure5</b></u></p>
  </body>
</html>
```

```
[root@server10 html_project1]# cd secure6
[root@server10 secure6]# vim index.html
```

```
<!doctype html>
<html>
  <head>
    <title>Project Part 1-Jacob Chedore</title>
  </head>
  <body>
    <p><b><u>Secure6</b></u></p>
  </body>
</html>
```

```
[root@server10 html_project1]# cd secure7
[root@server10 secure7]# vim index.html
```



```
<!doctype html>
<html>
  <head>
    <title>Project Part 1-Jacob Chedore</title>
  </head>
  <body>
    <p><b><u>Secure7</u></b></p>
  </body>
</html>
```

Configure the httpd configuration file according to the specific task for the first four secure folders

```
<Directory "/var/www/html_project1/secure1">
  AuthType Basic
  AuthName "Restricted Access"
  AuthUserFile "/var/www/.htpasswd"
  Require user user01
</Directory>

<Directory "/var/www/html_project1/secure2">
  <RequireAll>
    Require ip 192.168.50.0/24
    AuthType Basic
    AuthName "Restricted Access"
    AuthUserFile "/var/www/.htpasswd"
    Require user user01
  </RequireAll>
</Directory>
```

```
<Directory "/var/www/html_project1/secure3">
  AuthType Basic
  AuthName "Restricted Access"
  AuthUserFile "/var/www/.htpasswd"
  Require user user01
  Require ip 192.168.50.0/24
</Directory>

<Directory "/var/www/html_project1/secure4">
  AuthType Basic
  AuthName "Restricted Access"
  AuthUserFile "/var/www/.htpasswd"
  Require user user02
</Directory>
```

Configuring the last 3 secure folders using .htaccess files using the parameters given

```
[root@server10 ~]# vim /var/www/html_project1/secure5/.htaccess
```

```
AuthType Basic
AuthName "Access Restricted"
AuthUserFile "/var/www/.htpasswd"
Require user user01
```

```
[root@server10 ~]# vim /etc/httpd/conf/httpd.conf
```

```
<Directory "/var/www/html_project1/secure5">
    AllowOverride All
</Directory>
```

```
[root@server10 ~]# vim /var/www/html_project1/secure6/.htaccess
```

```
<RequireAll>
    AuthType Basic
    AuthName "Access Restricted"
    AuthUserFile "/var/www/.htpasswd"
    Require user user01
    Require ip 192.168.50.0/24
</RequireAll>
```

```
[root@server10 ~]# vim /etc/httpd/conf/httpd.conf
```

```
<Directory "/var/www/html_project1/secure6">
    AllowOverride All
</Directory>
```

```
[root@server10 ~]# vim /var/www/html_project1/secure7/.htaccess
```

```
AuthType Basic
AuthName "Access Restricted"
AuthUserFile "/var/www/.htpasswd"
Require user user01
Require ip 192.168.50.0/24
```

```
[root@server10 ~]# vim /etc/httpd/conf/httpd.conf
```

```
<Directory "/var/www/html_project1/secure7">
    AllowOverride All
</Directory>
```

Restarting the httpd service

```
[root@server10 ~]# systemctl restart httpd
```

**-On the Ubuntu machine**

Doing tests for each link on the website

## Project Part 1

### Task 2 - Secure directories:

[secure1 \(user01 - accessible\)](#)  
[secure2 \(user01 and 192.168.50.0/24 - accessible\)](#)  
[secure2 \(user01 and 10.35.16.1/24 - not accessible\)](#)  
[secure3 \(user01 or 192.168.50.0/24 - accessible\)](#)  
[secure3 \(user01 or 192.168.50.0/24 - accessible\)](#)  
[secure4 \(user02 - accessible\)](#)  
[secure5 \(user01 with .htaccess - accessible\)](#)  
[secure6 \(user01 and 192.168.50 with .htaccess - Accessible\)](#)  
[secure6 \(user01 and 10.35.16.1/24 with .htaccess - Not accessible\)](#)  
[secure7 \(user01 or 192.168.50 with .htaccess - Accessible\)](#)

### Sign in

http://192.168.50.10

Your connection to this site is not private

Username

Password

Cancel

Sign in

### Secure1

## Project Part 1

### Task 2 - Secure directories:

[secure1 \(user01 - accessible\)](#)  
[secure2 \(user01 and 192.168.50.0/24 - accessible\)](#)  
[secure2 \(user01 and 10.35.16.1/24 - not accessible\)](#)  
[secure3 \(user01 or 192.168.50.0/24 - accessible\)](#)  
[secure3 \(user01 or 192.168.50.0/24 - accessible\)](#)  
[secure4 \(user02 - accessible\)](#)  
[secure5 \(user01 with .htaccess - accessible\)](#)  
[secure6 \(user01 and 192.168.50 with .htaccess - Accessible\)](#)  
[secure6 \(user01 and 10.35.16.1/24 with .htaccess - Not accessible\)](#)  
[secure7 \(user01 or 192.168.50 with .htaccess - Accessible\)](#)

### Sign in


http://192.168.50.10

Your connection to this site is not private

Username

Password

### Secure2



## Project Part 1

### Task 2 - Secure directories:

- [secure1 \(user01 - accessible\)](#)
- [secure2 \(user01 and 192.168.50.0/24 - accessible\)](#)
- [secure2 \(user01 and 10.35.16.1/24 - not accessible\)](#)
- [secure3 \(user01 or 192.168.50.0/24 - accessible\)](#)
- [secure3 \(user01 or 192.168.50.0/24 - accessible\)](#)
- [secure4 \(user02 - accessible\)](#)
- [secure5 \(user01 with .htaccess - accessible\)](#)
- [secure6 \(user01 and 192.168.50 with .htaccess - Accessible\)](#)
- [secure6 \(user01 and 10.35.16.1/24 with .htaccess - Not accessible\)](#)
- [secure7 \(user01 or 192.168.50 with .htaccess - Accessible\)](#)



## Forbidden


You don't have permission to access this resource.



## Project Part 1

### Task 2 - Secure directories:

- [secure1 \(user01 - accessible\)](#)
- [secure2 \(user01 and 192.168.50.0/24 - accessible\)](#)
- [secure2 \(user01 and 10.35.16.1/24 - not accessible\)](#)
- [secure3 \(user01 or 192.168.50.0/24 - accessible\)](#)
- [secure3 \(user01 or 192.168.50.0/24 - accessible\)](#)
- [secure4 \(user02 - accessible\)](#)
- [secure5 \(user01 with .htaccess - accessible\)](#)
- [secure6 \(user01 and 192.168.50 with .htaccess - Accessible\)](#)
- [secure6 \(user01 and 10.35.16.1/24 with .htaccess - Not accessible\)](#)
- [secure7 \(user01 or 192.168.50 with .htaccess - Accessible\)](#)



### Secure3



## Project Part 1

### Task 2 - Secure directories:

[secure1 \(user01 - accessible\)](#)

[secure2 \(user01 and 192.168.50.0/24 - accessible\)](#)

[secure2 \(user01 and 10.35.16.1/24 - not accessible\)](#)

[secure3 \(user01 or 192.168.50.0/24 - accessible\)](#)

[secure3 \(user01 or 192.168.50.0/24 - accessible\)](#)

[secure4 \(user02 - accessible\)](#)

[secure5 \(user01 with .htaccess - accessible\)](#)

[secure6 \(user01 and 192.168.50 with .htaccess - Accessible\)](#)

[secure6 \(user01 and 10.35.16.1/24 with .htaccess - Not accessible\)](#)

[secure7 \(user01 or 192.168.50 with .htaccess - Accessible\)](#)

### Sign in

http://10.35.16.1

Your connection to this site is not private

Username

Password

Cancel

Sign in

### Secure3

## Project Part 1

### Task 2 - Secure directories:

- [secure1 \(user01 - accessible\)](#)
- [secure2 \(user01 and 192.168.50.0/24 - accessible\)](#)
- [secure2 \(user01 and 10.35.16.1/24 - not accessible\)](#)
- [secure3 \(user01 or 192.168.50.0/24 - accessible\)](#)
- [secure3 \(user01 or 192.168.50.0/24 - accessible\)](#)
- [secure4 \(user02 - accessible\)](#)
- [secure5 \(user01 with .htaccess - accessible\)](#)
- [secure6 \(user01 and 192.168.50 with .htaccess - Accessible\)](#)
- [secure6 \(user01 and 10.35.16.1/24 with .htaccess - Not accessible\)](#)
- [secure7 \(user01 or 192.168.50 with .htaccess - Accessible\)](#)

### Sign in

http://192.168.50.10

Your connection to this site is not private

Username

Password

Cancel

Sign in

### Secure4

## Project Part 1

### Task 2 - Secure directories:

[secure1 \(user01 - accessible\)](#)  
[secure2 \(user01 and 192.168.50.0/24 - accessible\)](#)  
[secure2 \(user01 and 10.35.16.1/24 - not accessible\)](#)  
[secure3 \(user01 or 192.168.50.0/24 - accessible\)](#)  
[secure3 \(user01 or 192.168.50.0/24 - accessible\)](#)  
[secure4 \(user02 - accessible\)](#)  
[secure5 \(user01 with .htaccess - accessible\)](#)  
[secure6 \(user01 and 192.168.50 with .htaccess - Accessible\)](#)  
[secure6 \(user01 and 10.35.16.1/24 with .htaccess - Not accessible\)](#)  
[secure7 \(user01 or 192.168.50 with .htaccess - Accessible\)](#)

### Sign in

http://192.168.50.10

Your connection to this site is not private

Username   
Password

Cancel

Sign in

### Secure5

## Project Part 1

### Task 2 - Secure directories:

[secure1 \(user01 - accessible\)](#)  
[secure2 \(user01 and 192.168.50.0/24 - accessible\)](#)  
[secure2 \(user01 and 10.35.16.1/24 - not accessible\)](#)  
[secure3 \(user01 or 192.168.50.0/24 - accessible\)](#)  
[secure3 \(user01 or 192.168.50.0/24 - accessible\)](#)  
[secure4 \(user02 - accessible\)](#)  
[secure5 \(user01 with .htaccess - accessible\)](#)  
[secure6 \(user01 and 192.168.50 with .htaccess - Accessible\)](#)  
[secure6 \(user01 and 10.35.16.1/24 with .htaccess - Not accessible\)](#)  
[secure7 \(user01 or 192.168.50 with .htaccess - Accessible\)](#)

### Sign in

http://192.168.50.10

Your connection to this site is not private

Username   
Password

Cancel

Sign in

### Secure6

## Project Part 1

### Task 2 - Secure directories:

- [secure1 \(user01 - accessible\)](#)
- [secure2 \(user01 and 192.168.50.0/24 - accessible\)](#)
- [secure2 \(user01 and 10.35.16.1/24 - not accessible\)](#)
- [secure3 \(user01 or 192.168.50.0/24 - accessible\)](#)
- [secure3 \(user01 or 192.168.50.0/24 - accessible\)](#)
- [secure4 \(user02 - accessible\)](#)
- [secure5 \(user01 with .htaccess - accessible\)](#)
- [secure6 \(user01 and 192.168.50 with .htaccess - Accessible\)](#)
- [secure6 \(user01 and 10.35.16.1/24 with .htaccess - Not accessible\)](#)
- [secure7 \(user01 or 192.168.50 with .htaccess - Accessible\)](#)

## Forbidden


You don't have permission to access this resource.

## Project Part 1

### Task 2 - Secure directories:

- [secure1 \(user01 - accessible\)](#)
- [secure2 \(user01 and 192.168.50.0/24 - accessible\)](#)
- [secure2 \(user01 and 10.35.16.1/24 - not accessible\)](#)
- [secure3 \(user01 or 192.168.50.0/24 - accessible\)](#)
- [secure3 \(user01 or 192.168.50.0/24 - accessible\)](#)
- [secure4 \(user02 - accessible\)](#)
- [secure5 \(user01 with .htaccess - accessible\)](#)
- [secure6 \(user01 and 192.168.50 with .htaccess - Accessible\)](#)
- [secure6 \(user01 and 10.35.16.1/24 with .htaccess - Not accessible\)](#)
- [secure7 \(user01 or 192.168.50 with .htaccess - Accessible\)](#)





## 3-Accessibility

### -On the AlmaLinux machine

Creating the four Project directories

```
[root@server10 html_project1]# mkdir Project1
[root@server10 html_project1]# mkdir Project2
[root@server10 html_project1]# mkdir Project3
[root@server10 html_project1]# mkdir Project4
[root@server10 html_project1]# ls
index.html Project1 Project2 Project3 Project4
```

Creating a .html for each project directory

```
[root@server10 html_project1]# vim Project1/project1.html
[root@server10 html_project1]# vim Project2/project2.html
[root@server10 html_project1]# vim Project3/project3.html
[root@server10 html_project1]# vim Project4/project4.html
```

Creating the necessary test files for each of the respective project directories

```
[root@server10 html_project1]# vim Project1/doc.txt
[root@server10 html_project1]# vim Project2/doc.txt
[root@server10 html_project1]# vim Project3/doc.txt
[root@server10 html_project1]# vim Project4/doc.txt
[root@server10 html_project1]# vim Project1/secret.doc
[root@server10 html_project1]# vim Project2/secret.doc
[root@server10 html_project1]# vim Project2/some.gif
[root@server10 html_project1]# vim Project3/some.gif
[root@server10 html_project1]# vim Project4/some.gif
[root@server10 html_project1]# vim Project3/some.jpg
[root@server10 html_project1]# vim Project4/test.html
```

Configuring the .txt file in apache to be seen only by the 192.168.50.10 address

```
[root@server10 html_project1]# vim /etc/httpd/conf/httpd.conf
```

```
<FilesMatch "\.txt$">
    Require all denied
    Require ip 192.168.50
</FilesMatch>
```

Making configurations according to each Project directory's specifications

```
<Directory "/var/www/html_project1/Project1">
  <RequireAll>
    Require all granted
    Require not ip 192.168.100
  </RequireAll>
  <Files "secret.*">
    Require all denied
    Require ip 192.168.50
  </Files>
</Directory>
```

```
<Directory "/var/www/html_project1/Project2">
  <RequireAll>
    Require all granted
    Require not ip 10.35.16
  </RequireAll>
</Directory>
```

```
<Directory "/var/www/html_project1/Project3">
  <RequireAll>
    Require all granted
    Require not ip 10.35.16
    Require not ip 10.35.17
  </RequireAll>
  <Files "*.gif">
    Require all denied
    Require ip 192.168.50
  </Files>
</Directory>
```

```
<Directory "/var/www/html_project1/Project4">
  <RequireAll>
    Require all granted
    Require not ip 10.35.17
  </RequireAll>
  <Files "test.html">
    Require all denied
    Require ip 192.168.50
  </Files>
</Directory>
```

Restarting the httpd service

```
[root@server10 html_project1]# systemctl restart httpd
```

**-On the Ubuntu machine**

Testing on the website

### Task 3 - Project 1:

[Project1 \(192.168.50.10 - All is accessible\)](#)

[Project1 \(10.35.16.1 accessible except files secret.\\* and \\*.txt\)](#)

[Project1 \(10.35.17.1 accessible except files secret.\\* and \\*.txt\)](#)

[Project1 \(192.168.100.1 Not accessible\)](#)



## Index of /Project1

Name	Last modified	Size	Description
 <a href="#">Parent Directory</a>		-	
 <a href="#">doc.txt</a>	2025-04-17 22:16	0	
 <a href="#">project1.html</a>	2025-04-17 22:08	0	
 <a href="#">secret.doc</a>	2025-04-17 22:16	0	

### Task 3 - Project 1:

[Project1 \(192.168.50.10 - All is accessible\)](#)

[Project1 \(10.35.16.1 accessible except files secret.\\* and \\*.txt\)](#)

[Project1 \(10.35.17.1 accessible except files secret.\\* and \\*.txt\)](#)

[Project1 \(192.168.100.1 Not accessible\)](#)



## Index of /Project1

Name	Last modified	Size	Description
 <a href="#">Parent Directory</a>		-	
 <a href="#">project1.html</a>	2025-04-17 22:08	0	

### Task 3 - Project 1:

[Project1 \(192.168.50.10 - All is accessible\)](#)

[Project1 \(10.35.16.1 accessible except files secret.\\* and \\*.txt\)](#)

[Project1 \(10.35.17.1 accessible except files secret.\\* and \\*.txt\)](#)



[Project1 \(192.168.100.1 Not accessible\)](#)

Index of /Project1

x
+

←
→
↻
⚠ Not secure
10.35.17.1/Project1/

# Index of /Project1

Name	Last modified	Size	Description
 <a href="#">Parent Directory</a>		-	
 <a href="#">project1.html</a>	2025-04-17 22:08	0	

### Task 3 - Project 1:

- [Project1 \(192.168.50.10 - All is accessible\)](#)
- [Project1 \(10.35.16.1 accessible except files secret.\\* and \\*.txt\)](#)
- [Project1 \(10.35.17.1 accessible except files secret.\\* and \\*.txt\)](#)
- [Project1 \(192.168.100.1 Not accessible\)](#)

403 Forbidden

x
+


←
→
↻
⚠ Not secure
192.168.100.1/Project1

# Forbidden

You don't have permission to access this resource.

### Task 3 - Project 2:

- [Project2 \(192.168.50.10 - All is accessible\)](#)
- [Project2 \(10.35.16.1 Not accessible\)](#)
- [Project2 \(10.35.17.1 accessible except files \\*.txt\)](#)
- [Project2 \(192.168.100.1 accessible except files \\*.txt\)](#)



## Index of /Project2

Name	Last modified	Size	Description
 <a href="#">Parent Directory</a>		-	
 <a href="#">doc.txt</a>	2025-04-17 22:16	0	
 <a href="#">project2.html</a>	2025-04-17 22:11	0	
 <a href="#">secret.doc</a>	2025-04-17 22:17	0	
 <a href="#">some.gif</a>	2025-04-17 22:18	0	


### Task 3 - Project 2:

[Project2 \(192.168.50.10 - All is accessible\)](#)

[Project2 \(10.35.16.1 Not accessible\)](#)

[Project2 \(10.35.17.1 accessible except files \\*.txt\)](#)

[Project2 \(192.168.100.1 accessible except files \\*.txt\)](#)



## Forbidden

You don't have permission to access this resource.

### Task 3 - Project 2:

[Project2 \(192.168.50.10 - All is accessible\)](#)

[Project2 \(10.35.16.1 Not accessible\)](#)

[Project2 \(10.35.17.1 accessible except files \\*.txt\)](#)

[Project2 \(192.168.100.1 accessible except files \\*.txt\)](#)



## Index of /Project2

Name	Last modified	Size	Description
<a href="#">Parent Directory</a>		-	
<a href="#">project2.html</a>	2025-04-17 22:11	0	
<a href="#">secret.doc</a>	2025-04-17 22:17	0	
<a href="#">some.gif</a>	2025-04-17 22:18	0	

### Task 3 - Project 2:

[Project2 \(192.168.50.10 - All is accessible\)](#)

[Project2 \(10.35.16.1 Not accessible\)](#)

[Project2 \(10.35.17.1 accessible except files \\*.txt\)](#)

[Project2 \(192.168.100.1 accessible except files \\*.txt\)](#)

## Index of /Project2

Name	Last modified	Size	Description
<a href="#">Parent Directory</a>		-	
<a href="#">project2.html</a>	2025-04-17 22:11	0	
<a href="#">secret.doc</a>	2025-04-17 22:17	0	
<a href="#">some.gif</a>	2025-04-17 22:18	0	


### Task 3 - Project 3:

[Project3 \(192.168.50.10 - All is accessible\)](#)

[Project3 \(10.35.16.1 Not accessible\)](#)

[Project3 \(10.35.17.1 Not accessible\)](#)

[Project3 \(192.168.100.1 accessible except files \\*.gif and \\*.txt\)](#)



## Index of /Project3

Name	Last modified	Size	Description
<a href="#">Parent Directory</a>		-	
<a href="#">doc.txt</a>	2025-04-17 22:16	0	
<a href="#">project3.html</a>	2025-04-17 22:11	0	
<a href="#">some.gif</a>	2025-04-17 22:18	0	
<a href="#">some.jpg</a>	2025-04-17 22:19	0	

### Task 3 - Project 3:

[Project3 \(192.168.50.10 - All is accessible\)](#)

[Project3 \(10.35.16.1 Not accessible\)](#)

[Project3 \(10.35.17.1 Not accessible\)](#)

[Project3 \(192.168.100.1 accessible except files \\*.gif and \\*.txt\)](#)



## Forbidden

You don't have permission to access this resource.

### Task 3 - Project 3:

[Project3 \(192.168.50.10 - All is accessible\)](#)

[Project3 \(10.35.16.1 Not accessible\)](#)

[Project3 \(10.35.17.1 Not accessible\)](#)

[Project3 \(192.168.100.1 accessible except files \\*.gif and \\*.txt\)](#)



## Forbidden

You don't have permission to access this resource.

### Task 3 - Project 3:

[Project3 \(192.168.50.10 - All is accessible\)](#)

[Project3 \(10.35.16.1 Not accessible\)](#)

[Project3 \(10.35.17.1 Not accessible\)](#)

[Project3 \(192.168.100.1 accessible except files \\*.gif and \\*.txt\)](#)



## Index of /Project3

Name	Last modified	Size	Description
<a href="#">Parent Directory</a>	-	-	-
<a href="#">project3.html</a>	2025-04-17 22:11	0	
<a href="#">some.jpg</a>	2025-04-17 22:19	0	

### Task 3 - Project 4:

[Project4 \(192.168.50.10 - All is accessible\)](#)

[Project4 \(10.35.16.1 accessible except files test.html\)](#)

[Project4 \(10.35.17.1 Not accessible\)](#)

[Project4 \(192.168.100.1 accessible except files test.html\)](#)



## Index of /Project4

Name	Last modified	Size	Description
<a href="#">Parent Directory</a>	-	-	-
<a href="#">doc.txt</a>	2025-04-17 22:16	0	
<a href="#">project4.html</a>	2025-04-17 22:11	0	
<a href="#">some.gif</a>	2025-04-17 22:19	0	
<a href="#">test.html</a>	2025-04-17 22:19	0	


### Task 3 - Project 4:

[Project4 \(192.168.50.10 - All is accessible\)](#)

[Project4 \(10.35.16.1 accessible except files test.html\)](#)

[Project4 \(10.35.17.1 Not accessible\)](#)

[Project4 \(192.168.100.1 accessible except files test.html\)](#)




### Task 3 - Project 4:

[Project4 \(192.168.50.10 - All is accessible\)](#)

[Project4 \(10.35.16.1 accessible except files test.html\)](#)

[Project4 \(10.35.17.1 Not accessible\)](#)

[Project4 \(192.168.100.1 accessible except files test.html\)](#)



### Task 3 - Project 4:

[Project4 \(192.168.50.10 - All is accessible\)](#)

[Project4 \(10.35.16.1 accessible except files test.html\)](#)

[Project4 \(10.35.17.1 Not accessible\)](#)

[Project4 \(192.168.100.1 accessible except files test.html\)](#)



Name	Last modified	Size	Description
<a href="#">Parent Directory</a>	-	-	-
<a href="#">project4.html</a>	2025-04-17 22:11	0	
<a href="#">some.gif</a>	2025-04-17 22:19	0	

## 4-Authorization

### -On the AlmaLinux machine

Creating the htdocs directory and adding department directories inside

```
[root@server10 www]# mkdir htdocs
[root@server10 www]# ls
cgi-bin  htdocs  html  html_project1
```

```
[root@server10 www]# cd htdocs
[root@server10 htdocs]# mkdir vendors
[root@server10 htdocs]# mkdir accountants
[root@server10 htdocs]# mkdir administrators
[root@server10 htdocs]# mkdir programmers
[root@server10 htdocs]# ls
accountants  administrators  programmers  vendors
```

Adding the proper files for testing to each department directory for testing

```
[root@server10 accountants]# touch accountants.html
[root@server10 accountants]# touch Picture.jpg
[root@server10 accountants]# touch Moving.gif
```

```
[root@server10 administrators]# touch administrators.html
[root@server10 administrators]# touch Picture.jpg
[root@server10 administrators]# touch Moving.gif
```

```
[root@server10 programmers]# touch programmers.html
[root@server10 programmers]# touch Picture.jpg
[root@server10 programmers]# touch Moving.gif
```

```
[root@server10 vendors]# touch vendors.html
[root@server10 vendors]# touch Picture.jpg
[root@server10 vendors]# touch Moving.gif
[root@server10 vendors]# touch file.txt
```



Configuring apache to user aliases for each department

```
[root@server10 ~]# vim /etc/httpd/conf/httpd.conf
```

```
Alias /accountants "/var/www/htdocs/accountants"  
Alias /administrators "/var/www/htdocs/administrators"  
Alias /programmers "/var/www/htdocs/programmers"  
Alias /vendors "var/www/htdocs/vendors"
```

Configuring apache with the proper settings for each department

```
<Directory "/var/www/htdocs">  
    Options Indexes  
    AllowOverride none  
    Require all granted  
</Directory>
```

```
<Directory "/var/www/htdocs/vendors">  
    <RequireAny>  
        Require ip 10.50.1  
        Require ip 10.52.1  
        Require ip 10.53.1  
    </RequireAny>  
    <FilesMatch "\.(gif|jpg)$">  
        Require ip 10.50.1  
        Require ip 10.52.1  
    </FilesMatch>  
</Directory>
```

```
<Directory "/var/www/htdocs/accountants">  
    Require ip 10.51.1  
    Require ip 10.52.1  
    Require ip 10.53.1  
    <FilesMatch "\.(gif|jpg)$">  
        Require ip 10.51.1  
        Require ip 10.52.1  
    </FilesMatch>  
</Directory>
```

```
<Directory "/var/www/htdocs/programmers">  
    Require ip 10.52.1  
    Require ip 10.53.1  
</Directory>
```

```
<Directory "/var/www/htdocs/administrators">  
    Require ip 10.52.1  
    Require ip 10.53.1  
    <FilesMatch "\.(gif|jpg)$">  
        Require ip 10.52.1  
    </FilesMatch>  
</Directory>
```

Testing the links on the website

#### Task 4 - Vendors website:

Accessible to Vendors (10.50.1.0/24)

Not accessible to Accountants (10.51.1.0/24)


Accessible to Administrators (10.52.1.0/24)

Accessible to Programmers (10.53.1.0/24) but not \*.gif and \*.jpg files




## Index of /vendors

Name	Last modified	Size	Description
<a href="#">Parent Directory</a>		-	
<a href="#">Moving.gif</a>	2025-04-18 09:49	0	
<a href="#">Picture.jpg</a>	2025-04-18 09:49	0	
<a href="#">vendors.html</a>	2025-04-18 09:48	0	



## Forbidden

You don't have permission to access [this](#) resource.




## Index of /vendors

Name	Last modified	Size	Description
<a href="#">Parent Directory</a>		-	
<a href="#">Moving.gif</a>	2025-04-18 09:49	0	
<a href="#">Picture.jpg</a>	2025-04-18 09:49	0	
<a href="#">vendors.html</a>	2025-04-18 09:48	0	



## Index of /vendors

<a href="#">Name</a>	<a href="#">Last modified</a>	<a href="#">Size</a>	<a href="#">Description</a>
 <a href="#">Parent Directory</a>		-	
 <a href="#">vendors.html</a>	2025-04-18 09:48	0	


### Task 4 - Accountants website:

Not accessible to Vendors (10.50.1.0/24) but not \*.html files

Accessible to Accountants (10.51.1.0/24)

Accessible to Administrators (10.52.1.0/24)

Accessible to Programmers (10.53.1.0/24) but not \*.gif and \*.jpg files



## Forbidden

You don't have permission to access this resource.



## Index of /accountants

<a href="#">Name</a>	<a href="#">Last modified</a>	<a href="#">Size</a>	<a href="#">Description</a>
 <a href="#">Parent Directory</a>		-	
 <a href="#">Moving.gif</a>	2025-04-18 09:46	0	
 <a href="#">Picture.jpg</a>	2025-04-18 09:46	0	
 <a href="#">accountants.html</a>	2025-04-18 09:45	0	

Index of /accountants

×

+

←

→

↻

🔒 Not Secure

http://10.52.1.1/accountants/

## Index of /accountants

Name	Last modified	Size	Description
 <a href="#">Parent Directory</a>		-	
 <a href="#">Moving.gif</a>	2025-04-18 09:46	0	
 <a href="#">Picture.jpg</a>	2025-04-18 09:46	0	
 <a href="#">accountants.html</a>	2025-04-18 09:45	0	

Index of /accountants

×

+

←



→

↻

🔒 Not Secure

http://10.53.1.1/accountants/

## Index of /accountants

Name	Last modified	Size	Description
 <a href="#">Parent Directory</a>		-	
 <a href="#">accountants.html</a>	2025-04-18 09:45	0	

### Task 4 - Programmers website:

[Not accessible to Vendors \(10.50.1.0/24\)](#)

[Not accessible to Accountants \(10.51.1.0/24\)](#)

[Accessible to Administrators \(10.52.1.0/24\)](#)

[Accessible to Programmers \(10.53.1.0/24\)](#)

403 Forbidden

×

+

←

→


↻

🔒 Not Secure

http://10.50.1.1/programmers/

## Forbidden

You don't have permission to access this resource.



## Forbidden

You don't have permission to access this resource.



## Index of /programmers

Name	Last modified	Size	Description
<a href="#">Parent Directory</a>		-	
<a href="#">Moving.gif</a>	2025-04-18 09:48	0	
<a href="#">Picture.jpg</a>	2025-04-18 09:48	0	
<a href="#">programmers.html</a>	2025-04-18 09:48	0	



## Index of /programmers

Name	Last modified	Size	Description
<a href="#">Parent Directory</a>		-	
<a href="#">Moving.gif</a>	2025-04-18 09:48	0	
<a href="#">Picture.jpg</a>	2025-04-18 09:48	0	
<a href="#">programmers.html</a>	2025-04-18 09:48	0	

### **Task 4 - Administrators website:**


Not accessible to Vendors (10.50.1.0/24) but not \*.html files

Not accessible to Accountants (10.51.1.0/24)

Accessible to Administrators (10.52.1.0/24)


Accessible to Programmers (10.53.1.0/24) but not \*.gif and \*.jpg files





## Forbidden

You don't have permission to access this resource.




## Forbidden

You don't have permission to access this resource.



## Index of /administrators

	<a href="#">Name</a>	<a href="#">Last modified</a>	<a href="#">Size</a>	<a href="#">Description</a>
	<a href="#">Parent Directory</a>		-	
	<a href="#">Moving.gif</a>	2025-04-18 09:47	0	
	<a href="#">Picture.jpg</a>	2025-04-18 09:47	0	
	<a href="#">administrators.html</a>	2025-04-18 09:47	0	



## Index of /administrators

	<a href="#">Name</a>	<a href="#">Last modified</a>	<a href="#">Size</a>	<a href="#">Description</a>
	<a href="#">Parent Directory</a>		-	
	<a href="#">administrators.html</a>	2025-04-18 09:47	0	

## 5-Creating a Compressed File with the Configs

-On the AlmaLinux machine



Use the tar command to name the file and provide all directories to go inside the file

```
[root@server10 ~]# tar -czf jacob_project1.tar /etc/httpd/conf/httpd.conf /var/www/html_project1 /var/www/htdocs
tar: Removing leading '/' from member names
tar: Removing leading '/' from hard link targets
[root@server10 ~]# ll
total 8
-rw-----, 1 root root 1287 Mar 24 14:54 anaconda-ks.cfg
-rw-r--r--, 1 root root 3817 Apr 18 13:51 jacob_project1.tar
```

Copy the compressed file over to a connected share folder

```
[root@server10 ~]# ls /mnt/hgfs
AlmaLinux-Temp-Share
[root@server10 ~]# ls
anaconda-ks.cfg jacob_project1.tar
[root@server10 ~]# cp jacob_project1.tar /mnt/hgfs/AlmaLinux-Temp-Share
```

This will allow the host machine to gain access to this newly compressed file

