

Q Quadratic: PARI guide

(version 0.2.5)

A PARI/GP package for integral binary quadratic forms and quaternion algebras over \mathbb{Q} , with an emphasis on indefinite quadratic forms and indefinite quaternion algebras.

James Rickards
Department of Mathematics and Statistics,
McGill University, Montreal
Personal homepage
Github repository

© James Rickards 2020

Contents

1	Introduction	2
1.1	Overview of the main available methods	2
1.2	Upcoming methods	3
1.3	How to use the library	3
1.4	Validation of methods	3
1.5	Programming style	3
1.6	How to use this manual	4
2	qq_base	4
2.1	Euclidean geometry	4
2.2	Infinity	5
2.3	Integer vectors	5
2.4	Linear equations and matrices	6
2.5	Lists	7
2.6	Random	9
2.7	Square roots modulo n	10
2.8	Time	10
3	qq_bqf	11
3.1	Discriminant methods	11
3.2	Basic methods for binary quadratic forms	13
3.3	Basic methods, but specialized	17
3.4	Basic methods for indefinite quadratic forms	22
3.5	Class group and composition of forms	27
3.6	Representation of integers by forms - description tables	29
3.7	Representation of integers by forms - methods	32
3.8	Checking GP inputs	38
4	qq_bqf_int	38
4.1	Intersection Data	38
4.2	Intersection number computation	40
5	qq_quat	43
5.1	Basic operations on elements in quaternion algebras	43
6	qq_visual	47
6.1	Histograms	47
7	Method declarations	49
7.1	qq_base	49
7.1.1	Complex geometry	49
7.1.2	Infinity	49
7.1.3	Integer vectors	50
7.1.4	Linear equations and matrices	50

7.1.5	Lists	50
7.1.6	Random	50
7.1.7	Solving equations modulo n	50
7.1.8	Time	50
7.2	qq-bqf	51
7.2.1	Discriminant methods	51
7.2.2	Basic methods for binary quadratic forms	51
7.2.3	Basic methods, but specialized	52
7.2.4	Basic methods for indefinite quadratic forms	52
7.2.5	Class group and composition of forms	53
7.2.6	Representation of integers by forms	53
7.2.7	Checking GP inputs	54
7.3	qq-bqf_int	54
7.3.1	Intersection Data	54
7.3.2	Intersection number computation	55
7.4	qq-quat	55
7.4.1	Basic operations on elements in quaternion algebras	55
7.5	qq-visual	56
7.5.1	Histograms	56

References	56
-------------------	-----------

1 Introduction

The roots for this library came from my thesis project, which involved studying intersection numbers of geodesics on modular and Shimura curves. To be able to do explicit computations, I wrote many GP scripts to deal with indefinite binary quadratic forms, and indefinite quaternion algebras. This library is a revised version of those scripts, rewritten in PARI ([The20]) for optimal efficiency.

While there already exist some PARI/GP methods to compute with quadratic forms and quaternion algebras (either installed or available online), I believe that this is the most comprehensive set of methods yet.

The package has been designed to be easily usable with GP, with more specific and powerful methods available to PARI users. More specifically, the GP functions are all given wrappers so as to not break, and the PARI methods often allow passing in of precomputed data like the discriminant, the reduced orbit of an indefinite quadratic form, etc. If you only intend on using this library in GP, please consult the GP manual instead.

1.1 Overview of the main available methods

For integral binary quadratic forms, there are methods available to:

- Generate lists of (fundamental, coprime to a given integer n) discriminants;
- Compute the basic properties, e.g. the automorph, discriminant, reduction, and equivalence of forms;
- For indefinite forms, compute all reduced forms, the Conway river, left and right neighbours of river/reduced forms;
- Compute the narrow class group and a set of generators, as well as a reduced form for each equivalence class in the group;
- Output all integral solutions (x, y) to $Ax^2 + Bxy + Cy^2 + Dx + Ey + F = n$ for any integers A, B, C, D, E, F, n ;
- Solve the simultaneous equations $Ax^2 + By^2 + Cz^2 + Dxy + Exz + Fyz = n_1$ and $Ux + Vy + Wz = n_2$ for any integers $A, B, C, D, E, F, U, V, W, n_1, n_2$.
- Compute the intersection number of two primitive indefinite binary quadratic form.

For quaternion algebras over \mathbb{Q} , there are methods available to:

- Initialize the algebra given the ramification, and initialize maximal/Eichler orders (with specific care given to algebras ramified at ≤ 2 finite places);
- Compute all optimal embeddings of a quadratic order into a quaternion algebra, and arrange them with respect to the class group action and their orientation;
- Compute the intersection number of pairs of optimal embeddings.

1.2 Upcoming methods

While the quadratic form section is mostly finished, there are more methods coming for quaternion algebras. Planned methods include:

- Compute the fundamental domain of unit groups of Eichler orders in indefinite algebras (Shimura curves);
- Solve the principal ideal problem in indefinite quaternion algebras;
- Improve the computation of optimal embeddings and intersection numbers.

1.3 How to use the library

As a first word of warning, this library is only guaranteed to work on Linux. The essential files (.so) were created with GP2C, and they are not usable with Windows (I don't think it works on Mac, but I don't know). However, the workaround for Windows is to install the Linux Subsystem for Windows, and install PARI/GP there (in fact, this is my current setup, and it works well).

If you plan on modifying the library, then you need all of the .h and .c files; I will assume that you know what to do from there.

Otherwise, if you plan on only using and not modifying the library, then you need the files **qquadraticdecl.h**, **libqqquadratic.so**, and **qqquadratic.gp**.

The file **pari_compile** was used to compile the .c files into .o files, and then into the shared .so file, with input coming from the file **qqquadratic_make**. See the source code for "pari_compile.c" to get a description on how to use it.

1.4 Validation of methods

Unless otherwise noted, non-static methods are stack clean (the main exceptions come from lists). I have made a good effort to ensure that this claim is true, and to validate that my methods do exactly what is claimed.

To test this, I have written a series of validation methods. For each function, I generate some "random data," enter it in the function, and test that the result is stack clean and that basic properties are obeyed (and then repeat this a few thousand times). For example, I can compute the narrow class group for a given D , check that the generators are all of the right order (by powering them and testing for equivalence with the identity), generating the whole group by composing the generators together, and checking that the group elements are all non-equivalent. Of course this isn't "proof" that I have no errors lurking in obscure parts of the algorithm, but it does provide good support.

If you do happen to find a bug, then please let me know! At the moment I have not posted my validation methods, but if for some reason you would like them, then I can send you the files directly.

1.5 Programming style

I have gone for optimal efficiency by using the most specific methods (e.g. `addii`, passing in precomputed data, etc.) whenever possible. What this means is that it is very easy to break the library if you feed in bad inputs! However, when working with GP we really do not want this to happen, so every method available to GP has a wrapper for protection against segmentation breaks (if it is required). This wrapper is always indicated by adding the suffix `_-typecheck` to the method, and its function is

basically to check that the inputs are kosher and feed them on to the appropriate method. There are some methods that do not require this wrapper, and they do not come with it.

If there is a piece of “standard data” that is very useful in a method, there is typically a method that does not require passing in of this data, and another that does. This allows the user to maximize efficiency by not recomputing this standard data repeatedly. For example, if you are doing a lot of computations with a fixed quadratic form q , then you can store the discriminant of q and pass it along with q when this is available. If you are more concerned with getting it correct and not breaking your programs, then you can just use the “_typecheck” methods, as they require no precomputed data and are hard to break. Once you have a working program, you can revisit this to optimize for efficiency.

1.6 How to use this manual

Sections 2-6 contain detailed descriptions of every function: the input, output, and what the function does. The sections are labeled by source files, and are divided into subsections of “similar” methods. If you are seeking a function for a certain task, have a look through here.

Section 7 contains simply the method declarations, and is useful as a quick reference. Clicking the name of a method in this section will take you to its full description in Sections 2-6, and clicking on the name there will take you back to Section 7.

Methods accessible to GP are given a green background, static methods are given a blue background, and precise non-GP accessible and non-static methods are in yellow. The methods are generally alphabetized, with static methods appearing at the end of sections. Any non-static method that is not stack clean is given a red background, and will be appropriately noted in the description. Start by looking at the green methods, and when you want to use one check the surrounding yellow methods for the precise version you want. Unless you are modifying these methods directly, you can ignore the blue methods.

2 qq_base

This is a collection of “basic” functions and structures, which are useful in various places. The main interesting method here is “sqmod”, which allows you to compute square roots modulo any integer n , and not just primes (which is already built into PARI/GP).

2.1 Euclidean geometry

These methods will likely be moved the geometry package, when I write that (the geometry package will support finding the fundamental domain for a discrete subgroup of $\mathrm{PSL}(2, \mathbb{R})$).

Name:	GEN crossratio
Input:	GEN a, GEN b, GEN c, GEN d
Input format:	a, b, c, d complex numbers or infinity, with at most one being infinity
Output format:	Complex number or $\pm\infty$
Description:	Returns the crossratio $[a,b;c,d]$.

Name:	GEN mat_eval
Input:	GEN M, GEN x
Input format:	M a 2x2 matrix and x a complex number or infinity
Output format:	Complex number or $\pm\infty$
Description:	Returns M acting on x via Mobius transformation.

Name:	GEN mat_eval_typecheck
Input:	GEN M, GEN x
Input format:	M a 2x2 matrix and x a complex number or infinity
Output format:	Complex number or $\pm\infty$
Description:	Checks that M is a 2x2 matrix, and returns mat_eval(M, x).

2.2 Infinity

In dealing with the completed complex upper half plane, the projective line over \mathbb{Q} , etc., we would like to work with ∞ , but currently PARI does not support adding/dividing infinities by finite numbers. The functions here are wrappers around addition and division to allow for this.

Name:	GEN addoo
Input:	GEN a, GEN b
Input format:	a, b complex numbers or infinity
Output format:	Complex number or $\pm\infty$
Description:	Returns a+b, where the output is a if a is infinite, b if b is infinite, and a+b otherwise.

Name:	GEN divoo
Input:	GEN a, GEN b
Input format:	a, b complex numbers or infinity
Output format:	Complex number or $\pm\infty$
Description:	Returns a/b, where a/0 will return $\pm\infty$ (depending on the sign of a), and $\pm\infty/b$ will return $\pm\infty$ (depending on the sign of b). Note that both 0/0 and ∞/∞ return ∞ .

2.3 Integer vectors

The following methods are typically available for ZC, but not for ZV.

Name:	GEN ZV_copy
Input:	GEN v
Input format:	v a vector with integer entries
Output format:	Vector
Description:	Returns a copy of the integral vector v.

Name:	int ZV_equal
Input:	GEN v1, GEN v2
Input format:	v1, v2 vectors with integer entries
Output format:	0 or 1
Description:	Returns 1 if v1=v2 and 0 else.

Name:	GEN ZV_Z_divexact
Input:	GEN v, GEN y
Input format:	v an integral vector, y a non-zero integer which divides all components of v
Output format:	Vector
Description:	Returns v/y.

Name:	GEN ZV_Z_mul
Input:	GEN v, GEN x
Input format:	v an integral vector, x an integer
Output format:	Vector
Description:	Returns vx.

2.4 Linear equations and matrices

`lin_intsolve` is essentially just `gbzout`, but it outputs to a format that is useful to me.

Name:	GEN lin_intsolve
Input:	GEN A, GEN B, GEN n
Input format:	Integers A, B, C
Output format:	<code>gen_0</code> or $[[m_x, m_y], [x_0, y_0]]$.
Description:	Solves $Ax + By = n$ using <code>gbzout</code> , where the general solution is $x = x_0 + m_x t$ and $y = y_0 + m_y t$ for $t \in \mathbb{Z}$.

Name:	GEN lin_intsolve_typecheck
Input:	GEN A, GEN B, GEN n
Input format:	Integers A, B, C
Output format:	<code>gen_0</code> or $[[m_x, m_y], [x_0, y_0]]$.
Description:	Checks that A, B, n are integral, and returns <code>lin_intsolve(A, B, n)</code> .

Name:	GEN mat3_complete
Input:	GEN A, GEN B, GEN C
Input format:	Integers A, B, C with $\gcd(A, B, C) = 1$
Output format:	Matrix
Description:	Returns a 3x3 integer matrix with determinant 1 and first row A, B, C.

Name:	<code>GEN mat3_complete_typecheck</code>
Input:	<code>GEN A, GEN B, GEN C</code>
Input format:	Integers A, B, C with $\gcd(A, B, C) = 1$
Output format:	Matrix
Description:	Checks that A, B, C are relatively prime integers, and returns <code>mat3_complete(A, B, C)</code> .

2.5 Lists

There are three dynamically linked lists implemented: `clist`, `glist`, `llist`. A circular list (`clist`) C stores a `GEN` (accessible by `C->data`), a pointer to the next element (`C->next`), and the previous element (`C->prev`). A generic list is the same, except it does not store a pointer to the previous element. A long list is the same as a generic list, except it stores the data type `long` instead of `GEN` (and hence does not enter into the PARI stack).

Lists should be initialized by calling `(c/g/l)list *L=NULL;`, and use the following methods to work with them. If you do not call the `togvec` or `tovecsmall` methods, you should free the list using the appropriate `(c/g/l)list_free` methods.

Name:	<code>void clist_free</code>
Input:	<code>clist *l, long length</code>
Input format:	Pointer to a <code>clist</code> l , length of the list <code>length</code>
Output format:	-
Description:	Frees the <code>clist</code> (each data point had been initialized with <code>pari_malloc</code>). If l is shorter than <code>length</code> , an error will occur, and if it is longer than the remaining part of the list has not been freed.

Name:	<code>void clist_putbefore</code>
Input:	<code>clist **head_ref, GEN new_data</code>
Input format:	-
Output format:	-
Description:	Adds an element containing <code>new_data</code> before the element pointed to by <code>head_ref</code> , and updates the list start position.

Name:	<code>void clist_putafter</code>
Input:	<code>clist **head_ref, GEN new_data</code>
Input format:	-
Output format:	-
Description:	Adds an element containing <code>new_data</code> after the element pointed to by <code>head_ref</code> , and updates the list start position.

Name:	GEN clist_togvec
Input:	clist *l, long length, int dir
Input format:	length the length of l, and dir=-1 or 1.
Output format:	Vector
Description:	Returns a vector consisting of the list from l and onward of length length, and frees the list. If dir=1 we go through the list via l->next, and if dir=-1 we go through via l->prev.

Name:	void glist_free
Input:	glist *l
Input format:	Pointer to a glist l
Output format:	-
Description:	Frees the glist (each data point had been initialized with pari_malloc).

Name:	GEN glist_pop
Input:	glist **head_ref
Input format:	-
Output format:	-
Description:	Removes the last element of the list, frees this list element, and returns the data entry. This does NOT copy the return element, so it is NOT stack safe.

Name:	void glist_putstart
Input:	glist **head_ref, GEN new_data
Input format:	-
Output format:	-
Description:	Adds an element containing new_data before the element pointed to by head_ref, and updates the list start position.

Name:	GEN glist_togvec
Input:	glist *l, long length, int dir
Input format:	length the length of l, and dir=-1 or 1.
Output format:	Vector
Description:	Returns a vector consisting of the list from l and onward of length length, and frees the list. If dir=1 we fill in the return vector from index 1 to length, and if dir=-1 we go in the opposite direction.

Name:	void llist_free
Input:	llist *l
Input format:	Pointer to a clist l
Output format:	-
Description:	Frees the llist (each data point had been initialized with pari_malloc). If l is shorter than length, an error will occur, and if it is longer than the remaining part of the list has not been freed.

Name:	<code>long llist_pop</code>
Input:	<code>llist **head_ref</code>
Input format:	-
Output format:	-
Description:	Removes the last element of the list, frees this list element, and returns the data entry.

Name:	<code>void llist_putstart</code>
Input:	<code>llist **head_ref, GEN new_data</code>
Input format:	-
Output format:	-
Description:	Adds an element containing <code>new_data</code> before the element pointed to by <code>head_ref</code> , and updates the list start position.

Name:	<code>GEN llist_togvec</code>
Input:	<code>llist *l, long length, int dir</code>
Input format:	<code>length</code> the length of <code>l</code> , and <code>dir</code> == -1 or 1.
Output format:	Vector
Description:	Returns a vector consisting of the list from <code>l</code> and onward of length <code>length</code> , and frees the list. If <code>dir</code> =1 we fill in the return vector from index 1 to <code>length</code> , and if <code>dir</code> =-1 we go in the opposite direction.

Name:	<code>GEN llist_tovecsmall</code>
Input:	<code>llist *l, long length, int dir</code>
Input format:	<code>length</code> the length of <code>l</code> , and <code>dir</code> == -1 or 1.
Output format:	Vecsmall
Description:	Returns a Vecsmall consisting of the list from <code>l</code> and onward of length <code>length</code> , and frees the list. If <code>dir</code> =1 we fill in the return vector from index 1 to <code>length</code> , and if <code>dir</code> =-1 we go in the opposite direction.

2.6 Random

Methods used for producing random things.

Name:	<code>GEN rand_elt</code>
Input:	<code>GEN v</code>
Input format:	<code>v</code> a vector
Output format:	
Description:	Returns a random component of <code>v</code> .

Name:	<code>long rand_l</code>
Input:	<code>long len</code>
Input format:	<code>len</code> a positive integer
Output format:	<code>long</code>
Description:	Returns a random long from 1 to <code>len</code> .

2.7 Square roots modulo n

In PARI/GP you can take square roots modulo p^e very easily, but there is not support for a general modulus n , and if the number you are square rooting is not a square, an error will occur. `sqmod` is designed to solve this problem, and uses the built in methods of `Zp_sqrt` and `chinese` to build the general solution.

Name:	<code>GEN sqmod</code>
Input:	<code>GEN x</code> , <code>GEN n</code> , <code>GEN fact</code>
Input format:	<code>x</code> a rational number with denominator coprime to <code>n</code> , a positive integer, and <code>fact</code> the factorization of <code>n</code> , which can be passed in as <code>gen_0</code> if not precomputed.
Output format:	<code>gen_0</code> or <code>v=[S, m]</code> .
Description:	Returns the full solution set to $y^2 \equiv x \pmod{n}$, where the solution set is described as $y \equiv s_i \pmod{m}$ for any $s_i \in S$.

Name:	<code>GEN sqmod_typecheck</code>
Input:	<code>GEN x</code> , <code>GEN n</code>
Input format:	<code>x</code> a rational number, <code>n</code> a non-zero integer.
Output format:	<code>gen_0</code> or <code>v=[S, m]</code> .
Description:	Checks that <code>x</code> is rational and <code>n</code> is a non-zero integer, replaces it by <code>-n</code> if negative, and returns <code>sqmod(x, n, gen_0)</code> .

Name:	<code>GEN sqmod_ppower</code>
Input:	<code>GEN x</code> , <code>GEN p</code> , <code>long n</code> , <code>GEN p2n</code> , <code>int iscoprime</code>
Input format:	<code>x</code> integer, <code>p</code> prime, <code>n</code> non-negative integer, <code>p2n</code> = p^n , <code>iscoprime</code> =0, 1
Output format:	<code>gen_0</code> or <code>v=[S, m]</code> .
Description:	Returns the full solution set to $y^2 \equiv x \pmod{p^n}$, where the solution set is described as $y \equiv s_i \pmod{m}$ for any $s_i \in S$ (m is necessarily a power of p dividing p^n). If <code>iscoprime</code> =1, the <code>x</code> , <code>p</code> are guaranteed to be coprime; otherwise this assumption is not made.

2.8 Time

Methods for returning and printing time. Uses the C library `time.h`, as this is significantly less work than `getwalltime()`.

Name:	<code>char* returntime</code>
Input:	-
Input format:	-
Output format:	-
Description:	Returns the current time as a string.

Name:	<code>void printtime</code>
Input:	-
Input format:	-
Output format:	-
Description:	Prints the current time.

3 qq_bqf

These methods primarily deal with primitive integral homogeneous positive definite/indefinite binary quadratic forms. Such a form is represented by the vector $[A, B, C]$, which represents $AX^2 + BXY + CY^2$. Some of the basic methods support non-primitive, negative definite, or square discriminant forms (like `bqf_disc` or `bqf_trans`), but more complex ones (like `bqf_isequiv`) may not.

On the other hand, the method `bqf_reps` allows non-primitive forms, as well as negative definite and square discriminant forms. Going further, `bqf_bigreps` allows non-homogeneous binary quadratic forms (but the integral requirement is never dropped).

In this and subsequent sections, a **BQF** is an integral binary quadratic form, an **IBQF** is an indefinite BQF, a **DBQF** is a positive definite BQF, a **PIBQF/PDBQF** is a primitive indefinite/positive definite BQF respectively, and a **PBQF** is either a PIBQF or a PDBQF.

In general, a method taking in a BQF will start with `bqf_`. This is further specialized to indefinite/positive definite/square discriminant/zero discriminant forms by adding the prefixes `i/d/s/z` respectively.

3.1 Discriminant methods

These methods deal with discriminant operations that do not involve quadratic forms.

Name:	<code>GEN disclist</code>
Input:	<code>GEN D1, GEN D2, int fund, GEN cop</code>
Input format:	Integers D1, D2, fund=0, 1, cop an integer
Output format:	Vector
Description:	Returns the set of discriminants (non-square integers equivalent to 0, 1 modulo 4) between D1 and D2 inclusive. If fund=1, only returns fundamental discriminants, and if cop≠0, only returns discriminants coprime to cop.

Name:	GEN <code>discprimeindex</code>
Input:	GEN D, GEN <code>facts</code>
Input format:	Discriminant D, <code>facts</code> =0 or the factorization of D (the output of <code>Z_factor</code>)
Output format:	Vector
Description:	Returns the set of primes p for which D/p^2 is a discriminant.

Name:	GEN <code>discprimeindex_typecheck</code>
Input:	GEN D
Input format:	Discriminant D
Output format:	Vector
Description:	Checks that D is a discriminant, and returns <code>discprimeindex(D, gen_0)</code> .

Name:	GEN <code>fdisc</code>
Input:	GEN D
Input format:	Discriminant D
Output format:	Integer
Description:	Returns the fundamental discriminant associated to D.

Name:	GEN <code>fdisc_typecheck</code>
Input:	GEN D
Input format:	Discriminant D
Output format:	Integer
Description:	Checks that D is a discriminant, and returns <code>fdisc(D)</code> if so. Returns <code>gen_0</code> if not a discriminant.

Name:	int <code>isdisc</code>
Input:	GEN D
Input format:	-
Output format:	0 or 1
Description:	Returns 1 if D is a discriminant and 0 else.

Name:	GEN <code>pell</code>
Input:	GEN D
Input format:	Positive discriminant D
Output format:	[T, U]
Description:	Returns the smallest solution in the positive integers to Pell's equation $T^2 - DU^2 = 4$.

Name:	GEN <code>pell_typecheck</code>
Input:	GEN D
Input format:	Positive discriminant D
Output format:	[T, U]
Description:	Checks that D is a positive discriminant, and returns <code>pell(D)</code> .

Name:	GEN posreg
Input:	GEN D, long prec
Input format:	Positive discriminant D, precision prec
Output format:	Real number
Description:	Returns the positive regulator of \mathcal{O}_D , i.e. the logarithm of the fundamental unit of norm 1 in the unique order of discriminant D .

Name:	GEN posreg_typecheck
Input:	GEN D, long prec
Input format:	Positive discriminant D, precision prec
Output format:	Real number
Description:	Checks that D is a positive discriminant, and returns posreg(D, prec).

Name:	GEN quadroot
Input:	GEN D
Input format:	Non-square integer D
Output format:	t_QUAD
Description:	Outputs the t_QUAD w for which $w^2 = D$.

Name:	GEN quadroot_typecheck
Input:	GEN D
Input format:	Discriminant D
Output format:	t_QUAD
Description:	Checks that D is a discriminant and returns quadroot(D).

3.2 Basic methods for binary quadratic forms

Recall that the BQF $AX^2 + BXY + CY^2$ is represented as the vector $[A, B, C]$.

Name:	GEN bqf_automorph_typecheck
Input:	GEN q
Input format:	PBQF q
Output format:	Matrix
Description:	Returns the invariant automorph M of q, i.e. the $\text{PSL}(2, \mathbb{Z})$ matrix with positive trace that generates the stabilizer of q (a cyclic group of order 1, 2, 3, or ∞).

Name:	int bqf_compare
Input:	void *data, GEN q1, GEN q2
Input format:	*data=NULL, q1 and q2 BQFs
Output format:	-1, 0, 1
Description:	Lexicographically compares q1 and q2, returning -1 if $q_1 < q_2$, 0 if $q_1 = q_2$, and 1 if $q_1 > q_2$. This method is used to sort and search a set of BQFs more efficiently (with gen_sort and gen_search).

Name:	<code>int bqf_compare_tmat</code>
Input:	<code>void *data, GEN d1, GEN d2</code>
Input format:	<code>*data=NULL, di=[qi, mi]</code> with <code>qi</code> a BQF for <code>i=1,2</code>
Output format:	<code>-1, 0, 1</code>
Description:	Lexicographically compares <code>q1</code> and <code>q2</code> , returning <code>-1</code> if $q_1 < q_2$, <code>0</code> if $q_1 = q_2$, and <code>1</code> if $q_1 > q_2$. This method is used to sort and search a set of BQFs where we are also keeping track of an extra data point <code>mi</code> , often a transition matrix (whose value has no effect on the output of this method).

Name:	<code>GEN bqf_disc</code>
Input:	<code>GEN q</code>
Input format:	BQF <code>q</code>
Output format:	Integer
Description:	Returns the discriminant of <code>q</code> , i.e. $B^2 - 4AC$ where <code>q=[A, B, C]</code> .

Name:	<code>GEN bqf_disc_typecheck</code>
Input:	<code>GEN q</code>
Input format:	BQF <code>q</code>
Output format:	Integer
Description:	Checks that <code>q</code> is a BQF, and returns <code>bqf_disc(q)</code> .

Name:	<code>GEN bqf_isequiv</code>
Input:	<code>GEN q1, GEN q2, GEN rootD, int Dsign, int tmat</code>
Input format:	PBQFs <code>q1, q2</code> of the same discriminant D , <code>rootD</code> the real square root of D if $D > 0$ (and anything if $D < 0$), <code>Dsign</code> the sign of D , <code>tmat=0, 1</code>
Output format:	<code>gen_0, gen_1</code> , or a matrix
Description:	Determines if <code>q1</code> and <code>q2</code> are equivalent or not. If <code>tmat=0</code> , returns <code>gen_0</code> or <code>gen_1</code> , and if <code>tmat=1</code> , returns <code>gen_0</code> if not equivalent and a $SL(2, \mathbb{Z})$ transition matrix taking <code>q1</code> to <code>q2</code> if they are equivalent.

Name:	<code>GEN bqf_isequiv_set</code>
Input:	<code>GEN q, GEN S, GEN rootD, int Dsign, int tmat</code>
Input format:	PBQFs <code>q</code> and set of PBQFs <code>S</code> , all of the same discriminant D , <code>rootD</code> the real square root of D if $D > 0$ (and anything if $D < 0$), <code>Dsign</code> the sign of D , <code>tmat=0, 1</code>
Output format:	Integer or <code>[i, M]</code>
Description:	Determines if <code>q</code> and an element of <code>S</code> are equivalent or not. If <code>tmat=0</code> , returns <code>gen_0</code> if not and an index <code>i</code> such that <code>q</code> is equivalent to <code>S[i]</code> if they are equivalent. If <code>tmat=1</code> , returns <code>gen_0</code> if not equivalent and <code>[i, M]</code> if they are, where $M \circ q = S[i]$.

Name:	GEN bcf_isequiv_typecheck
Input:	GEN q1, GEN q2, int tmat, long prec
Input format:	q1 a PBQF, q2 a PBQF or a set of PBQFs, tmat=0, 1, prec the precision
Output format:	Integer or matrix or [i, M]
Description:	Checks if q1 is a PBQF, q2 is a PBQF or a set of PBQFs, and returns bcf_isequiv or bcf_isequiv_set on q1 and q2 as appropriate. Elements of q2 need not have the same discriminant as each other or q1.

Name:	int bcf_isreduced
Input:	GEN q, int Dsign
Input format:	q a PBQF of discriminant D , Dsign the sign of D
Output format:	0, 1
Description:	Returns 1 if q is reduced, and 0 if q is not reduced. We use the standard reduced definition when $D < 0$, and the conditions $AC < 0$ and $B > A + C $ when $D > 0$.

Name:	int bcf_isreduced_typecheck
Input:	GEN q
Input format:	q a PBQF
Output format:	0, 1
Description:	Checks that q is a PBQF and returns 1 if reduced, and 0 if not reduced.

Name:	GEN bcf_random
Input:	GEN maxc, int type, int primitive
Input format:	maxc a positive integer, type, primitive=0, 1
Output format:	BQF
Description:	Returns a random BQF of non-square discriminant with coefficient size at most maxc. If type=-1 it will be positive definite, type=1 indefinite, and type=0 either type. If primitive=1 the form will be primitive, otherwise it need not be.

Name:	GEN bcf_random_D
Input:	GEN maxc, GEN D
Input format:	maxc a positive integer, D a discriminant
Output format:	BQF
Description:	Checks that maxc is a positive integer and D is a discriminant, and returns a random primitive BQF of discriminant D (positive definite if $D < 0$).

Name:	GEN bqf_red
Input:	GEN q, GEN rootD, int Dsign, int tmat
Input format:	q a PBQF of discriminant D , rootD the square root of D if $D > 0$ (and anything if $D < 0$), Dsign the sign of D , tmat=0,1
Output format:	BQF or $[q', M]$
Description:	Outputs the reduction of q. If tmat=0 this is a BQF, otherwise this is $[q', M]$ where the reduction is q' and the transition matrix is M.

Name:	GEN bqf_red_typecheck
Input:	GEN q, int tmat, long prec
Input format:	q a PBQF, tmat=0,1, prec the precision
Output format:	BQF or $[q', M]$
Description:	Checks that q is a PBQF, and returns bqf_red(q,...).

Name:	GEN bqf_roots
Input:	GEN q, GEN D, GEN w
Input format:	BQF q of discriminant D , with $w^2 = D$ where w is a t_QUAD if D is not a square
Output format:	$[r1, r2]$
Description:	Returns the roots of $q(x,1)=0$, with the first root coming first. If D is not a square, these are of type t_QUAD, and otherwise they will be rational or infinite. If $D=0$, the roots are equal.

Name:	GEN bqf_roots_typecheck
Input:	GEN q
Input format:	BQF q
Output format:	$[r1, r2]$
Description:	Checks that q is a BQF, and returns bqf_roots(q,...).

Name:	GEN bqf_trans
Input:	GEN q, GEN M
Input format:	BQF q, $M \in \text{SL}(2, \mathbb{Z})$
Output format:	BQF
Description:	Returns $M \circ q$.

Name:	GEN bqf_trans_typecheck
Input:	GEN q, GEN M
Input format:	BQF q, $M \in \text{SL}(2, \mathbb{Z})$
Output format:	BQF
Description:	Checks that q is q BQF and $M \in \text{SL}(2, \mathbb{Z})$, and returns bqf_trans(q, M).

Name:	GEN bqf_transL
Input:	GEN q, GEN n
Input format:	BQF q, integer n
Output format:	BQF
Description:	Returns $\begin{pmatrix} 1 & n \\ 0 & 1 \end{pmatrix} \circ q$.

Name:	GEN bqf_transR
Input:	GEN q, GEN n
Input format:	BQF q, integer n
Output format:	BQF
Description:	Returns $\begin{pmatrix} 1 & 0 \\ n & 1 \end{pmatrix} \circ q$.

Name:	GEN bqf_transS
Input:	GEN q
Input format:	BQF q
Output format:	BQF
Description:	Returns $\begin{pmatrix} 0 & 1 \\ -1 & 0 \end{pmatrix} \circ q$.

Name:	GEN bqf_trans_coprime
Input:	GEN q, GEN n
Input format:	BQF q, integer n coprime to gcd(q)
Output format:	BQF
Description:	Returns a BQF equivalent to q whose first coefficient is coprime to n.

Name:	GEN bqf_trans_coprime_typecheck
Input:	GEN q, GEN n
Input format:	BQF q, non-zero integer n
Output format:	BQF
Description:	Checks that q is a BQF and n is coprime to gcd(q), and returns bqf_trans_coprime(q, n).

Name:	GEN ideal_tobqf
Input:	GEN numf, GEN ideal
Input format:	numf a quadratic number field, ideal an ideal in numf
Output format:	BQF
Description:	Converts the ideal to a BQF and returns it.

3.3 Basic methods, but specialized

These are the above basic methods, but specialized to the positive definite/indefinite cases.

Name:	GEN dbqf_automorph
Input:	GEN q, GEN D
Input format:	PDBQF q of discriminant D
Output format:	Matrix
Description:	Returns the invariant automorph M of q in $\text{PSL}(2, \mathbb{Z})$, which is trivial if $D < -4$, has order 2 if $D = -4$, and order 3 if $D = -3$.

Name:	GEN dbqf_isequiv
Input:	GEN q1, GEN q2
Input format:	DBQFs q1, q2 of the same discriminant
Output format:	gen_0, gen_1
Description:	Returns 1 if q1 is equivalent to q2 and 0 if not.

Name:	long dbqf_isequiv_set
Input:	GEN q, GEN S
Input format:	DBQF q and a set of DBQFs S, with all forms in S and q having the same discriminant
Output format:	Integer
Description:	Returns gen_0 if q is not similar to any form in S, and an index i such that q is similar to S[i] otherwise.

Name:	GEN dbqf_isequiv_set_tmat
Input:	GEN q, GEN S
Input format:	DBQF q and a set of DBQFs S, with all forms in S and q having the same discriminant
Output format:	gen_0 or [i, M]
Description:	Returns gen_0 if q is not similar to any form in S, and otherwise returns [o, M], where q is similar to S[i] with transition matrix M.

Name:	GEN dbqf_isequiv_tmat
Input:	GEN q1, GEN q2
Input format:	DBQFs q1, q2 of the same discriminant
Output format:	0, matrix
Description:	Returns 0 if q1 is not equivalent to q2 and a possible transition matrix if it is.

Name:	GEN dbqf_red
Input:	GEN q
Input format:	q a DBQF
Output format:	DBQF
Description:	Returns the reduction of q.

Name:	GEN dbqf_red_tmat
Input:	GEN q
Input format:	q a DBQF
Output format:	[q', M]
Description:	Returns [q', M], where the reduction of q is q' and the transition matrix is M.

Name:	GEN ibqf_automorph_D
Input:	GEN q, GEN D
Input format:	q a PIBQF of discriminant D
Output format:	Matrix
Description:	Returns the invariant automorph of q, i.e. the generator with positive trace (and infinite order) of the stabilizer of q in $\text{PSL}(2, \mathbb{Z})$. This method calls <code>pell(D)</code> , so if this is already computed, use <code>ibqf_automorph_pell</code> instead.

Name:	GEN ibqf_automorph_pell
Input:	GEN q, GEN qpell
Input format:	q a PIBQF of discriminant D, where qpell is the output of <code>pell(D)</code>
Output format:	Matrix
Description:	Returns the invariant automorph of q. If you don't care about the output of <code>pell(D)</code> , then use <code>ibqf_automorph_D</code> instead.

Name:	GEN ibqf_isequiv
Input:	GEN q1, GEN q2, GEN rootD
Input format:	PIBQFs q1, q2 of the same discriminant D, rootD the real square root of D
Output format:	gen_0, gen_1
Description:	Determines if q1 and q2 are equivalent or not, and returns the answer.

Name:	long ibqf_isequiv_set_byq
Input:	GEN q, GEN S, GEN rootD
Input format:	PIBQFs q and set of PIBQFs S, all of the same discriminant D, rootD the real square root of D
Output format:	Integer
Description:	Determines if q and an element of S are equivalent or not. Returns 0 if not equivalent, and an index i such that q is equivalent to S[i] otherwise. Generally slower than <code>ibqf_isequiv_set_byS</code> , so not recommended for use.

Name:	<code>long ibqf_isequiv_set_byq_presorted</code>
Input:	GEN <code>qredssorted</code> , GEN <code>S</code> , GEN <code>rootD</code>
Input format:	<code>qredssorted</code> is <code>ibqf_redorbit_posonly(q, rootD)</code> , sorted with <code>gen_sort_inplace(qredssorted, NULL, &bqf_compare, NULL)</code> , <code>S</code> is a set of PIBQFs with all forms in <code>S</code> and <code>q</code> having discriminant D , and <code>rootD</code> is the positive square root of D
Output format:	Integer
Description:	<code>ibqf_isequiv_set_byq</code> where the sorted positive reduced orbit of <code>q</code> is inputted. Useful if you are making multiple calls to <code>bqf_is_equiv_set</code> with the same <code>q</code> but varying sets <code>S</code> . If this is not the case, <code>ibqf_isequiv_byS</code> is generally faster.

Name:	GEN <code>ibqf_isequiv_set_byq_tmat</code>
Input:	GEN <code>q</code> , GEN <code>S</code> , GEN <code>rootD</code>
Input format:	PIBQFs <code>q</code> and set of PIBQFs <code>S</code> , all of the same discriminant D , <code>rootD</code> the real square root of D
Output format:	<code>gen_0</code> , <code>[i, M]</code>
Description:	Determines if <code>q</code> and an element of <code>S</code> are equivalent or not. Returns <code>gen_0</code> if not equivalent, and <code>[i, M]</code> otherwise, where <code>q</code> is equivalent to <code>S[i]</code> with transition matrix <code>M</code> . Generally slower than <code>ibqf_isequiv_set_byS_tmat</code> , so not recommended for use.

Name:	GEN <code>ibqf_isequiv_set_byq_tmat_presorted</code>
Input:	GEN <code>qredssorted</code> , GEN <code>S</code> , GEN <code>rootD</code>
Input format:	<code>qredssorted</code> is <code>ibqf_redorbit_posonly_tmat(q, rootD)</code> sorted with <code>gen_sort_inplace(qredssorted, NULL, &bqf_compare_tmat, NULL)</code> , <code>S</code> is a set of PIBQFs with all forms in <code>S</code> and <code>q</code> having discriminant D , and <code>rootD</code> is the positive square root of D
Output format:	<code>gen_0</code> , <code>[i, M]</code>
Description:	<code>ibqf_isequiv_set_byq_tmat</code> where the sorted positive reduced orbit of <code>q</code> is inputted. Useful if you are making multiple calls to <code>bqf_is_equiv_set</code> with the same <code>q</code> but varying sets <code>S</code> . If this is not the case, <code>ibqf_isequiv_byS</code> is generally faster.

Name:	<code>long ibqf_isequiv_set_byS</code>
Input:	GEN <code>q</code> , GEN <code>S</code> , GEN <code>rootD</code>
Input format:	PIBQFs <code>q</code> and set of PIBQFs <code>S</code> , all of the same discriminant D , <code>rootD</code> the real square root of D
Output format:	Integer
Description:	Determines if <code>q</code> and an element of <code>S</code> are equivalent or not. Returns 0 if not equivalent, and an index <code>i</code> such that <code>q</code> is equivalent to <code>S[i]</code> otherwise. Generally faster than <code>ibqf_isequiv_set_byq</code> .

Name:	<code>long ibqf_isequiv_set_byS_presorted</code>
Input:	GEN <code>q</code> , GEN <code>Sreds</code> , GEN <code>perm</code> , GEN <code>rootD</code>
Input format:	<code>q</code> , <code>S</code> , and <code>rootD</code> as in <code>ibqf_isequiv_set_byS</code> , where the forms in <code>S</code> are reduced with <code>ibqf_red_pos</code> to get <code>Sreds</code> and sorted by <code>gen_sort_inplace(Sreds, NULL, &bqf_compare, &perm)</code>
Output format:	Integer
Description:	<code>ibqf_isequiv_set_byS</code> where we reduce <code>S</code> and sort it. Useful if you are making multiple calls to <code>bqf_is_equiv_set</code> with the same set <code>S</code> but varying forms <code>q</code> .

Name:	<code>GEN ibqf_isequiv_set_byS_tmat</code>
Input:	GEN <code>q</code> , GEN <code>S</code> , GEN <code>rootD</code>
Input format:	PIBQFs <code>q</code> and set of PIBQFs <code>S</code> , all of the same discriminant D , <code>rootD</code> the real square root of D
Output format:	<code>gen_0</code> , <code>[i, M]</code>
Description:	Determines if <code>q</code> and an element of <code>S</code> are equivalent or not. Returns <code>gen_0</code> if not equivalent, and <code>[i, M]</code> otherwise, where <code>q</code> is equivalent to <code>S[i]</code> with transition matrix <code>M</code> . Generally faster than <code>ibqf_isequiv_set_byq_tmat</code> .

Name:	<code>GEN ibqf_isequiv_set_byS_tmat_presorted</code>
Input:	GEN <code>q</code> , GEN <code>Sreds</code> , GEN <code>perm</code> , GEN <code>rootD</code>
Input format:	<code>q</code> , <code>S</code> , and <code>rootD</code> as in <code>ibqf_isequiv_set_byS</code> , where the forms in <code>S</code> are reduced with <code>ibqf_red_pos</code> to get <code>Sreds</code> and sorted by <code>gen_sort_inplace(Sreds, NULL, &bqf_compare_tmat, &perm)</code>
Output format:	<code>gen_0</code> , <code>[i, M]</code>
Description:	<code>ibqf_isequiv_set_byS_tmat</code> where we reduce <code>S</code> and sort it. Useful if you are making multiple calls to <code>bqf_is_equiv_set</code> with the same <code>q</code> but varying sets <code>S</code> .

Name:	<code>GEN ibqf_isequiv_tmat</code>
Input:	GEN <code>q1</code> , GEN <code>q2</code> , GEN <code>rootD</code>
Input format:	PIBQFs <code>q1</code> , <code>q2</code> of the same discriminant D , <code>rootD</code> the real square root of D
Output format:	<code>gen_0</code> , matrix
Description:	Determines if <code>q1</code> and <code>q2</code> are equivalent or not, returning a transition matrix if they are and <code>gen_0</code> if not.

Name:	<code>GEN ibqf_red</code>
Input:	GEN <code>q</code> , GEN <code>rootD</code>
Input format:	<code>q</code> an IBQF of discriminant D , <code>rootD</code> the square root of D
Output format:	BQF
Description:	Returns a reduction of <code>q</code> .

Name:	GEN <code>ibqf_red_tmat</code>
Input:	GEN <code>q</code> , GEN <code>rootD</code>
Input format:	<code>q</code> a PBQF of discriminant D , <code>rootD</code> the square root of D
Output format:	<code>[q', M]</code>
Description:	Returns <code>[q', M]</code> , where <code>q'</code> is a reduction of <code>q</code> and <code>M</code> is the transition matrix.

Name:	GEN <code>ibqf_red_pos</code>
Input:	GEN <code>q</code> , GEN <code>rootD</code>
Input format:	<code>q</code> an IBQF of discriminant D , <code>rootD</code> the square root of D
Output format:	BQF
Description:	Returns a reduction of <code>q</code> with positive first coefficient.

Name:	GEN <code>ibqf_red_pos_tmat</code>
Input:	GEN <code>q</code> , GEN <code>rootD</code>
Input format:	<code>q</code> a PBQF of discriminant D , <code>rootD</code> the square root of D
Output format:	<code>[q', M]</code>
Description:	Returns <code>[q', M]</code> , where <code>q'</code> is a reduction of <code>q</code> with positive first coefficient and <code>M</code> is the transition matrix.

3.4 Basic methods for indefinite quadratic forms

Methods in this section are specific to indefinite forms. The “river” is the river of the Conway topograph; it is a periodic ordering of the forms $[A, B, C] \sim q$ with $AC < 0$. Reduced forms with $A > 0$ occur between branches pointing down and up (as we flow along the river), and reduced forms with $A < 0$ occur between branches pointing up and down.

Name:	int <code>ibqf_isrecip</code>
Input:	GEN <code>q</code> , GEN <code>rootD</code>
Input format:	<code>q</code> an IBQF of discriminant D , <code>rootD</code> the square root of D
Output format:	0, 1
Description:	Returns 1 if <code>q</code> is reciprocal (<code>q</code> is similar to $-q$), and 0 else.

Name:	int <code>ibqf_isrecip_typecheck</code>
Input:	GEN <code>q</code> , long <code>prec</code>
Input format:	<code>q</code> an IBQF of discriminant D , <code>prec</code> the precision
Output format:	0, 1
Description:	Checks that <code>q</code> is an IBQF, and returns <code>ibqf_isrecip(q, rootD)</code> .

Name:	GEN <code>ibqf_leftnbr</code>
Input:	GEN <code>q</code> , GEN <code>rootD</code>
Input format:	<code>q</code> an IBQF of discriminant D with $AC < 0$, <code>rootD</code> the square root of D
Output format:	IBQF
Description:	Returns the left neighbour of <code>q</code> , i.e. the nearest reduced form on the river to the left of <code>q</code> .

Name:	GEN <code>ibqf_leftnbr_tmat</code>
Input:	GEN <code>q</code> , GEN <code>rootD</code>
Input format:	<code>q</code> an IBQF of discriminant D with $AC < 0$, <code>rootD</code> the square root of D
Output format:	<code>[q', M]</code>
Description:	Returns <code>[q', M]</code> , with <code>q'</code> the left neighbour of <code>q</code> , and the transition matrix is <code>M</code> .

Name:	GEN <code>ibqf_leftnbr_typecheck</code>
Input:	GEN <code>q</code> , int <code>tmat</code> , long <code>prec</code>
Input format:	<code>q</code> an IBQF of discriminant D with $AC < 0$, <code>tmat</code> =0, 1, <code>prec</code> the precision
Output format:	IBQF or <code>[q', M]</code>
Description:	Checks that <code>q</code> is an IBQF on the river, and returns the left neighbour. If <code>tmat</code> =0 only returns the IBQF, and if <code>tmat</code> =1 returns the form and transition matrix.

Name:	GEN <code>ibqf_leftnbr_update</code>
Input:	GEN <code>qvec</code> , GEN <code>rootD</code>
Input format:	<code>qvec</code> = <code>[q, M]</code> with <code>q</code> an IBQF of discriminant D with $AC < 0$ and $M \in \text{SL}(2, \mathbb{Z})$, <code>rootD</code> the square root of D
Output format:	<code>[q', M']</code>
Description:	Returns <code>[q', M']</code> , where <code>q'</code> is the left neighbour of <code>q</code> , the transition matrix is <code>M''</code> , and <code>M'=MM''</code> . This method makes it easier to apply the left neighbour function multiple times while keeping track of the transition matrix from our original starting point.

Name:	GEN <code>ibqf_redorbit</code>
Input:	GEN <code>q</code> , GEN <code>rootD</code>
Input format:	<code>q</code> an IBQF of discriminant D , <code>rootD</code> the square root of D
Output format:	Vector
Description:	Returns the reduced orbit of <code>q</code> .

Name:	GEN <code>ibqf_redorbit_tmat</code>
Input:	GEN <code>q</code> , GEN <code>rootD</code>
Input format:	<code>q</code> an IBQF of discriminant D , <code>rootD</code> the square root of D
Output format:	Vector
Description:	Returns the reduced orbit of <code>q</code> , where each entry is <code>[q', M]</code> , with the reduced form being <code>q'</code> and the transition matrix from <code>q</code> being <code>M</code> .

Name:	GEN <code>ibqf_redorbit_posonly</code>
Input:	GEN <code>q</code> , GEN <code>rootD</code>
Input format:	<code>q</code> an IBQF of discriminant D , <code>rootD</code> the square root of D
Output format:	Vector
Description:	Returns the reduced orbit of <code>q</code> , where we only keep the BQFs with positive first coefficient.

Name:	GEN <code>ibqf_redorbit_posonly_tmat</code>
Input:	GEN <code>q</code> , GEN <code>rootD</code>
Input format:	<code>q</code> an IBQF of discriminant D , <code>rootD</code> the square root of D
Output format:	Vector
Description:	Returns the reduced orbit with positive first coefficient of <code>q</code> , where each entry is $[q', M]$, with the reduced form being q' and the transition matrix from <code>q</code> being M .

Name:	GEN <code>ibqf_redorbit_typecheck</code>
Input:	GEN <code>q</code> , int <code>tmat</code> , int <code>posonly</code> , long <code>prec</code>
Input format:	<code>q</code> an IBQF, <code>tmat</code> , <code>posonly</code> =0, 1, <code>prec</code> the precision
Output format:	Vector
Description:	Returns the reduced orbit of <code>q</code> . If <code>tmat</code> =1 each entry is the pair $[q', M]$ of form and transition matrix, otherwise each entry is just the form. If <code>posonly</code> =1, we only take the reduced forms with positive first coefficient (half of the total), otherwise we take all reduced forms.

Name:	GEN <code>ibqf_rightnbr</code>
Input:	GEN <code>q</code> , GEN <code>rootD</code>
Input format:	<code>q</code> an IBQF of discriminant D with $AC < 0$, <code>rootD</code> the square root of D
Output format:	IBQF
Description:	Returns the right neighbour of <code>q</code> , i.e. the nearest reduced form on the river to the right of <code>q</code> .

Name:	GEN <code>ibqf_rightnbr_tmat</code>
Input:	GEN <code>q</code> , GEN <code>rootD</code>
Input format:	<code>q</code> an IBQF of discriminant D with $AC < 0$, <code>rootD</code> the square root of D
Output format:	$[q', M]$
Description:	Returns $[q', M]$, with q' the right neighbour of <code>q</code> , and the transition matrix is M .

Name:	GEN <code>ibqf_rightnbr_typecheck</code>
Input:	GEN <code>q</code> , int <code>tmat</code> , long <code>prec</code>
Input format:	<code>q</code> an IBQF of discriminant D with $AC < 0$, <code>tmat</code> =0, 1, <code>prec</code> the precision
Output format:	IBQF or [<code>q'</code> , <code>M</code>]
Description:	Checks that <code>q</code> is an IBQF on the river, and returns the right neighbour. If <code>tmat</code> =0 only returns the IBQF, and if <code>tmat</code> =1 returns the form and transition matrix.

Name:	GEN <code>ibqf_rightnbr_update</code>
Input:	GEN <code>qvec</code> , GEN <code>rootD</code>
Input format:	<code>qvec</code> =[<code>q</code> , <code>M</code>] with <code>q</code> an IBQF of discriminant D with $AC < 0$ and $M \in \text{SL}(2, \mathbb{Z})$, <code>rootD</code> the square root of D
Output format:	[<code>q'</code> , <code>M'</code>]
Description:	Returns [<code>q'</code> , <code>M'</code>], where <code>q'</code> is the right neighbour of <code>q</code> , the transition matrix is <code>M''</code> , and <code>M'</code> = <code>MM''</code> . This method makes it easier to apply the right neighbour function multiple times while keeping track of the transition matrix from our original starting point.

Name:	GEN <code>ibqf_river</code>
Input:	GEN <code>q</code> , GEN <code>rootD</code>
Input format:	<code>q</code> an IBQF of discriminant D , <code>rootD</code> the square root of D
Output format:	Vector
Description:	Returns the river sequence associated to <code>q</code> . The entry <code>gen_1</code> indicates going right, and <code>gen_0</code> indicates going left along the river.

Name:	GEN <code>ibqf_river_positions</code>
Input:	GEN <code>q</code> , GEN <code>rootD</code>
Input format:	<code>q</code> an IBQF of discriminant D , <code>rootD</code> the square root of D
Output format:	Vector
Description:	Returns [<code>Lpos</code> , <code>Rpos</code> , <code>riv</code>], where <code>riv</code> is <code>ibqf_river(q)</code> but as a <code>t_VECSMALL</code> , <code>Lpos</code> is a <code>t_VECSMALL</code> of indices <code>i</code> for which <code>riv[i]</code> =0, and <code>Rpos</code> is a <code>t_VECSMALL</code> of indices <code>i</code> for which <code>riv[i]</code> =1.

Name:	GEN <code>ibqf_river_positions_forms</code>
Input:	GEN <code>q</code> , GEN <code>rootD</code>
Input format:	<code>q</code> an IBQF of discriminant D , <code>rootD</code> the square root of D
Output format:	Vector
Description:	Returns [<code>Lpos</code> , <code>Rpos</code> , <code>rivforms</code>], where <code>rivforms</code> is the vector of forms on the river <code>riv</code> in order, <code>Lpos</code> is a <code>t_VECSMALL</code> of indices <code>i</code> for which <code>riv[i]</code> =0, and <code>Rpos</code> is a <code>t_VECSMALL</code> of indices <code>i</code> for which <code>riv[i]</code> =1.

Name:	GEN <code>ibqf_river_typecheck</code>
Input:	GEN <code>q</code> , long <code>prec</code>
Input format:	<code>q</code> an IBQF of discriminant D , <code>prec</code> the precision
Output format:	Vector
Description:	Checks that <code>q</code> is an IBQF and returns <code>ibqf_river(q)</code> .

Name:	GEN <code>ibqf_riverforms</code>
Input:	GEN <code>q</code> , GEN <code>rootD</code>
Input format:	<code>q</code> an IBQF of discriminant D , <code>rootD</code> the square root of D
Output format:	Vector
Description:	Returns the forms on the river of <code>q</code> , where we only take the forms with first coefficient positive.

Name:	GEN <code>ibqf_riverforms_typecheck</code>
Input:	GEN <code>q</code> , long <code>prec</code>
Input format:	<code>q</code> an IBQF of discriminant D , <code>prec</code> the precision
Output format:	Vector
Description:	Checks that <code>q</code> is an IBQF, and returns <code>ibqf_riverforms(q)</code> .

Name:	GEN <code>ibqf_symmetricarc</code>
Input:	GEN <code>q</code> , GEN <code>D</code> , GEN <code>rootD</code> , GEN <code>qpell</code> , long <code>prec</code>
Input format:	<code>q</code> an IBQF of discriminant D , <code>rootD</code> the positive square root of D , <code>qpell=pell(D)</code> , and <code>prec</code> the precision
Output format:	$[z, \gamma_q(z)]$
Description:	If γ_q is the invariant automorph of q , this computes the complex number z , where z is on the root geodesic of q and $z, \gamma_q(z)$ are symmetric (they have the same imaginary part). This gives a “nice” upper half plane realization of the image of the root geodesic of q on $\text{PSL}(2, \mathbb{Z}) \backslash \mathbb{H}$ (a closed geodesic). However, if the automorph of q is somewhat large, z and $\gamma_q(z)$ will be very close to the x -axis, and this method isn’t very useful.

Name:	GEN <code>ibqf_symmetricarc_typecheck</code>
Input:	GEN <code>q</code> , long <code>prec</code>
Input format:	<code>q</code> an IBQF of discriminant D , <code>prec</code> the precision
Output format:	$[z, \gamma_q(z)]$
Description:	Checks that <code>q</code> is an IBQF, and returns <code>ibqf_symmetricarc(q, ...)</code> .

Name:	GEN <code>ibqf_toriver</code>
Input:	GEN <code>q</code> , GEN <code>rootD</code>
Input format:	<code>q</code> an IBQF of discriminant D , <code>rootD</code> the square root of D
Output format:	IBQF
Description:	Reduces <code>q</code> to the river and returns it. Mostly useful as a supporting method for <code>ibqf_red</code> .

Name:	GEN <code>ibqf_toriver_tmat</code>
Input:	GEN <code>q</code> , GEN <code>rootD</code>
Input format:	<code>q</code> an IBQF of discriminant D , <code>rootD</code> the square root of D
Output format:	<code>[q', M]</code>
Description:	Reduces <code>q</code> to the river and returns the reduction <code>q'</code> and the transition matrix <code>M</code> . Mostly useful as a supporting method for <code>ibqf_red_tmat</code> .

Name:	GEN <code>mat_toibqf</code>
Input:	GEN <code>M</code>
Input format:	$M \in \text{SL}(2, \mathbb{Z})$
Output format:	PBQF
Description:	Output the PBQF corresponding to the equation $M(x)=x$. Typically used when <code>M</code> has determinant 1 and is hyperbolic, so that the output is a PIBQF (this method is inverse to <code>ibqf_automorph_D</code> in this case).

Name:	GEN <code>mat_toibqf_typecheck</code>
Input:	GEN <code>M</code>
Input format:	$M \in \text{SL}(2, \mathbb{Z})$
Output format:	PBQF
Description:	Checks that <code>M</code> is a 2x2 integral matrix, and returns <code>mat_toibqf(M)</code> . This method does not check that <code>M</code> is hyperbolic or that it has determinant 1.

3.5 Class group and composition of forms

This section deals with class group related computations. To compute the class group we take the built-in PARI methods, which cover the cases when D is fundamental and when the narrow and full class group coincide. For the remaining cases, we “boost up” the full class group to the narrow class group with `bqf_ncgp_nonfundnarrow`.

Name:	GEN <code>bqf_comp</code>
Input:	GEN <code>q1</code> , GEN <code>q2</code>
Input format:	PBQFs <code>q1</code> , <code>q2</code> of the same discriminant
Output format:	PBQF
Description:	Returns the composition of <code>q1</code> and <code>q2</code> .

Name:	GEN <code>bqf_comp_red</code>
Input:	GEN <code>q1</code> , GEN <code>q2</code> , GEN <code>rootD</code> , int <code>Dsign</code>
Input format:	PBQFs <code>q1</code> , <code>q2</code> of the same discriminant D , <code>rootD</code> the positive square root of D if $D > 0$ (and anything if $D < 0$), <code>Dsign</code> the sign of D
Output format:	PBQF
Description:	Composes <code>q1</code> , <code>q2</code> and returns an equivalent reduced form.

Name:	GEN bqf_comp_typecheck
Input:	GEN q1, GEN q2, int tored, long prec
Input format:	PBQFs q1, q2 of the same discriminant, tored=0, 1, prec the precision
Output format:	PBQF
Description:	Checks that q1, q2 have the same discriminant, and returns their composition. If tored=1 the form is reduced, otherwise it is not.

Name:	GEN bqf_idelt
Input:	GEN D
Input format:	Discriminant D
Output format:	BQF
Description:	Returns the identity element of discriminant D.

Name:	GEN bqf_ncgp
Input:	GEN D, long prec
Input format:	Discriminant D, prec the precision
Output format:	[n, orders, forms]
Description:	Computes and returns the narrow class group associated to D. n is the order of the group, orders=[d1, d2, ..., dk] where $d_1 \mid d_2 \mid \dots \mid d_k$ and the group is isomorphic to $\prod_{i=1}^k \frac{\mathbb{Z}}{d_i \mathbb{Z}}$, and forms is the length k vector of PBQFs corresponding to the decomposition (so forms[i] has order di).

Name:	GEN bqf_ncgp_lexic
Input:	GEN D, long prec
Input format:	Discriminant D, prec the precision
Output format:	[n, orders, forms]
Description:	Computes and returns the narrow class group associated to D. The output is the same as bqf_ncgp, except the third output is now a lexicographical listing of representatives of all equivalence classes of forms of discriminant D (instead of the generators).

Name:	GEN bqf_pow
Input:	GEN q, GEN n
Input format:	PBQF q, integer n
Output format:	PBQF
Description:	Returns q^n .

Name:	GEN bqf_pow_red
Input:	GEN q, GEN n, GEN rootD, int Dsign
Input format:	PBQF q of discriminant D, integer n, rootD the positive square root of D if $D > 0$ (and anything if $D < 0$), Dsign the sign of D
Output format:	PBQF
Description:	Returns a reduction of q^n .

Name:	GEN bqf_pow_typecheck
Input:	GEN q, GEN n, int tored, long prec
Input format:	PBQF q, integer n, tored=0, 1, prec the precision
Output format:	PBQF
Description:	Checks that q is a PBQF and n is an integer, and returns a form equivalent to q^n . If tored=1 the form is reduced, otherwise it is not necessarily.

Name:	GEN bqf_square
Input:	GEN q
Input format:	PBQF q
Output format:	PBQF
Description:	Returns q^2 .

Name:	GEN bqf_square_red
Input:	GEN q, GEN rootD, int Dsign
Input format:	PBQF q of discriminant D, rootD the positive square root of D if $D > 0$ (and anything if $D < 0$), Dsign the sign of D
Output format:	PBQF
Description:	Returns a reduction of q^2 .

Name:	GEN bqf_square_typecheck
Input:	GEN q, int tored, long prec
Input format:	PBQF q, tored=0, 1, prec the precision
Output format:	PBQF
Description:	Checks q is a PBQF, and returns a form equivalent to q^2 . If tored=1 the form is reduced, otherwise it is not necessarily.

Name:	GEN bqf_ncgp_nonfundnarrow
Input:	GEN cgp, GEN D, GEN rootD
Input format:	cgp=quadclassunit0(D, 0, NULL, prec), D a positive (typically non-fundamental) discriminant with norm of the fundamental unit being 1, rootD the positive square root of D
Output format:	[n, orders, forms]
Description:	With the described conditions, the narrow class group is twice the size of the class group. Since quadclassunit0 computes the class group, this method modifies the output to computing the full narrow class group, and returns it in the same format as bqf_ncgp.

3.6 Representation of integers by forms - description tables

This section deals with questions of representing integers by quadratic forms. The three main problems we solve are

- Find all integral solutions (X, Y) to $AX^2 + BXY + CY^2 = n$ (bqf_reps);

- Find all integral solutions (X, Y) to $AX^2 + BXY + CY^2 + DX + EY = n$ (**bqf_bigreps**);
- Find all integral solutions (X, Y, Z) to $AX^2 + BY^2 + CZ^2 + DXY + EXZ + FYZ = n_1$ and $UX + VY + WZ = n_2$ (**bqf_linearsolve**).

The general solution descriptions have a lot of cases, so we put the descriptions in Tables 1-3, and refer to the tables in the method descriptions.

For **bqf_reps**, let $q = [A, B, C]$ and let $d = B^2 - 4AC$. If there are no solutions the method will return **gen_0**, and otherwise it will return a vector **v**, where

$$v = [[\text{type}, v_{extra}], v_1, v_2, \dots, v_k].$$

The types are are

$$-1=\text{all}, 0=\text{finite}, 1=\text{positive}, 2=\text{linear}.$$

Each (family of) solution(s) is given by a v_i , possibly with reference to the extra data. In this table we will only describe **half** of all solutions: we are only taking one of (X, Y) and $(-X, -Y)$. If you want all solutions without this restriction, you just have to add in these negatives.

Table 1: General solution for **bqf_reps**

Type	Conditions to appear	v_{extra}	v_i format	General solution
-1	$q = 0, n = 0$	-	-	X, Y are any integers
0	$d < 0$	-	$[x_i, y_i]$	$X = x_i$ and $Y = y_i$
	$d = \square > 0, {}^a n \neq 0$			
	$d = \boxtimes, {}^a n = 0$			
1	$d = \boxtimes > 0, n \neq 0$	M ^b	$[x_i, y_i]$	$\begin{pmatrix} X \\ Y \end{pmatrix} = M^j \begin{pmatrix} x_i \\ y_i \end{pmatrix}$ for $j \in \mathbb{Z}$
2	$d = 0, n \neq 0$	-	$[[s_i, t_i], [x_i, y_i]]$	$X = x_i + s_i U, Y = y_i + t_i U$ for $U \in \mathbb{Z}$
	$d = \square > 0, n = 0$			

^a \square means square, and \boxtimes means non-square.

^b $M \in \text{SL}(2, \mathbb{Z})$

For **bqf_bigreps**, let $q = [A, B, C, D, E]$ and let $d = B^2 - 4AC$. If there are no solutions the method will return **gen_0**, and otherwise it will return a vector **v**, where

$$v = [[\text{type}, v_{extra}], v_1, v_2, \dots, v_k].$$

The types are are

$$-2=\text{quadratic}, -1=\text{all}, 0=\text{finite}, 1=\text{positive}, 2=\text{linear}.$$

Each (family of) solution(s) is given by a v_i , possibly with reference to the extra data.

Table 2: General solution for `bqf_bigreps`

Type	Conditions to appear	v_{extra}	v_i format	General solution
-2	$d = 0$ and condition ^a	-	$[[a_i, b_i, c_i],$ $[e_i, f_i, g_i]]$	$X = a_i U^2 + b_i U + c_i$ and $Y = e_i U^2 + f_i + g_i$ for $U \in \mathbb{Z}$
-1	$q = 0, n = 0$	-	-	X, Y are any integers
0	$d < 0$	-	$[x_i, y_i]$	$X = x_i$ and $Y = y_i$
	$d = \square > 0$, ^b some cases ^c			
1	$d = \boxtimes > 0, n \neq 0$	$M, [s_1, s_2]$ ^d	$[x_i, y_i]$ ^d	$\begin{pmatrix} X \\ Y \end{pmatrix} = M^j \begin{pmatrix} x_i \\ y_i \end{pmatrix} + \begin{pmatrix} s_1 \\ s_2 \end{pmatrix}$ for $j \in \mathbb{Z}$
2	$d = \square > 0$, ^b some cases ^c	-	$[[s_i, t_i], [x_i, y_i]]$	$x = x_i + s_i U, y = y_i + t_i U$ for $U \in \mathbb{Z}$
	$d = 0$, and condition ^e			

^a At least one of $A, B, C \neq 0$ and at least one of $D, E \neq 0$.

^b \square means square, and \boxtimes means non-square.

^c “Some cases” refers to if the translated equation has $n = 0$ or not.

^d $M \in \text{SL}(2, \mathbb{Z})$ and s_1, s_2 are *rational*; they need not be integral. Same for x_i, y_i .

^e $A = B = C = 0$ or $D = E = 0$. In this case, $s_i = s_j$ and $t_i = t_j$ for all i, j in fact.

For `bqf_linearsolve`, let $q = [A, B, C, D, E, F]$, and let $\text{lin} = [U, V, W]$. If there are no solutions the method will return `gen_0`, and otherwise it will return a vector \mathbf{v} , where

$$\mathbf{v} = [[\text{type}, v_{extra}], v_1, v_2, \dots, v_k].$$

The types are are

-2=quadratic, -1=plane, 0=finite, 1=positive, 2=linear.

Each (family of) solution(s) is given by a v_i , possibly with reference to the extra data.

Table 3: General solution for `bqf_linearsolve`

Type	v_{extra}	v_i format	General solution
-2	-	$[[x_1, x_2, x_3], [y_1, y_2, y_3], [z_1, z_2, z_3]]$	$X = x_1U^2 + x_2U + x_3,$ $Y = y_1U^2 + y_2U + y_3,$ $Z = z_1U^2 + z_2U + z_3, \text{ for } U \in \mathbb{Z}$
-1	-	$[[a_1, a_2, a_3], [b_1, b_2, b_3], [c_1, c_2, c_3]]^a$	$X = a_1U + b_1V + c_1$ $Y = a_2U + b_2V + c_2,$ $Z = a_3U + b_3V + c_3, \text{ for } U, V \in \mathbb{Z}$
0	-	$[a_i, b_i, c_i]$	$X = a_i, Y = b_i, \text{ and } Z = c_i$
1	$M, [s_1, s_2, s_3]^b$	$[a_i, b_i, c_i]^b$	$\begin{pmatrix} X \\ Y \\ Z \end{pmatrix} = M^j \begin{pmatrix} a_i \\ b_i \\ c_i \end{pmatrix} + \begin{pmatrix} s_1 \\ s_2 \\ s_3 \end{pmatrix} \text{ for } j \in \mathbb{Z}$
2	-	$[[a_1, a_2, a_3], [b_1, b_2, b_3]]$	$X = a_1U + b_1,$ $Y = a_2U + b_2,$ $Z = a_3U + b_3, \text{ for } U \in \mathbb{Z}$

^a In fact, $i = 1$ necessarily (there is one plane only).

^b $M \in \text{SL}(3, \mathbb{Z})$ and s_1, s_2, s_3 are *rational*; they need not be integral. Same for a_i, b_i, c_i .

3.7 Representation of integers by forms - methods

Name:	GEN <code>bqf_bigreps</code>
Input:	GEN <code>q</code> , GEN <code>n</code> , long <code>prec</code>
Input format:	<code>q</code> =[A, B, C, D, E] length 5 integer vector, <code>n</code> integer, <code>prec</code> the precision
Output format:	<code>gen_0</code> or <code>v</code> =[[<code>type</code> , <code>data</code>], <code>sol1</code> , ...]
Description:	Solves $AX^2 + BXY + CY^2 + DX + EY = n$, and returns ALL solutions. If no solutions returns <code>gen_0</code> ; otherwise <code>v[1][1]</code> gives the format of the general solution in Table 2.

Name:	GEN <code>bqf_bigreps_typecheck</code>
Input:	GEN <code>q</code> , GEN <code>n</code> , long <code>prec</code>
Input format:	<code>q</code> length 5 integer vector, <code>n</code> integer, <code>prec</code> the precision
Output format:	<code>gen_0</code> or <code>v</code> =[[<code>type</code> , <code>data</code>], <code>sol1</code> , ...]
Description:	Checks that <code>q</code> , <code>n</code> have the correct type, and returns <code>bqf_bigreps(q, n, prec)</code> .

Name:	GEN bqf_linearsolve
Input:	GEN q, GEN n1, GEN lin, GEN n2, long prec
Input format:	q=[A, B, C, D, E, F] length 6 integer vector, n1 an integer, lin=[U, V, W] length 3 integer vector, n2 an integer, prec the precision
Output format:	gen_0 or v=[[type, data], sol1, ...]
Description:	Solves $AX^2+BY^2+CZ^2+DXY+EXY+FYZ = n1$ and $UX+VY+WZ = n2$, and returns ALL solutions. If no solutions returns gen_0; otherwise v[1][1] gives the format of the general solution in Table 3.

Name:	GEN bqf_linearsolve_typecheck
Input:	GEN q, GEN n1, GEN lin, GEN n2, long prec
Input format:	q length 6 integer vector, n1 an integer, lin length 3 integer vector, n2 an integer, prec the precision
Output format:	gen_0 or v=[[type, data], sol1, ...]
Description:	Checks that q, n1, lin, n2 have the correct type, and returns bqf_linearsolve(q, n1, lin, n2).

Name:	GEN bqf_reps
Input:	GEN q, GEN n, int proper, int half, long prec
Input format:	q=[A, B, C] length 3 integer vector, n integer, proper=0, 1, half=0, 1, prec the precision
Output format:	gen_0 or v=[[type, data], sol1, ...]
Description:	Solves $AX^2 + BXY + CY^2 = n$, and returns ALL solutions. If no solutions returns gen_0; otherwise v[1][1] gives the format of the general solution in Table 1. If proper=1 and the form is indefinite/definite, we only output solutions with $\gcd(x,y) = 1$ (otherwise, no restriction). If half=1, only outputs one of (the families corresponding to) (x,y) and $(-x,-y)$, and if half=0 outputs both.

Name:	GEN bqf_reps_typecheck
Input:	GEN q, GEN n, int proper, int half, long prec
Input format:	q length 3 integer vector, n integer, proper=0, 1, half=0, 1, prec the precision
Output format:	gen_0 or v=[[type, data], sol1, ...]
Description:	Checks that q, n have the correct type, and returns bqf_reps(q, n, proper, half, prec).

Name:	GEN dbqf_reps
Input:	GEN qred, GEN D, GEN n, int proper, int half
Input format:	qred=[q',M] with q' a reduced PDBQF of discriminant D and M the transition matrix, n integer, proper=0, 1, half=0, 1
Output format:	gen_0 or v=[[0], sol1, ...]
Description:	Sub-method solving bqf_reps in the definite case. Useful when you want to call bqf_reps on the same q many times.

Name:	GEN ibqf_reps
Input:	GEN qorb, GEN qautom, GEN D, GEN rootD, GEN n, int proper, int half
Input format:	For q a PIBQF, qorb is the output of iqbf_redorbit_posonly_tmat(q) sorted with bqf_compare_tmat, qautom the automorph of q of discriminant D, rootD the positive real square root of D, n an integer, proper=0, 1, half=0, 1
Output format:	gen_0 or [[0], [0, 0]] or v=[[1, M], sol1, ...]
Description:	Sub-method solving bqf_reps in the indefinite case. Useful when you want to call bqf_reps on the same q many times.

Name:	GEN sbqf_reps
Input:	GEN q, GEN D, GEN rootD, GEN n, int half
Input format:	q a primitive BQF, of positive square discriminant D, rootD the positive (integer) square root of D, n an integer, half=0, 1
Output format:	gen_0 or v=[[0/2], sol1, ...]
Description:	Sub-method solving bqf_reps in the positive square discriminant case. Very minimal savings over bqf_reps.

Name:	GEN zbqf_reps
Input:	GEN A, GEN B, GEN n, int half
Input format:	q a primitive non-trivial BQF of discriminant zero expressed as $(AX + BY)^2$ with A, B coprime, n integer, half=0, 1
Output format:	gen_0 or v=[[2], sol1, ...]
Description:	Sub-method solving bqf_reps in the discriminant zero case. Useful when you want to call bqf_reps on the same q many times.

Name:	GEN zbqf_bigreps
Input:	GEN q, GEN n
Input format:	q length 5 primitive integral and non-trivial with $q[1], q[3]>0$, n integer
Output format:	gen_0 or v=[[+/-2], sol1, ...]
Description:	Sub-method solving bqf_bigreps in the discriminant zero case. Very minimal savings over bqf_bigreps.

In the following three methods, we have first primitivized q (length 5 integer vector of non-zero discriminant d), and computed a , b for which the substitutions $X = \frac{x+a}{d}$ and $Y = \frac{y+b}{d}$ yield homogenous

BQFs of discriminant d .

Name:	GEN <code>bqf_bigreps_creatervecfin</code>
Input:	GEN <code>newsols</code> , GEN <code>a</code> , GEN <code>b</code> , GEN <code>disc</code>
Input format:	<code>newsols</code> the output of <code>bqf_reps</code> applied to our translated form, <code>a</code> , <code>b</code> the integers used to translate, <code>disc</code> the discriminant
Output format:	<code>gen_0</code> or <code>v=[[0], sol1, sol2, ...]</code>
Description:	Takes the solutions to the translated form of type 0=finite and picks out only the ones which return to being integral.

Name:	GEN <code>bqf_bigreps_creatervecpos</code>
Input:	GEN <code>newsols</code> , GEN <code>a</code> , GEN <code>b</code> , GEN <code>disc</code>
Input format:	<code>newsols</code> the output of <code>bqf_reps</code> applied to our translated form, <code>a</code> , <code>b</code> the integers used to translate, <code>disc</code> the discriminant
Output format:	<code>gen_0</code> or <code>v=[[1, M, [s1, s2]], sol1, sol2, ...]</code>
Description:	Takes the solutions to the translated form of type 1=positive and picks out only the ones which return to being integral.

Name:	GEN <code>bqf_bigreps_creatervecclin</code>
Input:	GEN <code>newsols</code> , GEN <code>a</code> , GEN <code>b</code> , GEN <code>disc</code>
Input format:	<code>newsols</code> the output of <code>bqf_reps</code> applied to our translated form, <code>a</code> , <code>b</code> the integers used to translate, <code>disc</code> the discriminant
Output format:	<code>gen_0</code> or <code>v=[[2], sol1, sol2, ...]</code>
Description:	Takes the solutions to the translated form of type 2=linear and picks out only the ones which return to being integral.

Name:	GEN <code>bqf_reps_all</code>
Input:	GEN <code>n</code>
Input format:	<code>n</code> integer
Output format:	<code>gen_0</code> or <code>[[-1]]</code>
Description:	Solves <code>bqf_reps</code> for $q=0$.

Name:	GEN <code>bqf_reps_creatervec</code>
Input:	<code>glist *sols</code> , <code>glist *scale</code> , <code>llist *nsolslist</code> , <code>long *totnsols</code> , <code>long *count</code> , <code>int half</code>
Input format:	See C code
Output format:	Vector
Description:	This creates the return vector given the computed list of solutions to <code>bqf_reps</code> . This does not initialize the first component (the type), and is only useful internally to <code>bqf_reps</code> . The method is not stack clean, but the return is suitable for <code>gerepileupto</code> .

Name:	GEN <code>bqf_reps_creatervec_proper</code>
Input:	<code>glist *sols, long nsols, int half</code>
Input format:	See C code
Output format:	Vector
Description:	This creates the return vector given the computed list of solutions to <code>bqf_reps</code> . This does not initialize the first component (the type), and is only useful internally to <code>bqf_reps</code> . It differs to <code>bqf_reps_creatervec</code> in that it deals with the proper solutions only case, and is more efficient in this case. The method is not stack clean, but the return is suitable for <code>gerepile-upto</code> .

Name:	GEN <code>bqf_reps_makeprimitive</code>
Input:	GEN <code>q</code> , GEN <code>*n</code>
Input format:	BQF <code>q</code> , pointer to integer <code>n</code>
Output format:	<code>gen_0</code> or primitive BQF
Description:	We divide through <code>q</code> and <code>n</code> by $\gcd(q)$, update <code>n</code> , and return the new <code>q</code> . If <code>n</code> is no longer an integer (hence no solutions to <code>bqf_reps</code>), we return NULL. This clutters the stack.

Name:	GEN <code>bqf_reps_trivial</code>
Input:	<code>void</code>
Input format:	-
Output format:	<code>[[0], [0, 0]]</code>
Description:	Returns the trivial solution set.

Name:	<code>void bqf_reps_updatesolutions</code>
Input:	<code>glist **sols, long *nsols, GEN *a, GEN *b</code>
Input format:	See C code
Output format:	-
Description:	This method adds a new solution to the <code>glist</code> of solutions, and updates the relevant fields. This does not clutter the stack, but is NOT <code>gerepile</code> safe as the vector is created after the components. This is OK for the internal purposes of <code>bqf_reps</code> as the conversion from <code>glist</code> to vector includes a copying.

Name:	<code>void dbqf_reps_proper</code>
Input:	GEN <code>qred</code> , GEN <code>D</code> , GEN <code>n</code> , <code>glist **sols</code> , <code>long *nsols</code> , GEN <code>f</code> , <code>int *terminate</code>
Input format:	See C code
Output format:	-
Description:	This solves the proper representation case of <code>dbqf_reps</code> , updating the solution <code>glist</code> . Internal function for <code>dbqf_reps</code> .

Name:	<code>void ibqf_reps_proper</code>
Input:	GEN qorb, GEN D, GEN rootD, GEN n, glist **sols, long *nsols, GEN f, int *terminate
Input format:	See C code
Output format:	-
Description:	This solves the proper representation case of <code>ibqf_reps</code> , updating the solution glist. Internal function for <code>dbqf_reps</code> .

The following 5 methods all deal with `bqf_linearsolve`. We take a 3x3 matrix M with inverse Minv such that the top row is equal to `lin`, and substitute in $[x;y;z]=M*[X;Y;Z]$. This new equation has solutions $x=n2$ and y, z described by `yzsols`. The methods bump this back to solutions for X, Y, Z, depending on the nature of the y, z solutions.

Name:	GEN <code>bqf_linearsolve_zall</code>
Input:	GEN yzsols, GEN n2, GEN Minv
Input format:	As above
Output format:	<code>[[-1], [[a1, a2, a3], [b1, b2, b3], [c1, c2, c3]]]</code>
Description:	As above, where the type of yzsols is -1, i.e. anything.

Name:	GEN <code>bqf_linearsolve_zfin</code>
Input:	GEN yzsols, GEN n2, GEN Minv
Input format:	As above
Output format:	<code>[[0], sol1, ...]</code>
Description:	As above, where the type of yzsols is 0, i.e. finite.

Name:	GEN <code>bqf_linearsolve_zlin</code>
Input:	GEN yzsols, GEN n2, GEN Minv
Input format:	As above
Output format:	<code>[[2], sol1, ...]</code>
Description:	As above, where the type of yzsols is 2, i.e. linear.

Name:	GEN <code>bqf_linearsolve_zpos</code>
Input:	GEN yzsols, GEN n2, GEN Minv, GEN M
Input format:	As above
Output format:	<code>[[1, M, [s1, s2, s3]], sol1, ...]</code>
Description:	As above, where the type of yzsols is 1, i.e. positive.

Name:	GEN <code>bqf_linearsolve_zquad</code>
Input:	GEN yzsols, GEN n2, GEN Minv
Input format:	As above
Output format:	<code>[[-2], sol1, ...]</code>
Description:	As above, where the type of yzsols is -2, i.e. quadratic.

3.8 Checking GP inputs

Most methods in the library are easily breakable by having bad inputs. When working in GP, we do not want to cause segmentation faults, so we define wrapper functions to check the inputs. The methods in this section are useful in making these wrapper functions.

Name:	void bqf_check
Input:	GEN q
Input format:	-
Output format:	-
Description:	Checks that q is a BQF, and produces an error if not. Useful for making sure that GP inputs do not break our PARI functions.

Name:	GEN bqf_checkdisc
Input:	GEN q
Input format:	-
Output format:	Integer
Description:	Checks that q is a BQF with non-square discriminant and produces an error if not, where we return the discriminant of q if it passes. Useful for making sure that GP inputs do not break our PARI functions.

Name:	void intmatrix_check
Input:	GEN mtx
Input format:	-
Output format:	-
Description:	Checks that mtx is a 2x2 integral matrix, and produces an error if not. Useful for making sure that GP inputs do not break our PARI functions.

4 qq_bqf_int

Methods in this section deal with the intersection of primitive binary quadratic forms.

4.1 Intersection Data

This section deals with data related to an intersecting pair of quadratic forms.

Name:	GEN bqf_bdelta
Input:	GEN q1 , GEN q2
Input format:	q1 and q2 integral BQFs
Output format:	Integer
Description:	Let $q_i = [A_i, B_i, C_i]$, and this method returns $B_\Delta(q_1, q_2) = B_1B_2 - 2A_1C_2 - 2A_2C_1$.

Name:	GEN bqf_bdelta_typecheck
Input:	GEN q1, GEN q2
Input format:	q1 and q2 integral BQFs
Output format:	Integer
Description:	Checks that q1, q2 have the correct type, and returns bqf_bdelta(q1, q2).

Name:	GEN bqf_intlevel
Input:	GEN q1, GEN q2
Input format:	q1 and q2 integral BQFs
Output format:	Integer
Description:	Returns the signed intersection level of q1, q2.

Name:	GEN bqf_intlevel_typecheck
Input:	GEN q1, GEN q2
Input format:	q1 and q2 integral BQFs
Output format:	Integer
Description:	Checks that q1, q2 have the correct type, and returns bqf_intlevel(q1, q2).

Name:	GEN ibqf_intpairs_transtoq
Input:	GEN pairs, GEN q, GEN rootD
Input format:	pairs a set of pairs of integral IBQFs, q an IBQF that is similar to the first element of every entry in pairs, rootD the square root of the discriminant of disc(q).
Output format:	Vector of pairs [q, q']
Description:	For each pair [q1, q2] in pairs, simultaneously conjugates the pair to [q, q'], and returns the vector of transformed pairs.

Name:	GEN ibqf_intpoint
Input:	GEN q1, GEN q2, GEN location, GEN autom
Input format:	q1 and q2 IBQFs with intersecting root geodesics, location is 0, 1, or a complex point on ℓ_{q1} , autom the invariant automorph of q1 (only required if location $\neq 0, 1$).
Output format:	Imaginary t_QUAD
Description:	Outputs the upper half plane intersection point of q1, q2. If location=0, it is the intersection of q1, q2; if location=1, we translate it to the fundamental domain of $\text{PSL}(2, \mathbb{Z})$; if $\text{imag}(\text{location}) \neq 0$, then location is assumed to be a point on ℓ_{q1} . We translate the intersection point to the geodesic between location and $\gamma_{q1}(\text{location})$. If the invariant automorph is large, then we need to increase the precision to ensure accurate results.

Name:	GEN <code>ibqf_intpoint_typecheck</code>
Input:	GEN <code>q1</code> , GEN <code>q2</code> , GEN <code>location</code>
Input format:	<code>q1</code> and <code>q2</code> IBQFs with intersecting root geodesics, <code>location</code> is 0, 1, or a complex point on ℓ_{q1}
Output format:	Imaginary <code>t_QUAD</code>
Description:	Checks that <code>q1</code> , <code>q2</code> are the correct type and that <code>location</code> =0, 1, or is a complex upper half plane point, and returns <code>ibqf_intpoint(q1, q2, location, autom)</code> .

Name:	GEN <code>hdist</code>
Input:	GEN <code>z1</code> , GEN <code>z2</code> , long <code>prec</code>
Input format:	<code>z1</code> , <code>z2</code> upper half plane complex numbers, <code>prec</code> the precision
Output format:	Real number
Description:	Returns the hyperbolic distance between <code>z1</code> and <code>z2</code> .

Name:	GEN <code>hdist_typecheck</code>
Input:	GEN <code>z1</code> , GEN <code>z2</code> , long <code>prec</code>
Input format:	<code>z1</code> , <code>z2</code> upper half plane complex numbers, <code>prec</code> the precision
Output format:	Real number
Description:	Checks that <code>z1</code> , <code>z2</code> have the correct type, and returns <code>hdist(z1, z2)</code> .

Name:	GEN <code>bqf_iform</code>
Input:	GEN <code>q1</code> , GEN <code>q2</code>
Input format:	<code>q1</code> and <code>q2</code> IBQFs
Output format:	IBQF
Description:	For <code>qi</code> =[<code>Ai</code> , <code>Bi</code> , <code>Ci</code>], this returns $[-A1B2 + A2B1, -2A1C2 + 2A2C1, -B1C2 + B2C1]$.

4.2 Intersection number computation

This section deals with the computation of the intersection number of PIBQFs.

Name:	GEN <code>ibqf_int</code>
Input:	GEN <code>r1</code> , GEN <code>r2</code>
Input format:	<code>r1</code> , <code>r2</code> the output of <code>ibqf_river_positions(qi)</code>
Output format:	Integer
Description:	Computes the full intersection number of <code>q1</code> , <code>q2</code> , which correspond to the river data <code>r1</code> , <code>r2</code> .

Name:	GEN <code>ibqf_int_typecheck</code>
Input:	GEN <code>q1</code> , GEN <code>q2</code> , long <code>prec</code>
Input format:	<code>q1</code> , <code>q2</code> PIBQFs, <code>prec</code> the precision
Output format:	Integer
Description:	Checks that <code>q1</code> , <code>q2</code> are PIBQFs, and returns their full intersection number.

Name:	GEN <code>ibqf_intRS_byriver</code>
Input:	GEN <code>r1</code> , GEN <code>r2</code>
Input format:	<code>r1</code> , <code>r2</code> the output of <code>ibqf_river_positions(qi)</code>
Output format:	Integer
Description:	Computes the RS-intersection number of <code>q1</code> , <code>q2</code> , which correspond to the river data <code>r1</code> , <code>r2</code> .

Name:	GEN <code>ibqf_intRS_typecheck</code>
Input:	GEN <code>q1</code> , GEN <code>q2</code> , long <code>prec</code>
Input format:	<code>q1</code> , <code>q2</code> PIBQFs, <code>prec</code> the precision
Output format:	Integer
Description:	Checks that <code>q1</code> , <code>q2</code> are PIBQFs, and returns their RS-intersection.

Name:	GEN <code>ibqf_intforms_byriver</code>
Input:	GEN <code>r1</code> , GEN <code>r2</code> , int <code>data</code> , int <code>split</code>
Input format:	<code>r1</code> , <code>r2</code> the output of <code>ibqf_river_positions(qi)</code> , <code>data</code> =0, 1, <code>split</code> =0, 1
Output format:	Vector
Description:	Outputs the intersecting forms of <code>q1</code> , <code>q2</code> of all types. If <code>data</code> =1, each entry of the output is <code>[B_delta(f1,f2)</code> , level of int, length of river overlap, <code>f1</code> , <code>f2]</code> ; otherwise it is just the pair <code>[f1, f2]</code> . If <code>split</code> =0 outputs a single vector of the return data, and if <code>split</code> =1 it splits the output into <code>[[RS]</code> , <code>[R0]</code> , <code>[LS]</code> , <code>[L0]]</code> intersection.

Name:	GEN <code>ibqf_intforms_typecheck</code>
Input:	GEN <code>q1</code> , GEN <code>q2</code> , int <code>data</code> , int <code>split</code> , long <code>prec</code>
Input format:	<code>q1</code> , <code>q2</code> PIBQFs, <code>data</code> =0, 1, <code>split</code> =0, 1, <code>prec</code> the precision
Output format:	Vector
Description:	Checks the inputs and returns <code>ibqf_intforms_byriver</code> with the river data of <code>q1</code> , <code>q2</code> .

Name:	GEN <code>ibqf_intformsRS_byriver</code>
Input:	GEN <code>r1</code> , GEN <code>r2</code> , int <code>data</code>
Input format:	<code>r1</code> , <code>r2</code> the output of <code>ibqf_river_positions(qi)</code> , <code>data</code> =0, 1
Output format:	Vector
Description:	<code>ibqf_intforms_byriver</code> , except we only compute the forms for the RS-intersection.

Name:	GEN <code>ibqf_intformsRS_typecheck</code>
Input:	GEN <code>q1</code> , GEN <code>q2</code> , int <code>data</code> , long <code>prec</code>
Input format:	<code>q1</code> , <code>q2</code> PIBQFs, <code>data=0</code> , <code>1</code> , <code>prec</code> the precision
Output format:	Vector
Description:	Checks the inputs, computes the rivers, and returns <code>ibqf_intformsRS_byriver</code> .

Name:	GEN <code>ibqf_intformsRO_byriver</code>
Input:	GEN <code>r1</code> , GEN <code>r2</code> , int <code>data</code>
Input format:	<code>r1</code> , <code>r2</code> the output of <code>ibqf_river_positions(qi)</code> , <code>data=0</code> , <code>1</code>
Output format:	Vector
Description:	<code>ibqf_intforms_byriver</code> , except we only compute the forms for the RO-intersection. Uses <code>Int_RO(q1, q2)=Int_RS(-q2, q1)</code> .

Name:	GEN <code>ibqf_intformsRO_typecheck</code>
Input:	GEN <code>q1</code> , GEN <code>q2</code> , int <code>data</code> , long <code>prec</code>
Input format:	<code>q1</code> , <code>q2</code> PIBQFs, <code>data=0</code> , <code>1</code> , <code>prec</code> the precision
Output format:	Vector
Description:	Checks the inputs, computes the rivers, and returns <code>ibqf_intformsRO_byriver</code> .

Name:	GEN <code>ibqf_intformsLS_byriver</code>
Input:	GEN <code>r1</code> , GEN <code>r2</code> , int <code>data</code>
Input format:	<code>r1</code> , <code>r2</code> the output of <code>ibqf_river_positions(qi)</code> , <code>data=0</code> , <code>1</code>
Output format:	Vector
Description:	<code>ibqf_intforms_byriver</code> , except we only compute the forms for the LS-intersection. Uses <code>Int_LS(q1, q2)=Int_RS(q2, q1)</code> .

Name:	GEN <code>ibqf_intformsLS_typecheck</code>
Input:	GEN <code>q1</code> , GEN <code>q2</code> , int <code>data</code> , long <code>prec</code>
Input format:	<code>q1</code> , <code>q2</code> PIBQFs, <code>data=0</code> , <code>1</code> , <code>prec</code> the precision
Output format:	Vector
Description:	Checks the inputs, computes the rivers, and returns <code>ibqf_intformsLS_byriver</code> .

Name:	GEN <code>ibqf_intformsLO_byriver</code>
Input:	GEN <code>r1</code> , GEN <code>r2</code> , int <code>data</code>
Input format:	<code>r1</code> , <code>r2</code> the output of <code>ibqf_river_positions(qi)</code> , <code>data=0</code> , <code>1</code>
Output format:	Vector
Description:	<code>ibqf_intforms_byriver</code> , except we only compute the forms for the LO-intersection. Uses <code>Int_LO(q1, q2)=Int_RS(q1, -q2)</code> .

Name:	GEN <code>ibqf_intformsLO_typecheck</code>
Input:	GEN <code>q1</code> , GEN <code>q2</code> , int <code>data</code> , long <code>prec</code>
Input format:	<code>q1</code> , <code>q2</code> PIBQFs, <code>data=0</code> , <code>1</code> , <code>prec</code> the precision
Output format:	Vector
Description:	Checks the inputs, computes the rivers, and returns <code>ibqf_intformsLO_byriver</code> .

Name:	GEN <code>ibqf_int_reverseriver</code>
Input:	GEN <code>r</code>
Input format:	<code>r</code> the output of <code>ibqf_river_positions(q)</code>
Output format:	Vector
Description:	Computes the river corresponding to <code>-q</code> , i.e. reverses the river.

Name:	GEN <code>ibqf_intrS_splitindices</code>
Input:	GEN <code>river</code> , GEN <code>ind</code>
Input format:	<code>river</code> the <code>t_VECSMALL</code> representing the river of <code>q</code> , and <code>ind</code> a sorted <code>t_VECSMALL</code> of indices of <code>river</code>
Output format:	<code>[t_VECSMALL, t_VECSMALL]</code>
Description:	Splits the indices into those which are 0 and those which are 1, adds 1 to the indices, and returns them.

Name:	void <code>ibqf_intformsRS_byriver_indices</code>
Input:	GEN <code>r1</code> , GEN <code>r2</code> , llist <code>**inds1</code> , llist <code>**inds2</code> , llist <code>**lovelap</code> , long <code>*inum</code> , int <code>data</code>
Input format:	See C code
Output format:	
Description:	The computation of the the RS-intersection forms called in <code>ibqf_intformsRS_byriver</code> .

5 qq-quat

5.1 Basic operations on elements in quaternion algebras

Name:	GEN <code>qa_conj</code>
Input:	GEN <code>x</code>
Input format:	qelt <code>x</code>
Output format:	qelt
Description:	Returns the conjugate of <code>x</code> . Note that a QA is not inputted.

Name:	GEN qa_conj_typecheck
Input:	GEN x
Input format:	qelt x
Output format:	qelt
Description:	Checks that x is a qelt, and returns qa_conj(x).

Name:	GEN qa_conjby
Input:	GEN Q, GEN x, GEN y
Input format:	QA Q, qelts x, y with y invertible
Output format:	qelt
Description:	Returns xy^{-1} .

Name:	GEN qa_conjby_typecheck
Input:	GEN Q, GEN x, GEN y
Input format:	QA Q, qelts x, y with y invertible
Output format:	qelt
Description:	Checks the types of Q, x, y and returns qa_conjby(Q, x, y).

Name:	GEN qa_inv
Input:	GEN Q, GEN x
Input format:	QA Q, invertible qelt x
Output format:	qelt
Description:	Returns the inverse of x.

Name:	GEN qa_inv_typecheck
Input:	GEN Q, GEN x
Input format:	QA Q, invertible qelt x
Output format:	qelt
Description:	Checks the types of Q, x and returns qa_inv(Q, x).

Name:	GEN qa_m2rembed
Input:	GEN Q, GEN x
Input format:	IQA Q, qelt x
Output format:	2x2 t_MAT of t_QUADs
Description:	Returns the image of x under the standard embedding of Q into $M_2(\mathbb{R})$ (assumes that $a > 0$).

Name:	GEN qa_m2rembed_typecheck
Input:	GEN Q, GEN x
Input format:	IQA Q, qelt x
Output format:	2x2 t_MAT of t_QUADs
Description:	Checks the types of Q, x and returns qa_m2rembed(Q, x).

Name:	GEN qa_minpoly
Input:	GEN Q, GEN x
Input format:	QA Q, qelt x
Output format:	t_VEC
Description:	Returns the minimal polynomial of x. The format is 1, b, c for $x^2 + bx + c$, and [1, b] for $x + b$.

Name:	GEN qa_minpoly_typecheck
Input:	GEN Q, GEN x
Input format:	QA Q, qelt x
Output format:	t_VEC
Description:	Checks the types of Q, x, and returns qa_minpoly(Q, x).

Name:	GEN qa_mul
Input:	GEN Q, GEN x, GEN y
Input format:	QA Q, qelts x, y
Output format:	qelt
Description:	Returns xy.

Name:	GEN qa_mul_typecheck
Input:	GEN Q, GEN x, GEN y
Input format:	QA Q, qelts x, y
Output format:	qelt
Description:	Checks the types of Q, x, y, and returns qa_mul(Q, x, y).

Name:	GEN qa_norm
Input:	GEN Q, GEN x
Input format:	QA Q, qelt x
Output format:	t_INT
Description:	Returns the reduced norm of x.

Name:	GEN qa_norm_typecheck
Input:	GEN Q, GEN x
Input format:	QA Q, qelt x
Output format:	t_INT
Description:	Checks the types of Q, x, and returns qa_norm(Q, x).

Name:	GEN qa_pow
Input:	GEN Q, GEN x, GEN n
Input format:	QA Q, qelt x, integer n
Output format:	qelt
Description:	Returns x^n .

Name:	GEN <code>qa_pow_typecheck</code>
Input:	GEN <code>Q</code> , GEN <code>x</code> , GEN <code>n</code>
Input format:	QA <code>Q</code> , qelt <code>x</code> , integer <code>n</code>
Output format:	qelt
Description:	Checks the types of <code>Q</code> , <code>x</code> , <code>n</code> , and returns <code>qa_pow(Q, x, n)</code> .

Name:	GEN <code>qa_roots</code>
Input:	GEN <code>Q</code> , GEN <code>x</code> , long <code>prec</code>
Input format:	IQA <code>Q</code> , qelt <code>x</code> , precision <code>prec</code>
Output format:	Real/complex number
Description:	Returns the roots of <code>x</code> under the standard embedding into $M_2(\mathbb{R})$, first root first.

Name:	GEN <code>qa_roots_typecheck</code>
Input:	GEN <code>Q</code> , GEN <code>x</code> , long <code>prec</code>
Input format:	IQA <code>Q</code> , qelt <code>x</code> , precision <code>prec</code>
Output format:	Real/complex number
Description:	Checks the types of <code>Q</code> , <code>x</code> and returns <code>qa_roots(Q, x, prec)</code> .

Name:	GEN <code>qa_square</code>
Input:	GEN <code>Q</code> , GEN <code>x</code>
Input format:	QA <code>Q</code> , qelt <code>x</code>
Output format:	qelt
Description:	Returns x^2 .

Name:	GEN <code>qa_square_typecheck</code>
Input:	GEN <code>Q</code> , GEN <code>x</code>
Input format:	QA <code>Q</code> , qelt <code>x</code>
Output format:	qelt
Description:	Checks the types of <code>Q</code> , <code>x</code> , and returns <code>qa_square(Q, x)</code> .

Name:	GEN <code>qa_trace</code>
Input:	GEN <code>x</code>
Input format:	qelt <code>x</code>
Output format:	qelt
Description:	Returns the reduced trace of <code>x</code> . Note that a QA is not inputted.

Name:	GEN <code>qa_trace_typecheck</code>
Input:	GEN <code>x</code>
Input format:	qelt <code>x</code>
Output format:	qelt
Description:	Checks that <code>x</code> is a qelt, and returns <code>qa_trace(x)</code> .

6 qq-visual

These methods deal with the visualization of data. At the moment, they only include methods to bin data for histograms, and display the data.

6.1 Histograms

Since users will likely want to adjust the histograms created with these methods, this part of the package is best used in GP. See [Ric20] for a detailed description on how to use these methods in GP. In library mode, the most likely methods one would use are `hist_make`, `hist_tobins`, and possibly `hist_scale`. Since many of the user-supplied variable names are shared among methods, we describe them first, rather than repeat them in each method description.

- **GEN data:** The sorted (increasing order) raw data that you want to make a histogram with. Should be real numbers, but does not need to be of type `t_REAL`.
- **GEN histdata:** The output of any of the functions in this section returning a **GEN**, storing information about the histogram. Typically will not be created or altered by the user. The format is a length 8 vector, with entries (all translated into **GENs**):

`minx, maxx, nbins, scale, imagename, autofile, plotoptions, open.`

- **GEN minx, GEN maxx:** The boundaries of the bins and hence the histogram.
- **GEN nbins:** The number of bins
- **int compileneu:** set to 1 if the LaTeX document specified by `autofile` has NOT yet been written, and needs to be written. If the document already exists, set this to 0 so as to not overwrite it.
- **int open:** set to 1 if you want the PDF to automatically open, and 0 otherwise. This only works on the Linux subsystem for Windows, so please set to 0 if this is not the case.
- **int scale:** if 0, the histogram y-axis will be the the absolute counts for each bin. If 1, scales the counts so the entire graph has area 1. It is useful to scale the histogram if you are trying to fit the data to a function.
- **long prec:** the precision.
- **char *autofile:** The file name for the LaTeX file, without the `.tex` suffix. This should be found in the folder `“/images/build”`.
- **char *imagename:** The name of the tikz image created.
- **char *plotoptions:** Set to NULL if you want everything done automatically, or have created the LaTeX document yourself. If set to non-null, inserts the character string between `“\begin{axis}”` and `“\end{axis}”`. Thus it is useful to completely customize how you want the histogram to look like.

Note that the created PDF document will reside in the subfolder “/images”, and the LaTeX document and all the build files will reside in the subfolder “/images/build” (this helps keep the clutter of files sequestered). The methods will create these folders if they do not exist yet.

Name:	<code>void hist_autocompile</code>
Input:	<code>GEN minx, GEN maxx, char *imagename, char *autofile, char *plotoptions, int open</code>
Input format:	See bullets near top of Section 6.1
Output format:	
Description:	Writes the LaTeX document <code>autofile</code> automatically, using <code>plotoptions</code> if it is non-NULL.

Name:	<code>void hist_compile</code>
Input:	<code>char *imagename, char *autoname, int open</code>
Input format:	See bullets near top of Section 6.1
Output format:	
Description:	Compiles the LaTeX document <code>autofile</code> , and opens it if <code>open=1</code> .

Name:	<code>GEN hist_make</code>
Input:	<code>GEN data, char *imagename, char *autofile, int compileneu, char *plotoptions, int open, long prec</code>
Input format:	See bullets near top of Section 6.1
Output format:	Vector
Description:	Initiates the making of the histogram with default bins and <code>minx, maxx</code> . Should be called at most once per histogram.

Name:	<code>GEN hist_tobins</code>
Input:	<code>GEN data, GEN minx, GEN maxx, GEN nbins, int toscale, int compileneu, char *imagename, char *autofile, char *plotoptions, int open, long prec</code>
Input format:	See bullets near top of Section 6.1
Output format:	Vector
Description:	This method does the binning of the data according to the inputs, and calls the appropriate submethods to make and compile the LaTeX document. Should be called at most once per histogram.

Name:	<code>GEN hist_tobins_defaultbins</code>
Input:	<code>GEN data, GEN minx, GEN maxx, int toscale, int compileneu, char *imagename, char *autofile, char *plotoptions, int open, long prec</code>
Input format:	See bullets near top of Section 6.1
Output format:	Vector
Description:	Finds the default number of bins, according to the Freedman-Diaconis rule of bin width= $2IQR/(n^{1/3})$ (n data points), and calls <code>hist_tobins</code> .

Name:	GEN hist_rebin
Input:	GEN data, GEN histdata, GEN nbins, long prec
Input format:	See bullets near top of Section 6.1
Output format:	Vector
Description:	Remakes the histogram according to the new nbins.

Name:	void hist_recompile
Input:	GEN histdata
Input format:	See bullets near top of Section 6.1
Output format:	
Description:	Recompiles the LaTeX document. Used when the LaTeX document was modified manually (hence it is unlikely to be useful in library mode).

Name:	GEN hist_rerange
Input:	GEN data, GEN histdata, GEN minx, GEN maxx, long prec
Input format:	See bullets near top of Section 6.1
Output format:	Vector
Description:	Remakes the histogram according to the new range.

Name:	GEN hist_rescale
Input:	GEN data, GEN histdata, int scale, long prec
Input format:	See bullets near top of Section 6.1
Output format:	Vector
Description:	Remakes the histogram by either scaling it or not.

7 Method declarations

Methods in this section are divided into subsections by the files, and into subsubsections by their general function. They will appear approximately alphabetically in each subsubsection, with the static methods always appearing at the bottom. Clicking on a method name will bring you to its full description in the previous sections.

7.1 qq_base

7.1.1 Complex geometry

GEN	crossratio	GEN a, GEN b, GEN c, GEN d
GEN	mat_eval	GEN M, GEN x
GEN	mat_eval_typecheck	GEN M, GEN x

7.1.2 Infinity

GEN	addoo	GEN a, GEN b
GEN	divoo	GEN a, GEN b

7.1.3 Integer vectors

GEN	ZV_copy	GEN v
GEN	ZV_Z_divexact	GEN v, GEN y
GEN	ZV_Z_mul	GEN v, GEN x
int	ZV_equal	GEN v1, GEN v2

7.1.4 Linear equations and matrices

GEN	lin_intsolve	GEN A, GEN B, GEN n
GEN	lin_intsolve_typecheck	GEN A, GEN B, GEN n
GEN	mat3_complete	GEN A, GEN B, GEN C
GEN	mat3_complete_typecheck	GEN A, GEN B, GEN C

7.1.5 Lists

void	clist_free	clist *l, long length
void	clist_putafter	clist **head_ref, GEN new_data
void	clist_putbefore	clist **head_ref, GEN new_data
GEN	clist_togvec	clist *l, long length, int dir
void	glist_free	glist *l
GEN	glist_pop	glist **head_ref
void	glist_putstart	glist **head_ref, GEN new_data
GEN	glist_togvec	glist *l, long length, int dir
void	llist_free	llist *l
long	llist_pop	llist **head_ref
void	llist_putstart	llist **head_ref, long new_data
GEN	llist_togvec	llist *l, long length, int dir
GEN	llist_tovecsmall	llist *l, long length, int dir

7.1.6 Random

GEN	rand_elt	GEN v
long	rand_l	long len

7.1.7 Solving equations modulo n

GEN	sqmod	GEN x, GEN n, GEN fact
GEN	sqmod_typecheck	GEN x, GEN n
GEN	sqmod_ppower	GEN x, GEN p, long n, GEN p2n, int iscoprime

7.1.8 Time

void	printtime	void
char*	returntime	void

7.2 qq_bqf

7.2.1 Discriminant methods

GEN	disclist	GEN D1, GEN D2, int fund, GEN cop
GEN	discprimeindex	GEN D, GEN facs
GEN	discprimeindex_typecheck	GEN D
GEN	fdisc	GEN D
GEN	fdisc_typecheck	GEN D
int	isdisc	GEN D
GEN	pell	GEN D
GEN	pell_typecheck	GEN D
GEN	posreg	GEN D, long prec
GEN	posreg_typecheck	GEN D, long prec
GEN	quadroot	GEN D
GEN	quadroot_typecheck	GEN D

7.2.2 Basic methods for binary quadratic forms

GEN	bqf_automorph_typecheck	GEN q
int	bqf_compare	void *data, GEN q1, GEN q2
int	bqf_compare_tmat	void *data, GEN d1, GEN d2
GEN	bqf_disc	GEN q
GEN	bqf_disc_typecheck	GEN q
GEN	bqf_isequiv	GEN q1, GEN q2, GEN rootD, int Dsign, int tmat
GEN	bqf_isequiv_set	GEN q, GEN S, GEN rootD, int Dsign, int tmat
GEN	bqf_isequiv_typecheck	GEN q1, GEN q2, int tmat, long prec
int	bqf_isreduced	GEN q, int Dsign
int	bqf_isreduced_typecheck	GEN q
GEN	bqf_random	GEN maxc, int type, int primitive
GEN	bqf_random_D	GEN maxc, GEN D
GEN	bqf_red	GEN q, GEN rootD, int Dsign, int tmat
GEN	bqf_red_typecheck	GEN q, int tmat, long prec
GEN	bqf_roots	GEN q, GEN D, GEN w
GEN	bqf_roots_typecheck	GEN q
GEN	bqf_trans	GEN q, GEN M
GEN	bqf_trans_typecheck	GEN q, GEN M
GEN	bqf_transL	GEN q, GEN n
GEN	bqf_transR	GEN q, GEN n
GEN	bqf_transS	GEN q
GEN	bqf_trans_coprime	GEN q, GEN n
GEN	bqf_trans_coprime_typecheck	GEN q, GEN n
GEN	ideal_tobqf	GEN numf, GEN ideal

7.2.3 Basic methods, but specialized

GEN	dbqf_automorph	GEN q, GEN D
GEN	dbqf_isequiv	GEN q1, GEN q2
long	dbqf_isequiv_set	GEN q, GEN S
GEN	dbqf_isequiv_set_tmat	GEN q, GEN S
GEN	dbqf_isequiv_tmat	GEN q1, GEN q2
GEN	dbqf_red	GEN q
GEN	dbqf_red_tmat	GEN q
GEN	ibqf_automorph_D	GEN q, GEN D
GEN	ibqf_automorph_pell	GEN q, GEN qpell
GEN	ibqf_isequiv	GEN q1, GEN q2, GEN rootD
long	ibqf_isequiv_set_byq	GEN q, GEN S, GEN rootD
long	ibqf_isequiv_set_byq_ presorted	GEN qredssorted, GEN S, GEN rootD
GEN	ibqf_isequiv_set_byq_tmat	GEN q, GEN S, GEN rootD
GEN	ibqf_isequiv_set_byq_tmat_ presorted	GEN qredssorted, GEN S, GEN rootD
long	ibqf_isequiv_set_byS	GEN q, GEN S, GEN rootD
long	ibqf_isequiv_set_byS_ presorted	GEN q, GEN Sreds, GEN perm, GEN rootD
GEN	ibqf_isequiv_set_byS_tmat	GEN q, GEN S, GEN rootD
GEN	ibqf_isequiv_set_byS_tmat_ presorted	GEN q, GEN Sreds, GEN perm, GEN rootD
GEN	ibqf_isequiv_tmat	GEN q1, GEN q2, GEN rootD
GEN	ibqf_red	GEN q, GEN rootD
GEN	ibqf_red_tmat	GEN q, GEN rootD
GEN	ibqf_red_pos	GEN q, GEN rootD
GEN	ibqf_red_pos_tmat	GEN q, GEN rootD

7.2.4 Basic methods for indefinite quadratic forms

int	ibqf_isrecip	GEN q, GEN rootD
int	ibqf_isrecip_typecheck	GEN q, long prec
GEN	ibqf_leftnbr	GEN q, GEN rootD
GEN	ibqf_leftnbr_tmat	GEN q, GEN rootD
GEN	ibqf_leftnbr_typecheck	GEN q, int tmat, long prec
GEN	ibqf_leftnbr_update	GEN qvec, GEN rootD
GEN	ibqf_redorbit	GEN q, GEN rootD
GEN	ibqf_redorbit_tmat	GEN q, GEN rootD
GEN	ibqf_redorbit_posonly	GEN q, GEN rootD
GEN	ibqf_redorbit_posonly_tmat	GEN q, GEN rootD
GEN	ibqf_redorbit_typecheck	GEN q, int tmat, int posonly, long prec
GEN	ibqf_rightnbr	GEN q, GEN rootD
GEN	ibqf_rightnbr_tmat	GEN q, GEN rootD
GEN	ibqf_rightnbr_typecheck	GEN q, int tmat, long prec

GEN	ibqf_rightnbr_update	GEN qvec, GEN rootD
GEN	ibqf_river	GEN q, GEN rootD
GEN	ibqf_river_positions	GEN q, GEN rootD
GEN	ibqf_river_positions_forms	GEN q, GEN rootD
GEN	ibqf_river_typecheck	GEN q, long prec
GEN	ibqf_riverforms	GEN q, GEN rootD
GEN	ibqf_riverforms_typecheck	GEN q, long prec
GEN	ibqf_symmetricarc	GEN q, GEN D, GEN rootD, GEN qpell, long prec
GEN	ibqf_symmetricarc_typecheck	GEN q, long prec
GEN	ibqf_toriver	GEN q, GEN rootD
GEN	ibqf_toriver_tmat	GEN q, GEN rootD
GEN	mat_toibqf	GEN M
GEN	mat_toibqf_typecheck	GEN M

7.2.5 Class group and composition of forms

GEN	bqf_comp	GEN q1, GEN q2
GEN	bqf_comp_red	GEN q1, GEN q2, GEN rootD, int Dsign
GEN	bqf_comp_typecheck	GEN q1, GEN q2, int tored, long prec
GEN	bqf_idelt	GEN D
GEN	bqf_ncgp	GEN D, long prec
GEN	bqf_ncgp_lexic	GEN D, long prec
GEN	bqf_pow	GEN q, GEN n
GEN	bqf_pow_red	GEN q, GEN n, GEN rootD, int Dsign
GEN	bqf_pow_typecheck	GEN q, GEN n, int tored, long prec
GEN	bqf_square	GEN q
GEN	bqf_square_red	GEN q, GEN rootD, int Dsign
GEN	bqf_square_typecheck	GEN q, int tored, long prec
GEN	bqf_ncgp_nonfundnarrow	GEN cgp, GEN D, GEN rootD

7.2.6 Representation of integers by forms

GEN	bqf_bigreps	GEN q, GEN n, long prec
GEN	bqf_bigreps_typecheck	GEN q, GEN n, long prec
GEN	bqf_linearsolve	GEN q, GEN n1, GEN lin, GEN n2, long prec
GEN	bqf_linearsolve_typecheck	GEN q, GEN n1, GEN lin, GEN n2, long prec
GEN	bqf_reps	GEN q, GEN n, int proper, int half, long prec
GEN	bqf_reps_typecheck	GEN q, GEN n, int proper, int half, long prec
GEN	dbqf_reps	GEN qred, GEN D, GEN n, int proper, int half
GEN	ibqf_reps	GEN qorb, GEN qautom, GEN D, GEN rootD, GEN n, int proper, int half

GEN	sbqf_reps	GEN q, GEN D, GEN rootD, GEN n, int half
GEN	zbqf_reps	GEN A, GEN B, GEN n, int half
GEN	zbqf_bigreps	GEN q, GEN n
GEN	bqf_bigreps_creatervecfin	GEN newsols, GEN a, GEN b, GEN disc
GEN	bqf_bigreps_creatervecpos	GEN newsols, GEN a, GEN b, GEN disc
GEN	bqf_bigreps_creatervecclin	GEN newsols, GEN a, GEN b, GEN disc
GEN	bqf_reps_all	GEN n
GEN	bqf_reps_creatervec	glist *sols, glist *scale, llist *nsolslist, long *totnsols, long *count, int half
GEN	bqf_reps_creatervec_proper	glist *sols, long nsols, int half
GEN	bqf_reps_makeprimitive	GEN q, GEN *n
GEN	bqf_reps_trivial	void
void	bqf_reps_updatesolutions	glist **sols, long *nsols, GEN *a, GEN *b
void	dbqf_reps_proper	GEN qred, GEN D, GEN n, glist **sols, long *nsols, GEN f, int *terminate
void	ibqf_reps_proper	GEN qorb, GEN D, GEN rootD, GEN n, glist **sols, long *nsols, GEN f, int *terminate
GEN	bqf_linearsolve_zall	GEN yzsols, GEN n2, GEN Minv
GEN	bqf_linearsolve_zfin	GEN yzsols, GEN n2, GEN Minv
GEN	bqf_linearsolve_zlin	GEN yzsols, GEN n2, GEN Minv
GEN	bqf_linearsolve_zpos	GEN yzsols, GEN n2, GEN Minv, GEN M
GEN	bqf_linearsolve_zquad	GEN yzsols, GEN n2, GEN Minv

7.2.7 Checking GP inputs

void	bqf_check	GEN q
GEN	bqf_checkdisc	GEN q
void	intmatrix_check	GEN mtx

7.3 qq_bqf_int

7.3.1 Intersection Data

GEN	bqf_bdelta	GEN q1, GEN q2
GEN	bqf_bdelta_typecheck	GEN q1, GEN q2
GEN	bqf_intlevel	GEN q1, GEN q2
GEN	bqf_intlevel_typecheck	GEN q1, GEN q2
GEN	ibqf_intpairs_transtoq	GEN pairs, GEN q, GEN rootD
GEN	ibqf_intpoint	GEN q1, GEN q2, GEN location, GEN autom
GEN	ibqf_intpoint_typecheck	GEN q1, GEN q2, GEN location
GEN	hdist	GEN z1, GEN z2, long prec
GEN	hdist_typecheck	GEN z1, GEN z2, long prec
GEN	bqf_iform	GEN q1, GEN q2

7.3.2 Intersection number computation

GEN	ibqf_int	GEN r1, GEN r2
GEN	ibqf_int_typecheck	GEN q1, GEN q2, long prec
GEN	ibqf_intRS_byriver	GEN r1, GEN r2
GEN	ibqf_intRS_typecheck	GEN q1, GEN q2, long prec
GEN	ibqf_intforms_byriver	GEN r1, GEN r2, int data, int split
GEN	ibqf_intforms_typecheck	GEN q1, GEN q2, int data, int split, long prec
GEN	ibqf_intformsRS_byriver	GEN r1, GEN r2, int data
GEN	ibqf_intformsRS_typecheck	GEN q1, GEN q2, int data, long prec
GEN	ibqf_intformsRO_byriver	GEN r1, GEN r2, int data
GEN	ibqf_intformsRO_typecheck	GEN q1, GEN q2, int data, long prec
GEN	ibqf_intformsLS_byriver	GEN r1, GEN r2, int data
GEN	ibqf_intformsLS_typecheck	GEN q1, GEN q2, int data, long prec
GEN	ibqf_intformsLO_byriver	GEN r1, GEN r2, int data
GEN	ibqf_intformsLO_typecheck	GEN q1, GEN q2, int data, long prec
GEN	ibqf_int_reverseriver	GEN r
GEN	ibqf_intRS_splitindices	GEN river, GEN ind
void	ibqf_intformsRS_byriver_ indices	GEN r1, GEN r2, llist **inds1, llist **inds2, llist **lovelap, long *inum, int data

7.4 qq_quat

7.4.1 Basic operations on elements in quaternion algebras

GEN	qa_conj	GEN x
GEN	qa_conj_typecheck	GEN x
GEN	qa_conjby	GEN Q, GEN x, GEN y
GEN	qa_conjby_typecheck	GEN Q, GEN x, GEN y
GEN	qa_inv	GEN Q, GEN x
GEN	qa_inv_typecheck	GEN Q, GEN x
GEN	qa_m2rembed	GEN Q, GEN x
GEN	qa_m2rembed_typecheck	GEN Q, GEN x
GEN	qa_minpoly	GEN Q, GEN x
GEN	qa_minpoly_typecheck	GEN Q, GEN x
GEN	qa_mul	GEN Q, GEN x, GEN y
GEN	qa_mul_typecheck	GEN Q, GEN x, GEN y
GEN	qa_norm	GEN Q, GEN x
GEN	qa_norm_typecheck	GEN Q, GEN x
GEN	qa_pow	GEN Q, GEN x, GEN n
GEN	qa_pow_typecheck	GEN Q, GEN x, GEN n
GEN	qa_roots	GEN Q, GEN x, long prec
GEN	qa_roots_typecheck	GEN Q, GEN x, long prec
GEN	qa_square	GEN Q, GEN x

GEN	qa_square_typecheck	GEN Q, GEN x
GEN	qa_trace	GEN x
GEN	qa_trace_typecheck	GEN x

7.5 qq_visual

7.5.1 Histograms

void	hist_autocompile	GEN minx, GEN maxx, char *imagename, char *autofile, char *plotoptions, int open
void	hist_compile	char *imagename, char *autoname, int open
GEN	hist_make	GEN data, char *imagename, char *autofile, int compilenew, char *plotoptions, int open, long prec
GEN	hist_tobins	GEN data, GEN minx, GEN maxx, GEN nbins, int toscale, int compilenew, char *imagename, char *autofile, char *plotoptions, int open, long prec
GEN	hist_tobins_defaultbins	GEN data, GEN minx, GEN maxx, int toscale, int compilenew, char *imagename, char *autofile, char *plotoptions, int open, long prec
GEN	hist_rebin	GEN data, GEN histdata, GEN nbins, long prec
void	hist_recompile	GEN histdata
GEN	hist_rerange	GEN data, GEN histdata, GEN minx, GEN maxx, long prec
GEN	hist_rescale	GEN data, GEN histdata, int scale, long prec

References

- [Ric20] James Rickards. *Q Quadratic: GP guide*, 2020. available from <https://github.com/JamesRickards-Canada/Q-Quadratic>.
- [The20] The PARI Group, Univ. Bordeaux. *PARI/GP version 2.11.3*, 2020. available from <http://pari.math.u-bordeaux.fr/>.